

TECHNICAL DATA SHEET

DESCRIPTION

Snaplugs® are precast, high strength cement compound plugs designed to plug tie cone holes in concrete. Snaplugs® provide faster installation than conventional patching methods with less mess and waste. Snaplugs® are gray in color, have a smooth surface and can be painted or sealed. Snaplugs® are watertight and can be used interior or exterior, above or below grade. Available in 3 styles to fit most application requirements.

USE

Snaplugs® are used to fill the holes created by tie cones.

FEATURES

- Saves time and labor
- Quick, easy installation

PROPERTIES

Color: Gray

ESTIMATING GUIDE

Coverage Snaplugs® – 1 per tie hole
Snaplugs® Bonder – 1 pint (0.47 L) will install approximately 500 Snaplugs®

PACKAGING

ITEM #	DESCRIPTION	PACKAGING
304121	Snaplugs® Flush Gray 1 inch	1000
304122	Snaplugs® Reveal Gray 1 inch	2000
304124	Snaplugs® Reveal Gray 1 1/4 inch	500
303004	Snaplugs® Bonder	12 pint (0.47 L) jugs Per case

STORAGE

Keep Snaplugs® Bonder from freezing. Store Snaplugs® and Snaplugs® Bonder in a cool dry location.

APPLICATION

Surface Preparation: Tie holes should be clean and dry prior to installation.

Mixing: Shake or stir the Snaplugs® Bonder prior to use.

Placement: Coat the Snaplugs® with the Snaplugs® Bonder by inserting the Snaplugs® into the top of the Snaplugs® Bonder container. Invert container to coat the Snaplugs®. Return the container to an upright position and remove the Snaplugs®. Ensure the Snaplugs® is coated well with the Snaplugs® Bonder. Insert the Snaplugs® into the tie hole. Ensure Snaplugs® &

Snaplugs® Bonder are in full contact with the tie hole and a tight fit is achieved.

CLEAN UP

Snaplugs® Bonder can be cleaned with water prior to drying. After drying, mechanical methods such as sanding can be utilized.

LIMITATIONS FOR PROFESSIONAL USE ONLY

Do not install if temperature is below 40°F (4.4°C) or expected to fall below 40°F (4.4°C) within 24 hours.

PRECAUTIONS

READ MSDS PRIOR TO USING PRODUCT

- Use with adequate ventilation
- Wear protective clothing, gloves and eye protection (Goggles, Safety Glasses and/or Face Shield)
- Keep out of the reach of children
- Do not take internally
- In case of ingestion, seek medical help immediately
- May cause skin irritation upon contact, especially prolonged or repeated. If skin contact occurs, wash immediately with soap and water and seek medical help as needed
- If eye contact occurs, flush immediately with clean water and seek medical help as needed
- Dispose of waste material in accordance with federal, state and local requirements
- Contains Portland cement. Use protective gloves. Avoid contact with skin and eyes.

Sec 14
Concrete Repair

MANUFACTURER

Dayton Superior Corporation
1125 Byers Road
Miamisburg, OH 45342
Customer Service: 888-977-9600
Technical Services: 866-329-8724
Website: www.daytonsuperior.com

WARRANTY

Dayton Superior Corporation ("Dayton") warrants for 12 months from the date of manufacture or for the duration of the published product shelf life, whichever is less, that at the time of shipment by Dayton, the product is free of manufacturing defects and conforms to Dayton's product properties in force on the date of acceptance by Dayton of the order. Dayton shall only be liable under this warranty if the product has been applied, used, and stored in accordance with Dayton's instructions, especially surface preparation and installation, in force on the date of acceptance by Dayton of the order. The purchaser must examine the product when received and promptly notify Dayton in writing of any non-conformity before the product is used and no later than 30 days after such non-conformity is first discovered. If Dayton, in its sole discretion, determines that the product breached the above warranty, it will, in its sole discretion, replace the non-conforming product, refund the purchase price or issue a credit in the amount of the purchase price. This is the sole and exclusive remedy for breach of this warranty. Only a Dayton officer is authorized to modify this warranty. The information in this data sheet supersedes all other sales information received by the customer during the sales process. THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTIES, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM, TRADE OR OTHERWISE.

Dayton shall not be liable in contract or in tort (including, without limitation, negligence, strict liability or otherwise) for loss of sales, revenues or profits; cost of capital or funds; business interruption or cost of downtime, loss of use, damage to or loss of use of other property (real or personal); failure to realize expected savings; frustration of economic or business expectations; claims by third parties (other than for bodily injury), or economic losses of any kind; or for any special, incidental, indirect, consequential, punitive or exemplary damages arising in any way out of the performance of, or failure to perform, its obligations under any contract for sale of product, even if Dayton could foresee or has been advised of the possibility of such damages. The Parties expressly agree that these limitations on damages are allocations of risk constituting, in part, the consideration for this contract, and also that such limitations shall survive the determination of any court of competent jurisdiction that any remedy provided in these terms or available at law fails of its essential purpose.

Sec
14
Concrete Repair