

The Model RHA Series roof hatches provide for normal ladder, step ladder and stair access to roof from interior of the building. Manufactured from aluminum with weather resistant gasketing, these units feature long life, low maintenance and ease of operation. J.L. offers fully welded, mitered corners and box type door design. Units install easily over roof opening and are secured from base flange to roof deck.

**Certifications:** ASTM certified under specifications A792/A792M-06a, A653/A653M-06a, C726-05 and A36/A36M-05. Tested and approved to support a minimum live load of 40 lbs/sq of with a maximum deflection of 1/150th of the span, maximum negative load of 50 lbs/sq ft wind uplift and 110 mph wind load when cover is an open position.

**MATERIALS**

**Curb:** .090" aluminum. 12" high curb with 3-5/8" wide flange including holes for securing to roof deck. (Curb includes integral counter flashing)

**Cover:** .090" aluminum, with .040" aluminum liner. Hinged on the "width" side.

**Finish:** Bronze powder coat.

**Door Seal:** EPDM continuous hatch seal.

**Insulation:** 1" fiberboard insulation surrounding base. 1" mineral wool insulation between exterior door and liner.

**Hardware:** Heavy duty zinc-coated hinge and pin. Fastening hardware is zinc-coated.

**Linkage:** Heavy gauge automatic hold open arm with red vinyl grip for opening and closing.

**Closure:** Compression operated, shock absorbing cylinder.

**Latch:** Exterior handle, inside locking handle with interior and exterior padlock hasp.

**Options at Additional Cost:**

\_\_\_ [LP-4, LP-5](#), \_\_\_ [LP6](#), Ladder Posts (see separate submittals for more information)

\_\_\_ [Saf-T-Hatch Rooftop Safety Railing](#) - (see separate submittal for more information) OSHA Meets OSHA 1910.23


\_\_\_ **Stainless Steel Hardware:** Hinges, exterior handle, inside locking handle.

Double Wall RHA—See separate submittal



QTY	MODEL	CURB OPENING		SHIPPING WEIGHT
		Width	Length	
	RHA-1	2' 6"	3' 0"	91
	RHA-2	4' 6"	2' 6"	115
	RHA-3	8' 0"	2' 6"	190
	RHA-4	3' 0"	3' 0"	110
	RHA-5	4' 0"	4' 0"	160

**Other Sizes Available—Contact Customer Service**

 <b>ACTIVAR</b> INC. <small>www.activarcpg.com</small> Construction Products Group	Distributor:	Quantity:
	Contractor:	Approved By:
	Model #:	Architect::
	Project:	Date:
HEADQUARTERS & JL INDUSTRIES: 4450 WEST 78 <sup>TH</sup> ST CIRCLE, BLOOMINGTON, MN 55435-5416 PH: 800-554-6077 FAX: 952-835-2218 EMAIL: SALES@JLINDUSTRIES.COM WWW.ACTIVARCPG.COM ACPG SOUTHEAST (THOMAS ENTERPRISES): FT MYERS, FL ACPG WEST COAST (SAMSON): COMMERCE, CA WAREHOUSES: DALLAS TX, LANCASTER PA, ATLANTA GA, CHICAGO, IL, SEATTLE WA 5/7/13		