

Hydrotech® Gardendrain® GR25

formerly known as Gardendrain® GR25



BUILDING TRUST



GENERAL DESCRIPTION

Gardendrain GR25 is a composite product made of recycled polypropylene core with a fleece top cover fabric and a non-woven bottom fabric. All three components are bonded together in a single component that is designed for aeration, retention and promoting upward moisture movement.

BASIC USE

Gardendrain GR25 is specifically designed to act as a drainage, aeration, and water retention element in Hydrotech’s Garden Roof® Assembly.



INSTALLATION

- Gardendrain GR25 is installed as indicated in Hydrotech’s Garden Roof Installation Guidelines.
- Gardendrain GR25 must be installed white fleece side up.
- Gardendrain GR25 is a roll product with a 3-4” wide flap of extra top fleece along one edge and at the roll end. When installed, the flap edge is lapped over the top surface of the adjacent GR25 roll.

TECHNICAL DATA

ROLL SIZE:	48” wide x 50 ft. long (1.22 m x 15.24 m) (200 SF coverage per roll)
ROLL WEIGHT:	88 lbs. (38 kg)
THICKNESS:	Core alone: 1.0 inches (25.4mm) With fabrics: 1.05 inches approx. (27.5 mm approx.)
FLOW RATE:	30 gal/minute/ft (372 l/min/m) (ASTM D-4716; hydraulic gradient = 1)
WATER RETENTION:	Core alone: 0.11 gal/square foot With fabrics: 0.19 gal/square foot (est.)
COMPRESSIVE STRENGTH:	9,500 psf (455 kNm ²) (ASTM D-1621)
COVER FABRIC WEIGHT:	100 grams / square meters (ASTM D3776)
COVER FABRIC GRAB TENSILE:	70 / 75 lbs (ASTM D5034)
COVER FABRIC GRAB ELONGATION:	40% (ASTM D5034)
COVER FABRIC GRAB PUNCTURE:	238 lbs (ASTM D6241)
BOTTOM FABRIC WEIGHT:	129 grams / square meter (ASTM D3776)
BOTTOM FABRIC GRAB TENSILE:	100 lbs (ASTM D5034)
BOTTOM FABRIC GRAB ELONGATION:	60% (ASTM D5034)
BOTTOM FABRIC CBR PUNCTURE:	250 lbs (ASTM D6241)

LEED® INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	50 (pi) core <5 (pi) fabric	
Manufacture Location		Alpharetta, GA
Extraction/Harvesting Location		Alpharetta, GA

Prior to each use of any product of Sika Corporation, its subsidiaries or affiliates ("SIKA"), the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet which are available at usa.sika.com or by calling SIKA's Technical Service Department at 1-800-933-7452. Nothing contained in any SIKA literature or materials relieves the user of the obligation to read and follow the warnings and instructions for each SIKA product as set forth in the current product label, Product Data Sheet and Safety Data Sheet prior to use of the SIKA product.

SIKA warrants this product for one year from date of installation to be free from manufacturing defects and to meet the technical properties on the current Product Data Sheet if used as directed within the product's shelf life. User determines suitability of product for intended use and assumes all risks. User's and/or buyer's sole remedy shall be limited to the purchase price or replacement of this product exclusive of any labor costs. **NO OTHER WARRANTIES EXPRESS OR IMPLIED SHALL APPLY INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES. SIKA SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.**

Sale of SIKA products are subject to the Terms and Conditions of Sale which are available at <https://usa.sika.com/en/group/SikaCorp/termsandconditions.html> or by calling 1-800-933-7452.