

# Liquid Membrane 6090 Primer



A SIKA COMPANY

## GENERAL DESCRIPTION

Liquid Membrane 6090 Primer is a single component, water based, epoxy coating/sealer.

## BASIC USE

Liquid Membrane 6090 Primer is specifically designed to pre-treat concrete, wood and metal surfaces prior to the application of Liquid Membrane 6090 H or V.

## APPLICATION

Roller or spray apply Liquid Membrane 6090 Primer to concrete, wood and metal surfaces to receive Liquid Membrane 6090 H or V at a rate of approximately 300 square feet per gallon.

Allow Liquid Membrane 6090 Primer to dry thoroughly (20-30 minutes), before attempting application of Liquid Membrane 6090.

## LIMITATIONS/PRECAUTIONS

As a water based product, Liquid Membrane 6090 Primer must be kept from freezing and cannot be applied at temperatures at or below freezing.

## LEED® INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	0	
Manufacture Location		Corsicana, TX
Extraction/Harvesting Location		
VOC Content (g/L)		0

This information is intended only for general conceptual purposes. It is based on data and knowledge considered to be true and correct. It is offered for the user's consideration, investigation and verification and is not intended to substitute for the advice provided by appropriate professionals. Hydrotech assumes no liability for the use of this information. The determination of the suitability and applicability of this information is the sole responsibility of the user.