



VAPORTIGHT COAT-SG

Ultimate Protection for Non-Breathable Floor Coverings and Coatings



www.aquafin.net

GUARANTEED PROTECTION WITH VAPORTIGHT COAT-SG

The VAPORTIGHT COAT®-SG products reduce water vapor emission levels of up to 25 lbs/1000 ft²-24 h and RH up to 100% to well below accepted levels for subsequent application of flooring and coating systems such as epoxies, vinyl tiles, sheet vinyl, carpet, wood flooring, roofing, deck coatings and more.

WHY choose VAPORTIGHT COAT?

VAPORTIGHT COAT®-SG combines a wide variety of advantages in a unique product line

- Vapor barrier
- Moisture tolerant
- High chemical resistance
- Excellent adhesion to damp substrates
- Good adhesion after freeze/thaw cycling
- Easy to apply - one coat application
- Functions as negative side waterproofing
- Provides good bonding for additional top coatings such as adhesives, epoxies, self levelers and roofing membranes

Typical Applications

- Concrete slabs with missing or damaged vapor barriers
- Oil contaminated concrete substrates (SG2 only)*
- Fast track construction schedules - 5 day old concrete slabs
- New concrete slabs with excessive moisture content to receive a flooring or coating

Protect concrete slabs on, below or above grade in industrial/retail facilities, office buildings, hospitals and schools, field houses, running tracks (indoor/outdoor), concrete roof decks, hangars, warehouses, parking structures and more.

