

Safety Data Sheet

Revision Number: 3

Revision Date: 11-22-2022

1 Identification

Product identifier

Trade Name: Tactile Bond & Seal

Relevant identified uss of the substance or mixture: Sections

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Access Products Inc. 241 Main Street Stitle 100 Buffalo, NY 14203

Emergency telephone number: Chemtrec 1-800-424-9300 Int'l 703-527-3887 (collect) 301037/10-10

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Lig. 3 H226 Flammable liquid and vapour.



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHSM

GHS08

- · Signal word Danger
- · Hazard statements

Flammable liquid and vapour.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

· Precautionary statements

If medical advice is needed, have product container or label at hand.

(Contd. on page 2)

Printing Date 03/03/2014 Revision Number 2 Revision Date: 11-22-2022

Trade name: Tactile Bond & Seal

(Contd. of page 1)

Keep out of reach of children.

Read label before use.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Use explosion-proof electrical/ventilating/lighting/equipment.

In case of inadequate ventilation wear respiratory protection.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Specific treatment (see on this label).

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- NFPA ratings (scale 0 4)



Health = 2 Fire = 1 Reactivity = 0

HMIS-ratings (scale 0 - 4)



2 Health = 2

1 Fire = 1

PHYSICAL HAZARD O Physical Hazard = 0

- · Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous	components:	
1330-20-7	xylene	2.5-10%
13463-67-7	titanium dioxide	2.5-10%
64742-47-8	Distillates (petroleum), hydrotreated light	≤2.5%
100-41-4	ethylbenzene	≤1.0%
101-68-8	4,4'-methylenediphenyl diisocyanate	≤0.5%

4 First-aid measures

- Description of first aid measures
- After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Wash contaminated skin with soap and water.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Rinse out mouth with water. Drink 1 - 2 glasses of water but DO NOT induce vomiting. Do not give liquids to a drowsy, convulsing or unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Seek medical treatment.

- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Revision Date: 11-22-2022 Revision Number 2 Printing Date 03/03/2014

Trade name: Tactile Bond & Seal

(Contd. of page 2)

Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Use fire fighting measures that suit the environment.

- Advice for firefighters
- Protective equipment: Wear self-contained respiatory protective device.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose of contaminated material as waste in accordance with federal state and local regulations.

Ensure adequate ventilation.

- Reference to other sections
- See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- Handling:
- Precautions for safe handling

Avoid prolonged or repeated contact with skin.

Avoid contact with eyes.

Wash thoroughly after handling.

Ensure good ventilation/exhaustion at the workplace.

- Information about protection against explosions and fires; Keep ignition sources away Do not smoke.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location away from direct heat.
- Information about storage in one common storage facility: Store away from foodstuffs.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 4)

Printing Date 03/03/2014 Revision Number 2 Revision Date: 11-22-2022

Trade name: Tactile Bond & Seal

(Contd. of page 3) · Control parameters Components with limit values that require monitoring at the workplace: 1330-20-7 xylene (2.5-10%) PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm TLV Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm 13463-67-7 titanium dioxide (2.5-10%) PEL Long-term value: 15* mg/m³ *total dust REL See Pocket Guide App. A TLV Long-term value: (10) NIC-1* mg/m³ *respirable fraction, NIC-A3 100-41-4 ethylbenzene (≤1.0%) PEL Long-term value: 435 mg/m³, 100 ppm REL Short-term value: 545 mg/m³, 125 ppm Long-term value: 435 mg/m³, 100 ppm TLV Short-term value: 543 mg/m³, 125 ppm Long-term value: 87 mg/m³, 20 ppm **BEI** 101-68-84,4'-methylenediphenyl diisocyanate (≤0.5%) PEL Ceiling limit value: 0.2 mg/m³, 0.02 ppm REL Long-term value: 0.05 mg/m³, 0.005 ppm Ceiling limit value: 0.2* mg/m³, 0.02* ppm *10-min TLV Long-term value: 0.051 mg/m³, 0.005 ppm Ingredients with biological limit values: 1330-20-7 xylene (2.5-10%) BEI 1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids 100-41-4 ethylbenzene (≤1.0%) BEI 0.7 g/g creatinine Medium: urine Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative) Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative) Additional information: The lists that were valid during the creation were used as basis.

۸.

Printing Date 03/03/2014 Revision Number 2 Revision Date: 11-22-2022

Trade name: Tactile Bond & Seal

(Contd. of page 4)

Exposure controls

Personal protective equipment (see listings below)

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

· Breathing equipment:

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

Protection of hands:



Protective gloves

Eye protection: Safety glasses with side shields.
Body protection: Protective work clothing

9 Physical and chemical properties

Information on basic physical and General Information	l chemical properties	
Appearance:		
Form:	Viscous paste	
Color:	Gray	
· Odor:	Characteristic	
· Change in condition	and the second s	
Melting point:	Undetermined.	
Boiling point:	Undetermined.	
Flash point:	58 °C (136 °F) (solvent)	
· Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Specific gravity:	1.170	
Solubility in / Miscibility with	Tubustine Sturgets as	
Water:	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wa	tter): N/D	
· Solvent content:		= 1
Organic solvents:	3.5 %	
Solids content:	96.5%	
Other information	VOC: = 74 G/L	
	WEIGHT PER GALLON: = 9.74 LBS	

10 Stability and reactivity

- Reactivity
- Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 6)

(Contd. of page 5)

Safety Data Sheet acc. to OSHA HCS

Printing Date 03/03/2014 Revision Number 2 Revision Date: 11-22-2022

Trade name: Tactile Bond & Seal

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products:

Oxides of carbon and nitrogen.

Isocyanate

· Additional information: AVOID EXPOSURE TO AIR OR MOISTURE UNTIL READY TO USE.

11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- LD/LC50 values that are relevant for classification:

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral LD50 2200 mg/kg (mouse)

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization: Inhalation Sensitization possible through inhalation.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

· Carcinogenic categories

1330-20-7	xylene	3
13463-67-7	titanium dioxide	2B
100-41-4	ethylbenzene	2B
101-68-8	4,4'-methylenediphenyl diisocyanate	3

12 Ecological information

- Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes: At present there are no ecotoxicological assessments.
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

TTO

Printing Date 03/03/2014 Revision Number 2 Revision Date: 11-22-2022

Trade name: Tactile Bond & Seal

(Contd. of page 6)

13 Disposal considerations

- · Waste treatment methods
- · Recommendation: Must be specially treated adhering to official regulations.
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT, ADR, ADN, IMDG, IATA	Void
UN proper shipping name DOT, ADR, ADN, IMDG, IATA	Void
Transport hazard class(es)	
DOT, ADR, ADN, IMDG, IATA Class	Void
Packing group DOT, ADR, IMDG, IATA	Void
Environmental hazards:	Not applicable.
Special precautions for user	Not applicable.
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
Ty and a series of the series	
Transport/Additional information:	D ullet T, ADR, IMDG, IATA - Not regulated in transport. Not dangerous according to the above specifications.
UN "Model Regulation":	

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

Section	355	(extremely	hazardous	substances).

None of the ingredients is listed.

Section 313 (Specific toxic chemical listings):

1330-20-7	xylene

100-41-4 ethylbenzene

101-68-8 4,4'-methylenediphenyl diisocyanate

TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

- Proposition 65
- · Chemicals known to cause cancer:

100-41-4 ethylbenzene

(Contd. on page 8)

Printing Date 03/03/2014 Revision Number 2 Revision Date: 11-22-2022

Trade name: Tactile Bond & Seal

(Contd. of page 7)

· Chemicals known to cause reproductive toxicity:

None of the ingredients is listed.

· (DSL) Canada Dosmestic Substance List

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

· Cancerogenity categories

1330-20-7	xylene	I
100-41-4	ethylbenzene	D
101-68-8	4,4'-methylenediphenyl diisocyanate	CBD
TLV (Thre:	shold Limit Value established by ACGIH)	
1330-20-7	xylene	A4
13463-67-7	titanium dioxide	A4
100-41-4	ethylbenzene	A3
MAK (Geri	man Maximum Workplace Concentration)	
13463-67-7	titanium dioxide	3A
100-41-4	ethylbenzene	3A
101-68-8	4,4'-methylenediphenyl diisocyanate	4
NIOSH-Ca	(National Institute for Occupational Safety and Health)	
13463-67-7	titanium dioxide	
OSHA-Ca	(Occupational Safety & Health Administration)	
None of the	ingredients is listed.	

- · National regulations:
- · Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

Although the information and recommendations set forth in this SDS are presented in good faith and are believed to be correct as of the date of this SDS, Access Products Inc. makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Access Products Inc. or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the SDS.

- · Department issuing SDS: Environment protection department
- · Creation Date: 06/29/2007
- · Date of preparation / last revision: 03/03/2014 / 2
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 9)

Page 9/9

Safety Data Sheet acc. to OSHA HCS

Printing Date 03/03/2014 Revision Number 2

Trade name: Tactile Bond & Seal

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent Flam. Liq. 3: Flammable liquids, Hazard Category 3

Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

(Contd. of page 8)

Revision Date: 11-22-2022

USA