



Roofing Product Reference Guide



SHINGLES

UNDERLAYMENT


ACCESSORIES

Designer Shingles Featuring Scotchgard™ Protector

For lasting protection against black streaks caused by algae, install shingles featuring the Atlas Lifetime* Algae Resistance Limited Warranty.

StormMaster® Slate

High Wind And Impact Resistant Shingles



Length: 22¹/₁₆" / 576.3 mm
Width: 18¹/₂" / 469.9 mm
Exposure: 8¹/₂" / 215.9 mm
Shingles Per Bundle: 25



6 COLORS

Blackstone Slate
Chalkstone Slate
Emerald Slate
Hearthstone Slate
Pewter Slate
Weathered Slate

FEATURES

Scotchgard™ Protector
130 mph Wind Limited Warranty**
FASTAC™ Double Sealant Lines
Manufactured Using Core4™
Enhanced Polymer Technology
Class 4 Impact Resistance - UL 2218²
Atlas Lifetime* Algae Resistance
Limited Warranty
Lifetime Limited Warranty**
Atlas Signature Select® Eligible¹


ASTM

D7158, Class H Wind Resistance,
Passed at 150 mph
D6381, Uplift Resistance
D3018, Type 1
D3161, Class F, Tested at 110 mph
D3462, As Manufactured
E108, Class A Fire Resistance

UL

2218, Class 4 Impact Resistance
790, Class A Fire Resistance
2390, Class H Wind Resistance

CODES AND COMPLIANCES

Meets AC438 Criteria
CAN/CSA-A123.5-M90
Florida Building Code Approved – FL 16305
Miami-Dade County Product
Control Approved 




A Brand You
Know And Trust
Scotchgard™ Protector
25+ years of proven
performance.



For maximum protection and warranty coverage,
install an Atlas Signature Select® Roofing System with
components designed and backed by an Atlas warranty.

StormMaster® Shake

High Wind And Impact Resistant Shingles



Length: 42" / 1066.8 mm
Width: 14" / 355.6 mm
Exposure: 6" / 152.4 mm
Shingles Per Bundle: 18-20



10 COLORS

Natural Expressions:

Chestnut
Copper Canyon
Majestic Shake
Morning Harvest
Silver Stone

Classic:

Black Shadow
Hearthstone Gray
Highland Brown
Pewter
Weathered Wood

FEATURES

Scotchgard™ Protector
Up To 150 mph Wind Limited Warranty**
FASTAC™ Double Sealant Lines
Manufactured Using Core4™
Enhanced Polymer Technology
Class 4 Impact Resistance - UL 2218²
Atlas Lifetime* Algae Resistance
Limited Warranty
Lifetime Limited Warranty**
Atlas Signature Select® Eligible¹


ASTM

D7158, Class H Wind Resistance,
Passed at 150 mph
D6381, Uplift Resistance
D3018, Type 1
D3161, Class F, Tested at 110 mph
D3462, As Manufactured
E108, Class A Fire Resistance

UL


2218, Class 4 Impact Resistance
790, Class A Fire Resistance
2390, Class H Wind Resistance

CODES AND COMPLIANCES

Meets AC438 Criteria
CAN/CSA-A123.5-M90
Florida Building Code Approved – FL 16305
Miami-Dade County Product
Control Approved 

Pinnacle® Pristine

High Performance Architectural Shingles



Length: 42" / 1066.8 mm
Width: 14" / 355.6 mm
Exposure: 6" / 152.4 mm
Shingles Per Bundle: 18-20



19 COLORS

Natural Expressions:

Coastal Granite
Copper Canyon
Majestic Shake
Morning Harvest
Summer Storm

Classic:

Pristine Black
Pristine Desert
Pristine Hearthstone
Pristine Heather
Pristine Hickory
Pristine Oyster
Pristine Pewter
Pristine Sienna
Pristine Tan
Pristine Weathered Wood

Special Order:

Pristine Green
Pristine Pearl
Pristine Sunset
Pristine Weathered Shadow


FEATURES

Scotchgard™ Protector
130 mph Wind Limited Warranty**
FASTAC™ Double Sealant Lines
Atlas Lifetime* Algae Resistance
Limited Warranty
Lifetime Limited Warranty**
Atlas Signature Select® Eligible¹


ASTM

D7158, Class H Wind Resistance,
Passed at 150 mph
D6381, Uplift Resistance
D3018, Type 1
D3161, Class F, Tested at 110 mph
D3462, As Manufactured
E108, Class A Fire Resistance

UL


790, Class A Fire Resistance 
2390, Class H Wind Resistance

CODES AND COMPLIANCES

Meets AC438 Criteria
CAN/CSA-A123.5-M90
Florida Building Code Approved – FL 16305
Miami-Dade County Product
Control Approved 

Value Shingles

ProLam[®] Architectural Shingles



Length: 42" / 1066.8 mm
Width: 14" / 355.6 mm
Exposure: 6" / 152.4 mm
Shingles Per Bundle: 18-20



7 COLORS

Black Shadow
Burnt Sienna
Desert Shake
Hearthstone Gray
Heather
Pewter
Weathered Wood

FEATURES

Up To 130 mph Wind Limited Warranty**
Algae Resistant Shingle
Lifetime Limited Warranty**
3M Ceramic-Coated Granules

ASTM

D7158, Class H Wind Resistance, Passed at 150 mph
D6381, Uplift Resistance
D3018, Type 1
D3161, Class F, Tested at 110 mph
D3462, As Manufactured
E108, Class A Fire Resistance


UL

790, Class A Fire Resistance
2390, Class H Wind Resistance

CODES AND COMPLIANCES

Meets AC438 Criteria
CAN/CSA-A123.5-M90
Florida Building Code Approved – FL 16305
Miami-Dade County Product Control Approved

Legend[®] Designer Fiberglass Shingles



Length: 36" / 914.4 mm
Width: 12" / 304.8 mm
Exposure: 5" / 127 mm
Shingles Per Bundle: 26



5 COLORS

Black Shadow
Desert Shake
Hearthstone Gray
Heatherblend
Weathered Wood

FEATURES

Scotchgard[™] Protector
110 mph Wind Limited Warranty**
40-year Atlas Limited Warranty**
Atlas Signature Select[®] Eligible¹

ASTM

D7158, Class H Wind Resistance, Passed at 150 mph
D6381, Uplift Resistance
D3018, Type 1
D3161, Class F, Tested at 110 mph
D3462, As Manufactured
E108, Class A Fire Resistance


UL

790, Class A Fire Resistance
2390, Class H Wind Resistance

CODES AND COMPLIANCES

CAN/CSA-A123.5-M90
Florida Building Code Approved – FL 16305
Miami-Dade County Product Control Approved

GlassMaster[®] Performance Fiberglass Shingles



Length: 36" / 914.4 mm
Width: 12" / 304.8 mm
Exposure: 5" / 127 mm
Shingles Per Bundle: 26



12 COLORS

Black Shadow
Burnt Sienna
Cool White
Desert Shake
Dove Gray
Hearthstone Gray
Heatherblend
Oyster Shell
Pewter
Tan Mist
Weathered Wood
Woodland Green

FEATURES

60 mph Wind Limited Warranty**
30-Year Limited Warranty**
Algae-Resistant Shingle
3M Ceramic-Coated Granules
Atlas Signature Select[®] Eligible¹

ASTM

D7158, Class H Wind Resistance, Passed at 150 mph
D6381, Uplift Resistance
D3018, Type 1
D3161, Type 1, Class F, Tested at 110 mph
D3462, As Manufactured
E108, Class A Fire Resistance


UL

790, Class A Fire Resistance
2390, Class H Wind Resistance

CODES AND COMPLIANCES

Meets AC438 Criteria
CAN/CSA-A123.5-M90
Florida Building Code Approved – FL 16305
Miami-Dade County Product Control Approved

Tough-Glass[®] Original Fiberglass Shingles



Length: 36" / 914.4 mm
Width: 12" / 304.8 mm
Exposure: 5" / 127 mm
Shingles Per Bundle: 26



2 COLORS

Black Shadow
Weathered Wood

FEATURES

60 mph Wind Limited Warranty**
20-Year Limited Warranty**
3M Ceramic-Coated Granules

ASTM

D7158, Class H Wind Resistance, Passed at 150 mph
D6381, Uplift Resistance
D3018, Type 1
D3161, Type 1, Class F, Tested at 110 mph
D3462, As Manufactured
E108, Class A Fire Resistance

UL

790, Class A Fire Resistance
2390, Class H Wind Resistance

CODES AND COMPLIANCES

Meets AC438 Criteria
CAN/CSA-A123.5-M90
Florida Building Code Approved – FL 16305
Miami-Dade County Product Control Approved



Dreaming of a home redesign?

Get creative with the Roof Inspiration Center, a suite of home design tools from Atlas. Whether you have 3 minutes or 30, your new look is just around the corner.


AtlasRoofing.com/Roof-Inspiration

To provide homeowners the most accurate representation of color options, several photo scans and house shots were utilized in various lighting conditions. Variations in lighting illustrate the color gradients on asphalt shingle roofs.

Color blends vary from shingle to shingle. Before installation, consult with your contractor and request to view the actual shingles being installed on your roof to ensure confidence in your final color selection.


Roof Shingle Accessories

Pro-Cut® High Profile Hip & Ridge Shingles



Dimensions: 10" x 11½"
Exposure: 8¼"
Coverage: 20 Linear Feet
Shingles Per Package: 30

Pro-Cut® Hip & Ridge Shingles



Dimensions: 12" x 12"
Exposure: 5 5/8"
Coverage: 31 Linear Feet
Shingles Per Package: 66



COLORS

To match Atlas shingles

FEATURES

Scotchgard™ Protector
Manufactured Using SBS Asphalt
Atlas Lifetime* Algae Resistance
Limited Warranty
Lifetime Limited Warranty**
Atlas Signature Select® Eligible¹

CODES AND COMPLIANCES

Class A Fire Resistance (UL R21860)
Wind Resistance (UL 997)
CAN/CSA-A123.5-M90



COLORS

To match Atlas shingles

FEATURES

Scotchgard™ Protector
Manufactured Using Core4™
Enhanced Polymer Technology³
Class 4 Impact Resistance – UL 2218^{2,3}
Atlas Lifetime* Algae Resistance
Limited Warranty
Lifetime Limited Warranty**
Atlas Signature Select® Eligible¹

ASTM

D3018, Type 1
D3161, Type 1, Class F,
Tested at 110 mph
D3462, As Manufactured
E108, Class A Fire Resistance


UL

790, Class A Fire Resistance
2390, Class H Wind Resistance

CODES AND COMPLIANCES

Meets AC438 Criteria
CAN/CSA-A123.5-M90
Florida Building Code Approved –
FL 16305
Miami-Dade County Product
Control Approved

Pro-Cut® Starter Shingles



6XR STARTER SHINGLE ROLL

Roll Dimensions: 7.2" x 33' 4"
Exposure Limits: Up To 6"
Per Roll: 33' 4"

Universal 8.5x STARTER SHINGLES

Shingle Dimensions: 10 5/8" x 36"
Exposure Limits: Up To 8 1/2"
Per Bundle: 78 Linear Feet

Universal 10x STARTER SHINGLES

Shingle Dimensions: 12" x 36"
Exposure Limits: Up To 10"
Per Bundle: 78 Linear Feet

Premium Underlayments

Synthetic

Summit® 180 Premium Synthetic Underlayment



Length: 250'
Width: 48"
Square Per Roll Coverage: 10
Coverage with 4" Lap: 917 sq. ft.

CODES AND COMPLIANCES

AC 207, UV Exposure for 180 Days
AC 207, Accelerated Aging
ASTM E108, Fire Resistance
ASTM D6757, Inorganic Shingle
Underlayment Standard

PERFORMANCE

CHARACTERISTICS EXCEED:

ASTM D4869, Type I, Type II, Type III,
Type IV (Standard specification for
asphalt-saturated felt), ASTM D226
Type I & Type II
UL 790, Fire Resistance
UL Classified as a Prepared
Roofing Accessory
Florida Building Code Approved - FL 21350
Miami-Dade County Product
Control Approved

Summit® 60 Synthetic Underlayment



Length: 250'
Width: 48"
Square Per Roll Coverage: 10
Coverage with 4" Lap: 917 sq. ft.

CODES AND COMPLIANCES

AC 207, UV Exposure for 60 Days
AC 207, Accelerated Aging
ASTM E108, Fire Resistance
ASTM D6757, Inorganic Shingle
Underlayment Standard

PERFORMANCE

CHARACTERISTICS EXCEED:

ASTM D4869, Type I, Type II, Type III,
Type IV (Standard specification for
asphalt-saturated felt), ASTM D226
Type I & Type II
UL Classified as a Prepared
Roofing Accessory
Florida Building Code Approved - FL 21350

Engineered Felt

30 Gorilla Guard® 30 Engineered Underlayment



Length: 141.5'
Width: 36"
Square Per Roll Coverage: 4
Coverage with 2" Lap: 400 sq. ft.

CODES AND COMPLIANCES

UL Classified as a Roofing Accessory
ASTM D6757
Florida Building Code Approved - FL 17322
Meets Performance Characteristics of
ASTM D4869 (#15 & #30 Standard) and
ASTM D226 Type I

30 Gorilla Guard® Spec 30 Engineered Underlayment



Length: 72'
Width: 36"
Square Per Roll Coverage: 2
Coverage with 2" Lap: 200 sq. ft.

CODES AND COMPLIANCES

ASTM D4869, Type IV
ASTM D226, Type II
ASTM D6757
Florida Building Code Approved - FL 16226
Miami-Dade County Product
Control Approved

* In order to qualify for the Atlas Lifetime Algae Resistance Limited Warranty against black streaks caused by blue-green algae, installation must include Atlas Pro-Cut® Hip & Ridge shingles featuring Scotchgard™ Protector or Atlas Pro-Cut® High Profile Hip & Ridge shingles featuring Scotchgard™ Protector with Atlas shingles featuring Scotchgard™ Protector.

** Refer to the Atlas Roofing Limited Shingle Warranty for all coverage requirements.

¹ Refer to the Atlas Signature Select® Limited Warranty for all system coverage requirements.

² UL 2218 for Class 4 Impact Resistance is applicable to product manufactured at the Ardmore, OK plant.

³ Pro-Cut® Hip & Ridge manufactured in Hampton, GA is not made with modified asphalt and is not a Class 4 shingle.

⁴ Helps resist the black streaks caused by algae.

Scotchgard and the Scotchgard Protector logo, including the plaid design and 3M logo, are all trademarks of 3M.

SBS Peel & Stick Premium Underlayments



Length: 66.8'
Width: 36"
2 Square Roll Provides Approximately
200 sq. ft. of Material

CODES AND COMPLIANCES

Underwriters Laboratories Class A and
Class C Fire Rating – Based on Roof Covering
ASTM D1970, Ice Dam and Metal Underlayment
ICC-ES Report ER 1783
Florida Building Code Approved - FL 17322
Miami-Dade County Product
Control Approved



Length: 72.1'
Width: 36"
2 Square Roll Provides Approximately
216 sq. ft. of Material

CODES AND COMPLIANCES

ASTM D1970, Standard Ice Dam Underlayment
ICC-ES Report ER 1783
Florida Building Code Approved - FL 17322
Miami-Dade County Product
Control Approved



Length: 65'
Width: 36"
1.95 Square Roll Provides Approximately
195 sq. ft. of Material

CODES AND COMPLIANCES

Underwriters Laboratories Class A and
Class C Fire Rating – Based on Roof Covering
ASTM D1970, Standard Ice Dam Underlayment
ICC-ES Report ER 1783
Florida Building Code Approved - FL 17322
Miami-Dade County Product
Control Approved



Length: 33.3'
Width: 36"
1 Square Roll Provides Approximately
100 sq. ft. of Material

CODES AND COMPLIANCES

Underwriters Laboratories Class A and
Class C Fire Rating – Based on Roof Covering
ASTM D1970, Standard Ice Dam Underlayment
ICC-ES Report ER 1783
Florida Building Code Approved - FL 17322
Miami-Dade County Product
Control Approved



Length: 65'
Width: 36"
1.95 Square Roll Provides Approximately
195 sq. ft. of Material

CODES AND COMPLIANCES

Underwriters Laboratories Class A and
Class C Fire Rating – Based on Roof Covering
ASTM D1970, Standard Ice Dam Underlayment
ICC-ES Report ER 1783



Length: 72'
Width: 36"
2 Square Roll Provides Approximately
216 sq. ft. of Material

CODES AND COMPLIANCES

Underwriters Laboratories Class A and
Class C Fire Rating – Based on Roof Covering
ASTM D1970, Premium Ice Dam and Tile Underlayment
Florida Building Code Approved - FL 17322
Miami-Dade County Product
Control Approved



Length: 66.8'
Width: 36"
2 Square Roll Provides Approximately
200 sq. ft. of Material

CODES AND COMPLIANCES

Underwriters Laboratories Class A and
Class C Fire Rating – Based on Roof Covering
ASTM D1970, Standard Ice Dam Underlayment
Florida Building Code Approved - FL 17322



Length: 33.3' (1 sq.) 66.6' (2 sq.)
Width: 36"

CODES AND COMPLIANCES

ASTM D1970, Moisture Vapor Permeability
ASTM D4869, Liquid Water Transmission

Felt Underlayments

#30 Organic Saturated Felt



Length: 72'
Width: 36"
Square Per Roll Coverage: 2
Square Feet Per Roll: 216

CODES AND COMPLIANCES

ASTM D4869, Type 1
Florida Building Code Approved - FL 17322

#15 Organic Saturated Felt



Length: 144'
Width: 36"
Square Per Roll Coverage: 4
Square Feet Per Roll: 432

CODES AND COMPLIANCES

ASTM D4869, Type 1
Florida Building Code Approved - FL 17322



AtlasRoofing.com

#AtlasProtects

© Copyright 2020, Atlas Roofing Corporation ATL-205301-00 3/20