

Log on to **BILCO.com** to find a sales representative near you.



Type L

Service or Full Service Access

BILCO Service Stair access roof hatches are available in galvanized steel, aluminum or stainless steel construction to meet any job requirements. Aluminum products are also available in a thermally broken design that offers superior energy efficiency and resists condensation.

Material

- Steel: 14 gauge (1.9mm) galvanized steel
- Aluminum: 11 gauge (2.3mm)
- Stainless Steel: 14 gauge (1.9mm) Type 304 stainless

Insulation

- 1" (25mm) fiberglass insulation in cover and 1" fiberboard insulation in curb
- 3" (75mm) Polyisocyanurate (R = 20.3) in cover and curb (Thermally Broken Models)

Finish

- Steel: Alkyd base red oxide primer
- Aluminum: Mil finish
- Stainless Steel: Bead blast finish
- See page 18 for custom finish options

Hardware

- Zinc plated/chromate sealed
- Type 316 stainless steel

Specialty Roof Hatches *(see pages 10-11 for more information)*

- Daylighting with polycarbonate skylight
- Retrofit mounting
- Security Series

See pages 18-19 for a complete list of curb, finish and other special options.



Florida Product Approval

Type L-20HZ and L-50HZ only



Type L-TB
Thermally Broken
R-20+ Insulation

TYPE	INCHES	MM	MATERIAL	INSULATION	THERMALLY BROKEN
L-20	30 x 96	762 x 2438	Steel	1" (25mm)	No
L-50	30 x 96	762 x 2438	Aluminum	1" (25mm)	No
L-50-TB	30 x 96	762 x 2438	Aluminum	3" (75mm)	Yes
L-90	30 x 96	762 x 2438	Stainless Steel	1" (25mm)	No

Type L-40 models are available in steel curb and aluminum cover