



# GROUT & SEALANT Color Guide

**Dimension<sup>®</sup> RapidCure<sup>™</sup>, TruColor<sup>®</sup> RapidCure<sup>™</sup>, EzPoxy<sup>™</sup> EzClean<sup>™</sup>,  
Hydroment<sup>®</sup> Vivid<sup>™</sup>, Hydroment<sup>®</sup> Ceramic Tile Grout (Sanded),  
Hydroment<sup>®</sup> Dry Tile Grout (Unsanded), Pure Silicone<sup>™</sup>, Tub & Tile Caulk<sup>™</sup>**





**Watch for the video icon!**  
 Visit [youtube.com/BostikUSA](https://youtube.com/BostikUSA)  
 for videos on featured products.

# Grout Technology

## Breaking it all down

With an unequalled track record of technology-driven, performance-proven products, Bostik grouts exceed industry standards and offer exceptional application and cleanability properties.

More than just a design element, grout is a critical component of any tile installation system's overall performance. At Bostik, we recognize the importance of grout in an installation, and have developed a range of grout solutions that allow you to select products offering the ultimate in application and performance.

### Product Features

TruColor® RapidCure™  
 Dimension® RapidCure™  
 EzPoxy™ EzClean™  
 Hydroment® Vivid™  
 Hydroment® Ceramic Tile Grout (Sanitico)  
 Hydroment® Dry Tile Grout (Unsanitico)

Characteristic	TruColor® RapidCure™	Dimension® RapidCure™	EzPoxy™ EzClean™	Hydroment® Vivid™	Hydroment® Ceramic Tile Grout (Sanitico)	Hydroment® Dry Tile Grout (Unsanitico)
Antimicrobial Protection	•	•	•	•	•	•
Stain Resistance	•	•	•	•		
Chemical Resistance	•	•	•			
Floor & Wall Application	•	•	•	•	•	•
Indoor & Outdoor Use	•	•	•	•	•	•
Color Consistency	•	•	•	•		

## Epoxy Grout

Epoxy grout offers superior stain and chemical resistance which makes them more durable and easier to maintain. Use Bostik EzPoxy™ EzClean™ grout in demanding installations such as hospitals, restaurants, airports, swimming pools and steam rooms.

### EZPOXY™ EZCLEAN™

Bostik EzPoxy™ EzClean™ is a 100% Solids Epoxy Mortar & Grout with outstanding application and clean-up properties. Use with ceramic, quarry, porcelain, granite, slate, pre-cast terrazzo, dimensional and moisture sensitive stone tiles over properly prepared concrete, structurally sound, exterior grade plywood (interior/dry use only), cement backer board, Bostik GoldPlus™ and existing ceramic tile. EzPoxy™ EzClean™ has been formulated with an advanced binder system which offers superior thermal shock resistance and remarkable ease of initial clean-up. For use in grout joints from 1/16" to 1/2".

EXCELLENT CLEANABILITY

SUPERIOR CHEMICAL RESISTANCE

MEETS ANSI A118.3 SPECIFICATION



## Pre-Mixed Grout

Pre-mixed grout offers the best of all worlds. No messy mixing, it's ready to use. Simply open, stir and apply. Start and stop the job at any time by closing the lid tightly. No fuss, no waste. **Dimension® RapidCure™** and **TruColor® RapidCure™** offer great chemical and stain resistance and may be exposed to water in just 3 days. Both products offer Clean-As-You-Go™ Technology, which eliminates down time and speeds up the installation process.



Bostik premium, pre-mixed grouts offer HXD™ Technology. Bostik HXD™ Technology contains an exceptionally high concentration of cross-linking molecules which enables only Bostik to offer the highest performance resin system of any pre-mixed grout available. This breakthrough in polymer chemistry enables Bostik premium, pre-mixed grouts to offer unmatched toughness, water and stain resistance and overall durability.

### **DIMENSION® RAPIDCURE™**

Dimension® RapidCure™ Glass-Filled, Pre-Mixed, Urethane Grout is a patented, reflective, water based, urethane grout. Dimension® RapidCure™ contains micro-glass beads and a translucent, urethane binder that both reflects light as well as allows it to pass through. This creates a variety of aesthetic effects in virtually all tile options available today. It may add an elegant sparkle and/or blend naturally with traditional tile and stone. It also creates a three dimensional effect within clear glass tile installations. It can be used in horizontal (floor) grout joint widths from 1/16" to 1/2" and vertical (wall) grout joints from 1/16" to 1/4".



### **TRUCOLOR® RAPIDCURE™**

TruColor® RapidCure™ is approved for intermittent water exposure after only 3 days of cure and full water submersion after 7 days of cure. Unlike other grouts that contain loose color pigments (which can cause staining or be washed away during the installation process), TruColor® RapidCure™ quartz aggregate is color coated to ensure perfect color consistency every time. It can be used in horizontal (floor) grout joint widths from 1/16" to 1/2" and vertical (wall) grout joints from 1/16" to 1/4".



## High Performance Cement Grout

High performance cement grout offers enhanced performance and installation characteristics when compared to a standard cement grout. This grout offers a long pot life, followed by a quick set time for those jobs that require short down times and early foot traffic. Hydroment® Vivid™ offers superior application properties and exceptional cleanability.



HyDrix™ Technology allows Bostik to precisely control the timing and formation of the chemical and physical matrix of Hydroment® Vivid™ grout during the curing process. This advancement in materials science creates a micro structurally dense internal matrix that offers you the most durable, easy to use, cement-based grout available. This water tight matrix results in a superior grout joint which resists the penetration of liquids and most staining agents while also exhibiting best in class efflorescence resistance.

### **HYDROMENT® VIVID™**

Hydroment® Vivid™ is a rapid curing, premium grade, cement-based grout for demanding commercial and residential projects. Hydroment® Vivid™ offers consistent color technology with enhanced stain and efflorescence protection, and is extremely easy to clean. It is both fiber reinforced and rapid curing, which offers early strength development for demanding, high performance installations. Hydroment® Vivid™ exceeds requirements of ANSI A118.7. For use in grout joints from 1/16" to 1/2".





## Standard Cement Grout

Standard cement grout offers an economical solution for grouting tile and stone and is available in sanded and unsanded formulations.

### HYDROMENT® CERAMIC TILE GROUT™

Hydroment® Ceramic Tile Grout™ (Sanded) is a proven blend of carefully graded quartz aggregates, portland cement, colorfast pigments and other special proprietary ingredients. It provides superior strength and durability with a wide variety of tiles. Hydroment® Ceramic Tile Grout™ Sanded is a polymer-modified grout that exceeds the requirements of ANSI A118.6 when mixed with water, and ANSI A118.7 mixed with Bostik 425™ Multi-Purpose Acrylic Latex Admixture. For use in grout joints from 1/8" to 1-1/2".

### HYDROMENT® DRY TILE GROUT™

Bostik Hydroment® Dry Tile Grout™ (Unsanded) is formulated from select grades of ground quartz, portland cement, colorfast pigments and other special proprietary ingredients. It provides superior strength and durability with a wide variety of tiles. Exceeds ANSI A118.6 when mixed with water and A118.7 when mixed with Bostik 425™ Multi-Purpose Acrylic Latex Admixture. For use in grout joints up to 1/8".

INTERIOR AND EXTERIOR, FLOORS, WALLS AND CEILING INSTALLATIONS

EXCEEDS ANSI 118.6

MIX WITH WATER OR ADDITIVE



USE WITH MARBLE

FOR USE IN GROUT JOINTS UP TO 1/8"

UNSANDED SO IT WON'T SCRATCH TILE



## Additives

Bostik additives may be used to enhance Hydroment® Ceramic Tile Grout™ (Sanded) or Bostik Hydroment® Dry Tile Grout™ (Unsanded) for better freeze/thaw resistance and improved water resistance.

### 1900™

Bostik 1900™ Epoxy Modified Grout and Mortar Admixture, when mixed with Bostik Hydroment® Ceramic Tile Grout™ (sanded only), is for interior and exterior installations to set and/or grout all ceramic, porcelain, quarry, granite, slate, marble, and dimensional stone tiles. Exceeds ANSI A118.8.

EXCELLENT WORKABILITY

EASY CLEAN-UP

SUPERIOR CHEMICAL RESISTANCE



### 425™

Bostik 425™ Multi-Purpose Acrylic Latex Admixture is a high solids acrylic emulsion designed to improve the performance of Bostik Hydroment® Ceramic Tile Grout™, Hydroment® Dry Tile Grout™ Glass-Mate™, Single-Flex® FS, Tile-Mate® mortars, UltraFinish™ Pro, Webcrete® 95, UltraRamp™ and job site prepared mortar beds.

MORTAR, GROUT AND PATCH ADMIXTURE

IMPROVED WATER RESISTANCE

IMPROVED FREEZE/THAW RESISTANCE



# Grout Coverage

## Tile Size

1 x 1 x 1/4"    2 x 2 x 1/4"    3 x 6 x 1/4"    4 x 4 x 1/4"    4 1/2 x 4 1/2 x 1/4"    4 x 8 x 1/4"    6 x 6 x 1/4"    8 x 8 x 1/4"    12 x 12 x 1/4"    12 x 12 x 3/8"    13 x 13 x 3/8"    16 x 16 x 3/8"    18 x 18 x 3/8"    18 x 18 x 1/2"    12 x 24 x 1/4"    12 x 24 x 3/8"    24 x 24 x 3/8"

TruColor® RapidCure™ & Dimension® RapidCure™ – 18 Lb Bucket																	
1/16"	63	126	209	206	214	168	189	337	771	505	547	673	1153	758	2052	1026	1010
1/8"	32	63	107	106	107	84	95	168	338	253	274	337	580	379	1032	516	505
3/16"	-	-	73	73	71	56	63	112	261	168	182	224	388	253	692	346	337
1/4"	-	-	56	56	54	42	47	84	197	126	137	168	293	189	522	261	168
3/8"	-	-	-	-	36	28	32	56	133	84	91	112	197	126	352	176	168
1/2"	-	-	-	-	27	21	24	42	102	63	68	84	149	95	267	134	126
EzPoxy™ EzClean™ – 3.5 Gal bucket																	
1/16"	55	105	164	164	174	136	152	269	604	403	436	536	904	602	1607	804	802
1/8"	30	55	84	84	89	69	77	136	304	203	220	269	454	303	809	404	403
1/4"	17	30	44	44	46	36	40	70	155	103	111	136	229	153	409	205	203
3/8"	13	21	31	31	32	25	27	48	105	70	75	92	155	103	276	138	136
1/2"	11	17	24	24	25	19	21	36	77	53	57	70	117	78	210	105	103
Hydroment® Vivid™ – 25 Lb bag																	
1/16"	107	210	333	333	354	277	312	553	1243	829	898	1104	1863	1242	3312	1656	1655
1/8"	55	107	168	168	178	139	157	278	623	415	450	553	933	622	1659	829	829
1/4"	30	55	85	85	90	70	79	140	313	209	226	278	468	312	832	416	415
3/8"	21	38	57	58	61	47	53	94	210	140	151	186	313	209	557	278	278
1/2"	17	30	44	44	47	36	40	71	158	106	114	140	236	157	419	210	209
Hydroment® Ceramic Tile Grout™ (Sanded) – 25 Lb bag																	
1/16"	100	197	313	313	332	260	293	520	1168	778	843	1037	1750	1167	3111	1556	1555
1/8"	52	100	157	158	167	131	147	261	585	390	423	520	877	584	1558	779	778
1/4"	28	52	80	80	85	66	74	131	294	196	212	261	440	293	782	391	390
3/8"	20	36	54	54	58	45	50	88	197	131	142	175	294	196	523	262	261
1/2"	16	28	41	41	44	34	38	67	149	99	107	131	221	148	394	197	196
Hydroment® Dry Tile Grout (Unsanded) – 25 Lb bag																	
1/16"	155	304	483	483	513	402	452	802	1802	1201	1301	1601	2701	1800	4801	2401	2400
1/8"	80	155	243	243	258	202	227	403	903	602	652	802	1353	902	2405	1202	1201

The Bostik Grout & Sealant Color Guide is provided for initial color selection. Colors may vary due to job site conditions, absorption of tile, mixing ratio, installation method or type of grout or sealant used. Always test in an inconspicuous area prior to installation to ensure color meets the customer's requirements. For further coverage calculations, please visit <http://bit.ly/GroutCalculator>.

## Also Available In 35 Bostik Colors!

For more information  
on **Bostik Grouts &  
Additives**, scan this code:



### PURE SILICONE™

- Waterproof sealant
- Permanently flexible
- Fast cure – tack free in 30 minutes

### TUB & TILE CAULK™ (SANDED)

- Flexible & water cleanable
- Mold & mildew resistant
- Easy to apply

BOSTIK HOTLINE™

Smart help™  
**1-800-726-7845**

Bostik, Inc.

11320 W. Watertown Plank Road  
Wauwatosa, WI 53226

[www.bostik.com/us](http://www.bostik.com/us)

