

### PRODUCT DESCRIPTION

E-Etch is an environmentally friendly industrial strength floor cleaner, degreaser and light etching product. It is ideal for cleaning and preparing cementitious surfaces for acid staining, decorative overlays, water base stains, coatings application, etc. It may also be used on concrete, stucco, terrazzo and most masonry surfaces to open up the pores on the surface and clean grime, dirt, grease, scuff marks and stains. E-Etch, when used to prepare slabs for acid staining, will have little to no effect on acid stain results. It is biodegradable and easily rinsed off with water.

### USES

- Effectively cleans and prepares floors for acid stain, overlays and sealer application
- Strong and versatile may be used for maintenance of industrial facilities, parking garages, airport runways, and loading docks
- Safer formula contains no Hydrochloric Acid
- May be used on interiors and exteriors

### FEATURES

- Removes tough and stubborn materials and stains
- Made with natural ingredients
- Biodegradable
- Concentrated
- Removes Efflorescence
- Non-Corrosive
- Contains no harmful acids or petrochemicals.
- Safe to use in restaurants, schools, hospitals, hotels, stadiums, malls, and food processing plants.

### COVERAGE RATES AND PACKAGING

- Available in 1 gallon (3.785 L) bottle.
- One gallon (3.785 L) of undiluted E-Etch will color approximately 250 square feet (23.23 m<sup>2</sup>) of concrete surface.

### STORAGE & SHELF LIFE

- DO NOT allow product to freeze.
- Shelf life is approximately 36 months.

### USE & APPLICATION

#### PRECAUTIONS:

Brickform strongly recommends jobsite samples or mockups with these products. Individuals who will be performing the work should test different sections of the concrete to determine suitability, coverage, coverage rates and final appearance.

- E-Etch is not for use on metal or any other surface that may be damaged by acidic products. Wear protective gloves and goggles during application.

Neutralize floors prior to application of water based stains or sealers.

- To prepare floors for acid staining or overlays, BRICKFORM recommends using a floor scrubber with a pad. This will provide a deeper, more thorough cleaning, that will open the concrete pores and allow for deeper penetration of the stain, and better bonding of the sealer.

#### APPLICATION:

E-ETCH is concentrated and may be used straight or reduced with up to 50% water or more depending on floor condition and dirt or grime level. Use straight for heavily soiled areas. For normal cleaning start at a medium dilution then reduce or add water content as needed. Apply solution by brush mop, sponge, or sprayer and allow soaking in into the contaminants and surface for 2 to 3 minutes, let soak for 10 to 15 minutes when cleaning heavily soiled areas, then scrub with a brush or scrubbing machine with a black or medium abrasiveness pad. After surface is clean, rinse off with clean water and remove the residue with a wet-vac. Multiple applications may be needed for heavy-duty cleaning or high dirt build up. Do Not Allow E-etch to dry on the surface



### RECOMMENDED TOOLS & CLEAN UP

- Broom
- Pump Sprayer

#### CLEAN UP:

Clean and rinse equipment with clean water immediately after application.

### COMPLEMENTARY PRODUCTS

- Neutra Clean – Cleaning and neutralizing agent
- Artesian Stain
- Blush-tone Acid Stain

### SAFETY & PRECAUTIONS

KEEP OUT OF REACH OF CHILDREN. Before using or handling, read the Safety Data Sheet and Warranty. DO NOT TAKE INTERNALLY. Do not breathe vapors or mist. Use only with adequate ventilation and use a respirator when levels are above applicable limits. Avoid contact with skin and eyes. Close container after each use. Use good hygiene when handling this product and wash and bathe after each use. Be sure to wash clothing after each use.

### WARRANTY

This product is not intended for public use and is intended for use by licensed contractors and installers, experienced and trained in the use of these products. It is warranted to be of uniform quality, within manufacturing tolerances. The manufacturer has no control over the use of this product, therefore, no warranty, expressed or implied, is or can be made either as to the effects or results of such



use. In any case, the manufacturer's obligations shall be limited to refunding the purchase price or replacing material proven defective. The end user shall be responsible for determining product's suitability and assumes all risks and liability.

E-etch

Item Number: ES-1200

For more information go to:

[solomoncolors.com](http://solomoncolors.com) or [brickform.com](http://brickform.com)



