



ROOF GARDEN

Vegetated Plugs

Overview

Carlisle Vegetated Plugs are a cost-effective method of vegetating your roof. Available in many different varieties, they are shipped in flats containing twenty-four 2.5" or seventy-two 1.5" plugs. Each flat is 10" x 20" and weighs approximately 4 pounds.

Features and Benefits

- Many varieties available
- Easy, low-cost installation
- Rapid vegetative growth

Installation

2.5" diameter plugs are recommended to be spaced 8" to 9" on center (1.78 to 2.25 plugs per square foot). 1.5" diameter plugs are recommended to be spaced 6" to 8" on center (2.25 to 4 plugs per square foot). After spacing has been determined, a 2"-deep indentation is made into the growth media, the plug is inserted, vegetation facing upwards and the growth media is tamped by hand around the submerged plug base. Once planting is complete, irrigate the Roof Garden to the point of runoff. It is mandatory that an irrigation system be used during the remainder of the establishment period. The frequency and duration of these irrigation events varies depending on installation time. To determine your project's specific irrigation requirements please refer to the Carlisle Roof Garden Care & Maintenance Requirements ("Attachment I" of the Carlisle Roof Garden specification).

Note: Product availability dependent on region and installation season.



LEED® Information

Pre-consumer Recycled Content	0%
Post-consumer Recycled Content	0%
Manufacturing Locations	Princeton, ON Mt. Vernon, WA
Solar Reflectance Index (SRI)	N/A



Scan code to view installation video.

ROOF GARDEN

Vegetated Plugs

Popular Varieties



Sedum acre 'Gold Moss'



Sedum album 'Coral Carpet'



Sedum hispanicum 'Purple Form'



Sedum kamtschaticum



Sedum kamtschaticum
'Weihenstephaner Gold'




Sedum kamtschaticum k.
variegatum




Sedum reflexum 'Blue Spruce'



Sedum rupestre 'Angelina'



Sedum sexangulare



Sedum sieboldii

Limited Warranty

Carlisle Coatings & Waterproofing Incorporated (Carlisle) warrants this product to be free of defects in workmanship and materials only at the time of shipment from our factory. If any Carlisle materials prove to contain manufacturing defects that substantially affect their performance, Carlisle will, at its option, replace the materials or refund its purchase price. This limited warranty is the only warranty extended by Carlisle with respect to its materials. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose. Carlisle specifically disclaims liability for any incidental, consequential, or other damages, including but not limited to, loss of profits or damages to a structure or its contents, arising under any theory of law whatsoever. The dollar value of Carlisle's liability and buyer's remedy under this limited warranty shall not exceed the purchase price of the Carlisle material in question.