

Pair Black Diamond® Base Sheet or Flintlastic® Ultra Glass SA with the cap membrane that best meets your needs

POPULAR TORCH-APPLIED CAP MEMBRANES, 100 SQ. FT. (1 SQ)

Product	Material	Thickness	Weight/Roll	Why Buy?
Flintlastic® GTA	APP/POLY	4.0 mm (157 mils)	103 lbs.	CertainTeed's workhorse, torch- applied cap - available in 7 colors plus CoolStar® highly-reflective granules ⁶
Flintlastic GTA-FR	APP/POLY	4.0 mm (157 mils)	103 lbs.	Same as GTA (above) plus fire-retardant additives enable incorporation in Class A ³ fire-rated systems - available in 2 colors plus CoolStar highly-reflective granules ⁶
Flintlastic STA ⁴	APP/POLY	3.8 mm (150 mils)	86 lbs.	Smooth surface installs quickly with granule-free selvage edge
Flintlastic STA Plus ⁵	APP/POLY	4.5 mm (177 mils)	98 lbs.	Same as STA (above) plus premium product allows for extended warranties
Flintlastic GTS-FR	SBS/POLY	4.0 mm (157 mils)	103 lbs.	CertainTeed's most robust torch-applied cap sheet with a high-performance, extra-tough, stress-resistant (excellent elongation) Type II polyester mat. Fire retardant additives enables incorporation in Class A ² fire-rated systems. Available with CoolStar highly-reflective granules ⁶

POPULAR HOT OR COLD-APPLIED CAP MEMBRANES

Product	Material	Thickness	Weight/Roll	Why Buy?
Flintlastic GMS	SBS/POLY	3.7 mm (146 mils)	93 lbs.	CertainTeed's workhorse, mop-applied cap - available in 4 colors
Flintlastic FR-P	SBS/POLY	4.2 mm (165 mils)	100 lbs.	See GMS (above) plus additional modified asphalt and fire-retardant additives enable incorporation in Class A ³ fire rated-systems
Flintlastic Premium FR-P	SBS/POLY	4.2 mm (165 mils)	100 lbs.	See FR-P (above) with high-performance, extra-tough, heavy-duty, stress-resistant, Type II polyester mat. Available with CoolStar highly-reflective granules ⁶

Black Diamond Base Sheet cannot be paired with cold-applied cap membranes.

³Please visit www.ul.com/database and review CertainTeed's roof systems listing: TGFUR11656 to review fire ratings associated with desired base/cap combinations.

⁴Must be coated with SMARTCOAT for warranty coverage between 12 and 20 years.

⁵Must be coated with SMARTCOAT for warranty coverage between 15 and 25 years.

⁶Premium pricing applies for CoolStar granular surfaced membranes.



Hybrid Modified Bitumen Roof Systems

Reduce Labor Costs with Self-Adhered Base Sheets combined with or paired with Torch, Hot and Cold-Applied Cap Membranes



CertainTeed

CEILINGS • DECKING • FENCE • GYPSUM • INSULATION • RAILING • ROOFING • SIDING • TRIM
20 Moores Road, Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 certainteed.com

©03/23 CertainTeed, Printed in the USA, Code No. 01-00-721-NA-EN



Self-adhered, unpenetrated, highly UV-resistant base ply



Black Diamond® Base Sheet




BLACK DIAMOND BASE SHEET IS DESIGNED FOR SPEED & ENGINEERED FOR DURABILITY.

- Reduce labor by pairing this self-adhered base ply with any torch-applied or hot asphalt-applied interply or cap membrane; cannot be paired with ply or cap sheets applied with cold adhesive
- Fiberglass reinforcement adds strength and dimensional rooftop stability
 - Up to 15-year warranty coverage without insulation
- Flexible - especially in cold temperatures due to SBS-modified asphalt
- Black Diamond slag mineral surface allows for "in the dry" exposure, up to 6 months, without risk of asphalt degradation
- Classified as a vapor retarder
- Reduce installed cost by eliminating the need for cover board - adhere directly to FlintBoard® polyisocyanurate insulation
 - You may also adhere Black Diamond Base Sheet directly to bituminous anchor sheets, DensDeck® Prime, Securock®, coated 6-side high density wood fiberboard, and primed structural concrete

Self-adhered, unpenetrated, heavy-duty base ply

Flintlastic® Ultra Glass SA



FLINTLASTIC ULTRA GLASS SA IS CERTAINTEED'S MOST ROBUST & VERSATILE SELF-ADHERED BASE.

- Reduce labor by pairing this self-adhered base ply with any ply or cap membrane applied by torch, hot asphalt or cold adhesive
- High-performance strength & wind uplift resistance
 - 70% heavier fiberglass reinforcement than Black Diamond Base Sheet
 - Up to 20-year warranty coverage without insulation
- Superior cold-temperature flexibility with twice the SBS-modified asphalt of Black Diamond Base Sheet
- Classified as a vapor retarder
- Reduce installed cost by eliminating the need for cover board - adhere directly to FlintBoard® polyisocyanurate insulation
 - You may also adhere Flintlastic Ultra Glass SA directly to bituminous anchor sheets, DensDeck® Prime, Securock®, coated 6-side high density wood fiberboard, and primed structural concrete

ROLL PROPERTIES

Material	Thickness	Weight/Roll	Coverage	ASTM
SBS/FG	1.4 mm (55 mils)	78 lbs.	200 sq. ft.	D4601, Type I, D1970

RECOMMENDED SYSTEMS¹

Warranty Duration	Insulation	Base	Interply	Torch ¹ Cap ² Hot Asphalt		
				Torch ¹	Cap ²	Hot Asphalt
15 Years	Optional	All Weather/Empire® Base Sheet (MF)	Black Diamond Base Sheet	Flintlastic® GTA, GTA-FR, or STA with SMARTCOAT™	Flintlastic	GMS or FR-P
15 Years	Optional	Black Diamond Base Sheet	—	Flintlastic GTA, GTA-FR, or STA with SMARTCOAT	Flintlastic	GMS or FR-P
20 Years	Optional	Black Diamond Base Sheet	—	Flintlastic GTA-FR CoolStar®, GTS-FR CoolStar, or STA Plus with SMARTCOAT	Flintlastic	Premium FR-P CoolStar
25 Years	Double layer second layer adhered	Black Diamond Base Sheet	Flintlastic STA	Flintlastic GTA-FR, GTS-FR or STA Plus with SMARTCOAT	Flintlastic	Premium FR-P

¹For assistance selecting systems with UL, FBC, Miami Dade and/or FM approvals, contact your local Territory Manager or CertainTeed Commercial Roofing Technical Services at 800-396-8134 x2.

²See rear side for cap membrane selection guidance.

ROLL PROPERTIES

Material	Thickness	Weight/Roll	Coverage	ASTM
SBS/FG	3.0 mm (118 mils)	72 lbs.	100 sq. ft.	D6163, Type I, D1970

RECOMMENDED SYSTEMS¹

Warranty Duration	Insulation	Base	Interply	Torch ¹ Cap ² Hot Asphalt/Cold Adhesive		
				Torch ¹	Cap ² Hot Asphalt/Cold Adhesive	
20 Years	Optional	All Weather/Empire® Base Sheet (MF)	Flintlastic Ultra Glass SA	Flintlastic GTA, GTA-FR, or STA with SMARTCOAT	Flintlastic	GMS or FR-P
20 Years	Optional	Flintlastic Ultra Glass SA	—	Flintlastic GTA, GTA-FR, or STA with SMARTCOAT	Flintlastic	GMS or FR-P
25 Years	Double layer second layer adhered	Flintlastic Ultra Glass SA	—	Flintlastic GTA-FR, GTS-FR or STA Plus with SMARTCOAT	Flintlastic	Premium FR-P

¹For assistance selecting systems with UL, FBC, Miami Dade and/or FM approvals, contact your local Territory Manager or CertainTeed Commercial Roofing Technical Services at 800-396-8134 x2.

²See rear side for cap membrane selection guidance.