

#15 Double-V Control Joint (VVJZ)

Corrosion resistant expanded flange control joint

#15 Expanded Flange Control Joint (Double-V) is used to relieve stresses in large plastered areas of walls, ceilings, and stucco areas. The Double-V Control Joint counteracts the inherent shrinkage during stucco curing and general thermal changes and provides a higher degree of corrosion resistance than the galvanized steel version. This nearly inconspicuous, expanded wing control joint minimizes cracking and assures proper plaster and stucco thickness.

- Ground heights include 3/8" for thin coat plaster and 1/2", 3/4" and 7/8" for conventional plaster applications.
- Follow use provisions outlined in ASTM C1063.
- The #15 Double-V Control Joint is also available in galvanized steel for instances when increased corrosion resistance is not required.

Product Data & Ordering Information:

Material:	.018 99.97% pure Zinc, compliant with ASTM B69
	Also available in G-60 Hot-Dipped Galvanized Steel
Dimensions:	Nominal 2-7/8" Full Wing Flange

Ground	Length	Pcs./Ctn.	Ft./Ctn.	Wt./Ctn.	Ctn./Skid
1/2"	10'	24	240	54 lbs.	27
3/4"	10'	24	240	69 lbs.	30
7/8"	10'	24	240	76 lbs.	30

Code Approvals & Performance Standards

- [ASTM B69](#) Standard Specification for Rolled Zinc
- [ASTM C1063](#) Standard Specification for Installation of Lathing and Furring to Receive Interior and Exterior Portland Cement-Based Plaster
- [ASTM C1861](#) Standard Specification for Lathing and Furring Accessories, and Fasteners, for Interior and Exterior Portland Cement-Based Plaster
- [SDS Zinc Strip](#) Cold Formed Finished Products

Storage:

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather and surface contamination conforming to ASTM C1063.

