

Product Submittal Sheet

Technical Services: 888-437-3244, Engineering Services: 877-832-3206, Sales 800-543-7140

05.40.00 (Cold-Formed Metal Framing)

BlazeFrame Shield

20ga (33mil), 18ga (43mil) or 16ga (54mil) Fire Blocking System

ClarkDietrich's BlazeFrame Shield is specifically designed for use in conjunction with approved fireblocking materials per section 718 of the IBC. BlazeFrame Shield system simply installs by twisting into stud flanges and screwing into stud webs. The one piece preformed assembly eliminates cutting, notching and attaching clips.

- · Installs quickly and easily without clips
- Available for 16" and 24" stud spacing
- Available in 20ga (33mil), 18ga (43mil) or 16ga (54mil)
- Pre-notched for use on structural studs (1-5/8" flange only)

Product Data & Ordering Information:


Material:	Yield Strength: 33ksi for 33mils & 43mils, 50ksi for 54mils
Coating:	CP60
Thickness:	33mils (20ga) STR, 0.0346" Design Thickness, 0.0329" Min. Thickness 43mils (18ga), 0.0451" Design Thickness, 0.0428" Min. Thickness 54mils (16ga), 0.0566" Design Thickness, 0.0538" Min. Thickness
Dimensions:	Horizontal leg: 1" Width: 3-5/8", 4" or 6" Lengths: for 16" o.c. and 24" o.c. stud spacing
Connection tabs:	Top: 2", Bottom: 1-1/2"

Code Approvals & Performance Standards

- ASTM A1003 Standard Specification for Steel Sheet, Carbon, Metallic- and Nonmetallic-Coated for Cold-Formed Framing Members
- ASTM C955 Standard Specification for Cold-Formed Steel Structural Framing Members
 IBC Chapter 7 Fire and Smoke Protection Features
- ClarkDietrich's BlazeFrame Shield is specifically designed for use in conjunction with approved
- ClarkDietrich's BlazeFrame Shield is specifically designed for use in conjunction with approved fireblocking materials per section 718 of the IBC.

Sustainability Credits For more details and LEED letters contact Technical Services at 888-437-3244 or visit clarkdietrich.com/LEED.

- LEED v4.1 MR Credit: Environmental Product Declarations: EPD (1 point) Sourcing of Raw Materials (up to 2 points) Material Ingredients (1 point) Construction and Demolition Waste Management (up to 2 points)
- LEED v4 MR Credit: Building Product Disclosure and Optimization: EPD (1 point) Sourcing of Raw Materials (1 point) Material Ingredients (1 point) Construction and Demolition Waste Management (up to 2 points) Innovation Credit (up to 2 points).



- 16" and 24" stud spacing
- Three available widths
- Pre-notched around flanges (1-5/8" flange only)

