

Technical Services: 888-437-3244, Engineering Services: 877-832-3206, Sales 800-543-7140


09.22.16 (Non-Structural Metal Framing)

1-1/2" Furring / Hat Channel (150F125-43)

43mil (18ga)

Geometric Properties

Depth: 1.500 in Width: 1.250 in	Design Thickness: 0.0451 in Min. steel thickness: 0.0428 in	Yield stress, Fy: 33ksi Ultimate, Fu: 45ksi
	Gross Section Properties of Ful	I Section, Strong Axis
Cross sectional area	a (A)	0.225 in ²
Member weight per	foot of length	0.764 lb/ft
Moment of inertia (b	<)	0.071 in ⁴
Radius of gyration (Rx)	0.563 in
Gross moment of in	erita (ly)	0.119 in ⁴
Gross radius of gyra	ation (Ry)	0.728 in
	Effective Section Propert	ies, Strong Axis
Moment of inertia fo	r deflection (lx)	0.071 in ⁴
Section modulus (S	x)	0.091 in ³
Allowable bending r	noment (Ma)	149.7 ft-lb
Allowable shear for	ce (Va)	613 lb



Used in framing applications:

- Furring for walls & ceilings
- Furring out masonry walls
- · Framing for drop ceilings assemblies

Product Data & Ordering Information:

Coating: CP60 (CP90 Available) **Stock length:** 10'-0" and 12'-0" long pieces **Packaging:** 10 pieces per bundle - 440 pieces per pallet **Packaging weight:** 79 lbs/bundle

Furring / Hat Channel Allowable Ceiling Spans (Deflection: L/360)

Dead Load	4 psf			6 psf			13 psf		
Hat Spacing o.c.	12"	16"	24''	12"	16''	24''	12"	16"	24''
Single Span	9'-2"	8'-4"	7'-4"	8'-0"	7'-4"	6'-4"	6'-2"	5'-8"	4'-11"
Multiple Span	11'-4"	10'-4"	9'-0"	9'-11"	9'-0"	7'-11"	7'-8"	7'-0"	6'-1"

For more span tables and table notes see: www.clarkdietrich.com/products/furring-channel-hat-channel

Code Approvals & Performance Standards

- AISI S240-20 North American Standard for Cold-Formed Steel Structural Framing
 - (Compliant to ASTM C955, but IBC replaced with AISI S200 in IBC 2015, AISI S240 in IBC 2018)
 - Section A3 Material Chemical & mechanical requirements (Referencing ASTM A1003/A1003M)
 - Section A4 Corrosion Protection (Referencing ASTM A653/A653M)
 - Section C Installation (Referencing ASTM C1007)
- SDS For ASTM A1003 Steel Framing Products For Interior Framing, Exterior Framing and Clips/Accessories

Sustainability Credits For more details and LEED letters contact Technical Services at 888-437-3244 or visit clarkdietrich.com/LEED.

- LEED v4.1 MR Credit: Environmental Product Declarations: EPD (1 point) Sourcing of Raw Materials (up to 2 points) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points)
- LEED v4 MR Credit: Building Product Disclosure and Optimization: EPD (1 point) Sourcing of Raw Materials (1 point) Material Ingredients (1 point) Construction and Demolition Waste Management (up to 2 points) Innovation Credit (up to 2 points).



