



Clark Dietrich

Drywall

09.22.00 (Support for Plaster & Gypsum Board)

Quicksilver™ Corner Bead (CBS)

Hot-dipped Metal Corner Bead

Quicksilver™ corner bead is a hot-dipped, highly durable galvanized bead that offers superior corrosion protection. This bead is ideal for humid, moisture-prone conditions and high-traffic areas subject to more than normal abuse.

Recognized as a superior corrosion-resistant drywall finishing corner bead, Quicksilver™ corner bead provides a high-quality finish and solid protection at drywall corners. This traditional drywall finishing product is nailed, stapled, screwed or clinched into place. Flanges are deeply knurled and perforated for excellent joint compound adhesion.

Product Data & Ordering Information

Material: 0.0125" min. thickness, G30 hot-dipped galvanized steel

Dimensions: 1-1/4" leg x 1-1/4" leg

Width	Length	Wt./Ctn.	Pcs./Ctn.
1-1/4" x 1-1/4"	6'-9"	56 lbs	75
1-1/4" x 1-1/4"	6'-10"	57 lbs	75
1-1/4" x 1-1/4"	7'	56 lbs	72
1-1/4" x 1-1/4"	8'	56 lbs	63
1-1/4" x 1-1/4"	9'	56 lbs	56
1-1/4" x 1-1/4"	10'	55 lbs	50
1-1/4" x 1-1/4"	12'	56 lbs	42


Code Approvals & Performance Standards

- ASTM C1047 Standard Specification for Accessories for Gypsum Wallboard and Gypsum Veneer Base
- SDS For ASTM A653 Steel Finishing Products For Interior Finishing and Exterior Finishing

Storage

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.





- Strong metal reinforcement for drywall corners
- Exposed nose of the bead resists impact and forms a screed for finishing