


Technical Services: 888-437-3244, Engineering Services: 877-832-3206, Sales 800-543-7140

## 05.40.00 (Cold-Formed Metal Framing)

## TIOF CO (FOLA: ODCO)

600T125-68 (50ksi, CP60) 600 (6") structural track with T125 (1-1/4") leg - 68mils (14ga)				
Coating: CP60 per AISI S240			Color Code: Orange	
Geometric Properties				
Web depth: 6.250 in Leg width: 1.25 in	Thickness: 68mils (14ga) Design Thickness: 0.0713 in Min. steel thickness: 0.0677 in	Yield strength, Fy: 50 ksi *Fy with Cold-Work, Fya: 50.0 ksi Ultimate, Fu: 65.0 ksi		
Gross Section Properties of Full Section, Strong Axis				
Cross sectional area (A)			0.605 in <sup>2</sup>	
Member weight per foot of length			2.06 lb/ft	
Moment of inertia (Ix)			2.970 in <sup>4</sup>	
Section Modulus (Sx)			0.951in <sup>3</sup>	
Radius of gyration (Rx)			2.216 in	
Gross moment of inerita (ly)			0.067 in <sup>4</sup>	
Gross radius of gyration (Ry)			0.332 in	
Effective Section Properties, Strong Axis				
Effective Area (Ae)			0.358 in <sup>2</sup>	
Moment of inertia for deflection (Ix)			2.934 in <sup>4</sup>	
Section modulus (Sx)			0.858 in <sup>3</sup>	
Allowable bending moment (Ma)			25.69 in-k	
Allowable shear force in web			5350 lb	
Torsional Properties				
St. Venant torsional constant (J x 1000)			1.025 in <sup>4</sup>	



· Load-bearing walls

- · Curtain walls
- Tall interior walls
- · Floor & ceiling joists
- Trusses



· Effective properties incorporate the strength increase from the cold work of forming.

## **Code Approvals & Performance Standards**

- AISI S100-16 (2020) w/S2-20 North American Specification for the Design of Cold-Formed Steel Structural Members
- AISI S240-20 North American Standard for Cold-Formed Steel Structural Framing
- (Compliant to ASTM C955, but IBC replaced with AISI S200 in IBC 2015, AISI S240 in IBC 2018)

0.483 in<sup>6</sup>

-0.503 in

0.329 in

2.296 in

0.952

- Section A3 Material Chemical & mechanical requirements (Referencing ASTM A1003/A1003M)
- Section A4 Corrosion Protection (Referencing ASTM A653/A653M)
- · Section A5 Products Thickness, shapes, tolerances, identification
- Section C Installation (Referencing ASTM C1007)
- AISI S202-20 Code of Standard Practice for Cold-Formed Steel Structural Framing o Section F3 Delivery, Handling and Storage of Materials
- IBC 2021 International Building Code

Torsional flexural constant (Beta)

Distance from shear center to neutral axis (Xo)

Distance between shear center and web centerline (m)

Warping constant (Cw)

Radii of gyration (Ro)

- ICC-ES ESR-1166P Structural Studs and Track
- ESR-1166P LABC and LARC Supplement
- ESR-1166P Catalog ClarkDietrich Structural Technical Design Guide (6/22/20)
- Intertek CCRR-0206 Structural Studs and Track
- SFIA Stud Code Compliance Certification Program
- SDS For ASTM A1003 Steel Framing Products For Interior Framing, Exterior Framing and Clips/Accessories

Sustainability Credits For more details and LEED letters contact Technical Services at 888-437-3244 or visit clarkdietrich.com/LEED.

- LEED v4.1 MR Credit: Environmental Product Declarations: EPD (1 point) - Sourcing of Raw Materials (up to 2 points) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points)
- LEED v4 MR Credit: Building Product Disclosure and Optimization: EPD (1 point) -Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) -Innovation Credit (up to 2 points).