

Technical Services: 888-437-3244, Engineering Services: 877-832-3206, Sales 800-543-7140

## 05.40.00 (Cold-Formed Metal Framing)

## 600T125-97 (50ksi, CP60)

600 (6") structural track with T125 (1-1/4") leg - 97mils (12ga)

Coating: CP60 per AISI S240


Color Code: Red

## **Geometric Properties**

Web depth: 6.356 in<br/>Leg width: 1.25 inThickness: 97mils (12ga)<br/>Design Thickness: 0.1017 in<br/>Min. steel thickness: 0.0966 in

Yield strength, Fy: 50 ksi \*Fy with Cold-Work, Fya: 50.0 ksi Ultimate, Fu: 65.0 ksi

Gross Section Properties of Full Section, Strong Axis	
Cross sectional area (A)	0.862 in <sup>2</sup>
Member weight per foot of length	2.93 lb/ft
Moment of inertia (Ix)	4.282 in <sup>4</sup>
Section Modulus (Sx)	1.348in <sup>3</sup>
Radius of gyration (Rx)	2.229 in
Gross moment of inerita (ly)	0.092 in <sup>4</sup>
Gross radius of gyration (Ry)	0.327 in
Effective Section Properties, Strong Axis	
Effective Area (Ae)	0.661 in <sup>2</sup>
Moment of inertia for deflection (lx)	4.281 in <sup>4</sup>
Section modulus (Sx)	1.347 in <sup>3</sup>
Allowable bending moment (Ma)	45.31 in-k
Allowable shear force in web	10885 lb
Torsional Properties	
St. Venant torsional constant (J x 1000)	2.973 in <sup>4</sup>
Warping constant (Cw)	0.685 in <sup>6</sup>
Distance from shear center to neutral axis (Xo)	-0.491 in
Distance between shear center and web centerline (m)	0.321 in
Radii of gyration (Ro)	2.305 in
Torsional flexural constant (Beta)	0.955



Load-bearing walls

Curtain walls

Tall interior walls

Floor & ceiling joists

Trusses



• Effective properties incorporate the strength increase from the cold work of forming.

## **Code Approvals & Performance Standards**

- AISI S100-16 (2020) w/S2-20 North American Specification for the Design of Cold-Formed Steel Structural Members
- AISI S240-20 North American Standard for Cold-Formed Steel Structural Framing
- (Compliant to ASTM C955, but IBC replaced with AISI S200 in IBC 2015, AISI S240 in IBC 2018)
- Section A3 Material Chemical & mechanical requirements (Referencing ASTM A1003/A1003M)
- Section A4 Corrosion Protection (Referencing ASTM A653/A653M)
- · Section A5 Products Thickness, shapes, tolerances, identification
- Section C Installation (Referencing ASTM C1007)
- AISI S202-20 Code of Standard Practice for Cold-Formed Steel Structural Framing
  Section F3 Delivery, Handling and Storage of Materials
- IBC 2021 International Building Code
- ICC-ES ESR-1166P Structural Studs and Track
- ESR-1166P LABC and LARC Supplement
- ESR-1166P Catalog ClarkDietrich Structural Technical Design Guide (6/22/20)
- Intertek CCRR-0206 Structural Studs and Track
- SFIA Stud Code Compliance Certification Program
- SDS For ASTM A1003 Steel Framing Products For Interior Framing, Exterior Framing and Clips/Accessories

**Sustainability Credits** For more details and LEED letters contact Technical Services at 888-437-3244 or visit clarkdietrich.com/LEED.

- LEED v4.1 MR Credit: Environmental Product Declarations: EPD (1 point) - Sourcing of Raw Materials (up to 2 points) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points)
- LEED v4 MR Credit: Building Product Disclosure and Optimization: EPD (1 point) -Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) -Innovation Credit (up to 2 points).