

1150T150-54 (50ksi, CP60)
1150 (11-1/2") structural track with T150 (1-1/2") leg - 54mils (16ga)
Coating: CP60 per AISI S240

Color Code: Green

Geometric Properties

Web depth: 11.698 in **Thickness:** 54mils (16ga) **Yield strength, Fy:** 50 ksi
Leg width: 1.50 in **Design Thickness:** 0.0566 in ***Fy with Cold-Work, Fya:** 50.0 ksi
Min. steel thickness: 0.0538 in **Ultimate, Fu:** 65.0 ksi

Gross Section Properties of Full Section, Strong Axis

Cross sectional area (A)	0.820 in ²
Member weight per foot of length	2.79 lb/ft
Moment of inertia (Ix)	12.904 in ⁴
Section Modulus (Sx)	2.206 in ³
Radius of gyration (Rx)	3.967 in
Gross moment of inertia (Iy)	0.102 in ⁴
Gross radius of gyration (Ry)	0.353 in

Effective Section Properties, Strong Axis

Effective Area (Ae)	0.244 in ²
Moment of inertia for deflection (Ix)	10.896 in ⁴
Section modulus (Sx)	1.255 in ³
Allowable bending moment (Ma)	37.56 in-k
Allowable shear force in web	1414 lb


Torsional Properties

St. Venant torsional constant (J x 1000)	0.876 in ⁴
Warping constant (Cw)	2.757 in ⁶
Distance from shear center to neutral axis (Xo)	-0.467 in
Distance between shear center and web centerline (m)	0.317 in
Radii of gyration (Ro)	4.010 in
Torsional flexural constant (Beta)	0.986

- Effective properties incorporate the strength increase from the cold work of forming.
- **Web-height to thickness ratio exceeds 200. Web Stiffeners are required at all support points and concentrated loads.**

Code Approvals & Performance Standards

- **AISI S100-16 (2020) w/S2-20** North American Specification for the Design of Cold-Formed Steel Structural Members
- **AISI S240-20** North American Standard for Cold-Formed Steel Structural Framing
 - (Compliant to ASTM C955, but IBC replaced with AISI S200 in IBC 2015, AISI S240 in IBC 2018)
 - Section A3 Material - Chemical & mechanical requirements (Referencing ASTM A1003/A1003M)
 - Section A4 Corrosion Protection (Referencing ASTM A653/A653M)
 - Section A5 Products - Thickness, shapes, tolerances, identification
 - Section C Installation - (Referencing ASTM C1007)
- **AISI S202-20** Code of Standard Practice for Cold-Formed Steel Structural Framing
 - Section F3 Delivery, Handling and Storage of Materials
- **SDS For ASTM A1003 Steel Framing Products** For Interior Framing, Exterior Framing and Clips/Accessories



- Load-bearing walls
- Curtain walls
- Tall interior walls
- Floor & ceiling joists
- Trusses



Sustainability Credits For more details and LEED letters contact Technical Services at 888-437-3244 or visit clarkdietrich.com/LEED.

- **LEED v4.1 MR Credit:** Environmental Product Declarations: EPD (1 point) - Sourcing of Raw Materials (up to 2 points) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points)
- **LEED v4 MR Credit:** Building Product Disclosure and Optimization: EPD (1 point) - Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) - Innovation Credit (up to 2 points).