

362T250-43 (33ksi, CP60)
362 (3-5/8") structural track with T250 (2-1/2") leg - 43mils (18ga)
Coating: CP60 per AISI S240

Color Code: Yellow

Geometric Properties
Web depth: 3.786 in

Thickness: 43mils (18ga)

Yield strength, Fy: 33 ksi

Leg width: 2.50 in

Design Thickness: 0.0451 in

***Fy with Cold-Work, Fya:** 33.0 ksi

Min. steel thickness: 0.0428 in

Ultimate, Fu: 45.0 ksi

Gross Section Properties of Full Section, Strong Axis

Cross sectional area (A)	0.389 in ²
Member weight per foot of length	1.32 lb/ft
Moment of inertia (Ix)	0.966 in ⁴
Section Modulus (Sx)	0.510 in ³
Radius of gyration (Rx)	1.577 in
Gross moment of inertia (Iy)	0.260 in ⁴
Gross radius of gyration (Ry)	0.818 in

Effective Section Properties, Strong Axis

Effective Area (Ae)	0.181 in ²
Moment of inertia for deflection (Ix)	0.713 in ⁴
Section modulus (Sx)	0.282 in ³
Allowable bending moment (Ma)	5.56 in-k
Allowable shear force in web	1739 lb


Torsional Properties

St. Venant torsional constant (J x 1000)	0.263 in ⁴
Warping constant (Cw)	0.641 in ⁶
Distance from shear center to neutral axis (Xo)	-1.702 in
Distance between shear center and web centerline (m)	0.990 in
Radii of gyration (Ro)	2.460 in
Torsional flexural constant (Beta)	0.521

- Effective properties incorporate the strength increase from the cold work of forming.

Code Approvals & Performance Standards

- [AISI S100-16 \(2020\) w/S2-20](#) North American Specification for the Design of Cold-Formed Steel Structural Members
- [AISI S240-20](#) North American Standard for Cold-Formed Steel Structural Framing
 - (Compliant to ASTM C955, but IBC replaced with AISI S200 in IBC 2015, AISI S240 in IBC 2018)
 - Section A3 Material - Chemical & mechanical requirements (Referencing ASTM A1003/A1003M)
 - Section A4 Corrosion Protection (Referencing ASTM A653/A653M)
 - Section A5 Products - Thickness, shapes, tolerances, identification
 - Section C Installation - (Referencing ASTM C1007)
- [AISI S202-20](#) Code of Standard Practice for Cold-Formed Steel Structural Framing
 - Section F3 Delivery, Handling and Storage of Materials
- [IBC 2021](#) International Building Code
- [ICC-ES ESR-1166P](#) Structural Studs and Track
 - [ESR-1166P LABC and LARC](#) Supplement
 - [ESR-1166P Catalog](#) ClarkDietrich Structural Technical Design Guide (6/22/20)
- [Intertek CRR-0206](#) Structural Studs and Track
- [SFIA Stud](#) Code Compliance Certification Program
- [SDS For ASTM A1003 Steel Framing Products](#) For Interior Framing, Exterior Framing and Clips/Accessories



- Load-bearing walls
- Curtain walls
- Tall interior walls
- Floor & ceiling joists
- Trusses



Sustainability Credits For more details and LEED letters contact Technical Services at 888-437-3244 or visit clarkdietrich.com/LEED.

- **LEED v4.1 MR Credit:** Environmental Product Declarations: EPD (1 point) - Sourcing of Raw Materials (up to 2 points) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points)
- **LEED v4 MR Credit:** Building Product Disclosure and Optimization: EPD (1 point) - Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) - Innovation Credit (up to 2 points).