


Technical Services: 888-437-3244, Engineering Services: 877-832-3206, Sales 800-543-7140

05.40.00 (Cold-Formed Metal Framing)

1200T300-68 (50) 1200 (12") structural tr	<mark>(Si, CP60)</mark> ack with T300 (3'') leg - 68mils	(14ga)
Coating: CP60 per AISI S240		Color Code: Orange
Geometric Properti	es	
Web depth: 12.250 in Leg width: 3.00 in	Thickness: 68mils (14ga) Design Thickness: 0.0713 in Min. steel thickness: 0.0677 in	Yield strength, Fy: 50 ksi *Fy with Cold-Work, Fya: 50.0 ksi Ultimate, Fu: 65.0 ksi
Gross Section Properties of Full Section, Strong Axis		
Cross sectional area (A)		1.282 in ²
Member weight per foot of length		4.36 lb/ft
Moment of inertia (Ix)		26.087 in ⁴
Section Modulus (Sx)		4.259in ³
Radius of gyration (Rx)		4.510 in
Gross moment of inerita (ly)		0.932 in ⁴
Gross radius of gyration (Ry)		0.852 in
	Effective Section Properties,	
Effective Area (Ae)		0.393 in ²
Moment of inertia for deflection (lx)		20.345 in ⁴
Section modulus (Sx)		2.140 in ³
Allowable bending moment (Ma)		64.06 in-k
Allowable shear force in web		2713 lb
	Torsional Propertie	es
St. Venant torsional constant (J x 1000)		2.173 in ⁴
Warping constant (Cw)		25.471 in ⁶
Distance from shear center to neutral axis (Xo)		-1.369 in
Distance between shear center and web centerline (m)		0.880 in
Radii of gyration (Ro)		4.790 in
Torsional flexural constant (Beta)		0.918



Load-bearing walls

Curtain walls

Tall interior walls

· Floor & ceiling joists

Trusses



• Effective properties incorporate the strength increase from the cold work of forming.

Code Approvals & Performance Standards

- AISI S100-16 (2020) w/S2-20 North American Specification for the Design of Cold-Formed Steel Structural Members
- AISI S240-20 North American Standard for Cold-Formed Steel Structural Framing
- (Compliant to ASTM C955, but IBC replaced with AISI S200 in IBC 2015, AISI S240 in IBC 2018)
- Section A3 Material Chemical & mechanical requirements (Referencing ASTM A1003/A1003M)
- Section A4 Corrosion Protection (Referencing ASTM A653/A653M)
- · Section A5 Products Thickness, shapes, tolerances, identification
- Section C Installation (Referencing ASTM C1007)
- IBC 2021 International Building Code
- ICC-ES ESR-1166P Structural Studs and Track
- ESR-1166P LABC and LARC Supplement
- ESR-1166P Catalog ClarkDietrich Structural Technical Design Guide (6/22/20)
- Intertek CCRR-0206 Structural Studs and Track
- SFIA Stud Code Compliance Certification Program
- SDS For ASTM A1003 Steel Framing Products For Interior Framing, Exterior Framing and Clips/Accessories

Sustainability Credits For more details and LEED letters contact Technical Services at 888-437-3244 or visit clarkdietrich.com/LEED.

- LEED v4.1 MR Credit: Environmental Product Declarations: EPD (1 point) - Sourcing of Raw Materials (up to 2 points) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points)
- LEED v4 MR Credit: Building Product Disclosure and Optimization: EPD (1 point) -Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) -Innovation Credit (up to 2 points).