

**725T350-97 (50ksi, CP60)**
**725 (7-1/4") structural track with T350 (3-1/2") leg - 97mils (12ga)**
**Coating:** CP60 per AISI S240

**Color Code:** Red

**Geometric Properties**
**Web depth:** 7.606 in

**Thickness:** 97mils (12ga)

**Yield strength, Fy:** 50 ksi

**Leg width:** 3.50 in

**Design Thickness:** 0.1017 in

**\*Fy with Cold-Work, Fya:** 50.0 ksi

**Min. steel thickness:** 0.0966 in

**Ultimate, Fu:** 65.0 ksi

**Gross Section Properties of Full Section, Strong Axis**

|                                  |                        |
|----------------------------------|------------------------|
| Cross sectional area (A)         | 1.447 in <sup>2</sup>  |
| Member weight per foot of length | 4.92 lb/ft             |
| Moment of inertia (Ix)           | 13.206 in <sup>4</sup> |
| Section Modulus (Sx)             | 3.473 in <sup>3</sup>  |
| Radius of gyration (Rx)          | 3.021 in               |
| Gross moment of inertia (Iy)     | 1.769 in <sup>4</sup>  |
| Gross radius of gyration (Ry)    | 1.106 in               |

**Effective Section Properties, Strong Axis**

|                                       |                        |
|---------------------------------------|------------------------|
| Effective Area (Ae)                   | 0.754 in <sup>2</sup>  |
| Moment of inertia for deflection (Ix) | 10.901 in <sup>4</sup> |
| Section modulus (Sx)                  | 2.318 in <sup>3</sup>  |
| Allowable bending moment (Ma)         | 69.40 in-k             |
| Allowable shear force in web          | 10885 lb               |

**Torsional Properties**

|  |                        |
|--|------------------------|
| St. Venant torsional constant (J x 1000)             | 4.989 in <sup>4</sup>  |
| Warping constant (Cw)                                | 17.609 in <sup>6</sup> |
| Distance from shear center to neutral axis (Xo)      | -2.102 in              |
| Distance between shear center and web centerline (m) | 1.266 in               |
| Radii of gyration (Ro)                               | 3.843 in               |
| Torsional flexural constant (Beta)                   | 0.701                  |

- Effective properties incorporate the strength increase from the cold work of forming.

**Code Approvals & Performance Standards**

- [AISI S100-16 \(2020\) w/S2-20](#) North American Specification for the Design of Cold-Formed Steel Structural Members
- [AISI S240-20](#) North American Standard for Cold-Formed Steel Structural Framing
  - (Compliant to ASTM C955, but IBC replaced with AISI S200 in IBC 2015, AISI S240 in IBC 2018)
  - Section A3 Material - Chemical & mechanical requirements (Referencing ASTM A1003/A1003M)
  - Section A4 Corrosion Protection (Referencing ASTM A653/A653M)
  - Section A5 Products - Thickness, shapes, tolerances, identification
  - Section C Installation - (Referencing ASTM C1007)
- [AISI S202-20](#) Code of Standard Practice for Cold-Formed Steel Structural Framing
  - Section F3 Delivery, Handling and Storage of Materials
- [SDS For ASTM A1003 Steel Framing Products](#) For Interior Framing, Exterior Framing and Clips/Accessories



- Load-bearing walls
- Curtain walls
- Tall interior walls
- Floor & ceiling joists
- Trusses



**Sustainability Credits** For more details and LEED letters contact Technical Services at 888-437-3244 or visit [clarkdietrich.com/LEED](http://clarkdietrich.com/LEED).

- **LEED v4.1 MR Credit:** Environmental Product Declarations: EPD (1 point) - Sourcing of Raw Materials (up to 2 points) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points)
- **LEED v4 MR Credit:** Building Product Disclosure and Optimization: EPD (1 point) - Sourcing of Raw Materials (1 point) - Material Ingredients (1 point) - Construction and Demolition Waste Management (up to 2 points) - Innovation Credit (up to 2 points).