

## PRO-Bull 3/4" Archway

### Bullnose Corner Bead

3/4" radius bullnose corner bead designed with slotted flange that easily forms to curves and arches with a soft, rounded finish. Notched flanges enable this bead to be arched to an inside or outside radius.

Each tab on the archway bead should be secured with adhesive or staples before application of joint compound. Multiple perforations along the flanges enhance joint compound bond.

### Product Data & Ordering Information:

Product Code	Radius	Flanges	Length	Pcs./Ctn.
PROBULL A-8	3/4"	7/8"	8'	35
PROBULL A-10	3/4"	7/8"	10'	35

### Code Approvals & Performance Standards

- [ASTM C840](#) Standard Specification for Application and Finishing of Gypsum Board
- [ASTM C1047](#) Standard Specification for Accessories for Gypsum Wallboard and Gypsum Veneer Base
- [ASTM D1784](#) Standard Classification System and Basis for Specification for Rigid Poly(Vinyl Chloride) (PVC) Compounds and Chlorinated Poly(Vinyl Chloride) (CPVC) Compounds
- [ASTM D3678](#) Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) Interior - Profile Extrusions
- [SDS Vinyl Corp](#) PVC Compounds

### Storage:

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.

