

09.22.00 (Support for Plaster & Gypsum Board)

Partition End Caps

Drvwall

2-1/2" and 3-5/8" Partition End Cap

Partition End Caps quickly finish doorways, knee walls and wall ends by capping the ends of a wall and providing a finish face. Vinyl partition end caps are designed with a special factory punched slotted flange. The slots can be cut easily to form arches or curves. This product provides time (cost) savings through single-piece installation versus installing two corner beads. You also use less compound than two corner bead applications. Multiple perforations enhance strength of joint compound adhesion. Easy to cut, rust proof and dent resistant.

Product Data & Ordering Information:

Material: 0.028" PVC (Polyvinyl Chloride) Dimensions: 2-1/2" & 3-5/8" widths

Product code	Board thickness	Overall width	"T" slotted flanges	Length	Pcs./Ctn.
PEC50-358-10	1/2"	4-5/8"	1-1/8"	10'	10
PEC58-358-10	5/8"	4-7/8"	1-1/8"	10'	10
PEC50-250-10	1/2"	3-1/2"	1-1/8"	10'	10
PEC58-250-10	5/8"	3-3/4"	1-1/8"	10'	10


 $\begin{array}{l} \mathsf{PEC50-358} = 3\text{-}5/8" \text{ stud with } 1/2" \text{ gypsum board each side for an overall width of } 4\text{-}5/8"\\ \mathsf{PEC58-358} = 3\text{-}5/8" \text{ stud with } 5/8" \text{ gypsum board each side for an overall width of } 4\text{-}7/8"\\ \mathsf{PEC50-250} = 2\text{-}1/2" \text{ stud with } 1/2" \text{ gypsum board each side for an overall width of } 3\text{-}1/2"\\ \mathsf{PEC58-250} = 2\text{-}1/2" \text{ stud with } 5/8" \text{ gypsum board each side for an overall width of } 3\text{-}3/4"\\ \end{array}$

Code Approvals & Performance Standards

- ASTM C840 Standard Specification for Application and Finishing of Gypsum Board
- ASTM C841 Standard Specification for Installation of Interior Lathing and Furring
- ASTM C1047 Standard Specification for Accessories for Gypsum Wallboard and Gypsum Veneer Base
- ASTM D3678 Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) Interior Profile Extrusions
 SDS Vinyl Corp PVC Compounds

Storage:

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.



- · Rust proof and dent resistant
- Available for 1/2" and 5/8" gypsum wallboard
- One-piece installed cost savings
- · Easily forms arches or curves

