

Technical Services: 888-437-3244, Engineering Services: 877-832-3206, Sales 800-543-7140

Plaster

09.22.00 (Support for Plaster & Gypsum Board)

Zinc Mini-Bead[™] 800 (ZB80) and 900 (ZB90)

Zinc Corner Bead

Zinc Mini-Bead[™] 800 and 900 are fine-mesh corner beads used to provide corner reinforcement for onecoat and two-coat veneer plaster systems. 1-1/4" wide fine-mesh flanges are tapered along the outer edges to enhance veneer plaster concealment. Mini-Bead[™] 800 has 1/16" grounds for one-coat veneer plaster and 90 keys per linear foot for excellent bonding and strong corners. Mini-Bead[™] 900 has 3/32" grounds for two-coat veneer plaster systems. Flange attachments can be accomplished by either nailing or stapling.

Product Data & Ordering Information

Material: .012" 99.97% pure Zinc, compliant with ASTM B-69 Also available in G-30 Hot-Dipped Galvanized Steel Dimensions: 1-1/4" x 1-1/4"


Product Data & Ordering Information:

Product Code	Ground	Flanges	Length	Wt./Ctn.	Pcs./Ctn.
ZB80	1/16"	1-1/4" x 1-1/4"	10'	42 lbs	60
ZB90	3/32"	1-1/4" x 1-1/4"	10'	42 lbs	60

Code Approvals & Performance Standards

ASTM B69 Standard Specification for Rolled Zinc

- ASTM C841 Standard Specification for Installation of Interior Lathing and Furring
- SDS Zinc Strip Cold Formed Finished Products



- Mini-mesh flanges for keying
- Eliminates shadowing
- Zinc coated for corrosion protection
- Also available in Galvanized

