ConcreteSealersUSA

Professional Concrete Solutions You Can Trust

PS104 Lithium Silicate w/ Siliconate Densifier WB Penetrating Sealer

Page 1

Identification

1

PRODUCT NAME: PS104 Lithium Silicate w/ Siliconate Densifier WB Penetrating Sealer PRODUCT CODES: PS104 MANUFACTURER: Concrete Sealers USA STREET ADDRESS: P.O. Box 5464 CITY, STATE, ZIP: De Pere, WI 54115 INFORMATION PHONE: 888-583-2991 EMERGENCY PHONE: 800-424-9300 FAX PHONE: N/A DATE REVISED: 11/30/24 Chemical Name or Class: Lithium Silicate Mixture w/ Siliconate

2 Hazard(s) Identification

Hazard Overview

GHS Classification: Serious eye irritation category 1, Skin corrosion/irritation category 1C Label Elements: Corrosion **GHS Label Elements and Precautionary Statements: Hazard Statements:** Danger: Causes severe skin burns and eye damage. Danger: Causes serious eye damage. **Precautionary statements:** P102 Keep out of reach of children. P103 Read label before use. P260 Do not breathe dust/fume/gas/mist/vapours/spray. P264 Wash hands thoroughly after handling. P280 Wear protective gloves/protective clothing/eye protection/face protection. **Response:** P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/Take off Immediately all contaminated clothing. Rinse SKIN with water/shower. P303 + P361 + P353 Wash contaminated clothing before reuse. P363 P304 + P340IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P310 Immediately call a POISON CENTER or doctor/physician. P321 If skin irritation or burns develop, Call a doctor/physician. P305 + P351 + P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Store locked up.

Storage:

P405

Concrete Sealers USA | P.O. Box 5464 | De Pere, WI 54115 Toll-Free: 888.583.2991 | Emergency: 800.424.9300 info@concretesealersusa.com | www.concretesealersusa.com

C ancQ

PS104 Lithium Silicate w/ Siliconate Densifier WB Penetrating Sealer

Disposal:							
P501		Dispose of contents/container to a waste disposal facility in accordance with local, state, federal or international laws.					
HMIS HAZARD C	LASSIFICATION						
HEALTH: 1	FLAMMABILITY: 1	REACTIVITY: 0	PERSONAL PROTECTIVE EQUIPMENT: B				
POTENTIAL HEAL	TH EFFECTS						
EYES: DIRECT CO	NTACT CAN BURN EYES AN	D CAUSE POSSIBLE PERM	ANENT INJURY.				
SKIN: CONTACT W	/ITH SKIN CAN CAUSE BURN	IS OR IRRITATION.					
INGESTION: CAN	CAUSE BURNS TO THE MOL	JTH, THROAT OR DIGESTIV	E SYSTEM IF SWALLOWED.				
INHALATION: MI	ST MAY SERIOUSLY IRRIT	TATE NOSE, THROAT, AN	D LUNGS DEPENDING ON CONCENTRATION AND DURATION OF				
EXPOSURE.							
HEALTH HAZARD	S (ACUTE AND CHRONIC):	CONTACT CAN CAUSE BU	RNS TO EYES OR SKIN. CONTACT CAN CAUSE IRRITATION.				
MEDICAL CONDIT	TIONS GENERALLY AGGRA	VATED BY EXPOSURE: NO	DNE KNOWN.				
CARCINOGENICIT	Y						
OSHA: NO NT	P: NO IARC: NO						
	OF THIS PRODUCT ARE LIS						

Composition / Information on Ingredients								
INGREDIENT	CAS NO.	OSHA PEL	ACGIH TLV	OSHA STEL	WEIGHT %			
LITHIUM SILICATE	12627-14-4	NONE	NONE	NONE	4-7			
POTASSIUM METHYL SILICONATE WATER	31795-24-1 7732-18-5	NONE NONE	NONE NONE	NONE NONE	4-7 60-100			

SECTION 3 NOTES: No toxic chemical(s) subject to reporting requirements of section 313 of Title III and of 40 CFR 372.

Note: Ingredients listed without percentages, the percentages are considered a trade secret.

4 First-Aid Measures

EYES: IMMEDIATELY FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES AND SEEK MEDICAL ATTENTION.

SKIN: FLUSH SKIN IMMEDIATELY WITH WATER FOR AT LEAST 15 MINUTES AND SEEK MEDICAL ATTENTION IF NECESSARY.

INGESTION: DO NOT INDUCE VOMITING AND SEEK MEDICAL ATTENTION.

INHALATION: REMOVE TO FRESH AIR AREA AND RECEIVE MEDICAL ATTENTION IF ILL EFFECTS PERSIST.

NOTES TO PHYSICIANS OR FIRST AID PROVIDERS: IN ALL CASES OF EXPOSURE, TREAT ACCORDING TO PERSON'S CONDITION AND SPECIFIC EFFECTS OF EXPOSURE.

PS104 Lithium Silicate w/ Siliconate Densifier WB Penetrating Sealer

Page 3

5 Fire-Fighting Measures

 FLAMMABLE LIMITS IN AIR,
 UPPER: N/A

 (% by volume)
 LOWER: N/A

 FLASH POINT: >212°F
 METHOD USED: SETA FLASH

 EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.
 SPECIAL FIRE FIGHTING PROCEDURES: SELF CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS.

UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE KNOWN.

6 Accidental Release Measures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WEAR THE APPROPRIATE SAFETY EQUIPMENT. DYKE MATERIAL AND TAKE UP REMAINDER WITH ABSORBANT TO SALVAGE CONTAINER.

7 Handling and Storage

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: WEAR SUITABLE PROTECTIVE CLOTHING TO AVOID CONTACT WITH MATERIAL. WEAR NEOPRENE OR RUBBER GLOVES. WEAR SPLASH GOGGLES WITH SIDE SHIELDS. STORE AWAY FROM HIGH HEAT, CONTACT WITH FLAMES AND/OR SPARKS. KEEP MATERIAL IN SEALED CONTAINERS THAT ARE PROPERLY LABELED. DO NOT ALLOW MATERIAL TO FREEZE. **OTHER PRECAUTIONS:** USE GENERAL SAFETY PRECAUTIONS WHEN USING THIS MATERIAL. WASH HANDS BEFORE USING TOILET FACILITIES. REMOVE CONTAMINATED CLOTHING PROMPTLY.

8 Exposure Controls / Personal Protection

RESPIRATORY PROTECTION: AVOID THE INHALATION OF ANY MISTS THAT MAY BE GENERATED IN THE APPLICATION PROCESS. **VENTILATION:** PROVIDE FOR ADEQUATE GENERAL VENTILATION.

PROTECTIVE GLOVES: IMPERVIOUS GLOVES, NEOPRENE OR RUBBER.

EYE PROTECTION: SPLASH PROOF GOGGLES OR SAFETY GLASSES WITH SIDE SHIELDS.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: PROVIDE NECESSARY CLOTHING AND SAFETY EQUIPMENT TO PREVENT CONTACT WITH MATERIAL.

WORK HYGIENIC PRACTICES: TYPICAL HYGENIC PRACTICES SHOULD BE EMPLOYED TO PREVENT EXPOSURE AND CONTACT TO MATERIAL. SEE SECTION 3 FOR OCCUPATIONAL EXPOSURE LIMIT VALUES.

9 Physical and Chemical Properties

APPEARANCE AND ODOR: TRANSPARENT WHITE OR COLORLESS LIQUID WITH SLIGHT ODOR BOILING POINT OR RANGE: 0°F - 212°F VAPOR DENSITY (AIR = 1): N/A SPECIFIC GRAVITY (H2O = 1): 1.0 EVAPORATION RATE: N/A

Page 4

PS104 Lithium Silicate w/ Siliconate Densifier WB Penetrating Sealer

9 Physical and Chemical Properties (Continued)

SOLUBILITY IN WATER: NOT DETERMINED Odor Threshhold: N/A pH: <10 Melting point/freezing point: N/A Vapor Pressure: N/A Auto Ignition Temperature: N/A Partition Coefficient: n-octanol/water: N/A Decomposition Temperature: N/A

10 Stability and Reactivity

STABILITY: STABLE.

CONDITIONS TO AVOID (STABILITY): NONE KNOWN. INCOMPATIBILITY (MATERIAL TO AVOID): AVOID CONTACT WITH OXIDIZING MATERIALS. HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: CARBON OXIDES AND TRACES OF INCOMPLETE CARBON COMPOUNDS, SILICON DIOXIDE (HIGH HEAT), METAL OXIDES AND FORMALDEHYDE. HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

11 Toxicological Information

No data for the product itself.

Component data:

Component: LITHIUM SILICATE CAS# 12627-14-4. Acute Data: When tested for primary irritation potential, a similar material caused moderate irritation to the eyes and moderate irritation to the skin. Subchronic Data: Repeated ingestion or ingestion of large doses of soluble lithium compounds is reported to cause temporary mental function impairment. Special Studies: Repeated ingestion or ingestion of large doses of soluble lithium compounds during pregnancy is reported to cause fetal abnormalities. Frequent ingestion over extended periods of time of gram quantities of silicates is associated with the formation of kidney stones and other siliceous urinary calculi in humans. Lithium silicate is not listed by IARC, NTP or OSHA as a carcinogen.

Ingredient: POTASSIUM METHYL SILICONATE.

Acute toxicity not classified based on available information.

Skin corrosion/irritation: Rabbit Result: Corrosive after 3 minutes or less of exposure Remarks: Based on data from similar materials. **Serious eye damage/eye irritation:** Rabbit Result: Irreversible effects on the eye Remarks: Based on test data.

Respiratory or skin sensitization: Skin sensitization: Not classified based on available information. Respiratory sensitization: Not classified based on available information.

Germ cell mutagenicity: Not classified based on available information.

Carcinogenicity: Not classified based on available information.

Reproductive toxicity: Not classified based on available information.

STOT-single exposure: Not classified based on available information.

STOT-repeated exposure: Not classified based on available information.

Toll-Free: 888.583.2991 | Emergency: 800.424.9300 info@concretesealersusa.com | www.concretesealersusa.com

PS104 Lithium Silicate w/ Siliconate Densifier WB Penetrating Sealer

Page 5

12 Ecological Information

No data for the product itself.

Component data:

Component: LITHIUM SILICATE CAS# 12627-14-4. Eco toxicity: This product has not been tested for ecotoxicity potential. Environmental Fate: The high pH of this material may be acutely harmful to aquatic life. It does not contribute to BOD. Physical/Chemical: Sinks and mixes with water. Only water will evaporate from this material.

Ingredient: POTASSIUM METHY SILICONATE. No available data.

13 Disposal Considerations

WASTE DISPOSAL METHOD: DISPOSE OF THE MATERIAL IN A WASTE DISPOSAL SITE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL LAWS.

14 Transport Information

DOT: Not Regulated **IMO/IMDG:** Not Regulated

15 Regulatory Information

No data for the product itself.

Component data:

Component: LITHIUM SILICATE CAS# 12627-14-4. CERCLA: No CERCLA Reportable Quantity has been established for this material. SARA TITLE III: Not an Extremely Hazardous Substance under §302. Not a Toxic Chemical under §313. Hazard Categories under §§311/312: Acute TSCA: All ingredients of this material are listed on the TSCA inventory. Component is on the Canada DSL list.

Ingredients: Potassium Methyl Siliconate and Water.

SARA 304 Extremely Hazardous Substances Reportable Quantity. This material does not contain any components with a section 304 EHS RQ. SARA 311/312 Hazards: Acute Health Hazard SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302. SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313. US State Regulations Pennsylvania Right To Know and New Jersey Right to Know: Water CAS# 7732-18-5 50, Potassium Methyl Siliconate CAS# 31795-24-1. The ingredients of this product are reported in the following inventories: KECI: All ingredients listed, exempt or notified. REACH: All ingredients (pre-)registered or exempt. TSCA: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances. AICS: All ingredients listed or exempt. IECSC: All ingredients listed or exempt. PICCS: All ingredients listed or exempt. DSL: All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL). ENCS/ISHL: All components are listed on ENCS/ISHL or exempted from inventory listing. NZIoC: All ingredients listed or exempt. INventories AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), NECSI (Taiwan), TSCA (USA).

PS104 Lithium Silicate w/ Siliconate Densifier WB Penetrating Sealer

Page 6

16 Other Information

DISCLAIMER: THE INFORMATION CONTAINED HEREIN IS BASED ON THE DATA AVAILABLE AND IS BELIEVED TO BE ACCURATE. HOWEVER, THE MANUFACTURER MAKES NO WARRANTY EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS OBTAINED FROM THE USE THEREOF. ACCORDINGLY, WE ASSUME NO RESPONSIBILITY FOR INJURY FROM THE USE OF THIS PRODUCT.

N/A = Not Available. See Section 1 for date of preparation.

> Concrete Sealers USA | P.O. Box 5464 | De Pere, WI 54115 Toll-Free: 888.583.2991 | Emergency: 800.424.9300 info@concretesealersusa.com | www.concretesealersusa.com