

acc. to OSHA HCS

Printing date 02/14/2024

Reviewed on 02/14/2024

Page 1/10

1 Identification

- · Product identifier
- · Trade name: CreteStrip
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier CureCrete 1203 Spring Creek Place Springville, UT 84663

Tech Support (801) 489-5663

 Information department: Technical Services
 Emergency telephone number: (800) 633-8253 (United States/Canada)
 +1 (801) 629-0667 International Emergency Number

2 Hazard(s) identification

Classification of the substance or mixture



Flammable Liquids 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways.



Skin Irritation 2H315 Causes skin irritation.Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Danger

acc. to OSHA HCS

Printing date 02/14/2024

Trade name: CreteStrip

· Hazard-determining components of labeling: d-limonene

Hazard statements
 Flammable liquid and vapor.
 Causes skin irritation.
 May cause an allergic skin reaction.
 May be fatal if swallowed and enters airways.
 Classification system:

• NFPA ratings (scale 0 - 4)



Health = 1 Fire = 2 Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH1Health = 1FIRE2Fire = 2REACTIVITY0Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 5989-27-5 d-limonene	>70-<80%
Nonylphenyl polyethylene glycol ether	>12-<13%
CAS: 106-65-0 dimethyl succinate · Non-hazardous ingredients	>4-<4.25%
CAS: 1119-40-0 Pentanedioic acid, 1,5-dimethyl ester	>10-<11%
CAS: 627-93-0 dimethyl adipate	>4-<4.25%

4 First-aid measures

· Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

(Contd. of page 1)

Reviewed on 02/14/2024

acc. to OSHA HCS

Printing date 02/14/2024

Reviewed on 02/14/2024

Trade name: CreteStrip

• Indication of any immediate medical attention and special treatment needed No further relevant information available.

(Contd. of page 2)

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
 Methods and material for containment and cleaning up:

 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Dispose contaminated material as waste according to section 13.
 Ensure adequate ventilation.

 Reference to other sections

 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.
- Protective Action Criteria for Chemicals
- · PAC-1:

CAS: 5989-27-5 d-limonene: 15 ppm

Nonylphenyl polyethylene glycol ether: 30 mg/m³

- CAS: 106-65-0 dimethyl succinate: 2.5 ppm
- CAS: 75-21-8 ethylene oxide: 5 ppm
- CAS: 123-91-1 1,4-dioxane: 17 ppm
- · PAC-2:
- CAS: 5989-27-5 d-limonene: 67 ppm

Nonylphenyl polyethylene glycol ether: 330 mg/m³

- CAS: 106-65-0 dimethyl succinate: 28 ppm
- CAS: 75-21-8 ethylene oxide: 45 ppm
- CAS: 123-91-1 1,4-dioxane: 320 ppm
- · PAC-3:
- CAS: 5989-27-5 d-limonene: 170 ppm

Nonylphenyl polyethylene glycol ether: 2,000 mg/m³

- CAS: 106-65-0 dimethyl succinate: 170 ppm
- CAS: 75-21-8 ethylene oxide: 200 ppm
- CAS: 123-91-1 1,4-dioxane: 760 ppm

(Contd. on page 4)

US .

acc. to OSHA HCS

Printing date 02/14/2024

Reviewed on 02/14/2024

Trade name: CreteStrip

(Contd. of page 3)

7 Handling and storage

- · Handling:
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

- · Components with limit values that require monitoring at the workplace:
- The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Safety Data Sheet acc. to OSHA HCS

Printing date 02/14/2024

Trade name: CreteStrip

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties Information on basic physical and chemical properties General Information Appearance: 		
Form: Color: Odor: Odor:	Fluid Whitish Solvent like Not determined.	
· pH-value at 20 °C (68 °F):	7.2	
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Undetermined. 93 °C (199.4 °F)	
· Flash point:	46 °C (114.8 °F)	
· Flammability (solid, gaseous):	Flammable.	
· Auto igniting:	255 °C (491 °F)	
· Decomposition temperature:	Not determined.	
· Ignition temperature:	Product is not selfigniting.	
[.] Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.	
 Explosion limits: Lower: Upper: 	0.7 Vol % 6.1 Vol %	
· Vapor pressure at 20 °C (68 °F):	2.3 hPa (1.7 mm Hg)	
 Density at 20 °C (68 °F): Relative density Vapor density Evaporation rate 	0.87 g/cm³ (7.26015 lbs/gal) Not determined. Not determined. Not determined.	
 Solubility in / Miscibility with Water: 	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wate	er): Not determined.	
 Viscosity: Dynamic: Kinematic: 	Not determined. Not determined.	
 Solvent content: Organic solvents: VOC content: 	71.0 % 71.01 % 617.8 g/l / 5.16 lb/gal	

(Contd. of page 4)

Reviewed on 02/14/2024

acc. to OSHA HCS

Printing date 02/14/2024

Reviewed on 02/14/2024

(Contd. of page 5)

Trade name: CreteStrip

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · **Incompatible materials:** No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

CAS: 5989-27-5 d-limonene

Oral LD50 4,400 mg/kg (rat)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- on the eye: No irritating effect.

· Sensitization: Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 5989-27-5 d-limonene: 3

CAS: 75-21-8 ethylene oxide: 1

- CAS: 123-91-1 1,4-dioxane: 2B
- NTP (National Toxicology Program)

CAS: 75-21-8 ethylene oxide: K

CAS: 123-91-1 1,4-dioxane: R

· OSHA-Ca (Occupational Safety & Health Administration)

CAS: 75-21-8 ethylene oxide

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:
- Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 7)

acc. to OSHA HCS

Printing date 02/14/2024

Reviewed on 02/14/2024

(Contd. of page 6)

Trade name: CreteStrip

· Results	of PB1	and vPvB	assessment
-----------	--------	----------	------------

- · PBT: Not applicable.
- · vPvB: Not applicable.

• Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• **Recommendation:** Disposal must be made according to official regulations.

14 Transport information	
· UN-Number	
· DOT, IMDG, IATA	UN2052
 UN proper shipping name 	
DOT	Dipentene mixture
·IMDG	DIPENTENE mixture, MARINE POLLUTANT
	DIPENTENE mixture
 Transport hazard class(es) 	
· DOT	
RAMME COR	
Class	3 Flammable liquids
· Label	3
·IMDG	
· Class	3 Flammable liquids
·Label	3
· Class	3 Flammable liquids
Label	3
· Packing group	
· DOT, IMDG, IATA	
Environmental hazards:	Product contains environmentally hazardous substances: d-limonene
Marine pollutant:	Symbol (fish and tree)
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code):	
· EMS Number:	F-E,S-E (Contd. on page 8)
	(Cond. of page 6)

acc. to OSHA HCS

Printing date 02/14/2024

Reviewed on 02/14/2024

Trade name: CreteStrip

Stowage Category	(Contd. of page 7) A
 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	Not applicable.
· Transport/Additional information:	
· DOT · Quantity limitations	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
 IMDG Limited quantities (LQ) Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml
· UN "Model Regulation":	Maximum net quantity per outer packaging: 1000 ml UN 2052 DIPENTENE MIXTURE, 3, III, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available. · Sara Section 355 (extremely hazardous substances): CAS: 75-21-8 ethylene oxide Section 313 (Specific toxic chemical listings): Nonylphenyl polyethylene glycol ether CAS: 75-21-8 ethylene oxide CAS: 123-91-1 1,4-dioxane • TSCA (Toxic Substances Control Act): All components have the value ACTIVE. Hazardous Air Pollutants CAS: 75-21-8 ethylene oxide CAS: 123-91-1 1,4-dioxane · Proposition 65 · Chemicals known to cause cancer: CAS: 75-21-8 ethylene oxide CAS: 123-91-1 1,4-dioxane · Chemicals known to cause reproductive toxicity for females: CAS: 75-21-8 ethylene oxide · Chemicals known to cause reproductive toxicity for males: CAS: 75-21-8 ethylene oxide · Chemicals known to cause developmental toxicity: CAS: 75-21-8 ethylene oxide · Carcinogenic categories · EPA (Environmental Protection Agency) CAS: 75-21-8 ethylene oxide: CaH CAS: 123-91-1 1,4-dioxane: L • TLV (Threshold Limit Value) CAS: 75-21-8 ethylene oxide: A2 CAS: 123-91-1 1,4-dioxane: A3

(Contd. on page 9)

acc. to OSHA HCS

Printing date 02/14/2024

Trade name: CreteStrip

· NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 75-21-8 ethylene oxide

CAS: 123-91-1 1,4-dioxane

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Danger

- Hazard-determining components of labeling: d-limonene
- · Hazard statements

Flammable liquid and vapor.

Causes skin irritation.

May cause an allergic skin reaction.

May be fatal if swallowed and enters airways.

Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Technical Services
- · Contact:
- · Date of preparation / last revision 02/14/2024
- **Abbreviations and acronyms:** IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation

(Contd. of page 8)

Reviewed on 02/14/2024

acc. to OSHA HCS

Printing date 02/14/2024

Trade name: CreteStrip

IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flammable Liquids 3: Flammable liquids - Category 3 Skin Irritation 2: Skin corrosion/irritation - Category 2 Sensitization - Skin 1: Skin sensitisation - Category 1 Aspiration Hazard 1: Aspiration hazard - Category 1

Reviewed on 02/14/2024

(Contd. of page 9)

US -