



# Safety Data Sheet

**24 Hour Emergency Phone Numbers**  
**Medical/Poison Control:**  
 In U.S.: Call 1-800-222-1222

**Outside U.S.: Call your local poison control center**

**Transportation/National Response Center:**

**1-800-535-5053-35**  
**2-323-3500**

NOTE: The National Response Center emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this SDS are further described in Section 16.

## 1. Identification

<b>Product Name:</b>	Alex Painters Acrylic Latex Caulk	<b>Revision Date:</b>	3/27/2024
<b>Product UPC Number:</b>	070798180659	<b>Supercedes Date:</b>	8/22/2023
<b>Manufacturer:</b>	DAP Global Inc. 2400 Boston Street Suite 200 Baltimore, MD 21224-4723 888-327-8477 (non - emergency matters)	<b>Product Use/Class:</b>	Caulking Compound
	SDS Coordinator: MSDS@dap.com	<b>SDS No:</b>	1001101
	Emergency Telephone: Transportation: 1-800-535 -5053 1-352-323-3500 Poison Control: 1-800-222-1222	<b>Preparer:</b>	Regulatory and Environmental Affairs

## 2. Hazards Identification

**EMERGENCY OVERVIEW:** Under normal use conditions, this product is not expected to cause adverse health effects.

### GHS Classification

Eye Irrit. 2A, Skin Irrit. 2

### Symbol(s) of Product



### Signal Word

Warning

### Possible Hazards

57% of the mixture consists of ingredients of unknown acute toxicity

### GHS HAZARD STATEMENTS

Skin Irritation, category 2	H315	Causes skin irritation.
Eye Irritation, category 2A	H319	Causes serious eye irritation.

**GHS LABEL PRECAUTIONARY STATEMENTS**

P264	Wash thoroughly after handling.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321	Specific treatment (see ... on this label).
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P362	Take off contaminated clothing.

**3. Composition/Information on Ingredients**

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Limestone	1317-65-3	30-60	GHS07	H315-319
Lubricating petroleum oil	72623-86-0	5-10	GHS07	H332
Petroleum distillates	64741-88-4	1-5	No Information	No Information
Stoddard solvent	8052-41-3	0.1-1.0	GHS02-GHS08	H226-304-372

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

**4. First-aid Measures**

**FIRST AID - INHALATION:** Material is not likely to present an inhalation hazard at ambient conditions. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

**FIRST AID - SKIN CONTACT:** In case of contact, wash skin immediately with soap and water.

**FIRST AID - EYE CONTACT:** In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

**FIRST AID - INGESTION:** If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

**5. Fire-fighting Measures**

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** None Known.

**SPECIAL FIREFIGHTING PROCEDURES:** Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

**EXTINGUISHING MEDIA:** Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Spray or Fog, Water

**6. Accidental Release Measures**

**ENVIRONMENTAL MEASURES:** Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate. Dispose of saturated absorbent or cleaning materials appropriately. Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this SDS provide information regarding certain federal and state requirements.

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Use personal protective equipment as necessary. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

**7. Handling and Storage**

**HANDLING:** KEEP OUT OF REACH OF CHILDREN! DO NOT TAKE INTERNALLY. Use only with adequate ventilation. Ensure fresh air entry during application and drying. Wash thoroughly after handling.

**STORAGE:** Avoid excessive heat and freezing. Do not store at temperatures above 120 °F (49 °C). Store away from caustics and oxidizers.

## 8. Exposure Controls/Personal Protection

### Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
Limestone	N.E.	N.E.	15 mg/m <sup>3</sup> TWA total dust, 5 mg/m <sup>3</sup> TWA respirable fraction	N.E.
Lubricating petroleum oil	N.E.	N.E.	N.E.	N.E.
Petroleum distillates	N.E.	N.E.	N.E.	N.E.
Stoddard solvent	100 ppm TWA	N.E.	500 ppm TWA, 2900 mg/m <sup>3</sup> TWA	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

### Personal Protection



**RESPIRATORY PROTECTION:** No personal respiratory protective equipment normally required.



**SKIN PROTECTION:** Rubber gloves.



**EYE PROTECTION:** Goggles or safety glasses with side shields.



**OTHER PROTECTIVE EQUIPMENT:** Not required under normal use.



**HYGIENIC PRACTICES:** Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

## 9. Physical and Chemical Properties

<b>Color:</b>	White to Off-White	<b>Appearance:</b>	Paste
<b>Odor:</b>	Very Slight Ammonia	<b>Physical State:</b>	Solid
<b>Density, g/cm<sup>3</sup>:</b>	1.55 - 1.61	<b>Odor Threshold:</b>	Not Established
<b>Freeze Point, °C:</b>	Not Established	<b>pH:</b>	Between 7.0 and 12.0
<b>Solubility in Water:</b>	Not Established	<b>Viscosity (mPa.s):</b>	Not Established
<b>Decomposition Temperature, °C:</b>	Not Established	<b>Partition Coeff., n-octanol/water:</b>	Not Established
<b>Boiling Range, °C:</b>	N.A. Mixture w/o a constant boiling point.	<b>Explosive Limits, %:</b>	N.E.
<b>Flash Point, °C:</b>	Water - based, does not flash.	<b>Auto-Ignition Temperature, °C</b>	Not Established
<b>Evaporation Rate:</b>	Slower Than n-Butyl Acetate	<b>Vapor Pressure, mmHg:</b>	Not Established
<b>Vapor Density:</b>	Heavier Than Air	<b>Flash Method:</b>	Not Applicable
<b>Combustible Dust:</b>	Does not support combustion		

(See "Other information" Section for abbreviation legend)

(If product is an aerosol, the flash point stated above is that of the propellant.)

## 10. Stability and Reactivity

**STABILITY:** Stable under recommended storage conditions.

**CONDITIONS TO AVOID:** Excessive heat and freezing.

**INCOMPATIBILITY:** Incompatible with strong bases and oxidizing agents.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Normal decomposition products, i.e., COx, NOx.

## 11. Toxicological Information

**EFFECT OF OVEREXPOSURE - INHALATION:** Under normal use conditions, this product is not expected to cause adverse health effects. Inhalation of vapors in high concentration may cause mild irritation of respiratory system (nose, mouth, mucous membranes).

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Under normal use conditions, this product is not expected to cause adverse health effects. Prolonged or repeated contact with skin may cause mild irritation.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** Under normal use conditions, this product is not expected to cause adverse health effects. Direct eye contact may cause irritation.

**EFFECT OF OVEREXPOSURE - INGESTION:** Under normal use conditions, this product is not expected to cause adverse health effects. Single dose oral toxicity is very low. Amounts ingested incidental to industrial handling are not likely to cause injury; however, ingestion of large amounts may cause injury.

**CARCINOGENICITY:** No Information

**EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS:** Repeated or prolonged exposure may cause mild irritation of eyes and skin. Constituents of this product include crystalline silica which, if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

**PRIMARY ROUTE(S) OF ENTRY:** Skin Contact

### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
1317-65-3	Limestone	6450 mg/kg Rat	N.I.	N.I.
72623-86-0	Lubricating petroleum oil	>5000 mg/kg Rat	>2000 mg/kg Rabbit	N.I.
64741-88-4	Petroleum distillates	>5000 mg/kg Rat	>5000 mg/kg Rabbit	N.I.
8052-41-3	Stoddard solvent	>7000 mg/kg Rat	>2000 mg/kg Rabbit	21 mg/L Rat

N.I. = No Information

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Ecological injuries are not known or expected under normal use.

## 13. Disposal Information

**DISPOSAL INFORMATION:** Dispose of material in accordance with all federal, state and local regulations.

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Use personal protective equipment as necessary. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

## 14. Transport Information

DOT UN/NA Number:	N.A.
DOT Proper Shipping Name:	Not Regulated
DOT Technical Name:	N.A.
DOT Hazard Class:	N.A.
Hazard SubClass:	N.A.
Packing Group:	N.A.

**SPECIAL TRANSPORT PRECAUTIONS:** No Information

## 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Skin Corrosion or Irritation, Serious eye damage or eye irritation

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

#### TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

## 16. Other Information

**Revision Date:** 3/27/2024 **Supersedes Date:** 8/22/2023

**Reason for revision:** Product Composition Changed  
 Substance and/or Product Properties Changed in Section(s):  
 02 - Hazards Identification  
 05 - Flammability Information  
 08 - Exposure Controls/Personal Protection  
 09 - Physical & Chemical Information  
 15 - Regulatory Information  
 16 - Other Information  
 Substance Regulatory CAS Number Changed  
 Substance Hazardous Flag Changed  
 Substance Hazard Threshold % Changed  
 Revision Statement(s) Changed

**Datasheet produced by:** Regulatory Department

#### HMIS Ratings:

Health:	Flammability:	Reactivity:	Personal Protection:
1	1	0	X

VOC Less Water Less Exempt Solvent, g/L: 50.0

VOC Material, g/L: 35

VOC as Defined by California Consumer Product Regulation, Wt/Wt%: 1.01

VOC Actual, Wt/Wt%: 2.2

#### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.

**Icons for GHS Pictograms shown in Section 3 describing each ingredient:**

GHS02



GHS07



GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

We believe the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.