


TECHNICAL DATA SHEET

DESCRIPTION

A90W is a high strength scaffold bracket that meets state building codes and OSHA minimum requirements.

APPLICATION

The Dayton Superior A90W Scaffold Bracket supports scaffolding on nearly any type of formwork.



WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.

FEATURES

- SWL of approximately 1,000 lbs
- It can be flush mounted or adjusted to fit various size vertical or horizontal walers or strongbacks
- The maximum bracket spacing should be limited to 8'-0" on center

INSTALLATION

1. The A90W Scaffold Bracket hooks over 2x4 or 2x6 walers to provide safe, solid scaffolding on wall forms.
2. Waler hooks are removable for flush wall mount applications.

RELATED PRODUCTS

- A90 Scaffold Bracket Jack

ORDERING INFORMATION

| Product Code | Description | Weight |
|--------------|-------------|-----------|
| 144823 | WEST COAST | 23.000 LB |

MANUFACTURER

Dayton Superior Corporation
 1125 Byers Road
 Miamisburg, OH 45342
 Customer Service: 888-977-9600
 Technical Services: 877-266-7732
 Website: www.daytonsuperior.com