

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/19/2023

Reviewed on 04/19/2023

## 1 Identification

- **Product identifier**
- **Trade name:** AggreGloss™ J25
- **Article number:** 69056
- **Application of the substance / the mixture**
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Dayton® Superior  
4226 Kansas Avenue  
Kansas City, KS 66106

Tel.: (866) 329-8724

*Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.*

- **Information department:** Environmental, Health, and Safety department.

## 2 Hazard(s) identification

- **Classification of the substance or mixture**  

|                 |      |  |
|-----------------|------|--|
| Flam. Liq. 3    | H226 | Flammable liquid and vapor.  |
| Acute Tox. 4    | H332 | Harmful if inhaled.  |
| Skin Irrit. 2   | H315 | Causes skin irritation.  |
| Repr. 1B        | H360 | May damage fertility or the unborn child.                                      |
| STOT RE 2       | H373 | May cause damage to the hearing organs through prolonged or repeated exposure. |
| Asp. Tox. 1     | H304 | May be fatal if swallowed and enters airways.                                  |
| Aquatic Acute 3 | H402 | Harmful to aquatic life.   |
- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02   GHS07   GHS08

- **Signal word** *Danger*
- **Hazard-determining components of labeling:**  
*xylene  
ethylbenzene  
dibutyl phthalate  
toluene*
- **Hazard statements**  
*Flammable liquid and vapor.  
Harmful if inhaled.  
Causes skin irritation.  
May damage fertility or the unborn child.  
May cause damage to the hearing organs through prolonged or repeated exposure.  
May be fatal if swallowed and enters airways.  
Harmful to aquatic life.*
- **Precautionary statements**  
*If swallowed: Immediately call a poison center/doctor.*

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/19/2023

Reviewed on 04/19/2023

**Trade name: AggreGloss™ J25**

(Contd. of page 1)

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**

|                 |   |                |
|-----------------|---|----------------|
| HEALTH          | 1 | Health = *1    |
| FIRE            | 3 | Fire = 3       |
| PHYSICAL HAZARD | 0 | Reactivity = 0 |

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

|           |                   |             |
|-----------|-------------------|-------------|
| 1330-20-7 | xylene            | ≥10-<70%    |
| 100-41-4  | ethylbenzene      | ≥10-<16%    |
| 84-74-2   | dibutyl phthalate | ≥0.25-<2.1% |
| 108-88-3  | toluene           | ≥0.1-<0.6%  |

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

### 4 First-aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

In the event of persistent symptoms receive medical treatment.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

Immediately move exposed person to fresh air. If breathing difficulty persists or develops get prompt medical attention.

· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** Seek medical treatment.

(Contd. on page 3)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 04/19/2023

Reviewed on 04/19/2023

Trade name: AggreGloss™ J25

(Contd. of page 2)

- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, sand, extinguishing powder. Do not use water.  
Foam
- **For safety reasons unsuitable extinguishing agents:** Water
- **Special hazards arising from the substance or mixture** Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:**  
Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.  
Mouth respiratory protective device.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:** cool and dry
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:** Keep receptacle tightly sealed.

(Contd. on page 4)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/19/2023

Reviewed on 04/19/2023

Trade name: AggreGloss™ J25

(Contd. of page 3)

· **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.· **Control parameters**· **Components with limit values that require monitoring at the workplace:**

### 1330-20-7 xylene

PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppmREL Short-term value: 655 mg/m<sup>3</sup>, 150 ppmLong-term value: 435 mg/m<sup>3</sup>, 100 ppmTLV Short-term value: 651 mg/m<sup>3</sup>, 150 ppmLong-term value: 434 mg/m<sup>3</sup>, 100 ppm

BEI

### 100-41-4 ethylbenzene

PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppmREL Short-term value: 545 mg/m<sup>3</sup>, 125 ppmLong-term value: 435 mg/m<sup>3</sup>, 100 ppmTLV Long-term value: 87 mg/m<sup>3</sup>, 20 ppm

BEI

### 84-74-2 dibutyl phthalate

PEL Long-term value: 5 mg/m<sup>3</sup>REL Long-term value: 5 mg/m<sup>3</sup>TLV Long-term value: 5 mg/m<sup>3</sup>

### 108-88-3 toluene

PEL Long-term value: 200 ppm

Ceiling limit value: 300; 500\* ppm

\*10-min peak per 8-hr shift

REL Short-term value: 560 mg/m<sup>3</sup>, 150 ppmLong-term value: 375 mg/m<sup>3</sup>, 100 ppmTLV Long-term value: 75 mg/m<sup>3</sup>, 20 ppm

BEI

· **Ingredients with biological limit values:**

### 1330-20-7 xylene

BEI 1.5 g/g creatinine

Medium: urine

Time: end of shift

Parameter: Methylhippuric acids

### 100-41-4 ethylbenzene

BEI 0.7 g/g creatinine

Medium: urine

Time: end of shift at end of workweek

Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-

Medium: end-exhaled air

Time: not critical

Parameter: Ethyl benzene (semi-quantitative)

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/19/2023

Reviewed on 04/19/2023

Trade name: AggreGloss™ J25

(Contd. of page 4)

**108-88-3 toluene**

BEI 0.02 mg/L  
 Medium: blood  
 Time: prior to last shift of workweek  
 Parameter: Toluene

0.03 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: Toluene

0.3 mg/g creatinine  
 Medium: urine  
 Time: end of shift  
 Parameter: o-Cresol with hydrolysis (background)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Wear appropriate eye protection to prevent eye contact.

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

**Form:** Liquid

**Color:** According to product specification

· **Odor:** Characteristic

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/19/2023

Reviewed on 04/19/2023

Trade name: AggreGloss™ J25

(Contd. of page 5)

|   |  |
|---|--|
| · <b>Odor threshold:</b>  | Not determined.  |
| · <b>pH-value:</b>  | Not determined.  |
| · <b>Change in condition</b><br><b>Melting point/Melting range:</b> | Undetermined.  |
| <b>Boiling point/Boiling range:</b>                                 | 137 °C (278.6 °F)  |
| · <b>Flash point:</b>   | 31 °C (87.8 °F)  |
| · <b>Flammability (solid, gaseous):</b>                             | Not applicable.  |
| · <b>Ignition temperature:</b>                                      | 430 °C (806 °F)  |
| · <b>Decomposition temperature:</b>                                 | Not determined.  |
| · <b>Auto igniting:</b>   | Product is not selfigniting.   |
| · <b>Danger of explosion:</b>                                       | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |
| · <b>Explosion limits:</b><br><b>Lower:</b>                         | 1 Vol %  |
| <b>Upper:</b>   | 7.8 Vol %  |
| · <b>Vapor pressure at 20 °C (68 °F):</b>                           | 9.5 hPa (7.1 mm Hg)  |
| · <b>Density at 20 °C (68 °F):</b>                                  | 0.82364 g/cm <sup>3</sup> (6.87328 lbs/gal)  |
| · <b>Relative density</b>   | Not determined.  |
| · <b>Vapor density</b>  | Not determined.  |
| · <b>Evaporation rate</b>   | Not determined.  |
| · <b>Solubility in / Miscibility with</b><br><b>Water:</b>          | Not miscible or difficult to mix.  |
| · <b>Partition coefficient (n-octanol/water):</b>                   | Not determined.  |
| · <b>Viscosity:</b><br><b>Dynamic:</b>                              | Not determined.  |
| <b>Kinematic:</b>   | Not determined.  |
| · <b>Solvent content:</b><br><b>Organic solvents:</b>               | 76.9 %   |
| <b>Solids content:</b>  | 25.0 %   |
| · <b>Other information</b>  | No further relevant information available.   |
| · <b>Volatile Organic Compounds:</b>                                | Contains less than 700 g/L.  |

## 10 Stability and reactivity

- **Reactivity** No decomposition if stored and applied as directed.
- **Chemical stability** No decomposition if stored and applied as directed
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Keep away from heat and sources of ignition.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

US  
(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/19/2023

Reviewed on 04/19/2023

Trade name: AggreGloss™ J25

(Contd. of page 6)

## 11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

**1330-20-7 xylene**

|        |      |                      |
|--------|------|----------------------|
| Oral   | LD50 | 4,300 mg/kg (rat)    |
| Dermal | LD50 | 2,000 mg/kg (rabbit) |

**100-41-4 ethylbenzene**

|        |      |                       |
|--------|------|-----------------------|
| Oral   | LD50 | 3,500 mg/kg (rat)     |
| Dermal | LD50 | 17,800 mg/kg (rabbit) |

**84-74-2 dibutyl phthalate**

|        |      |                       |
|--------|------|-----------------------|
| Oral   | LD50 | 8,000 mg/kg (rat)     |
| Dermal | LD50 | 20,000 mg/kg (rabbit) |

- **Primary irritant effect:**

- **on the skin:** May cause skin irritation.

- **on the eye:** No irritating effect known.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

|           |              |    |
|-----------|--------------|----|
| 1330-20-7 | xylene       | 3  |
| 100-41-4  | ethylbenzene | 2B |
| 108-88-3  | toluene      | 3  |

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

## 12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (Self-assessment): slightly hazardous for water

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/19/2023

Reviewed on 04/19/2023

Trade name: AggreGloss™ J25



(Contd. of page 7)

- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of as normal garbage. Do not allow product to reach sewage system.  
It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

## 14 Transport information

- |   |  |
|---|--|
| <ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· <b>DOT, ADR, IMDG, IATA</b></li> </ul>   | <p style="text-align: right;">UN1268</p>   |
| <ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· <b>DOT</b></li> <li>· <b>ADR</b></li> <li>· <b>IMDG, IATA</b></li> </ul> | <p style="text-align: right;">Petroleum distillates, n.o.s.<br/>1268 PETROLEUM DISTILLATES, N.O.S.<br/>PETROLEUM DISTILLATES, N.O.S.</p> |
| <ul style="list-style-type: none"> <li>· <b>Transport hazard class(es)</b></li> <li>· <b>DOT</b></li> </ul>   | <div style="text-align: center;">  </div>             |
| <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>  | <p style="text-align: right;">3 Flammable liquids<br/>3</p>  |
| <ul style="list-style-type: none"> <li>· <b>ADR, IMDG, IATA</b></li> </ul>  | <div style="text-align: center;">  </div>             |
| <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>  | <p style="text-align: right;">3 Flammable liquids<br/>3</p>  |
| <ul style="list-style-type: none"> <li>· <b>Packing group</b></li> <li>· <b>DOT, ADR, IMDG, IATA</b></li> </ul>   | <p style="text-align: right;">III</p>  |
| <ul style="list-style-type: none"> <li>· <b>Environmental hazards:</b></li> <li>· <b>Marine pollutant:</b></li> </ul>                                       | <p style="text-align: right;">No</p>   |
| <ul style="list-style-type: none"> <li>· <b>Special precautions for user</b></li> <li>· <b>Danger code (Kemler):</b></li> </ul>                             | <p style="text-align: right;">Warning: Flammable liquids<br/>30</p>  |

(Contd. on page 9)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/19/2023

Reviewed on 04/19/2023

Trade name: AggreGloss™ J25

(Contd. of page 8)

|   |  |
|---|--|
| · <b>EMS Number:</b>  | F-E,S-E  |
| · <b>Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code</b> | Not applicable.  |
| · <b>Transport/Additional information:</b>  |  |
| · <b>ADR</b>  |  |
| · <b>Excepted quantities (EQ)</b>   | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · <b>U.S. Domestic Ground Shipments:</b>  | Same as listed for Standard Shipments above.   |
| · <b>U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:</b> | Same as listed for Standard Shipments above.   |
| · <b>Emergency Response Guide (ERG) Number:</b>                                   | Not determine  |
| · <b>IMDG</b>   |  |
| · <b>Limited quantities (LQ)</b>  | 5L   |
| · <b>Excepted quantities (EQ)</b>   | Code: E1<br>Maximum net quantity per inner packaging: 30 ml<br>Maximum net quantity per outer packaging: 1000 ml |
| · <b>UN "Model Regulation":</b>   | UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, III  |

## 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

### · **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

### · **Section 313 (Specific toxic chemical listings):**

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

|           |                   |             |
|-----------|-------------------|-------------|
| 1330-20-7 | xylene            | ≥10-<70%    |
| 100-41-4  | ethylbenzene      | ≥10-<16%    |
| 84-74-2   | dibutyl phthalate | ≥0.25-<2.1% |
| 108-88-3  | toluene           | ≥0.1-<0.6%  |

### · **TSCA (Toxic Substances Control Act):**

|           |                   |        |
|-----------|-------------------|--------|
| 1330-20-7 | xylene            | ACTIVE |
| 100-41-4  | ethylbenzene      | ACTIVE |
| 84-74-2   | dibutyl phthalate | ACTIVE |
| 108-88-3  | toluene           | ACTIVE |

### · **Hazardous Air Pollutants**

All ingredients are listed.

### · **Proposition 65**

#### · **Chemicals known to the State of California (Prop. 65) to cause cancer:**

100-41-4 ethylbenzene

#### · **Chemicals known to cause reproductive toxicity for females:**

84-74-2 dibutyl phthalate

(Contd. on page 10)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/19/2023

Reviewed on 04/19/2023

Trade name: AggreGloss™ J25

(Contd. of page 9)

· **Chemicals known to cause reproductive toxicity for males:**

84-74-2 dibutyl phthalate

· **Chemicals known to cause developmental toxicity:**

84-74-2 dibutyl phthalate

108-88-3 toluene

· **Cancerogenity categories**

· **EPA (Environmental Protection Agency)**

1330-20-7 xylene

I

100-41-4 ethylbenzene

D

84-74-2 dibutyl phthalate

D

108-88-3 toluene

II

· **TLV (Threshold Limit Value established by ACGIH)**

1330-20-7 xylene

A4

100-41-4 ethylbenzene

A3

108-88-3 toluene

A4

· **MAK (German Maximum Workplace Concentration)**

100-41-4 ethylbenzene

3A

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02

GHS07

GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

xylene

ethylbenzene

dibutyl phthalate

toluene

· **Hazard statements**

Flammable liquid and vapor.

Harmful if inhaled.

Causes skin irritation.

May damage fertility or the unborn child.

May cause damage to the hearing organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Harmful to aquatic life.

· **Precautionary statements**

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

Take off contaminated clothing and wash it before reuse.

Store locked up.

(Contd. on page 11)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 04/19/2023

Reviewed on 04/19/2023

**Trade name: AggreGloss™ J25**

(Contd. of page 10)

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **National regulations:**

· **Water hazard class:** Water hazard class 2 (Self-assessment): hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

### 16 Other information

*The provided information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Department issuing SDS:** Environmental, Health & Safety Department

· **Contact:** Environmental, Health & Safety Manager

· **Date of preparation / last revision** 04/19/2023 / 106

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Repr. 1B: Reproductive toxicity – Category 1B

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3