

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

1 Identification

- **Product identifier**

- **Trade name:** Anti Spall J33

- **Article number:** 69179

- **Application of the substance / the mixture**

- **Details of the supplier of the safety data sheet**

- **Manufacturer/Supplier:**

Dayton® Superior
4226 Kansas Avenue
Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call international number, +1 703 741-5970. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

2 Hazard(s) identification

- **Classification of the substance or mixture**

Flam. Liq. 3 H226 Flammable liquid and vapor.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2B H320 Causes eye irritation.

Carc. 1B H350 May cause cancer.

STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** *Danger*

- **Hazard-determining components of labeling:**

Stoddard solvent

Naphtha (petroleum), hydrodesulfurized heavy

Distillates (petroleum), hydrotreated light

Solvent naphtha (petroleum), light arom.

- **Hazard statements**

Flammable liquid and vapor.

Causes skin and eye irritation.

May cause cancer.

Causes damage to the central nervous system through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Harmful to aquatic life with long lasting effects.

- **Precautionary statements**

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Anti Spall J33

(Contd. of page 1)

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = *2
FIRE	2	Fire = 2
PHYSICAL HAZARD	0	Reactivity = 0

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**· **Description:** Mixture of the substances listed below with nonhazardous additions.· **Dangerous components:**

64742-47-8	Distillates (petroleum), hydrotreated light	<25.0%
8052-41-3	Stoddard solvent	≥10-<18%
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	≥10-<18%
64742-95-6	Solvent naphtha (petroleum), light arom.	≥0.1-<1.2%
95-63-6	1,2,4-trimethylbenzene	≥0.25-≤1.1%
103-65-1	propylbenzene	≥0.25-<0.5%
98-82-8	cumene	≥0.1-<0.25%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First-aid measures

· **Description of first aid measures**· **After inhalation:** Supply fresh air; consult doctor in case of complaints.· **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.· **After swallowing:** Seek medical treatment.· **Information for doctor:**· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Anti Spall J33

(Contd. of page 2)

· **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, sand, extinguishing powder. Do not use water.
Foam
- **For safety reasons unsuitable extinguishing agents:** Water
- **Special hazards arising from the substance or mixture** Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:**
Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

US

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Anti Spall J33

(Contd. of page 3)

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

8052-41-3 Stoddard solvent	
PEL	Long-term value: 2900 mg/m ³ , 500 ppm
REL	Long-term value: 350 mg/m ³ Ceiling limit value: 1800* mg/m ³ *15-min
TLV	Long-term value: 525 mg/m ³ , 100 ppm
95-63-6 1,2,4-trimethylbenzene	
REL	Long-term value: 125 mg/m ³ , 25 ppm
TLV	Long-term value: 123 mg/m ³ , 25 ppm
98-82-8 cumene	
PEL	Long-term value: 245 mg/m ³ , 50 ppm Skin
REL	Long-term value: 245 mg/m ³ , 50 ppm Skin
TLV	Long-term value: (246) NIC-0.5 mg/m ³ , (50) NIC-0.1 ppm NIC-A3

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Anti Spall J33

(Contd. of page 4)

· **Eye protection:** Wear appropriate eye protection to prevent eye contact.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

Form: Liquid
Color: According to product specification

· **Odor:** Characteristic· **Odor threshold:** Not determined.· **pH-value:** Not determined.· **Change in condition**

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 121 °C (249.8 °F)

· **Flash point:** 39 °C (102.2 °F)· **Flammability (solid, gaseous):** Not applicable.· **Ignition temperature:** 210 °C (410 °F)· **Decomposition temperature:** Not determined.· **Auto igniting:** Product is not selfigniting.· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.· **Explosion limits:**

Lower: 0.5 Vol %
Upper: 6.5 Vol %

· **Vapor pressure at 20 °C (68 °F):** 2 hPa (1.5 mm Hg)· **Density at 20 °C (68 °F):** 0.82292 g/cm³ (6.86727 lbs/gal)· **Relative density** Not determined.· **Vapor density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.· **Viscosity:**

Dynamic: Not determined.
Kinematic: Not determined.

· **Solvent content:**

Organic solvents: 3.0 %

Solids content: 29.8 %

· **Other information** No further relevant information available.· **Volatile Organic Compounds:** Contains less than 400 g/L.

US

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Anti Spall J33

(Contd. of page 5)

10 Stability and reactivity

- **Reactivity** No decomposition if stored and applied as directed.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** Keep away from heat and sources of ignition.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
------	------	--------------------

Dermal	LD50	>3,400 mg/kg (rab)
--------	------	--------------------

Inhalative	LC50/4 h	>10.2 mg/l (rat)
------------	----------	------------------

- **Primary irritant effect:**
- **on the skin:** May cause skin irritation.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Carcinogenic.

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

98-82-8	cumene	2B
1330-20-7	xylene	3
91-20-3	naphthalene	2B
100-41-4	ethylbenzene	2B
7440-48-4	cobalt	2B

· **NTP (National Toxicology Program)**

98-82-8	cumene	R
91-20-3	naphthalene	R
7440-48-4	cobalt	R

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Anti Spall J33



(Contd. of page 6)

- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Water hazard class 1 (Self-assessment): slightly hazardous for water
Harmful to aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of as normal garbage. Do not allow product to reach sewage system.
It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to Federal, State, and Local regulations.

14 Transport information

- | | |
|---|-------------------------------------|
| UN-Number | UN1268 |
| DOT, ADR, IMDG, IATA | |
| UN proper shipping name | Petroleum distillates, n.o.s. |
| DOT | 1268 PETROLEUM DISTILLATES, N.O.S., |
| ADR | ENVIRONMENTALLY HAZARDOUS |
| IMDG, IATA | PETROLEUM DISTILLATES, N.O.S. |
| Transport hazard class(es) | |
| DOT | |
|  | |
| Class | 3 Flammable liquids |
| Label | 3 |
| ADR, IMDG, IATA | |
|  | |
| Class | 3 Flammable liquids |

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Anti Spall J33

(Contd. of page 7)

· Label	3
· Packing group · DOT, ADR, IMDG, IATA	III
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user · Danger code (Kemler): · EMS Number:	Warning: Flammable liquids 30 F-E,S-E
· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· ADR · Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· U.S. Domestic Ground Shipments:	Combustible liquids, n.o.s. (Petroleum Distillates), NA1993, PG III
· U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:	DOT: Not regulated (Reclassified as per 49CFR 173.150).
· Emergency Response Guide (ERG) Number:	Not determine
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, III, ENVIRONMENTALLY HAZARDOUS

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

95-63-6	1,2,4-trimethylbenzene	≥0.25-≤1.1%
98-82-8	cumene	≥0.1-<0.25%
1330-20-7	xylene	<0.1%
91-20-3	naphthalene	≥0.025-<0.1%
100-41-4	ethylbenzene	<0.1%
7440-48-4	cobalt	<0.1%
7439-96-5	manganese	<0.1%

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Anti Spall J33

(Contd. of page 8)

· TSCA (Toxic Substances Control Act):		
64742-47-8	Distillates (petroleum), hydrotreated light	ACTIVE
8052-41-3	Stoddard solvent	ACTIVE
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	ACTIVE
25551-13-7	Trimethylbenzene	ACTIVE
64742-95-6	Solvent naphtha (petroleum), light arom.	ACTIVE
95-63-6	1,2,4-trimethylbenzene	ACTIVE
103-65-1	propylbenzene	ACTIVE
98-82-8	cumene	ACTIVE
1330-20-7	xylene	ACTIVE
91-20-3	naphthalene	ACTIVE
100-41-4	ethylbenzene	ACTIVE
7440-48-4	cobalt	ACTIVE
7439-96-5	manganese	ACTIVE

· Hazardous Air Pollutants		
98-82-8	cumene	
1330-20-7	xylene	
91-20-3	naphthalene	
100-41-4	ethylbenzene	
7440-48-4	cobalt	
7439-96-5	manganese	

· Proposition 65

· Chemicals known to the State of California (Prop. 65) to cause cancer:		
64742-95-6	Solvent naphtha (petroleum), light arom.	
98-82-8	cumene	
91-20-3	naphthalene	
100-41-4	ethylbenzene	
7440-48-4	cobalt	

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)		
95-63-6	1,2,4-trimethylbenzene	II
98-82-8	cumene	D, CBD
1330-20-7	xylene	I
91-20-3	naphthalene	C, CBD
100-41-4	ethylbenzene	D
7439-96-5	manganese	D

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Anti Spall J33

(Contd. of page 9)

· TLV (Threshold Limit Value established by ACGIH)		
1330-20-7	xylene	A4
91-20-3	naphthalene	A4
100-41-4	ethylbenzene	A3
7440-48-4	cobalt	A3

· MAK (German Maximum Workplace Concentration)		
91-20-3	naphthalene	2
100-41-4	ethylbenzene	3A
7440-48-4	cobalt	2

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**
None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



· **Signal word** Danger

· **Hazard-determining components of labeling:**

Stoddard solvent

Naphtha (petroleum), hydrodesulfurized heavy

Distillates (petroleum), hydrotreated light

Solvent naphtha (petroleum), light arom.

· **Hazard statements**

Flammable liquid and vapor.

Causes skin and eye irritation.

May cause cancer.

Causes damage to the central nervous system through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Take off contaminated clothing and wash it before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Water hazard class:** Water hazard class 3 (Self-assessment): extremely hazardous for water.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

US

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 04/21/2023

Reviewed on 04/21/2023

Trade name: Anti Spall J33

(Contd. of page 10)

16 Other information

The provided information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environmental, Health & Safety Department

· **Contact:** Environmental, Health & Safety Manager

· **Date of preparation / last revision** 04/21/2023 / 67

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2B: Serious eye damage/eye irritation – Category 2B

Carc. 1B: Carcinogenicity – Category 1B

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3