

UL Product iQ™



## VFXT.EX1289 - HANGERS, PIPE

## Hangers, Pipe

See General Information for Hangers, Pipe

**DEWALT, INC**701 East Joppa Rd  
Towson, MD 21286 USA**For Installation in Wood:**

EX1289

<b>Model Designation</b>	<b>Hanger Type</b>	<b>Rod Size</b>	<b>Nominal Pipe Size</b>	<b>Comments</b>
<b>HangerMate+ PFM2251100</b>	Self-Threading Anchor	3/8	3	For vertical installation into the bottom of a wood timber or joist. Min. 1-1/2 in. wood thickness
<b>HangerMate+ PFM2251150</b>	Self-Threading Anchor	3/8	4	For vertical installation into the bottom of a wood timber or joist. Min. 1-1/2 in. wood thickness
<b>HangerMate+ PFM2251200</b>	Self-Threading Anchor	3/8	3	For vertical installation into the bottom of a wood timber or joist. Min. 1-1/2 in. wood thickness
<b>HangerMate+ PFM2251250</b>	Self-Threading Anchor	3/8	3	For vertical installation into the bottom of a wood timber or joist. Min. 1-1/2 in. wood thickness
<b>HangerMate+ PFM2251350 (Step Thread)</b>	Self-Threading Anchor	3/8, 1/2	3	For vertical installation into the bottom of a wood timber or joist. Min. 1-1/2 in. wood thickness
<b>HangerMate+ PFM2261100</b>	Self-Threading Anchor	3/8	3	For Horizontal installation into the side of a wood timber or joist. Min. 1-1/2 in. wood thickness.
<b>HangerMate+ PFM2261150</b>	Self-Threading Anchor	3/8	4	For Horizontal installation into the side of a wood timber or joist. Min. 1-1/2 in. wood thickness.

**For Installation in Steel:**

<b>Model Designation</b>	<b>Hanger Type</b>	<b>Rod Size, in.</b>	<b>Nominal Pipe Size</b>	<b>Comments</b>
<b>Vertigo 7154</b>	Self-Drilling Anchor	3/8	4	For vertical installation into steel. Min. 0.06 in. steel thickness.
<b>Vertigo 7158</b>	Self-Drilling Anchor	3/8	4	For vertical installation into steel. Min. 0.06 in. steel thickness.
<b>Vertigo 7160</b>	Self-Drilling Anchor	3/8	Up to 4	For vertical installation into steel. Min. 0.06 in. steel thickness.
<b>Vertigo 7161</b>	Self-Drilling Anchor	1/2	Up to 8	For vertical installation into steel. Min. 0.25 in. steel thickness.
<b>Vertigo 7184</b>	Self-Drilling Anchor	3/8	4	For horizontal installation into steel. Min. 0.06 in. steel thickness.
<b>Vertigo 7186</b>	Self-Drilling Anchor	3/8	4	For horizontal installation into steel. Min. 0.06 in. steel thickness.
<b>Vertigo 7188</b>	Self-Drilling Anchor	3/8	4	For horizontal installation into steel. Min. 0.06 in. steel thickness.
<b>Vertigo 7201</b>	Self-Drilling Anchor	3/8	4	For horizontal installation into steel. Min. 0.06 in. steel thickness.

**For Installation in Concrete:**

<b>Model Designation</b>	<b>Hanger Type</b>	<b>Rod Size, in.</b>	<b>Nominal Pipe Size</b>	<b>Comments</b>
<b>Drive-In</b>	Drive-In Anchor	3/8	Up to 4	—
<b>Drive-In</b>	Drive-In Anchor	1/2	5, 6, 7, 8	—
<b>Lok Bolts</b>	Sleeve Anchor	3/8	Up to 4	—
<b>Lok Bolts</b>	Sleeve Anchor	1/2	5, 6, 7, 8	—
<b>Lok Bolts</b>	Sleeve Anchor	5/8	10, 12	—
<b>Dropin 6200</b>	Expansion Anchor	3/8	Up to 4	—
<b>Dropin 6200</b>	Expansion Anchor	1/2	5, 6, 7, 8	—
<b>Dropin 6200</b>	Expansion Anchor	5/8	10, 12	—
<b>Dropin 6200</b>	Expansion Anchor	3/4, 20 mm	12	—
<b>Dropin 6300</b>	Expansion Anchor	3/8	Up to 4	—
<b>Dropin 6300</b>	Expansion Anchor	1/2	5, 6, 7, 8	—

<b>Dropin 6300</b>	Expansion Anchor	5/8	10, 12	—
<b>Dropin 6300</b>	Expansion Anchor	3/4, 20 mm	12	—
<b>Power-Bolt 6900</b>	Heavy Duty Sleeve Anchor	3/8	Up to 4	—
<b>Power-Bolt 6900</b>	Heavy Duty Sleeve Anchor	1/2	5, 6, 7, 8	—
<b>Power-Bolt 6900</b>	Heavy Duty Sleeve Anchor	5/8	10, 12	Series 6900
<b>Power-Bolt 6900</b>	Heavy Duty Sleeve Anchor	3/4, 20 mm	12	—
<b>Power Stud 7200</b>	Wedge Anchor	3/8	Up to 4	—
<b>Power Stud 7200</b>	Wedge Anchor	1/2	5, 6, 7, 8	—
<b>Power Stud 7200</b>	Wedge Anchor	5/8, 20 mm	10, 12	—
<b>Power Stud 7200</b>	Wedge Anchor	3/4, 20 mm	12	—
<b>Power Stud 7200</b>	Wedge Anchor	7/8, 20 mm	12	—
<b>Power Stud 7300</b>	Wedge Anchor	3/8	Up to 4	—
<b>Power Stud 7300</b>	Wedge Anchor	1/2	5, 6, 7, 8	—
<b>Power Stud 7300</b>	Wedge Anchor	5/8, 20 mm	10, 12	—
<b>Power Stud 7300</b>	Wedge Anchor	3/4	12	—
<b>Power Stud 7300</b>	Wedge Anchor	7/8	12	—
<b>Power Stud 7400</b>	Wedge Anchor	3/8, 20 mm	Up to 4	—
<b>Power Stud 7400</b>	Wedge Anchor	1/2, 20 mm	5, 6, 7, 8	—
<b>Power Stud 7400</b>	Wedge Anchor	5/8, 20 mm	10, 12	—

<b>Power Stud 7400</b>	Wedge Anchor	3/4, 20 mm	12	—
<b>Power Stud 7600</b>	Wedge Anchor	3/8, 20 mm	Up to 4	—
<b>Power Stud 7600</b>	Wedge Anchor	1/2	5, 6, 7, 8	—
<b>Power Stud 7600</b>	Wedge Anchor	5/8	10, 12	—
<b>Power Stud 7600</b>	Wedge Anchor	3/4	Up to 12	—
<b>Power Stud 7600</b>	Wedge Anchor	7/8	12	—
<b>Power Stud 7700</b>	Wedge Anchor	3/8	Up to 4	—
<b>Power Stud 7700</b>	Wedge Anchor	1/2, 20 mm	5, 6, 7, 8	—
<b>Power Stud 7700</b>	Wedge Anchor	5/8, 20 mm	10, 12	—
<b>Power Stud 7700</b>	Wedge Anchor	3/4, 20 mm	12	—
<b>Power Stud 7700</b>	Wedge Anchor	7/8, 20 mm	12	—
<b>Power Stud 7800</b>	Wedge Anchor	3/8, 20 mm	Up to 4	—
<b>Power Stud 7800</b>	Wedge Anchor	1/2, 20 mm	5, 6, 7, 8	—
<b>Power Stud 7800</b>	Wedge Anchor	5/8, 20 mm	10, 12	—
<b>Power Stud 7800</b>	Wedge Anchor	3/4, 20 mm	12	—
<b>Power Stud 7800</b>	Wedge Anchor	7/8, 20 mm	12	—
<b>Hollow Set 9340</b>	Expansion Anchor	3/8	Up to 4	—
<b>Hollow Set 9350</b>	Expansion Anchor	1/2	Up to 8	—

<b>Hollow Set 9360</b>	Expansion Anchor	5/8	Up to 12	—
<b>SD1</b>	Expansion Anchor	3/8	Up to 4	Lengths, in.: 3, 3-1/2, 3-3/4, 5, 7
<b>SD1</b>	Expansion Anchor	1/2	Up to 8	Lengths, in.: 3-3/4, 4-1/2, 5-1/2, 7, 8-1/2
<b>SD1</b>	Expansion Anchor	5/8	Up to 12	Lengths, in.: 5, 6, 7, 8-1/2, 10
<b>SD2</b>	Expansion Anchor	3/8	Up to 4	Lengths, in.: 3, 3-1/2, 3-3/4, 5
<b>SD2</b>	Expansion Anchor	5/8	Up to 12	Lengths, in.: 4-3/4, 5, 6, 7, 8-1/2
<b>SD2</b>	Expansion Anchor	3/4	Up to 12	Lengths, in.: 5-1/2, 6-1/4, 7, 8-1/2
<b>Smart DI+</b>	Expansion Anchor	3/8	Up to 4	—
<b>Smart DI+</b>	Expansion Anchor	1/2	Up to 8	—
<b>Smart DI+</b>	Expansion Anchor	5/8, 20 mm	Up to 12	—
<b>Smart DI+</b>	Expansion Anchor	3/4, 20 mm	Up to 12	—

**Cast-In-Place Concrete Insert Installation:**

<b>Model Designation</b>	<b>Hanger Type</b>	<b>Rod Size, in.</b>	<b>Nominal Pipe Size</b>	<b>Comments</b>
<b>Bang-It+ 07542-PWR</b>	Cast-In-Place Concrete Insert	3/8	Up to 4	Also suitable for use in air-handling spaces.
<b>Bang-It+ 07543-PWR</b>	Cast-In-Place Concrete Insert	3/8 1/2	Up to 4 Up to 8	Also suitable for use in air-handling spaces.
<b>Bang-It+ 07544-PWR</b>	Cast-In-Place Concrete Insert	1/2	Up to 8	Also suitable for use in air-handling spaces.
<b>Bang-It+ 07546-PWR</b>	Cast-In-Place Concrete Insert	5/8	Up to 8	Also suitable for use in air-handling spaces.
<b>Bang-It+ 07548-PWR</b>	Cast-In-Place Concrete Insert	3/4	Up to 8	Also suitable for use in air-handling spaces.

<b>Bang-It+ PFM3521438</b>	Cast-In-Place Concrete Insert	3/8	Up to 4	Also suitable for use in air-handling spaces
<b>Bang-It+ PFM3525834</b>	Cast-In-Place Concrete Insert	5/8 3/4	Up to 10 Up to 10	Also suitable for use in air-handling spaces
<b>Bang-It+ PFM353143812</b>	Cast-In-Place Concrete Insert	3/8 1/2	Up to 4 Up to 8	Also suitable for use in air-handling spaces
<b>Bang-It+ PFM353381258</b>	Cast-In-Place Concrete Insert	3/8 1/2 5/8	Up to 4 Up to 8 Up to 10	Also suitable for use in air-handling spaces
<b>Wood-Knocker 7552</b>	Cast-In-Place Concrete Insert	3/8	Up to 4	Also suitable for use in air-handling spaces.
<b>Wood-Knocker 7554</b>	Cast-In-Place Concrete Insert	1/2	Up to 8	Also suitable for use in air-handling spaces.
<b>Wood-Knocker 7556</b>	Cast-In-Place Concrete Insert	5/8	Up to 8	Also suitable for use in air-handling spaces.
<b>Wood-Knocker II+ PFM2521150</b>	Cast-In-Place Concrete Insert	3/8	Up to 4	Also suitable for use in air-handling spaces.
<b>Pan-Knocker II+ PFM2521150NN</b>	Cast-In-Place Concrete Insert	3/8	Up to 4	Also suitable for use in air-handling spaces.
<b>Wood-Knocker II+ PFM2521200</b>	Cast-In-Place Concrete Insert	1/2	Up to 8	Also suitable for use in air-handling spaces.
<b>Pan-Knocker II+ PFM2521200NN</b>	Cast-In-Place Concrete Insert	1/2	Up to 8	Also suitable for use in air-handling spaces.
<b>Wood-Knocker II+ PFM2521250</b>	Cast-In-Place Concrete Insert	5/8	Up to 8	Also suitable for use in air-handling spaces.
<b>Pan-Knocker II+ PFM2521250NN</b>	Cast-In-Place Concrete Insert	5/8	Up to 8	Also suitable for use in air-handling spaces.

<b>Wood-Knocker II+ PFM2521300</b>	Cast-In-Place Concrete Insert	3/4	Up to 8	Also suitable for use in air-handling spaces.
<b>Pan-Knocker II+ PFM2521300NN</b>	Cast-In-Place Concrete Insert	3/4	Up to 8	Also suitable for use in air-handling spaces.
<b>Double Thread Wood Form Products</b>				
<b>Wood-Knocker II+ PFM2521350</b>	Cast-In-Place Concrete Insert	3/8 1/2	Up to 4 Up to 8	Also suitable for use in air-handling spaces.
<b>Wood-Knocker II+ PFM2521438</b>	Cast-In-Place Concrete Insert	3/8	Up to 4	Also suitable for use in air-handling spaces.
<b>Wood-Knocker II+ PFM2525834</b>	Cast-In-Place Concrete Insert	5/8 3/4	Up to 12 Up to 12	Also suitable for use in air-handling spaces.
<b>Pan-Knocker II+ PFM2521438NN</b>	Cast-In-Place Concrete Insert	3/8	Up to 4	Also suitable for use in air-handling spaces.
<b>Pan-Knocker II+ PFM2521350NN</b>	Cast-In-Place Concrete Insert	3/8 1/2	Up to 4 Up to 8	Also suitable for use in air-handling spaces.
<b>Pan-Knocker II+ PFM2525834NN</b>	Cast-In-Place Concrete Insert	5/8 3/4	Up to 12 Up to 12	Also suitable for use in air-handling spaces.
<b>Triple Thread Wood Form Products</b>				
<b>Wood-Knocker II+ PFM253143812</b>	Cast-In-Place Concrete Insert	3/8 1/2	Up to 4 Up to 8	Also suitable for use in air-handling spaces.
<b>Wood-Knocker II+ PFM253381258</b>	Cast-In-Place Concrete Insert	3/8 1/2 5/8	Up to 4 Up to 8 Up to 12	Also suitable for use in air-handling spaces.
<b>Pan-Knocker II+ PFM253143812NN</b>	Cast-In-Place Concrete Insert	3/8 1/2	Up to 4 Up to 8	Also suitable for use in air-handling spaces.

<b>Pan-Knocker II+ PFM253381258NN</b>	Cast-In-Place Concrete Insert	3/8 1/2 5/8	Up to 4 Up to 8 Up to 12	Also suitable for use in air-handling spaces.
<b>Low Profile Wood Form Products</b>				
<b>Wood-Knocker II+ PFM2500038</b>	Cast-In-Place Concrete Insert	3/8	Up to 4	Also suitable for use in air-handling spaces.
<b>Wood-Knocker II+ PFM2501438</b>	Cast-In-Place Concrete Insert	3/8	Up to 4	Also suitable for use in air-handling spaces.
<b>Pan-Knocker II+ PFM2500038NN</b>	Cast-In-Place Concrete Insert	3/8	Up to 4	Also suitable for use in air-handling spaces.
<b>Pan-Knocker II+ PFM2501438NN</b>	Cast-In-Place Concrete Insert	3/8	Up to 4	Also suitable for use in air-handling spaces.
<b>CIPPIT and DDI+</b>				
<b>CIPPIT PFM2610012</b>	Cast-In-Place Concrete Insert	1/2	Up to 8	Also suitable for use in air-handling spaces.
DDI+	Concrete Insert	3/8	4	Intended for use in concrete, minimum compressive strength of 2800 psi. Limited to a 45 degree installation orientation of metal strip on metal deck.
DDI+	Concrete Insert	1/2	8	Intended for use in concrete, minimum compressive strength of 2800 psi. Limited to a 45 degree installation orientation of metal strip on metal deck.
DDI+	Concrete Insert	5/8	12	Intended for use in concrete, minimum compressive strength of 2800 psi. Limited to a 45 degree installation orientation of metal strip on metal deck.
DDI+	Concrete Insert	3/4	12	Intended for use in concrete, minimum compressive strength of 2800 psi. Limited to a 45 degree installation orientation of metal strip on metal deck.
DDI+	Concrete Insert	7/8	12	Intended for use in concrete, minimum compressive strength of 2800 psi. Limited to a 45 degree installation orientation of metal strip on metal deck.



**Pipe hangers****For Installation into Steel**

<b>Model</b>	<b>Hanger Type</b>	<b>Min Steel Thkns, in.</b>	<b>Rod Size, in.</b>	<b>NPS*</b>	<b>Comments</b>
PFM2231050	Self-drilling anchor	0.125	3/8	4	—
PFM2231100	Self-drilling anchor	0.125	3/8	4	—
PFM223110N	Self-drilling anchor	0.060	3/8	4	—
PFM2231200	Self-drilling anchor	0.125	3/8	4	—
PFM223120N	Self-drilling anchor	0.060	3/8	4	—
PFM2231150	Self-drilling anchor	0.125	3/8	4	—
PFM223115N	Self-drilling anchor	0.060	3/8	4	—
PFM2231250	Self-drilling anchor	0.125	3/8	4	—
PFM2231300	Self-drilling anchor	0.125	3/8	4	—
PFM224110N	Self-drilling anchor	0.060	3/8	4	—
PFM224115N	Self-drilling anchor	0.060	3/8	4	—
PFM224120N	Self-drilling anchor	0.060	3/8	4	—
PFM227110N	Self-drilling anchor	0.1046 (12 ga.)	3/8	4	Horizontal and Vertical Installation
PFM227120N	Self-drilling anchor	0.1046 (12 ga.)	3/8	4	Horizontal and Vertical Installation
PFM227130N	Self-drilling anchor	0.1046 (12 ga.)	3/8	4	Horizontal and Vertical Installation

**For Installation into Wood**

<b>Model</b>	<b>Hanger Type</b>	<b>Min Wood Thkns, in.</b>	<b>Rod Size, in.</b>	<b>NPS*</b>	<b>Comments</b>
--------------	--------------------	--------------------------------	--------------------------	-------------	-----------------

PFM2271000	Self-threading anchor	1-1/2	3/8	4	Horizontal and Vertical Installation
------------	-----------------------	-------	-----	---	--------------------------------------

\* NPS = Nominal pipe size

Last Updated on 2020-01-14

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"