

**GENERAL INFORMATION**

**DOMESTIC WEDGE ANCHOR**

Carbon Steel and Stainless Steel Wedge Expansion Anchors

\*Anchor produced in the U.S.A., nut and washer made in Taiwan or China (domestic nut and washer by request)

**PRODUCT DESCRIPTION**

The Domestic Wedge Anchor is a threaded, torque-controlled, carbon steel or stainless steel wedge expansion anchor which is designed for consistent performance in concrete. Suitable base materials are normal-weight and lightweight concrete. The anchor is manufactured with carbon steel body and expansion clip or a stainless steel body and expansion clip. Nut and washer are included.

**GENERAL APPLICATIONS AND USES**

- Steel fixtures
- Support connections
- Equipment and railing

**FEATURES AND BENEFITS**

- + Anchors made in the U.S.A.
- + Nut and washer made in Taiwan or China, domestic nut and washer available upon request
- + Nominal drill bit size is the same as the anchor diameter
- + Anchor can be installed through standard size fixture clearance holes
- + Length ID code and identifying marking stamped on head of each anchor
- + Corrosion resistant stainless steel anchors available

**APPROVALS AND LISTINGS**

- Tested in accordance with ASTM E488

**GUIDE SPECIFICATIONS**

CSI Divisions: 03 16 00 - Concrete Anchors, 04 05 19.16 - Masonry Anchors and 05 05 19 - Post-Installed Concrete Anchors. Expansion anchors shall be Domestic Wedge Anchor as supplied by DEWALT, Towson, MD. Anchors shall be installed in accordance with published instructions and the Authority Having Jurisdiction.

**MATERIAL SPECIFICATIONS**

Anchor component	Specification		
	Carbon Steel <sup>1</sup>	Type 303	Type 316
Anchor body	AISI C12L14	303 Stainless Steel	316 Stainless Steel
Washer	AISI C1010-1018	300 Series Stainless Steel	316 Stainless Steel
Hex Nut	Low Carbon Steel, ASTM A563, Grade A	18-8 Stainless Steel	316 Stainless Steel
Expansion wedge (clip)	AISI C1010-1018	18-8 Stainless Steel	316 Stainless Steel

1. Zinc plated in accordance with ASTM B633, SC1 Type III.  
\* Domestic nut and washer available upon request.

**SECTION CONTENTS**

General Information..... 1  
 Material Specifications ..... 1  
 Installation Specifications ..... 2  
 Installation Instructions ..... 2  
 Reference Performance Data ..... 3  
 Ordering Information..... 5



DOMESTIC WEDGE ANCHOR ASSEMBLY

**THREAD VERSION**

- Threaded Stud (UNC)

**ANCHOR MATERIALS**

- Carbon Steel
- 303 Stainless Steel
- 316 Stainless Steel

**ANCHOR SIZE RANGE (TYP.)**

- 1/4" through 1-1/4" diameters

**SUITABLE BASE MATERIALS**

- Normal-weight Concrete
- Lightweight Concrete

**INSTALLATION SPECIFICATIONS**

**Installation Specifications Table for Domestic Wedge Anchor**

Anchor Property/ Setting Information	Notation	Units	Nominal Anchor Diameter (inch)							
			1/4	3/8	1/2	5/8	3/4	7/8	1	1-1/4
Anchor outside diameter	d	in.	0.25	0.375	0.500	0.625	0.750	0.875	1.000	1.250
Nominal drill bit diameter (ANSI)	d <sub>bit</sub>	in.	1/4	3/8	1/2	5/8	3/4	7/8	1	1-1/4
Minimum diameter of hole clearance in fixture	d <sub>h</sub>	in.	5/16	7/16	9/16	11/16	13/16	15/16	1-1/8	1-3/8
Minimum nominal embedment depth	h <sub>nom</sub>	in.	1-1/8	1-1/2	2-1/4	2-3/4	3-1/4	3-7/8	4-1/2	5-1/2
Minimum hole depth	h <sub>o</sub>	in.	1-3/8	1-7/8	2-3/4	3-1/4	3-3/4	4-3/8	5	6
Installation torque	T <sub>inst</sub>	ft.-lbf.	5-10	25-30	50-60	75-90	150-175	200-250	250-300	400-450
Torque wrench/socket size	-	in.	7/16	9/16	3/4	15/16	1-1/8	1-5/16	1-1/2	1-7/8
Nut height	-	in.	7/32	21/64	7/16	35/64	41/64	3/4	55/64	1-1/16


For SI: 1 inch = 25.4 mm, 1 ft-lbf = 1.356 N-m.

**Length Identification**

Mark	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S
From	1-1/2"	2"	2-1/2"	3"	3-1/2"	4"	4-1/2"	5"	5-1/2"	6"	6-1/2"	7"	7-1/2"	8"	8-1/2"	9"	9-1/2"	10"	11"
Up to but not including	2"	2-1/2"	3"	3-1/2"	4"	4-1/2"	5"	5-1/2"	6"	6-1/2"	7"	7-1/2"	8"	8-1/2"	9"	9-1/2"	10"	11"	12"

Length identification mark indicates overall length of anchor.

**DWA Anchor Detail**




**Nomenclature**


- d = Diameter of anchor
- d<sub>bit</sub> = Diameter of drill bit
- d<sub>h</sub> = Diameter of fixture clearance hole
- h = Base material thickness  
The minimum value of h should be 1.5h<sub>nom</sub> or 4" whichever is greater
- h<sub>nom</sub> = Minimum embedment depth

**INSTALLATION INSTRUCTIONS**


**Installation Instructions for Domestic Wedge Anchor**




**Step 1**  
Using the proper drill bit size, drill a hole into the base material to the required depth. The tolerances of the drill bit used should meet the requirements of ANSI Standard B212.15.



**Step 2**  
Remove dust and debris from the hole during drilling (e.g. dust extractor, hollow bit) or following drilling (e.g. suction, forced air) to extract loose particles created by drilling.



**Step 3**  
Position the washer on the anchor and thread on the nut. If installing through a fixture, drive the anchor through the hole. Be sure the anchor is driven to the minimum required embedment depth.



**Step 4**  
Tighten the anchor with a torque wrench by applying the required installation torque, T<sub>inst</sub>.

**PERFORMANCE DATA (ASD)**

**Ultimate Load Capacities for Domestic Wedge Anchor in Normal-Weight Concrete<sup>1,2</sup>**

Nominal Anchor Diameter (in.)	Minimum Embedment Depth (in.)	Concrete Compressive Strength, f'c					
		2,000 psi		4,000 psi		6,000 psi	
		Ultimate Tension Load Capacity (lbs.)	Ultimate Shear Load Capacity (lbs.)	Ultimate Tension Load Capacity (lbs.)	Ultimate Shear Load Capacity (lbs.)	Ultimate Tension Load Capacity (lbs.)	Ultimate Shear Load Capacity (lbs.)
1/4	1-1/8	1,170	1,445	1,770	1,815	2,775	2,635
	1-3/4	1,840		2,410		2,775	
	2-3/4	1,975		2,750		2,830	
3/8	1-1/2	1,630	4,320	3,640	5,120	4,450	6,235
	3	3,230		5,655		5,975	
	5	4,075		6,330		6,360	
1/2	2-1/4	4,000	7,420	6,715	9,380	9,615	9,890
	4	6,335		8,945		10,190	
	6	6,900		10,175		12,065	
5/8	2-3/4	5,000	8,265	8,750	12,930	9,760	16,375
	5	8,855		15,590		16,800	
	7	9,380		16,710		17,735	
3/4	3-1/4	6,640	12,505	11,315	17,050	16,230	22,965
	6	10,085		18,410		21,095	
	8	11,170		19,805		22,525	
7/8	3-7/8	8,395	18,250	16,355	20,235	16,800	23,980
	5-3/4	12,065		18,250		23,405	
	4-1/2	9,775		18,250		27,460	
1	7-1/2	11,890	23,620	26,725	27,605	34,960	28,910
	10	15,590		30,490		37,840	
	5-1/2	17,550		22,970		32,370	
1-1/4	7	21,050	32,275	27,845	42,690	48,365	55,565
	10	27,895		34,790		61,270	

1. Tabulated load values are for anchors installed in uncracked concrete with no edge or spacing considerations. Concrete compressive strength must be at the specified minimum at the time of installation.
2. Ultimate load capacities must be reduced by a minimum safety factor of 4.0 or greater to determine allowable working loads.

**MECHANICAL ANCHORS**

**DOMESTIC WEDGE ANCHOR**  
Carbon Steel and Stainless Steel Wedge Expansion Anchors

**Allowable Load Capacities for Carbon Steel and Stainless Steel Domestic Wedge Anchor in Normal-Weight Concrete<sup>1,2,3</sup>**



Nominal Anchor Diameter (in.)	Minimum Embedment Depth (in.)	Concrete Compressive Strength, f'c					
		2,000 psi		4,000 psi		6,000 psi	
		Allowable Tension Load Capacity (lbs.)	Allowable Shear Load Capacity (lbs.)	Allowable Tension Load Capacity (lbs.)	Allowable Shear Load Capacity (lbs.)	Allowable Tension Load Capacity (lbs.)	Allowable Shear Load Capacity (lbs.)
1/4	1-1/8	295	360	445	455	695	660
	1-3/4	460		600		695	
	2-3/4	495		690		710	
3/8	1-1/2	410	1,080	910	1,280	1,115	1,560
	3	810		1,415		1,495	
	5	1,020		1,580		1,590	
1/2	2-1/4	1,000	1,855	1,680	2,345	2,405	2,475
	4	1,585		2,235		2,550	
	6	1,725		2,545		3,015	
5/8	2-3/4	1,250	2,065	2,190	3,235	2,440	4,095
	5	2,215		3,900		4,200	
	7	2,345		4,180		4,435	
3/4	3-1/4	1,660	3,125	2,830	4,265	4,060	5,740
	6	2,520		4,600		5,275	
	8	2,795		4,950		5,630	
7/8	3-7/8	2,100	4,565	4,090	5,060	4,200	5,995
	5-3/4	3,015		4,565		5,850	
1	4-1/2	2,445	5,905	4,565	6,900	6,865	7,230
	7-1/2	2,975		6,685		8,740	
	10	3,900		7,625		9,460	
1-1/4	5-1/2	4,390	8,070	5,745	10,675	8,095	13,890
	7	5,265		6,960		12,095	
	10	6,975		8,700		15,320	

1. Tabulated load values are for anchors installed in uncracked concrete. Concrete compressive strength must be at the specified minimum at the time of installation.  
 2. Allowable load capacities listed are calculated using and applied safety factor of 4.0.  
 3. Allowable loads for lightweight concrete may be determined by multiplying the tabulated allowable load capacities for normal weight concrete by 0.60.

**MECHANICAL ANCHORS**

**DOMESTIC WEDGE ANCHOR**  
Carbon Steel and Stainless Steel Wedge Expansion Anchors

**ORDERING INFORMATION**



**\*Domestic Wedge Anchor (Carbon Steel)**

Cat. No.	Size	Thread Length	Pack Qty.	Carton Qty.
7400USA-PWR	1/4" x 1-3/4"	3/4"	100	500
7402USA-PWR	1/4" x 2-1/4"	3/4"	100	500
7404USA-PWR	1/4" x 3-1/4"	3/4"	100	500
7410USA-PWR	3/8" x 2-1/4"	7/8"	50	250
7412USA-PWR	3/8" x 2-3/4"	1-1/8"	50	250
7413USA-PWR	3/8" x 3"	1-1/8"	50	250
7415USA-PWR	3/8" x 3-3/4"	1-1/8"	50	250
7416USA-PWR	3/8" x 5"	1-1/8"	50	250
7417USA-PWR	3/8" x 6-1/2"	1-1/8"	50	200
7420USA-PWR	1/2" x 2-3/4"	1-1/4"	50	200
7422USA-PWR	1/2" x 3-3/4"	1-1/4"	50	200
7423USA-PWR	1/2" x 4-1/2"	1-1/4"	50	200
7424USA-PWR	1/2" x 5-1/2"	1-1/4"	50	150
7426USA-PWR	1/2" x 7"	1-1/4"	25	100
7428USA-PWR	1/2" x 10"	1-1/4"	25	100
7430USA-PWR	5/8" x 3-1/2"	2"	25	100
7432USA-PWR	5/8" x 4-1/2"	2"	25	100
7433USA-PWR	5/8" x 5"	2"	25	100
7434USA-PWR	5/8" x 6"	2"	25	75
7436USA-PWR	5/8" x 7"	2"	25	75
7440USA-PWR	3/4" x 4-1/4"	2"	20	60
7441USA-PWR	3/4" x 4-3/4"	2"	20	60
7442USA-PWR	3/4" x 5-1/2"	2"	20	60
7444USA-PWR	3/4" x 6-1/4"	2"	20	60
7446USA-PWR	3/4" x 7"	2"	20	60
7449USA-PWR	3/4" x 10"	2"	10	30
7461USA-PWR	1" x 6"	2-1/4"	10	40
7475USA-PWR	1-1/4" x 12"	3-1/4"	5	15

**Installation Accessories**

Cat. No.	Description	Pack Qty
08280-PWR	Hand pump / dust blower	1

\*Made to Order

The published size includes the diameter and the overall length of the carbon and stainless steel anchors.

All anchors are packaged with nuts and washers.

**\*Domestic Wedge Anchor (303 Stainless Steel)**

Cat. No.	Size	Thread Length	Pack Qty.	Carton Qty.
7300USA-PWR	1/4" x 1-3/4"	3/4"	100	500
7304USA-PWR	1/4" x 3-1/4"	3/4"	100	500
7312USA-PWR	3/8" x 2-3/4"	1-1/8"	50	250
7313USA-PWR	3/8" x 3"	1-1/8"	50	250
7314USA-PWR	3/8" x 3-1/2"	1-1/8"	50	250
7315USA-PWR	3/8" x 3-3/4"	1-1/8"	50	250
7316USA-PWR	3/8" x 5"	1-1/8"	50	250
7320USA-PWR	1/2" x 2-3/4"	1-1/4"	50	200
7322USA-PWR	1/2" x 3-3/4"	1-1/4"	50	200
7323USA-PWR	1/2" x 4-1/2"	1-1/4"	50	200
7324USA-PWR	1/2" x 5-1/2"	1-1/4"	50	150
7326USA-PWR	1/2" x 7"	1-1/4"	25	100
7332USA-PWR	5/8" x 4-1/2"	2"	25	100
7341USA-PWR	3/4" x 4-3/4"	2"	20	60
7348USA-PWR	3/4" x 8-1/2"	2"	10	40
7349USA-PWR	3/4" x 10"	2"	10	30

**\*Domestic Wedge Anchor (316 Stainless Steel)**

Cat. No.	Size	Thread Length	Pack Qty.	Carton Qty.
7600USA-PWR	1/4" x 1-3/4"	3/4"	100	500
7602USA-PWR	1/4" x 2-1/4"	3/4"	100	500
7610USA-PWR	3/8" x 2-1/4"	7/8"	50	250
7612USA-PWR	3/8" x 2-3/4"	1-1/8"	50	250
7613USA-PWR	3/8" x 3"	1-1/8"	50	250
7614USA-PWR	3/8" x 3-1/2"	1-1/8"	50	250
7615USA-PWR	3/8" x 3-3/4"	1-1/8"	50	250
7616USA-PWR	3/8" x 5"	1-1/8"	50	250
7626USA-PWR	1/2" x 7"	1-1/4"	25	100
7632USA-PWR	5/8" x 4-1/2"	2"	25	100
7633USA-PWR	5/8" x 5"	2"	25	100
7634USA-PWR	5/8" x 6"	2"	25	75
7636USA-PWR	5/8" x 7"	2"	25	75
7638USA-PWR	5/8" x 8-1/2"	2"	25	75
7642USA-PWR	3/4" x 5-1/2"	2"	20	60
7646USA-PWR	3/4" x 7"	2"	20	60