

DEWALT®

ANCHORS & FASTENERS

CONCRETE SCREWS

CARBON STEEL &
STAINLESS STEEL
CONCRETE SCREW ANCHORS

GUARANTEED TOUGH.®

ICDWULTRACONBR



UltraCon®+

Blue, Carbon Steel
3/16 in. & 1/4 in. Diameters

UltraCon®+

Bronze, Carbon Steel
3/16 in. & 1/4 in. Diameters

UltraCon®+

Silver, Carbon Steel
3/16 in. & 1/4 in. Diameters

UltraCon®+

White, Carbon Steel
3/16 in. & 1/4 in. Diameters

UltraCon®

Silver, Carbon Steel
5/16 in. Diameter

UltraCon® SS4

410 Stainless Steel
1/4 in. Diameter

Crete-Flex®

410 Stainless Steel
3/16 in. & #14 Diameters






Aggre-Gator®

304 Stainless Steel
1/4 in. Diameter

TYPICAL APPLICATIONS

- Temporary Framing
- Window Frames
- Conduit Clips
- Furring Strips
- Sill Plate
- Storm Shutters

BASE MATERIALS

	 Concrete	 Masonry	 Brick	 Chemically Treated Lumber	 Wood
UltraCon®+	■	■	■	■	■
UltraCon® (5/16 in.)	■	■	□	□	■
UltraCon® SS4	■	■	□	□	□
Crete-Flex®	■	■	□	□	■
Aggre-Gator®	■	■	■	■	■

■ : Suitable base material. □ : May be considered.

NEW 6-LOBE STAR DRIVE FLAT HEAD

- More Consistent Driving
- Better Bit Grip
- Less Susceptible to Cam-Out
- Longer Bit-Tip Life
- Featured in All Colors & Sizes



UltraCon+ ICC-ES Approved for use in concrete, masonry, chemically treated lumber and wood-to-wood applications.

APPROVALS



ESR-3068 Concrete
ESR-3196 Masonry
ESR-3213 Chemically Treated Lumber
ESR-3042 Wood-to-Wood

UltraCon®+**



Miami-Dade NOA
Notice of Acceptance

UltraCon®+

UltraCon® (5/16 in.)

Aggre-Gator®

Crete-Flex®

UltraCon® SS4



Florida Building Code
(including Residential)

UltraCon®+

UltraCon® (5/16 in.)

Aggre-Gator®

Crete-Flex®

UltraCon® SS4

** 3/16 in. & 1/4 in. carbon steel UltraCon+ diameters are ICC approved in select lengths.

HEADSTYLE OFFERINGS

	COLOR	HEX WASHER	HEX TRIMFIT	HEX FLANGE	FLAT HEAD	TRIMFIT HEAD	OVERSIZED HEAD	SIZE RANGE			
UltraCon®+	Blue Stalgard Coating							HEX WASHER HEAD: 3/16 in. x 1-1/4 in. to 3/16 in. x 4 in. 1/4 in. x 1 in. to 1/4 in. x 6 in.	T25 STAR DRIVE FLAT HEAD 3/16 in. x 1-1/4 in. to 3/16 in. x 4 in. 1/4 in. x 1-1/4 in. to 1/4 in. x 6 in.		
	White Stalgard Coating							HEX WASHER HEAD: 3/16 in. x 1-1/4 in. to 3/16 in. x 3-1/4 in., 1/4 in. x 1-1/4 in. to 1/4 in. x 6 in.	HEX FLANGE HEAD: 1/4 in. x 1-3/4 in. to 1/4 in. x 3-1/4 in.	T25 STAR DRIVE FLAT HEAD 3/16 in. x 1-1/4 in. to 3/16 in. x 3-3/4 in. 1/4 in. x 1-1/4 in. to 1/4 in. x 3-1/4 in.	T25 STAR DRIVE TRIMFIT HEAD 1/4 in. x 1-3/4 in. to 1/4 in. x 4 in.
	Silver Stalgard Coating							HEX WASHER HEAD: 1/4 in. x 1-1/4 in. to 1/4 in. x 3-1/4 in.	HEX FLANGE HEAD: 1/4 in. x 1-3/4 in. to 1/4 in. x 3-1/4 in.	T25 STAR DRIVE FLAT HEAD 3/16 in. x 1-1/4 in. to 3/16 in. x 3-3/4 in.	T25 STAR DRIVE TRIMFIT HEAD 1/4 in. x 1-1/4 in. to 1/4 in. x 4 in.
	Bronze Stalgard Coating							HEX WASHER HEAD: 1/4 in. x 4 in. to 1/4 in. x 4 in.			T25 STAR DRIVE TRIMFIT HEAD 3/16 in. x 2-3/4 in. to 3/16 in. x 2-3/4 in., 1/4 in. x 2-3/4 in. to 1/4 in. x 4 in.
UltraCon® (5/16 in.)	Silver Stalgard Coating							HEX WASHER HEAD: 5/16 in. x 1-3/4 in. to 5/16 in. x 6 in.	HEX TRIMFIT WASHER HEAD: 5/16 in. x 1-3/4 in. to 5/16 in. x 3-3/4 in.	T30 STAR DRIVE FLAT HEAD 5/16 in. x 2-1/4 in. to 5/16 in. x 6 in.	T30 STAR DRIVE TRIMFIT HEAD 5/16 in. x 2-1/4 in. to 5/16 in. x 5 in.
	Crete-Flex®							HEX WASHER HEAD: 3/16 in. x 1-1/4 in. to 3/16 in. x 2-3/4 in., #14 x 1-1/4 in. to #14 x 3-3/4 in.	HEX FLANGE HEAD: #14 x 1-3/4 in. to #14 x 2-1/4 in.	T25 STAR DRIVE FLAT HEAD 3/16 in. x 1-1/4 in. to 3/16 in. x 3-1/4 in., #14 x 1-1/4 in. to #14 x 6 in.	T25 STAR DRIVE TRIMFIT HEAD 5/16 in. x 3 in. to 5/16 in. x 6 in.
Aggre-Gator®	Silver Stalgard Coating							HEX WASHER HEAD: 1/4 in. x 1-1/4 in. to 1/4 in. x 4 in.			T25 STAR DRIVE TRIMFIT HEAD 1/4 in. x 1-1/4 in. to 1/4 in. x 4 in.
UltraCon® SS4	Silver Stalgard Coating							HEX WASHER HEAD: 1/4 in. x 1-1/4 in. to 1/4 in. x 6 in.		T25 STAR DRIVE FLAT HEAD 1/4 in. x 1-1/4 in. to 1/4 in. x 4 in.	



RELATED PRODUCTS & ACCESSORIES

DRILL / FASTEN	ACCESSORIES	EXTRACTORS	DRILL / DRIVE SYSTEM
 <p>DCH273 20V MAX XR® Brushless 1 in. L-Shape SDS Plus Rotary Hammer</p>	 <p>DWH303DH Dust Extractor for DCH273 1 in. L-Shape SDS Plus Rotary Hammer</p>	 <p>DCV585 DEWALT FLEXVOLT® 60V MAX™ Dust Extractor</p>	<p>DW5366 UltraCon+ Installation Kit</p> 
 <p>DCH172 20V MAX™ ATOMIC Brushless 5/8 in. SDS+ Rotary Hammer Drill</p>	 <p>DWH205DH Dust Extractor for DCH263 1-1/8 in. D-Handle SDS Plus Rotary Hammer</p>	<p>DWH161 20V MAX™ Brushless Universal Dust Extractor Kit</p> 	<p>DW5381 5/32 in. UltraCon+ Hex SDS+ Bit</p> 
 <p>DCH263 20V MAX XR® Brushless 1-1/8 in. D-Handle Rotary Hammer</p>	 <p>DWH050 Large Hammer Dust Extraction - Hole Cleaning</p>	<p>DWV010 8 Gallon Wet/Dry HEPA/RRP Dust Extractor</p> 	<p>DW5382 3/16 in. UltraCon+ Hex SDS+ Bit</p> 
	 <p>DWH200D Dust Extraction Tube Kit With Hose</p>	<p>DWV015 10 Gallon Dust Extractor</p> 	<p>Drive Sleeve</p> 
			<p>DWAF1TX251R3 DEWALT 1in T25 FLEXTORQ®</p> 
			<p>DWAF1TX301R3 DEWALT 1in T30 FLEXTORQ®</p> 
			<p>1/4 in. Hex Socket</p> 
			<p>5/16 in. Hex Socket</p> 

* Maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18. Copyright © 2024 DEWALT. The following are trademarks for one or more DEWALT power tools, accessories, anchors and concrete adhesives: The yellow and black color scheme; the in.Din.-shaped air intake grill; the array of pyramids on the handgrip; the kit box configuration; and the array of lozenge-shaped humps on the surface of the tool.

ICDWULTRACONBR