

**GENERAL INFORMATION**

**WALL-DOG™**

Universal Light Duty Anchor

**PRODUCT DESCRIPTION**

The Wall-Dog is an all steel, one-piece screw anchor, which features high-profile threads for easy fastening into wallboard and other masonry base materials. The deep cutting, corkscrew-like threads provide for smooth entry and a powerful hold. When removed, the Wall-Dog leaves a much smaller hole than toggles or other systems. For aesthetic appearances, the Wall-Dog is available in several color finishes and head styles.

For fastening into wallboard or wood, no pre-drilling is required – the anchor is inserted through the fixture and screwed in with an ordinary Phillips screwdriver (Robertson head style also available). Fastening into concrete, hollow or grout-filled concrete masonry, brick and plaster requires a pre-drilled hole using a 3/16" ANSI bit. Typical applications include lightweight fixtures, drapery supports, as well as electrical, telephone and cable accessories.

**FEATURES AND BENEFITS**

- + Installs in a variety of base materials.
- + Installs directly through fixtures into wallboard – no second step or hole spotting required
- + When removed the anchor leaves a much smaller hole than toggles or other systems
- + Thread design prevents spinning and stripping
- + Heat treated point penetrates wood studs and thin metal
- + Several finished head styles to match application
- + No pilot hole required for wallboard
- + Can be easily backed out of hole
- + Fits through 7/32" clearance holes in fixtures


**MATERIAL SPECIFICATIONS**

Anchor Component	Component Material
Anchor Body	Carbon Steel
Plating / Finish	Zinc, White, Black, Bronze or Brass


**INSTALLATION SPECIFICATIONS**

ANSI Drill Bit Size (in.)	3/16 (Required for concrete, masonry and plaster)
Head Size	No. 8
Driver	No. 2 Phillips

**INSTALLATION GUIDELINES**



For fastening into wallboard or wood, no pre-drilling is required. The anchor is inserted through the fixture and screwed in with an ordinary Phillips screwdriver (or Robertson driver for Robertson head style).



Fastening into concrete, grout-filled or hollow block, brick or plaster requires a 3/16" pre-drilled hole using a carbide tipped drill bit.

**SECTION CONTENTS**

General Information..... 1  
 Installation Guidelines..... 1  
 Performance Data..... 2  
 Ordering Information..... 3



COMBO HEX WASHER HEAD



PHILLIPS WAFER HEAD



ROBERTSON HEAD



PHILLIPS OVAL HEAD



PHILLIPS PAN HEAD

**ANCHOR MATERIALS**

- Carbon Steel

**ANCHOR SIZE RANGE (TYP.)**

- 1/4" Diameter with No. 8 Head

**SUITABLE BASE MATERIALS**

- Concrete
- Grout-Filled Concrete Masonry
- Hollow Concrete Masonry
- Brick Masonry
- Wallboard
- Plywood
- Plaster

**PERFORMANCE DATA**

**Ultimate and Allowable Load Capacities for Wall-Dog in Normal-Weight Concrete<sup>1,2</sup>**

Anchor Diameter in.	Minimum Embedment in. (mm)	Minimum Concrete Compressive Strength f'c ≥ 4,000 psi (27.6 MPa)			
		Ultimate Load		Allowable Load	
		Tension lbs. (kN)	Shear lbs. (kN)	Tension lbs. (kN)	Shear lbs. (kN)
1/4	3/4 (19.1)	350 (1.6)	1,030 (4.6)	90 (0.4)	260 (1.2)
	1 (25.4)	700 (3.2)	1,070 (4.8)	175 (0.8)	270 (1.2)

1. Allowable load capacities listed are calculated using an applied safety factor of 4.0.  
2. These fasteners are not recommended for use overhead or applications where holding values are critical.

**Ultimate Load Capacities for Wall-Dog in Wallboard and Plywood<sup>1,2</sup>**

Anchor Diameter in.	1/2" Wallboard		5/8" Wallboard		3/4" Plywood	
	Tension lbs. (kN)	Shear lbs. (kN)	Tension lbs. (kN)	Shear lbs. (kN)	Tension lbs. (kN)	Shear lbs. (kN)
1/4	85 (0.4)	245 (1.1)	135 (0.6)	360 (1.6)	255 (1.1)	600 (2.7)

1. Ultimate load capacities are provided for reference and must be reduced by a minimum safety factor of 4.0 or greater to determine allowable working loads.  
2. These fasteners are not recommended for use overhead or applications where holding values are critical.

**Allowable Load Capacities for Wall-Dog in Wallboard and Plywood<sup>1,2</sup>**

Anchor Diameter in.	1/2" Wallboard		5/8" Wallboard		3/4" Plywood	
	Tension lbs. (kN)	Shear lbs. (kN)	Tension lbs. (kN)	Shear lbs. (kN)	Tension lbs. (kN)	Shear lbs. (kN)
1/4	20 (0.1)	60 (0.3)	35 (0.2)	90 (0.4)	65 (0.3)	150 (0.7)

1. Allowable load capacities listed are calculated using an applied safety factor of 4.0.  
2. These fasteners are not recommended for use overhead or applications where holding values are critical.

**Ultimate Load Capacities for Wall-Dog in Grout-Filled, Hollow Concrete Masonry and Brick Masonry<sup>1,2</sup>**

Anchor Diameter in.	Minimum Embedment in. (mm)	Anchor Location	Grout-Filled Concrete Masonry		Hollow Concrete Masonry		Brick Masonry	
			Tension lbs. (kN)	Shear lbs. (kN)	Tension lbs. (kN)	Shear lbs. (kN)	Tension lbs. (kN)	Shear lbs. (kN)
1/4	3/4 (19.1)	Center of Masonry Unit	–	–	–	–	400 (1.8)	650 (2.9)
	3/4 (19.1)	Bed Joint or T-Joint	–	–	–	–	350 (1.6)	600 (2.7)
	1 (25.4)	Center of Masonry Unit	285 (1.3)	825 (3.7)	305 (1.4)	825 (3.7)	600 (2.7)	900 (4.1)
	1 (25.4)	Bed Joint or T-Joint	290 (1.3)	915 (4.1)	290 (1.3)	915 (4.1)	380 (1.7)	825 (3.7)

1. Ultimate load capacities are provided for reference and must be reduced by a minimum safety factor of 5.0 or greater to determine allowable working loads.  
2. These fasteners are not recommended for use overhead or applications where holding values are critical.

**Allowable Load Capacities for Wall-Dog in Grout-Filled, Hollow Concrete Masonry and Brick Masonry<sup>1,2</sup>**

Anchor Diameter in.	Minimum Embedment in. (mm)	Anchor Location	Grout-Filled Concrete Masonry		Hollow Concrete Masonry		Brick Masonry	
			Tension lbs. (kN)	Shear lbs. (kN)	Tension lbs. (kN)	Shear lbs. (kN)	Tension lbs. (kN)	Shear lbs. (kN)
1/4	3/4 (19.1)	Center of Masonry Unit	–	–	–	–	80 (0.4)	130 (0.6)
	3/4 (19.1)	Bed Joint or T-Joint	–	–	–	–	70 (0.3)	120 (0.5)
	1 (25.4)	Center of Masonry Unit	55 (0.2)	165 (0.7)	60 (0.3)	165 (0.7)	120 (0.5)	180 (0.8)
	1 (25.4)	Bed Joint or T-Joint	60 (0.3)	185 (0.8)	60 (0.3)	185 (0.8)	75 (0.3)	165 (0.7)

1. Allowable load capacities listed are calculated using an applied safety factor of 5.0.  
2. These fasteners are not recommended for use overhead or applications where holding values are critical.

**ORDERING INFORMATION**

**Wall-Dog**

Cat No.	Head Style	Color	Length	Box Qty	Carton Qty
02271-PWR	Combo Hex Washer Head	Zinc	1-1/4"	100	500
02277-PWR	Phillips Wafer Head	White	1-1/2"	100	500
02278-PWR	Phillips Wafer Head	White	2"	100	500
02279-PWR	Phillips Wafer Head	White	2-1/4"	100	500
02280-PWR	Phillips Wafer Head	White	2-1/2"	100	500
02266-PWR	Robertson Head	Zinc	1-1/4"	100	500
02314-PWR	Oval Head	Zinc	1-1/4"	100	1000
02328-PWR	Oval Head	White	1-1/4"	100	1000
02288-PWR	Oval Head	Black	1-1/4"	100	500
02316-PWR	Phillips Pan Head	Zinc	1-1/4"	100	1000
02330-PWR	Phillips Pan Head	White	1-1/4"	100	1000
02273-PWR	Phillips Pan Head	White	1-1/2"	100	600
02274-PWR	Phillips Pan Head	Bronze	1-1/2"	100	600
02275-PWR	Phillips Pan Head	Zinc	1-1/2"	100	600
02276-PWR	Phillips Pan Head	Black	1-1/2"	100	600
02286-PWR	Phillips Pan Head	Black	1-1/4"	100	500
02294-PWR	Phillips Pan Head	Brass	1-1/4"	100	500

Screws with a white finish have a white head and a zinc body.



Combo Hex Washer Head



Phillips Wafer Head



Robertson Head



Phillips Oval Head



Phillips Pan Head

**Bulk Wall-Dog**

Cat No.	Head Style	Color	Length	Box Qty
02265-PWR	Combo Hex Washer Head	Zinc	1-1/4"	5000
02281-PWR	Robertson Head	Zinc	1-1/4"	5000
02331-PWR	Phillips Pan Head	White	1-1/4"	5000
02315-PWR	Phillips Pan Head	Zinc	1-1/4"	5000