



BUILDING TRUST



# Sika Emseal Safety Data Sheet Product Package

## BEJS System

The information contained in these Emseal-specific or Sika-specific Safety Data Sheets applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof.

Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika Emseal product, which are available at web site and/or telephone number listed in Section 1 of this SDS

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.





**EMSEAL Joint Systems, Ltd.**  
 25 Bridle Lane, Westborough, MA 01581 USA  
[www.emseal.com](http://www.emseal.com)

# Safety Data Sheet

## BEJS Foam

**Preparation Date** March 15, 2015    **Revision Date** June 19, 2018

### 1. Identification of the Substance / Preparation

<b>Product identifier</b>	<b>BEJS</b>
<b>Other identifier or names</b>	BEJS System, BEJS Foam
<b>UN ID number</b>	None
<b>Manufacturer Address</b>	EMSEAL LLC 111 Royal Group Crescent Woodbridge, Ontario L4H 1X9 Canada
<b>Company Phone</b>	(508) 836-0280 M-F 9am - 5pm
<b>Emergency Phone</b>	CHEMTREC (800) 424-9300 (24 Hours)
<b>CHEMTREC International Phone</b>	+1 703-527-3887 (24 Hours)

### 2. Hazardous Identification

<b>Hazardous Classification</b>	This product is not classified as hazardous when used as intended.
<b>Signal Word</b>	None
<b>Pictograms</b>	None
<b>Emergency Overview:</b>	No emergency requirements.

### 3. Composition / Information on Ingredients

*EMSEAL BEJS is composed of polyurethane foam impregnated with a proprietary solid acrylic polymer bonded to a fully cured silicone sealant. It is classified as Non-Hazardous.*

**NOTE: Silicone facing is fully cured. The composition of the silicone in its liquid state is comprised of the following:**

<b>Chemical Name</b>	<b>CAS #</b>	<b>% by Weight</b>	<b>GHS Classification Hazard Statements</b>
Polydimethyl Siloxane Diol	70131-67-8 3	0.0–60.0	SELF CLASSIFICATION Classification: Not Applicable
Calcium Carbonate (Limestone)	1317-65-3		SELF CLASSIFICATION
Synthetic Calcium Carbonate	371-34-1	10.0–40.0	Classification: Not Applicable
Phenyl Oximino Silane	34036-80-1	1.0–5.0	Classification: STOT RE Cat. 2, Skin Sensitization Cat. 1, Aquatic, Chronic Toxicity Cat. 3 Hazard Statement Codes: H373, H317, H412
Silicon Dioxide, Fumed	112945-52-5	1.0–5.0	SELF CLASSIFICATION Classification: Not Applicable
Mineral Spirits	8052-41-3	0.0-1.0	Classification: Carcinogenic Cat. 1B, Mutagenic Cat. 1B, Aspiration Hazard Cat. 1 Hazard Statement Codes: H350, H340, H304
Quartz	14808-60-7 14464-46-1	Trace	SELF CLASSIFICATION Classification: Carcinogenic Cat. 1B Hazard Statement Codes: H350

Water and other components.

Each of the other components is present in less than 1 percent concentration (0.1% concentration for potential carcinogens, reproductive toxins, respiratory tract sensitizers, and mutagens).

Classification: Not Applicable



## 4. First Aid Measures

---

- 4.1 EYES:** Flush with water for at least 15 minutes, and call physician if problems persist.
- 4.2 SKIN:** Product may leave a sticky residue, and mild irritation if prolonged exposure. Scrub with soapy water until adhesive is removed.
- 4.3 INGESTION:** Do not eat – call physician if ingested.

## 5. Fire-fighting Measures

---

- 5.2 FLAMMABILITY:** Slight. Material can support an open flame or smoldering ignition. The foam can melt while burning which can contribute fire to spread.
- 5.2 FLASH POINT:** Unknown.
- 5.3 AUTO-IGNITION TEMPERATURE:** Unknown.
- 5.4 EXTINGUISHING MEDIA:** Large volumes of water, or ABC chemical may be appropriate for initial control or small volumes of impregnated foam.
- 5.5 HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon di/mon oxides will be formed as well as other noxious and toxic fumes upon combustion – do not breath combustion products.

## 6. Accidental Release Measures

---

If material is unusable pick up pieces and dispose of in accordance with local regulations; material and all components are non-toxic and normal landfill will most often be acceptable.

## 7. Handling and Storage

---

Store in original packaging below 35°C. There are no special handling instructions.

## 8. Exposure Controls / Personal Protection

---

- 8.1 RESPIRATORY PROTECTION:** Not required
- 8.2 EYE PROTECTION:** Not required
- 8.3 SKIN PROTECTION:** Gloves of any material are suitable if desired, but not required. No other protection is required.

## 9. Physical and Chemical Properties

---

- 9.1 APPEARANCE:** Dark grey / charcoal colored foam and colored silicone with product identifying packaging.
- 9.2 ODOR:** Slight characteristic odor.
- 9.3 PERCENT SOLIDS BY WEIGHT:** 100%
- 9.4 PHYSICAL STATE:** Solid
- 9.5 PERCENT VOLATILE:** <1% wt/wt
- 9.6 DENSITY:** 0.4g/cm<sup>3</sup>
- 9.7 DECOMPOSITION:** > 300°C
- 9.8 SOLUBILITY IN WATER:** None



## 10. Stability and Reactivity

---

Stable under normal conditions – avoid temperatures in excess of 300°C, strong acids and bases, and open flame.

## 11. Toxicological Information

---

Unknown.

## 12. Ecological Information

---

Unknown

## 13. Disposal Considerations

---

No known hazard. Dispose of in accordance with local regulations; material and all components are non-toxic and disposal in normal landfill will most often be acceptable.

## 14. Transportation Information

---

Not hazardous – safe for non-hazardous shipping.

## 15. Regulatory Information

---

Unknown.

## 16. Other Information

---

No other information provided.

# Northern Manufacturing Construction Grade Epoxy Part A

Revision Date 06/14/2019

Print Date 07/25/2020

## SECTION 1. IDENTIFICATION

Product name : Northern Manufacturing Construction Grade Epoxy Part A

Company name : Northern Manufacturing  
111 Royal Group Crescent, Unit NM  
Woodbridge, ON L4H 1X9 Canada

Telephone : 416-740-2090 (8AM - 5PM EST) (M-F)

Emergency telephone : :Chemtrec 1-800-424-9300 (24 Hours)

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

## SECTION 2. HAZARDS IDENTIFICATION

### GHS classification in accordance with 29 CFR 1910.1200

Skin irritation : Category 2

Eye irritation : Category 2A


Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Specific target organ system-ic toxicity - single exposure : Category 3 (Respiratory system)

Specific target organ system-ic toxicity - repeated exposure : Category 1 (Lungs)

### GHS label elements

Hazard pictograms : 

# Northern Manufacturing Construction Grade Epoxy

## Part A

Revision Date 06/14/2019

Print Date 07/25/2020

Signal Word	:	Danger
Hazard Statements	:	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H350i May cause cancer by inhalation. H372 Causes damage to organs (Lungs) through prolonged or repeated exposure.
Precautionary Statements	:	<b>Prevention:</b> P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. P264 Wash skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. <b>Response:</b> P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 + P364 Take off contaminated clothing and wash it before reuse. <b>Storage:</b> P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. <b>Disposal:</b> P501 Dispose of contents/ container to an approved waste disposal plant.

### Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

# Northern Manufacturing Construction Grade Epoxy

## Part A

Revision Date 06/14/2019

Print Date 07/25/2020

**Other hazards**

None known.

---

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**
**Mixtures****Components**

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Quartz (SiO <sub>2</sub> )	14808-60-7	Carc. 1A; H350i STOT RE 1; H372 STOT SE 3; H335	>= 30 - < 50
bisphenol-A-(epichlorhydrin) epoxy resin	25068-38-6	Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Skin Sens. 1; H317	>= 10 - < 20
oxirane, mono[(C12-14-alkyloxy)methyl]derivatives	68609-97-2	Skin Irrit. 2; H315 Skin Sens. 1; H317	>= 5 - < 10

Actual concentration is withheld as a trade secret

---

**SECTION 4. FIRST AID MEASURES**

General advice	: Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attendance.
If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.
Most important symptoms and effects, both acute and delayed	: irritant effects sensitizing effects carcinogenic effects Cough Respiratory disorder Allergic reactions



# Northern Manufacturing Construction Grade Epoxy

## Part A

Revision Date 06/14/2019

Print Date 07/25/2020

Excessive lachrymation  
Erythema  
Dermatitis  
Causes skin irritation.  
May cause an allergic skin reaction.  
Causes serious eye irritation.  
May cause respiratory irritation.  
May cause cancer by inhalation.  
Causes damage to organs through prolonged or repeated exposure.

Notes to physician : Treat symptomatically.

---

### SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

---

### SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.

**Northern Manufacturing Construction Grade Epoxy  
Part A**

Revision Date 06/14/2019

Print Date 07/25/2020

For personal protection see section 8.  
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : Prevent unauthorized access.  
Store in original container.  
Keep in a well-ventilated place.  
Observe label precautions.  
Store in accordance with local regulations.

Further information on storage stability : No decomposition if stored and applied as directed.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO2)	14808-60-7	TWA (Respirable fraction)	0.025 mg/m3	ACGIH
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		TWA (respirable)	10 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO2+5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable fraction)	0.025 mg/m3 (Silica)	ACGIH
		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
		TWA (Respirable fraction)	0.025 mg/m3	ACGIH
		TWA (Respirable fraction)	0.025 mg/m3 (Silica)	ACGIH

# Northern Manufacturing Construction Grade Epoxy

## Part A

Revision Date 06/14/2019

Print Date 07/25/2020

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

**Personal protective equipment**

**Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

**Hand protection**  
Remarks : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

**Skin and body protection** : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

**Hygiene measures** : Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
Remove contaminated clothing and protective equipment before entering eating areas.  
Wash thoroughly after handling.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : paste

Color : white

Odor : aromatic

# Safety Data Sheet

## Northern Manufacturing Construction Grade Epoxy Part A

Revision Date 06/14/2019

Print Date 07/25/2020

---

Odor Threshold	:	No data available
pH	:	Not applicable
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	> 212 °F / > 100 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	0.01 hpa
Relative vapor density	:	No data available
Density	:	1.99 g/ml
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm <sup>2</sup> /s
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	2.5 g/l A+B Combined

# Northern Manufacturing Construction Grade Epoxy

## Part A

Revision Date 06/14/2019

Print Date 07/25/2020

---

### SECTION 10. STABILITY AND REACTIVITY

- Reactivity : No dangerous reaction known under conditions of normal use.
- Chemical stability : The product is chemically stable.
- Possibility of hazardous reactions : Stable under recommended storage conditions.
- Conditions to avoid : No data available
- Incompatible materials : No data available

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Components:

#### bisphenol-A-(epichlorhydrin) epoxy resin:

- Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
- Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

#### Skin corrosion/irritation

Causes skin irritation.

#### Serious eye damage/eye irritation

Causes serious eye irritation.

#### Respiratory or skin sensitization

#### Skin sensitization

May cause an allergic skin reaction.

#### Respiratory sensitization

Not classified based on available information.

#### Germ cell mutagenicity

Not classified based on available information.

#### Carcinogenicity

May cause cancer by inhalation.

<b>IARC</b>	Group 1: Carcinogenic to humans	
	Quartz (SiO <sub>2</sub> )	14808-60-7
	(Silica dust, crystalline)	
	Group 2B: Possibly carcinogenic to humans	
	titanium dioxide	13463-67-7

**OSHA** Not applicable

# Northern Manufacturing Construction Grade Epoxy

## Part A

Revision Date 06/14/2019

Print Date 07/25/2020

<b>NTP</b>	Known to be human carcinogen Quartz (SiO <sub>2</sub> ) (Silica, Crystalline (Respirable Size))	14808-60-7
------------	---	------------

### Reproductive toxicity

Not classified based on available information.

### STOT-single exposure

May cause respiratory irritation.

### STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure.  
Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

### Aspiration toxicity

Not classified based on available information.

### Further information

#### Product:

Remarks : Titanium dioxide (13463-67-7)  
In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have shown to cause an increase in lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. The potential for these adverse health effects appears to be closely related to the particle size and the amount of the exposed surface area that comes into contact with the lung. However, tests with other laboratory animals such as mice and hamsters, indicate that rats are significantly more susceptible to the pulmonary overload and inflammation that causes lung cancer. Epidemiological studies do not suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide. Titanium dioxide has been characterized by IARC as possibly carcinogenic to humans (Group 2B) through inhalation (not ingestion). It has not been characterized as a potential carcinogen by either NTP or OSHA.

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

bisphenol-A-(epichlorhydrin) epoxy resin:

# Northern Manufacturing Construction Grade Epoxy

## Part A

Revision Date 06/14/2019

Print Date 07/25/2020

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 1.8 mg/l  
aquatic invertebrates Exposure time: 48 h

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

---

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### IATA-DGR

Not regulated as a dangerous good

#### IMDG-Code

Not regulated as a dangerous good

### Domestic regulation

#### 49 CFR

Not regulated as a dangerous good

# Northern Manufacturing Construction Grade Epoxy

## Part A

Revision Date 06/14/2019

Print Date 07/25/2020

---

### SECTION 15. REGULATORY INFORMATION

**TSCA list** : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

#### EPCRA - Emergency Planning and Community Right-to-Know

##### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

##### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

##### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.


**SARA 311/312 Hazards** : Skin corrosion or irritation  
Serious eye damage or eye irritation  
Respiratory or skin sensitization  
Carcinogenicity  
Specific target organ toxicity (single or repeated exposure)

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

#### California Prop 65

 **WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

---

### SECTION 16. OTHER INFORMATION

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants  
OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts  
ACGIH / TWA : 8-hour, time-weighted average  
OSHA P0 / TWA : 8-hour time weighted average  
OSHA Z-1 / TWA : 8-hour time weighted average  
OSHA Z-3 / TWA : 8-hour time weighted average



Safety Data Sheet

**Northern Manufacturing Construction Grade Epoxy  
Part A**

Revision Date 06/14/2019

Print Date 07/25/2020

---

# Northern Manufacturing Construction Grade Epoxy Part B

Revision Date 06/14/2019

Print Date 07/25/2020

## SECTION 1. IDENTIFICATION

Product name : Northern Manufacturing Construction Grade Epoxy Part B  
B

Company name : Northern Manufacturing  
111 Royal Group Crescent, Unit NM  
Woodbridge, ON L4H 1X9 Canada

Telephone : 416-740-2090 (8AM - 5PM EST) (M-F)

Emergency telephone : Chemtrec 1-800-424-9300 (24 Hours)

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

## SECTION 2. HAZARDS IDENTIFICATION

### GHS classification in accordance with 29 CFR 1910.1200

Skin corrosion : Category 1A

Serious eye damage : Category 1

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Specific target organ system-ic toxicity - single exposure : Category 3 (Respiratory system)

Specific target organ system-ic toxicity - repeated exposure : Category 1 (Lungs)

### GHS label elements

Hazard pictograms :



# Northern Manufacturing Construction Grade Epoxy

## Part B

Revision Date 06/14/2019

Print Date 07/25/2020

Signal Word	:	Danger
Hazard Statements	:	H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. H350i May cause cancer by inhalation. H372 Causes damage to organs (Lungs) through prolonged or repeated exposure.
Precautionary Statements	:	<b>Prevention:</b> P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray. P264 Wash skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. <b>Response:</b> P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/doctor. P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P362 + P364 Take off contaminated clothing and wash it before reuse. <b>Storage:</b> P403 + P233 Store in a well-ventilated place. Keep container tightly closed. P405 Store locked up. <b>Disposal:</b> P501 Dispose of contents/ container to an approved waste disposal plant.

# Northern Manufacturing Construction Grade Epoxy

## Part B

Revision Date 06/14/2019

Print Date 07/25/2020

### Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

### Other hazards

Intentional misuse by deliberate concentration and inhalation of vapor may be harmful or fatal.

---

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

### Mixtures

#### Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Quartz (SiO <sub>2</sub> )	14808-60-7	Carc. 1A; H350i STOT RE 1; H372 STOT SE 3; H335	$\geq 50 - < 70$
N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine	10563-29-8	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1A; H314 Eye Dam. 1; H318 Skin Sens. 1; H317	$\geq 5 - < 10$
benzyl alcohol	100-51-6	Acute Tox. 4; H302 Acute Tox. 4; H332 Eye Irrit. 2A; H319	$\geq 5 - < 10$
m-phenylenebis(methylamine)	1477-55-0	Acute Tox. 4; H302 Acute Tox. 4; H332 Skin Corr. 1B; H314 Skin Sens. 1; H317	$\geq 1 - < 5$

Actual concentration is withheld as a trade secret

---

## SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.  
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.  
Wash off with soap and plenty of water.  
Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

**Northern Manufacturing Construction Grade Epoxy  
Part B**

Revision Date 06/14/2019

Print Date 07/25/2020

- Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.  
Do not induce vomiting without medical advice.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : Health injuries may be delayed.  
corrosive effects  
irritant effects  
sensitizing effects  
carcinogenic effects  
Cough  
Respiratory disorder  
Allergic reactions  
Dermatitis  
May cause an allergic skin reaction.  
Causes serious eye damage.  
May cause respiratory irritation.  
May cause cancer by inhalation.  
Causes damage to organs through prolonged or repeated exposure.  
Causes severe burns.
- Notes to physician : Treat symptomatically.

**SECTION 5. FIRE-FIGHTING MEASURES**

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.  
If the product contaminates rivers and lakes or drains inform respective authorities.

**Northern Manufacturing Construction Grade Epoxy  
Part B**

Revision Date 06/14/2019

Print Date 07/25/2020

Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

**SECTION 7. HANDLING AND STORAGE**

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products.

Conditions for safe storage : Prevent unauthorized access.  
Store in original container.  
Keep in a well-ventilated place.  
Observe label precautions.  
Store in accordance with local regulations.

Materials to avoid : Explosives  
Oxidizing agents  
Poisonous gases  
Dangerous when wet  
Flammable solids  
Organic peroxides  
Poisonous liquids  
Spontaneously Combustible Substances

Further information on storage stability : No decomposition if stored and applied as directed.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Ingredients with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO <sub>2</sub> )	14808-60-7	TWA (Res-	0.025 mg/m <sup>3</sup>	ACGIH

**Northern Manufacturing Construction Grade Epoxy  
Part B**

Revision Date 06/14/2019

Print Date 07/25/2020

		pirable frac- tion)		
		TWA (Res- pirable dust)	0.05 mg/m <sup>3</sup>	OSHA Z-1
		TWA (respir- able)	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
		TWA (respir- able)	250 mppcf / %SiO <sub>2</sub> +5	OSHA Z-3
		TWA (respir- able dust fraction)	0.1 mg/m <sup>3</sup>	OSHA P0
		TWA (Res- pirable frac- tion)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH
		TWA (respir- able dust fraction)	0.1 mg/m <sup>3</sup>	OSHA P0
		TWA (Res- pirable frac- tion)	0.025 mg/m <sup>3</sup>	ACGIH
		TWA (Res- pirable frac- tion)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH
benzyl alcohol	100-51-6	TWA	10 ppm	US WEEL
m-phenylenebis(methylamine)	1477-55-0	C	0.1 mg/m <sup>3</sup>	ACGIH
		C	0.1 mg/m <sup>3</sup>	OSHA P0

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

**Personal protective equipment**

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection

**Northern Manufacturing Construction Grade Epoxy  
Part B**

Revision Date 06/14/2019

Print Date 07/25/2020

Remarks	:	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eye protection	:	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
Skin and body protection	:	Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Hygiene measures	:	Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Remove contaminated clothing and protective equipment before entering eating areas. Wash thoroughly after handling.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	:	paste
Color	:	dark gray
Odor	:	amine-like
Odor Threshold	:	No data available
pH	:	Not applicable
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	> 212 °F / > 100 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	0.07 hpa



# Safety Data Sheet

## Northern Manufacturing Construction Grade Epoxy Part B

Revision Date 06/14/2019

Print Date 07/25/2020

---

Relative vapor density	:	No data available
Density	:	2.01 g/ml
Solubility(ies)		
Water solubility	:	slightly soluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm <sup>2</sup> /s
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	2.5 g/l A+B Combined

---

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available

---

### SECTION 11. TOXICOLOGICAL INFORMATION

#### Acute toxicity

Not classified based on available information.

#### Components:

##### benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1,620 mg/kg

# Northern Manufacturing Construction Grade Epoxy

## Part B

Revision Date 06/14/2019

Print Date 07/25/2020

Acute inhalation toxicity : LC50 (Rat): > 4.178 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

### **m-phenylenebis(methylamine):**

Acute oral toxicity : LD50 Oral (Rat): 930 mg/kg

Acute inhalation toxicity : LC50 (Rat): 1.34 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 Dermal (Rat): > 3,100 mg/kg

### **Skin corrosion/irritation**

Causes severe burns.

### **Serious eye damage/eye irritation**

Causes serious eye damage.

### **Respiratory or skin sensitization**

#### **Skin sensitization**

May cause an allergic skin reaction.

#### **Respiratory sensitization**

Not classified based on available information.

#### **Germ cell mutagenicity**

Not classified based on available information.

#### **Carcinogenicity**

May cause cancer by inhalation.

<b>IARC</b>	Group 1: Carcinogenic to humans Quartz (SiO <sub>2</sub> ) (Silica dust, crystalline)	14808-60-7
-------------	---	------------

<b>OSHA</b>	Not applicable
-------------	----------------

<b>NTP</b>	Known to be human carcinogen Quartz (SiO <sub>2</sub> ) (Silica, Crystalline (Respirable Size))	14808-60-7
------------	---	------------

#### **Reproductive toxicity**

Not classified based on available information.

#### **STOT-single exposure**

May cause respiratory irritation.

#### **STOT-repeated exposure**

Causes damage to organs (Lungs) through prolonged or repeated exposure.

# Northern Manufacturing Construction Grade Epoxy

## Part B

Revision Date 06/14/2019

Print Date 07/25/2020

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

### Aspiration toxicity

Not classified based on available information.

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

---

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

##### benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
aquatic invertebrates Exposure time: 48 h

##### m-phenylenebis(methylamine):

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): > 10 - 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 10 - 100 mg/l  
aquatic invertebrates Exposure time: 48 h

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.  
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

# Northern Manufacturing Construction Grade Epoxy

## Part B

Revision Date 06/14/2019

Print Date 07/25/2020

---

### SECTION 13. DISPOSAL CONSIDERATIONS

**Disposal methods**

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

### SECTION 14. TRANSPORT INFORMATION

**International Regulations****IATA-DGR**

- UN/ID No. : UN 1760
- Proper shipping name : Corrosive liquid, n.o.s.  
(N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine, m-phenylenebis(methylamine))
- Class : 8
- Packing group : III
- Labels : Corrosives
- Packing instruction (cargo aircraft) : 856
- Packing instruction (passenger aircraft) : 852

**IMDG-Code**

- UN number : UN 1760
- Proper shipping name : CORROSIVE LIQUID, N.O.S.  
(N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine, m-phenylenebis(methylamine))
- Class : 8
- Packing group : III
- Labels : 8
- EmS Code : F-A, S-B
- Marine pollutant : no

**Domestic regulation****49 CFR**

- UN/ID/NA number : UN 1760
- Proper shipping name : Corrosive liquids, n.o.s.  
(N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine, m-phenylenebis(methylamine))
- Class : 8
- Packing group : III
- Labels : CORROSIVE
- ERG Code : 154
- Marine pollutant : no

# Northern Manufacturing Construction Grade Epoxy

## Part B

Revision Date 06/14/2019

Print Date 07/25/2020

DOT: For Limited Quantity exceptions reference 49 CFR 173.154 (b)  
IMDG: For Limited Quantity special provisions reference IMDG Code Chapter 3.4

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

## SECTION 15. REGULATORY INFORMATION

**TSCA list** : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

### EPCRA - Emergency Planning and Community Right-to-Know

#### CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

#### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Skin corrosion or irritation  
Serious eye damage or eye irritation  
Respiratory or skin sensitization  
Carcinogenicity  
Specific target organ toxicity (single or repeated exposure)

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

**California Prop 65**  **WARNING:** Cancer – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

---

## SECTION 16. OTHER INFORMATION

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
OSHA P0 : USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

# Northern Manufacturing Construction Grade Epoxy

## Part B

Revision Date 06/14/2019

Print Date 07/25/2020

---

	its for Air Contaminants
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
US WEEL	: USA. Workplace Environmental Exposure Levels (WEEL)
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / C	: Ceiling limit
OSHA P0 / TWA	: 8-hour time weighted average
OSHA P0 / C	: Ceiling limit
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-3 / TWA	: 8-hour time weighted average
US WEEL / TWA	: 8-hr TWA

**Northern Manufacturing Construction Grade Epoxy Part A**

Revision Date 12/05/2019

Print Date 12/05/2019

**1. Identification**

Product name : Northern Manufacturing Construction Grade Epoxy Part A

Supplier : Northern Manufacturing  
111 Royal Group Crescent, Unit NM  
Woodbridge, ON L4H 1X9 Canada

Telephone : 416-740-2090 (8AM - 5PM EST) (M-F)

Emergency telephone : Chemtrec 1-800-424-9300 (24 Hours)

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

**2. Hazards identification****GHS Classification**

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2A	H319: Causes serious eye irritation.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Carcinogenicity, Category 1A (Inhalation)	H350i: May cause cancer by inhalation.
Specific target organ systemic toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ systemic toxicity - repeated exposure, Category 1, Lungs	H372: Causes damage to organs through prolonged or repeated exposure.

**GHS label elements**

Hazard pictograms



Signal Word

: Danger

Hazard Statements

: H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H350i May cause cancer by inhalation.  
H372 Causes damage to organs (Lungs) through prolonged or



## 1. Identification

Product name : Sikasil® WS-295

Supplier : Sika Corporation  
201 Polito Avenue  
Lyndhurst, NJ 07071  
USA  
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300  
INTERNATIONAL: 703-527-3887


Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

## 2. Hazards identification

### GHS Classification

Flammable liquids, Category 4	H227: Combustible liquid.
Eye irritation, Category 2A	H319: Causes serious eye irritation.
Skin sensitization, Category 1	H317: May cause an allergic skin reaction.
Reproductive toxicity, Category 2	H361f: Suspected of damaging fertility.
Specific target organ systemic toxicity - repeated exposure, Category 2 (Oral)	H373: May cause damage to organs through prolonged or repeated exposure if swallowed.

### GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : H227 Combustible liquid.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H361f Suspected of damaging fertility.  
H373 May cause damage to organs through prolonged or repeated exposure if swallowed.

Precautionary Statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read





and understood.  
 P210 Keep away from heat/sparks/open flames/hot surfaces.  
 No smoking.  
 P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.  
 P264 Wash skin thoroughly after handling.  
 P272 Contaminated work clothing must not be allowed out of the workplace.  
 P280 Wear protective gloves/ eye protection/ face protection.  
 P281 Use personal protective equipment as required.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
 P337 + P313 If eye irritation persists: Get medical advice/ attention.  
 P363 Wash contaminated clothing before reuse.  
 P370 + P378 In case of fire: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment for extinction.

**Storage:**

P403 + P235 Store in a well-ventilated place. Keep cool.  
 P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

See Section 11 for more detailed information on health effects and symptoms.  
 There are no hazards not otherwise classified that have been identified during the classification process.  
 There are no ingredients with unknown acute toxicity used in a mixture at a concentration  $\geq 1\%$ .

---

### 3. Composition/information on ingredients

**Hazardous ingredients**

Chemical name	CAS-No.	Concentration (%)
2-butanone-O,O',O''-(phenylsilylidyne)trioxime	34036-80-1	$\geq 2 - < 5\%$
butan-2-one-O,O',O''-(methylsilylidyne)trioxime	22984-54-9	$\geq 1 - < 2\%$
N-(2-aminoethyl)-N'-[3-(trimethoxysilyl)propyl]ethylenediamine	35141-30-1	$\geq 1 - < 2\%$
octamethylcyclotetrasiloxane	556-67-2	$< 1\%$

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.



#### 4. First aid measures

If inhaled	: Move to fresh air. Consult a physician after significant exposure.
In case of skin contact	: Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water. If symptoms persist, call a physician.
In case of eye contact	: Immediately flush eye(s) with plenty of water. Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	: Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting without medical advice. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. Obtain medical attention.
Most important symptoms and effects, both acute and delayed	: irritant effects sensitizing effects  Allergic reactions Excessive lachrymation See Section 11 for more detailed information on health effects and symptoms.  May cause an allergic skin reaction. Causes serious eye irritation. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure if swallowed.
Protection of first-aiders	: Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attendance.
Notes to physician	: Treat symptomatically.

#### 5. Fire-fighting measures

Suitable extinguishing media	: Carbon dioxide (CO <sub>2</sub> )
Unsuitable extinguishing media	: Water
Specific extinguishing methods	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Special protective equipment for fire-fighters	: In the event of fire, wear self-contained breathing apparatus.



## 6. Accidental release measures

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.

## 7. Handling and storage

- Advice on safe handling : Do not breathe vapors or spray mist.  
Avoid exceeding the given occupational exposure limits (see section 8).  
Do not get in eyes, on skin, or on clothing.  
For personal protection see section 8.  
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
Smoking, eating and drinking should be prohibited in the application area.  
Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Store in original container.  
Keep in a well-ventilated place.  
Observe label precautions.  
Store in accordance with local regulations.
- Materials to avoid : No data available

## 8. Exposure controls/personal protection

Component	CAS-No.	Basis **	Value	Exposure limit(s)* / Form of exposure
calcium carbonate	471-34-1	CAL PEL	PEL	10 mg/m <sup>3</sup> Total dust
		CAL PEL	PEL	5 mg/m <sup>3</sup> respirable dust fraction



\*The above mentioned values are in accordance with the legislation in effect at the date of the release of this safety data sheet.

**\*\*Basis**

- ACGIH. Threshold Limit Values (TLV)
- OSHA P0. Table Z-1, Limit for Air Contaminat (1989 Vacated Values)
- OSHA P1. Permissible Exposure Limits (PEL), Table Z-1, Limit for Air Contaminant
- OSHA P2. Permissible Exposure Limits (PEL), Table Z-2
- OSHA Z3. Table Z-3, Mineral Dust

**Engineering measures** : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.  
The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

**Personal protective equipment**

**Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

**Hand protection**  
**Remarks** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

**Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.

**Skin and body protection** : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

**Hygiene measures** : Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
Remove respiratory and skin/eye protection only after vapors have been cleared from the area.  
Remove contaminated clothing and protective equipment before entering eating areas.  
Wash thoroughly after handling.

**9. Physical and chemical properties**

Appearance	: paste
Color	: various
Odor	: mild musty
Odor Threshold	: No data available
Flash point	: 185 °F (85 °C)
Ignition temperature	: No data available
Decomposition temperature	: No data available
Lower explosion limit (Vol%)	: No data available
Upper explosion limit (Vol%)	: No data available
Flammability (solid, gas)	: No data available
Oxidizing properties	: No data available
pH	: Note: Not applicable
Melting point/range / Freezing point	: No data available
Boiling point/boiling range	: No data available
Vapor pressure	: 0.01 mmHg (0.01 hpa)
Density	: ca.1.12 g/cm <sup>3</sup> at 73 °F (23 °C)
Water solubility	: Note: insoluble
Partition coefficient: n- octanol/water	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 20.5 mm <sup>2</sup> /s at 104 °F (40 °C)
Relative vapor density	: No data available
Evaporation rate	: No data available
Burning rate	: No data available
Volatile organic compounds (VOC) content	: 37 g/l

**10. Stability and reactivity**

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions.
Conditions to avoid	: Extremes of temperature and direct sunlight.
Incompatible materials	: No data available

---

**11. Toxicological information****Acute toxicity**

Not classified based on available information.

**Ingredients:****N-(2-aminoethyl)-N'-[3-(trimethoxysilyl)propyl]ethylenediamine:**

Acute oral toxicity : LD50 Oral (Rat): 7,758 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): 16,640 mg/kg

**octamethylcyclotetrasiloxane:**

Acute inhalation toxicity : LC50 (Rat): 36 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor

**Skin corrosion/irritation**

Not classified based on available information.

**Serious eye damage/eye irritation**

Causes serious eye irritation.

**Respiratory or skin sensitization**

Skin sensitization: May cause an allergic skin reaction.

Respiratory sensitization: Not classified based on available information.

**Germ cell mutagenicity**

Not classified based on available information.

**Reproductive toxicity**

Suspected of damaging fertility.

**STOT-single exposure**

Not classified based on available information.

**STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure if swallowed.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

**Aspiration toxicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

<b>IARC</b>	Group 2B: Possibly carcinogenic to humans	
	titanium dioxide	13463-67-7
	Carbon black	1333-86-4
<b>NTP</b>	Not applicable	

Carbon black (1333-86-4)

Animal Toxicity:

Rat, oral, duration 2 year  
Effect: no tumors

Mouse, oral, duration 2 years  
Effect: no tumors

Mouse, dermal, duration 18 months  
Effect: no skin tumors

Rat, inhalation, duration 2 years  
Target organ: lungs  
Effect: inflammation, fibrosis, tumors

Note: Tumors in the rat lung are considered to be related to the "particle overload phenomenon" rather than to a specific chemical effect of carbon black itself in the lung. These effects in rats have been reported in many studies on other poorly soluble inorganic particles and appear to be rat specific. Tumors have not been observed in other species (i.e., mouse and hamster) for carbon black or other poorly soluble particles under similar circumstances and study conditions.

Mortality studies (human data): A study on carbon black production workers in the UK (Sorahan, 2001) found an increased risk of lung cancer in two of the five plants studied; however, the increase was not related to the dose of carbon black. Thus, the authors did not consider the increased risk in lung cancer to be due to carbon black exposure. A German study of carbon black workers at one plant (Morfeld, 2006; Buechte, 2006) found a similar increase in lung cancer risk but, like the Sorahan, 2001 (UK study) found no association with carbon black exposure. A large US study of 18 plants showed a reduction in lung cancer risk in carbon black production workers (DEll, 2006). Based upon these studies, the February 2006 Working Group at the International Agency for Research on Cancer (IARC) concluded that the human evidence for carcinogenicity was inadequate (IARC, 2010).

Since the IARC evaluation of carbon black, Sorahan and Harrington (2007) have re-analyzed the UK study data using an alternative exposure hypothesis and found a positive association with carbon black exposure in two of the five plants. The same exposure hypothesis was applied by Morfeld and McCunney (2009) to the German cohort; in contrast, they found no association between carbon black exposure and lung cancer risk and, thus, no support for the alternative exposure hypothesis used by Sorahan and Harrington.

Overall, as a result of these detailed investigations, no causative link between carbon black exposure and cancer risk in humans has been demonstrated.

**IARC CANCER CLASSIFICATION:** In 2006 IARC re-affirmed its 1995 finding that there is "inadequate evidence" from human health studies to assess whether carbon black causes cancer in humans. IARC concluded that there is "sufficient evidence" in experimental animal studies for the carcinogenicity of carbon black. IARC's overall evaluation is that carbon black is "possibly carcinogenic to humans" (Group 2B)". This conclusion was based on IARC's



guidelines, which generally require such a classification if one species exhibits carcinogenicity in two or more animal studies (IARC, 2010).

Solvent extracts of carbon black were used in one study of rats in which skin tumors were found after dermal application and several studies of mice in which sarcomas were found following subcutaneous injection. IARC concluded that there was "sufficient evidence" that carbon black extracts can cause cancer in animals (Group 2B).

**ICGIH CANCER CLASSIFICATION:** Confirmed Animal Carcinogen with Unknown Relevance to Humans (Category A3 Carcinogen).

**ASSESSMENT:** Applying the guidelines of self-classification under the Globally Harmonized System of Classification and Labeling of Chemicals, carbon black is not classified as a carcinogen. Lung tumors are induced in rats as a result of repeated exposure to inert, poorly soluble particles like carbon black and other poorly soluble particles. Rats tumors are a result of a secondary non-genotoxic mechanism that has questionable relevance for classification in humans. In support of this opinion, the CLP Guidance for Specific Target Organ Toxicity - Repeated Exposure (STOT-RE), cites lung overload under mechanisms not relevant to humans. Human health studies show that exposure to carbon black does not increase the risk to carcinogenicity.

Titanium dioxide (13463-67-7)

In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have been shown to cause an increase in lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. The potential for these adverse health effects appears to be closely related to the particle size and the amount of the exposed surface area that comes into contact with the lung. However, tests with other laboratory animals such as mice and hamsters, indicate that rats are significantly more susceptible to the pulmonary overload and inflammation that cause lung cancer. Epidemiology studies do not suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide. Titanium dioxide has been characterized by IARC as possibly carcinogenic to humans (Group 2B) through inhalation (not ingestion). It has not been characterized as a potential carcinogen by either NTP or OSHA.

---

## 12. Ecological information

Other information	Do not empty into drains; dispose of this material and its container in a safe way. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
-------------------	--

---

## 13. Disposal considerations

### Disposal methods

Waste from residues	: Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional
---------------------	--





local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

---

#### 14. Transport information

**DOT**

Not dangerous goods

**IATA**

Not dangerous goods

**IMDG**

Not dangerous goods

**Special precautions for user**

No data available

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable

---

#### 15. Regulatory information

**TSCA list** : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

**EPCRA - Emergency Planning and Community Right-to-Know**

**CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA304 Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Fire Hazard  
Acute Health Hazard  
Chronic Health Hazard

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

**Ozone-Depletion Potential**

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

**California Prop 65**

WARNING! This product contains a chemical known in the State of California to cause cancer.

WARNING: This product contains a chemical known in the State of California to cause birth defects or other reproductive harm.

**16. Other information****HMIS Classification**

<b>Health</b>	*	2
<b>Flammability</b>		2
<b>Physical Hazard</b>		0
<b>Personal Protection</b>		X

**Caution:** HMIS® rating is based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® rating is not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® rating is to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). Please note HMIS® attempts to convey full health warning information to all employees.

**Notes to Reader**

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at [www.sikausa.com](http://www.sikausa.com) or 201-933-8800.

Revision Date 01/26/2017

Safety Data Sheet

**Sikasil® WS-295**



Revision Date 01/26/2017

Print Date 01/26/2017

---

Material number: 481215