



BUILDING TRUST



Sika Emseal Safety Data Sheet Product Package

Emshield[®] WFR2

The information contained in these Emseal-specific or Sika-specific Safety Data Sheets applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof.

Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika Emseal product, which are available at web site and/or telephone number listed in Section 1 of this SDS

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.



EMSEAL Joint Systems, Ltd.
25 Bridle Lane, Westborough, MA 01581 USA
www.emseal.com

Safety Data Sheet

WFR Foam

A SIKA COMPANY

Preparation Date March 15, 2015 **Revision Date** September 20, 2024

1. Identification of the Substance / Preparation

Product identifier	EMSHIELD WFR
Other identifier or names	WFR1, WFR2, WFR3
UN ID number	None
Manufacturer Address	EMSEAL LLC 111 Royal Group Crescent Woodbridge, Ontario L4H 1X9 Canada
Company Phone	(508) 836-0280 M-F 9am - 5pm
Emergency Phone	CHEMTREC (800) 424-9300 (24 Hours)
CHEMTREC International Phone	+1 703-527-3887 (24 Hours)

2. Hazardous Identification

Hazardous Classification	This product is not classified as hazardous when used as intended.
Signal Word	None
Pictograms	None
Emergency Overview:	No emergency requirements.

3. Composition / Information on Ingredients

EMSHIELD WFR is composed of polyurethane foam impregnated with a with a proprietary solid inorganic fire retardant bonded to a fully cured silicone sealant. It is classified as Non-Hazardous.

NOTE: Silicone facing is fully cured. The composition of the silicone in its liquid state is comprised of the following:

Chemical Name	CAS #	% by Weight	GHS Classification Hazard Statements
Polydimethyl Siloxane Diol	70131-67-8 3	0.0–60.0	SELF CLASSIFICATION Classification: Not Applicable
Calcium Carbonate (Limestone)	1317-65-3		SELF CLASSIFICATION
Synthetic Calcium Carbonate	371-34-1	10.0–40.0	Classification: Not Applicable
Phenyl Oximino Silane	34036-80-1	1.0–5.0	Classification: STOT RE Cat. 2, Skin Sensitization Cat. 1, Aquatic, Chronic Toxicity Cat. 3 Hazard Statement Codes: H373, H317, H412
Silicon Dioxide, Fumed	112945-52-5	1.0–5.0	SELF CLASSIFICATION Classification: Not Applicable
Mineral Spirits	8052-41-3	0.0-1.0	Classification: Carcinogenic Cat. 1B, Mutagenic Cat. 1B, Aspiration Hazard Cat. 1 Hazard Statement Codes: H350, H340, H304
Quartz	14808-60-7 14464-46-1	Trace	SELF CLASSIFICATION Classification: Carcinogenic Cat. 1B Hazard Statement Codes: H350

Water and other components.

Each of the other components is present in less than 1 percent concentration (0.1% concentration for potential carcinogens, reproductive toxins, respiratory tract sensitizers, and mutagens).

Classification: Not Applicable



A SIKA COMPANY

4. First Aid Measures

- 4.1 EYES:** Flush with water for at least 15 minutes, and call physician if problems persist.
- 4.2 SKIN:** Product may leave a sticky residue, and mild irritation if prolonged exposure. Scrub with soapy water until adhesive is removed.
- 4.3 INGESTION:** Do not eat – call physician if ingested.

5. Fire-fighting Measures

- 5.2 FLAMMABILITY:** Slight. The material composition does not support combustion.
- 5.2 FLASH POINT:** Unknown.
- 5.3 AUTO-IGNITION TEMPERATURE:** Unknown.
- 5.4 EXTINGUISHING MEDIA:** Large volumes of water, or ABC chemical may be appropriate for initial control or small volumes of impregnated foam.
- 5.5 HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon di/mon oxides will be formed as well as other noxious and toxic fumes upon combustion – do not breath combustion products.

6. Accidental Release Measures

If material is unusable pick up pieces and dispose of in accordance with local regulations; material and all components are non-toxic and normal landfill will most often be acceptable.

7. Handling and Storage

Store in original packaging below 35°C. There are no special handling instructions.

8. Exposure Controls / Personal Protection

- 8.1 RESPIRATORY PROTECTION:** Not required
- 8.2 EYE PROTECTION:** Not required
- 8.3 SKIN PROTECTION:** Gloves of any material are suitable if desired, but not required. No other protection is required.

9. Physical and Chemical Properties

- 9.1 APPEARANCE:** Dark grey / charcoal colored foam and colored silicone with product identifying packaging.
- 9.2 ODOR:** Slight characteristic odor.
- 9.3 PERCENT SOLIDS BY WEIGHT:** 100%
- 9.4 PHYSICAL STATE:** Solid
- 9.5 PERCENT VOLATILE:** <1% wt/wt
- 9.6 DENSITY:** 0.4g/cm³
- 9.7 DECOMPOSITION:** > 300°C
- 9.8 SOLUBILITY IN WATER:** None



A SIKA COMPANY

10. Stability and Reactivity

Stable under normal conditions – avoid temperatures in excess of 300°C, strong acids and bases, and open flame.

11. Toxicological Information

Unknown.

12. Ecological Information

Unknown

13. Disposal Considerations

No known hazard. Dispose of in accordance with local regulations; material and all components are non-toxic and disposal in normal landfill will most often be acceptable.

14. Transportation Information

Not hazardous – safe for non-hazardous shipping.

15. Regulatory Information

Unknown.

16. Other Information

No other information provided.

This page has been left blank.



Northern Manufacturing Construction Grade Epoxy Part A

Revision Date 08/21/2024

Print Date 08/21/2024

SECTION 1. IDENTIFICATION

Product name : Northern Manufacturing Construction Grade Epoxy Part A

Company name : Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
USA
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300
INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Reproductive toxicity : Category 1B

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

Specific target organ toxicity - repeated exposure : Category 1 (Lungs)


GHS label elements



Northern Manufacturing Construction Grade Epoxy Part A

Revision Date 08/21/2024

Print Date 08/21/2024

Hazard pictograms	:	
Signal Word	:	Danger
Hazard Statements	:	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H350 May cause cancer by inhalation. H360 May damage fertility or the unborn child. H372 Causes damage to organs (Lungs) through prolonged or repeated exposure.
Precautionary Statements	:	Prevention: P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P260 Do not breathe mist or vapors. P264 Wash skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. Response: P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P308 + P313 IF exposed or concerned: Get medical advice/ attention. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 + P364 Take off contaminated clothing and wash it before reuse. Storage: P403 + P233 Store in a well-ventilated place. Keep container tightly closed.



Northern Manufacturing Construction Grade Epoxy

Part A

Revision Date 08/21/2024

Print Date 08/21/2024

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration \geq 1%.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Quartz (SiO ₂) >5 μ m	14808-60-7	Carc. 1A; H350 STOT RE 1; H372 STOT SE 3; H335	\geq 30 - < 50
bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)	25068-38-6	Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Skin Sens. 1; H317	\geq 10 - < 20
oxirane, mono[(C12-14-alkyloxy)methyl]derivatives	68609-97-2	Skin Irrit. 2; H315 Skin Sens. 1; H317 Repr. 1B; H360	\geq 5 - < 10

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.



Northern Manufacturing Construction Grade Epoxy Part A

Revision Date 08/21/2024

Print Date 08/21/2024

- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : Cough
Respiratory disorder
Allergic reactions
Excessive lachrymation
Erythema
Dermatitis
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye irritation.
May cause respiratory irritation.
May cause cancer by inhalation.
May damage fertility or the unborn child.
Causes damage to organs through prolonged or repeated exposure.
irritant effects
sensitizing effects
toxic effects for reproduction
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform



Northern Manufacturing Construction Grade Epoxy

Part A

Revision Date 08/21/2024

Print Date 08/21/2024

respective authorities.
 Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
 Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8).
 Do not get in eyes, on skin, or on clothing.
 For personal protection see section 8.
 Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
 Smoking, eating and drinking should be prohibited in the application area.
 Pregnant women or women of child-bearing age should not be exposed to this product.
 Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Store in original container.
 Keep in a well-ventilated place.
 Observe label precautions.
 Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO ₂) >5µm	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m ³	ACGIH
		TWA (Respirable dust)	0.05 mg/m ³	OSHA Z-1
		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3



Northern Manufacturing Construction Grade Epoxy Part A

Revision Date 08/21/2024

Print Date 08/21/2024

		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m ³	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH
		PEL (respirable)	0.05 mg/m ³	OSHA CARC
		TWA (respirable dust fraction)	0.1 mg/m ³	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m ³	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.



Northern Manufacturing Construction Grade Epoxy Part A

Revision Date 08/21/2024

Print Date 08/21/2024

- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
Remove contaminated clothing and protective equipment before entering eating areas.
Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : paste
- Color : white
- Odor : aromatic
- Odor Threshold : No data available
- pH : Not applicable
- Melting point/ range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : > 212 °F / > 100 °C
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapor pressure : 0.01 hpa
- Relative vapor density : No data available
- Density : 1.99 g/ml
- Solubility(ies)



Northern Manufacturing Construction Grade Epoxy Part A

Revision Date 08/21/2024

Print Date 08/21/2024

Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm ² /s
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds (VOC) content	:	2.5 g/l A+B Combined

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions.
Conditions to avoid	:	No data available
Incompatible materials	:	No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700):

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg



Northern Manufacturing Construction Grade Epoxy

Part A

Revision Date 08/21/2024

Print Date 08/21/2024

Acute dermal toxicity : LD50 Dermal (Rabbit): > 20,000 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

May cause cancer by inhalation.

IARC	Group 1: Carcinogenic to humans	
	Quartz (SiO ₂) (Silica dust, crystalline)	14808-60-7
OSHA	Group 2B: Possibly carcinogenic to humans	
	Titanium dioxide (> 10 µm)	13463-67-7
OSHA	OSHA specifically regulated carcinogen	
	Quartz (SiO ₂) (crystalline silica)	14808-60-7
NTP	Known to be human carcinogen	
	Quartz (SiO ₂) (Silica, Crystalline (Respirable Size))	14808-60-7

Reproductive toxicity

May damage fertility or the unborn child.

STOT-single exposure

May cause respiratory irritation.

STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure.

Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified due to lack of data.



Northern Manufacturing Construction Grade Epoxy Part A

Revision Date 08/21/2024

Print Date 08/21/2024

Further information

Product:

Remarks

: Titanium dioxide (13463-67-7)
In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have shown to cause an increase in lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. The potential for these adverse health effects appears to be closely related to the particle size and the amount of the exposed surface area that comes into contact with the lung. However, tests with other laboratory animals such as mice and hamsters, indicate that rats are significantly more susceptible to the pulmonary overload and inflammation that causes lung cancer. Epidemiological studies do not suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide. Titanium dioxide has been characterized by IARC as possibly carcinogenic to humans (Group 2B) through inhalation (not ingestion). It has not been characterized as a potential carcinogen by either NTP or OSHA.

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.8 mg/l
Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available



Northern Manufacturing Construction Grade Epoxy

Part A

Revision Date 08/21/2024

Print Date 08/21/2024

Other adverse effects

Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

TSCA list : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ



Northern Manufacturing Construction Grade Epoxy

Part A

Revision Date 08/21/2024

Print Date 08/21/2024

SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Respiratory or skin sensitization
Carcinogenicity
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)
Skin corrosion or irritation
Serious eye damage or eye irritation

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including Quartz (SiO₂) >5µm, which is known to the State of California to cause cancer, and Oxirane, (chloromethyl)- Epichlorohydrin, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
OSHA CARC : OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA : 8-hour, time-weighted average
OSHA CARC / PEL : Permissible exposure limit (PEL)
OSHA P0 / TWA : 8-hour time weighted average
OSHA Z-1 / TWA : 8-hour time weighted average
OSHA Z-3 / TWA : 8-hour time weighted average

Notes to Reader



Northern Manufacturing Construction Grade Epoxy Part A

Revision Date 08/21/2024

Print Date 08/21/2024

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 08/21/2024

100000022096
US / Z8



Northern Manufacturing Construction Grade Epoxy Part B

Revision Date 08/21/2024

Print Date 08/21/2024

SECTION 1. IDENTIFICATION

Product name : Northern Manufacturing Construction Grade Epoxy Part B

Company name : Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
USA
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300
INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin irritation : Category 2

Serious eye damage : Category 1

Skin sensitization : Category 1

Carcinogenicity (Inhalation) : Category 1A

Specific target organ toxicity : Category 3 (Respiratory system)
- single exposure

Specific target organ toxicity : Category 1 (Lungs)
- repeated exposure

GHS label elements



Northern Manufacturing Construction Grade Epoxy Part B

Revision Date 08/21/2024

Print Date 08/21/2024

Hazard pictograms :



Signal Word :

Danger

Hazard Statements :

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H335 May cause respiratory irritation.
H350 May cause cancer by inhalation.
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure.

Precautionary Statements :

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe mist or vapors.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.



Northern Manufacturing Construction Grade Epoxy Part B

Revision Date 08/21/2024

Print Date 08/21/2024

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration $\geq 1\%$.

Other hazards

Intentional misuse by deliberate concentration and inhalation of vapor may be harmful or fatal.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)
Quartz (SiO ₂) >5 μ m	14808-60-7	Carc. 1A; H350 STOT RE 1; H372 STOT SE 3; H335	$\geq 30 - < 50$
N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine	10563-29-8	Acute Tox. 4; H302 Acute Tox. 4; H312 Skin Corr. 1A; H314 Eye Dam. 1; H318 Skin Sens. 1; H317	$\geq 5 - < 10$
Benzyl alcohol	100-51-6	Acute Tox. 4; H302 Eye Irrit. 2A; H319 Skin Sens. 1B; H317	$\geq 5 - < 10$
Aliphatic Amines	Not Assigned	Skin Sens. 1; H317	$\geq 1 - < 5$

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tis-



Northern Manufacturing Construction Grade Epoxy Part B

Revision Date 08/21/2024

Print Date 08/21/2024

- sue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Keep eye wide open while rinsing.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects
sensitizing effects
Cough
Respiratory disorder
Allergic reactions
Excessive lachrymation
Erythema
Dermatitis
Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.
May cause cancer by inhalation.
Causes damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency measures : Use personal protective equipment.
Deny access to unprotected persons.



Northern Manufacturing Construction Grade Epoxy

Part B

Revision Date 08/21/2024

Print Date 08/21/2024

gency procedures

- Environmental precautions : Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities. Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Avoid exceeding the given occupational exposure limits (see section 8). Do not get in eyes, on skin, or on clothing. For personal protection see section 8. Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Store in original container. Keep in a well-ventilated place. Observe label precautions. Store in accordance with local regulations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Quartz (SiO ₂) >5µm	14808-60-7	TWA (Respirable particulate matter)	0.025 mg/m ³	ACGIH
		TWA (Respirable dust)	0.05 mg/m ³	OSHA Z-1



Northern Manufacturing Construction Grade Epoxy Part B

Revision Date 08/21/2024

Print Date 08/21/2024

		TWA (respirable)	10 mg/m ³ / %SiO ₂ +2	OSHA Z-3
		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
		TWA (respirable dust fraction)	0.1 mg/m ³	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH
		PEL (respirable)	0.05 mg/m ³	OSHA CARC
		TWA (respirable dust fraction)	0.1 mg/m ³	OSHA P0
		TWA (Respirable particulate matter)	0.025 mg/m ³	ACGIH
		TWA (Respirable particulate matter)	0.025 mg/m ³ (Silica)	ACGIH

The above constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

Personal protective equipment

Respiratory protection : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec-



Northern Manufacturing Construction Grade Epoxy Part B

Revision Date 08/21/2024

Print Date 08/21/2024

- essary.
- Eye protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures : Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
Remove contaminated clothing and protective equipment before entering eating areas.
Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : paste
- Color : dark gray
- Odor : amine-like
- Odor Threshold : No data available
- pH : 8.2
- Melting point/ range / Freezing point : No data available
- Boiling point/boiling range : No data available
- Flash point : > 212 °F / > 100 °C
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit / Upper flammability limit : No data available
- Lower explosion limit / Lower flammability limit : No data available
- Vapor pressure : 0.07 hpa
- Relative vapor density : No data available
- Density : 2.01 g/ml



Northern Manufacturing Construction Grade Epoxy Part B

Revision Date 08/21/2024

Print Date 08/21/2024

Solubility(ies)	
Water solubility	: slightly soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Autoignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 20.5 mm ² /s
Explosive properties	: No data available
Oxidizing properties	: No data available
Volatile organic compounds (VOC) content	: 2.5 g/l A+B Combined

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: The product is chemically stable.
Possibility of hazardous reactions	: Stable under recommended storage conditions.
Conditions to avoid	: No data available
Incompatible materials	: No data available
Hazardous decomposition products	: No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified due to lack of data.

Components:

N'-(3-aminopropyl)-N,N-dimethylpropane-1,3-diamine:



Northern Manufacturing Construction Grade Epoxy Part B

Revision Date 08/21/2024

Print Date 08/21/2024

Acute oral toxicity : LD50 Oral (Rat): 1,669 mg/kg

Acute dermal toxicity : LD50 Dermal (Rat): 1,310 mg/kg

Benzyl alcohol:

Acute oral toxicity : LD50 Oral (Rat): 1,200 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Product:

Method : In Vitro Membrane Barrier Test Method for Skin Corrosion -
CORROSITEX

Result : Irritating to skin.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Skin sensitization

May cause an allergic skin reaction.

Respiratory sensitization

Not classified due to lack of data.

Germ cell mutagenicity

Not classified due to lack of data.

Carcinogenicity

May cause cancer by inhalation.

IARC	Group 1: Carcinogenic to humans Quartz (SiO ₂) (Silica dust, crystalline)	14808-60-7
-------------	---	------------

OSHA	OSHA specifically regulated carcinogen Quartz (SiO ₂) (crystalline silica)	14808-60-7
-------------	--	------------

NTP	Known to be human carcinogen Quartz (SiO ₂) (Silica, Crystalline (Respirable Size))	14808-60-7
------------	---	------------

Reproductive toxicity

Not classified due to lack of data.

STOT-single exposure

May cause respiratory irritation.



Northern Manufacturing Construction Grade Epoxy Part B

Revision Date 08/21/2024

Print Date 08/21/2024

STOT-repeated exposure

Causes damage to organs (Lungs) through prolonged or repeated exposure.
Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified due to lack of data.

Further information

Product:

Quartz (14808-60-7): This classification is relevant when exposed to Quartz (silicon dioxide) in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

Benzyl alcohol:

Toxicity to fish : LC50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.



Northern Manufacturing Construction Grade Epoxy Part B

Revision Date 08/21/2024

Print Date 08/21/2024

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

- TSCA list** : All chemical substances in this product are either listed as active on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

CERCLA Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 304 Extremely Hazardous Substances Reportable Quantity

Listed substances in the product are at low enough levels to not be expected to exceed the RQ

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

- SARA 311/312 Hazards** : Respiratory or skin sensitization
Carcinogenicity
Specific target organ toxicity (single or repeated exposure)
Skin corrosion or irritation



Northern Manufacturing Construction Grade Epoxy Part B

Revision Date 08/21/2024

Print Date 08/21/2024


Serious eye damage or eye irritation

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

 **WARNING:** This product can expose you to chemicals including Quartz (SiO₂) >5µm, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
OSHA CARC	:	OSHA Specifically Regulated Chemicals/Carcinogens
OSHA P0	:	USA. Table Z-1-A Limits for Air Contaminants (1989 vacated values)
OSHA Z-1	:	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	:	USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
ACGIH / TWA	:	8-hour, time-weighted average
OSHA CARC / PEL	:	Permissible exposure limit (PEL)
OSHA P0 / TWA	:	8-hour time weighted average
OSHA Z-1 / TWA	:	8-hour time weighted average
OSHA Z-3 / TWA	:	8-hour time weighted average

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE



Northern Manufacturing Construction Grade Epoxy Part B

Revision Date 08/21/2024

Print Date 08/21/2024

RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY
PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at
www.sikausa.com or 201-933-8800.

Revision Date 08/21/2024

100000022097
US / Z8



Safety Data Sheet

Copyright,2016,3M Canada Company

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group: 09-5451-1 **Version number:** 9.00
Issue Date: 2018/05/24 **Supersedes Date:** 2015/01/07

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

SECTION 1: Identification

1.1. Product identifier

3M Brand Fire Barrier CP-25WB+

Product Identification Numbers

42-0016-4710-8	42-0016-4715-7	42-0016-4716-5	98-0400-5380-7	98-0400-5381-5
98-0400-5382-3	98-0400-5383-1	98-0400-5406-0	98-0400-5456-5	98-0400-5562-0
98-0400-5573-7	98-0400-5610-7	98-0400-5629-7	DE-2729-4483-1	DE-2729-4484-9
JE-4100-2482-0	JE-4900-0628-3	JE-4900-0629-1	JE-4900-0630-9	JE-4900-0741-4
JE-6000-0304-8	JN-3301-2827-1	KA-0000-0150-9		

1.2. Recommended use and restrictions on use

Recommended use

Fire Protection, Used as Firestop in buildings.

1.3. Supplier's details

Company: 3M Canada Company
Division: Industrial Adhesives and Tapes Division
Address: 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1
Telephone: (800) 364-3577
Website: www.3M.ca

1.4. Emergency telephone number

Medical Emergency Telephone: (519) 451-2500, Ext. 2222; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Serious Eye Damage/Irritation: Category 2B.

2.2. Label elements

Signal word

Warning

Symbols

3M Brand Fire Barrier CP-25WB+

Not applicable.

Pictograms

Not applicable.

Hazard statements

Causes eye irritation.

Precautionary statements**General:**

Keep out of reach of children. Read label before use. If medical advice is needed, have product container or label at hand.

Prevention:

Wash thoroughly after handling.

Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt
Sodium Silicate	1344-09-8	10 - 30
Water	7732-18-5	10 - 30
Zinc Borate 2335	138265-88-0	10 - 30
Polymer	Trade Secret	10 - 30
Ethylhexyldiphenyl Phosphate	1241-94-7	3 - 7
Iron Oxide	1309-37-1	1 - 5
Oxide Glass Chemicals	65997-17-3	1 - 5
Polyethylene Glycol	25322-68-3	1 - 5
Di-2-ethylhexylphenyl phosphate	16368-97-1	< 1.0
Polyoxyethylene monoethylphenyl ether	9036-19-5	< 1
Triphenyl Phosphate	115-86-6	< 1.0
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	55965-84-9	< 0.001

Polymer is a non-hazardous Trade Secret material according to WHMIS criteria.

Sodium Silicate is a hazardous Trade Secret material according to WHMIS criteria. Refer to Section 15 for further information.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Wash with soap and water. If signs/symptoms develop, get medical attention.

Eye Contact:

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1. Information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Non-combustible. Use a fire fighting agent suitable for surrounding fire.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid eye contact. Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment.

7.2. Conditions for safe storage including any incompatibilities

Keep cool. Store away from heat. Store away from areas where product may come into contact with food or pharmaceuticals. Store in a dry place.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

3M Brand Fire Barrier CP-25WB+**Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
Triphenyl Phosphate	115-86-6	ACGIH	TWA:3 mg/m3	
Iron Oxide	1309-37-1	ACGIH	TWA(respirable fraction):5 mg/m3	
Polyethylene Glycol	25322-68-3	AIHA	TWA(as particulate):10 mg/m3	
Oxide Glass Chemicals	65997-17-3	Manufacturer determined	TWA(as dust):10 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

Neoprene

Nitrile Rubber

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state

Solid

Specific Physical Form:	Paste
Appearance/Odour	Red with negligible odour
Odour threshold	<i>No Data Available</i>
Melting point/Freezing point	<i>No Data Available</i>
Flash Point	No flash point
Flammability (solid, gas)	Not Classified
Flammable Limits(LEL)	<i>Not Applicable</i>
Flammable Limits(UEL)	<i>Not Applicable</i>
Relative density	1.35 [<i>Ref Std: WATER=1</i>]
Water solubility	Complete
Solubility- non-water	<i>No Data Available</i>
Autoignition temperature	<i>Not Applicable</i>
Decomposition temperature	<i>No Data Available</i>
Molecular weight	<i>No Data Available</i>
Volatile Organic Compounds	<=0.5 % weight [<i>Test Method:tested per EPA method 24</i>]
VOC Less H2O & Exempt Solvents	<=6 g/l [<i>Test Method:tested per EPA method 24</i>]

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified
Oxides of Phosphorus	Not Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

3M Brand Fire Barrier CP-25WB+**Inhalation:**

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Ingestion:

May be harmful if swallowed. Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE 2,000 - 5,000 mg/kg
Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Polymer	Ingestion	Rat	LD50 > 2,000 mg/kg
Zinc Borate 2335	Dermal	Rabbit	LD50 > 10,000 mg/kg
Zinc Borate 2335	Ingestion	Rat	LD50 > 10,000 mg/kg
Sodium Silicate	Dermal	Rabbit	LD50 > 4,640 mg/kg
Sodium Silicate	Ingestion	Rat	LD50 500 mg/kg
Ethylhexyldiphenyl Phosphate	Dermal	Rabbit	LD50 > 7,940 mg/kg
Ethylhexyldiphenyl Phosphate	Ingestion	Rat	LD50 > 24,000 mg/kg
Iron Oxide	Dermal	Not available	LD50 3,100 mg/kg
Iron Oxide	Ingestion	Not available	LD50 3,700 mg/kg
Polyethylene Glycol	Dermal	Rabbit	LD50 > 20,000 mg/kg
Polyethylene Glycol	Ingestion	Rat	LD50 32,770 mg/kg
Oxide Glass Chemicals	Dermal		LD50 estimated to be > 5,000 mg/kg
Oxide Glass Chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Polyoxyethylene monoocetylphenyl ether	Dermal	Rabbit	LD50 > 3,000 mg/kg
Polyoxyethylene monoocetylphenyl ether	Ingestion	Rat	LD50 > 500 mg/kg
Triphenyl Phosphate	Dermal	Rabbit	LD50 > 7,900 mg/kg
Triphenyl Phosphate	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 50 mg/l
Triphenyl Phosphate	Ingestion	Rat	LD50 > 3,000 mg/kg
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Dermal	Rabbit	LD50 87 mg/kg
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Inhalation-Dust/Mist (4 hours)	Rat	LC50 0.33 mg/l
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Ingestion	Rat	LD50 40 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Polymer	Rabbit	Minimal irritation
Sodium Silicate	Rabbit	Corrosive

3M Brand Fire Barrier CP-25WB+

Iron Oxide	Rabbit	No significant irritation
Polyethylene Glycol	Rabbit	Minimal irritation
Oxide Glass Chemicals	Professional judgement	No significant irritation
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Rabbit	Corrosive

Serious Eye Damage/Irritation

Name	Species	Value
Polymer	Professional judgement	Mild irritant
Sodium Silicate	Rabbit	Corrosive
Iron Oxide	Rabbit	No significant irritation
Polyethylene Glycol	Rabbit	Mild irritant
Oxide Glass Chemicals	Professional judgement	No significant irritation
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
Sodium Silicate	Mouse	Not sensitizing
Iron Oxide	Human	Some positive data exist, but the data are not sufficient for classification
Polyethylene Glycol	Guinea pig	Not sensitizing
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Human and animal	Sensitizing

Photosensitization

Name	Species	Value
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Human and animal	Not sensitizing

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Sodium Silicate	In Vitro	Not mutagenic
Sodium Silicate	In vivo	Not mutagenic
Iron Oxide	In Vitro	Not mutagenic
Polyethylene Glycol	In Vitro	Not mutagenic
Polyethylene Glycol	In vivo	Not mutagenic
Oxide Glass Chemicals	In Vitro	Some positive data exist, but the data are not sufficient for classification
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	In vivo	Not mutagenic
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	In Vitro	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

3M Brand Fire Barrier CP-25WB+

Name	Route	Species	Value
Iron Oxide	Inhalation	Human	Some positive data exist, but the data are not sufficient for classification
Polyethylene Glycol	Ingestion	Rat	Not carcinogenic
Oxide Glass Chemicals	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Dermal	Mouse	Not carcinogenic
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Ingestion	Rat	Not carcinogenic

Reproductive Toxicity
Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test result	Exposure Duration
Sodium Silicate	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Mouse	NOAEL 200 mg/kg/day	during gestation
Polyethylene Glycol	Ingestion	Not toxic to female reproduction	Rat	NOAEL 1,125 mg/kg/day	during gestation
Polyethylene Glycol	Ingestion	Not toxic to male reproduction	Rat	NOAEL 5699 +/- 1341 mg/kg/day	5 days
Polyethylene Glycol	Not Specified	Some positive reproductive/developmental data exist, but the data are not sufficient for classification		NOEL N/A	
Polyethylene Glycol	Ingestion	Some positive developmental data exist, but the data are not sufficient for classification	Mouse	NOAEL 562 mg/animal/day	during gestation
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Ingestion	Not toxic to female reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Ingestion	Not toxic to male reproduction	Rat	NOAEL 10 mg/kg/day	2 generation
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Ingestion	Not toxic to development	Rat	NOAEL 15 mg/kg/day	during organogenesis

Target Organ(s)
Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Sodium Silicate	Inhalation	respiratory irritation	May cause respiratory irritation	official classification	NOAEL Not available	
Polyethylene Glycol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.008 mg/l	2 weeks
3(2H)-Isothiazolone, 5-chloro-2-methyl-, mixt. with 2-methyl-3(2H)-isothiazolone	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Sodium Silicate	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Dog	LOAEL 2,400 mg/kg/day	4 weeks
Sodium Silicate	Ingestion	endocrine system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 804 mg/kg/day	3 months

3M Brand Fire Barrier CP-25WB+

Sodium Silicate	Ingestion	blood	All data are negative	Rat	NOAEL 804 mg/kg/day	3 months
Sodium Silicate	Ingestion	heart liver	All data are negative	Rat	NOAEL 1,259 mg/kg/day	8 weeks
Iron Oxide	Inhalation	pulmonary fibrosis pneumoconiosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Polyethylene Glycol	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1.008 mg/l	2 weeks
Polyethylene Glycol	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 5,640 mg/kg/day	13 weeks
Polyethylene Glycol	Ingestion	heart endocrine system hematopoietic system liver nervous system	All data are negative	Rat	NOAEL 5,640 mg/kg/day	13 weeks
Oxide Glass Chemicals	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

No data available.

SECTION 13: Disposal considerations

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****Global inventory status**

Contact 3M for more information. The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA.

Trade Secret Information:**HMIRA Registry Number:** Filing date:**Claim status:****Date of decision:**

TBD

Claim for exemption has been filed.

SECTION 16: Other information

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Health: 1 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification

Health: 2 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M Canada SDSs are available at www.3M.ca

Product Safety Data Sheet

Silicone Information

This product contains ONE of the following silicones:

Sikasil® WS-295

DOWSIL™ 790 (refers to Gray -- applicable for any color)

Pecora 890 NST™

**SECTION 1. IDENTIFICATION**

Product name : Sikasil® WS-295

Company name : Sika Corporation
201 Polito Avenue
Lyndhurst, NJ 07071
USA
www.sikausa.com

Telephone : (201) 933-8800

Telefax : (201) 804-1076

E-mail address : ehs@sika-corp.com

Emergency telephone : CHEMTREC: 800-424-9300
INTERNATIONAL: +1-703-527-3887

Recommended use of the chemical and restrictions on use : For further information, refer to product data sheet.

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)**

Flammable liquids : Category 4

Eye irritation : Category 2A

Skin sensitization : Category 1

Reproductive toxicity : Category 2

Specific target organ toxicity - repeated exposure : Category 2

GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : H227 Combustible liquid.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H361 Suspected of damaging fertility or the unborn child.



H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements :

Prevention:

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
 P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
 P264 Wash skin thoroughly after handling.
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P337 + P313 If eye irritation persists: Get medical advice/ attention.
 P362 + P364 Take off contaminated clothing and wash it before reuse.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 Store in a well-ventilated place.
 P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labeling

There are no ingredients with unknown acute toxicity used in a mixture at a concentration \geq 1%.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration (% w/w)



2-Butanone, O,O',O''-(phenylsilylidyne)trioxime	34036-80-1	Skin Sens. 1; H317 STOT RE 2; H373	>= 1 - < 5
butan-2-one O,O',O''-(methylsilylidyne)trioxime	22984-54-9	Eye Irrit. 2A; H319 Skin Sens. 1; H317 STOT RE 2; H373	>= 1 - < 5
N-(2-aminoethyl)-N'-[3-(trimethoxysilyl)propyl]ethylenediamine	35141-30-1	Acute Tox. 4; H332 Eye Dam. 1; H318 Skin Sens. 1A; H317	>= 1 - < 5
octamethylcyclotetrasiloxane	556-67-2	Flam. Liq. 3; H226 Repr. 2; H361	>= 0.1 - < 1

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this material safety data sheet to the doctor in attendance.
- If inhaled : Move to fresh air.
Consult a physician after significant exposure.
- In case of skin contact : Take off contaminated clothing and shoes immediately.
Wash off with soap and plenty of water.
If symptoms persist, call a physician.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Clean mouth with water and drink afterwards plenty of water.
Do not induce vomiting without medical advice.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
Obtain medical attention.
- Most important symptoms and effects, both acute and delayed : irritant effects
sensitizing effects
Allergic reactions
Excessive lachrymation
May cause an allergic skin reaction.
Causes serious eye irritation.
Suspected of damaging fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure.
- Notes to physician : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

- Suitable extinguishing media : Carbon dioxide (CO₂)



- Unsuitable extinguishing media : Water
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Deny access to unprotected persons.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.
If the product contaminates rivers and lakes or drains inform respective authorities.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Advice on safe handling : Do not breathe vapors or spray mist.
Avoid exceeding the given occupational exposure limits (see section 8).
Do not get in eyes, on skin, or on clothing.
For personal protection see section 8.
Persons with a history of skin sensitization problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Follow standard hygiene measures when handling chemical products.
- Conditions for safe storage : Store in original container.
Keep in a well-ventilated place.
Observe label precautions.
Store in accordance with local regulations.
- Materials to avoid : Explosives



Oxidizing agents
Poisonous gases
Poisonous liquids

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures : Use of adequate ventilation should be sufficient to control worker exposure to airborne contaminants. If the use of this product generates dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

Personal protective equipment

- Respiratory protection** : Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
- The filter class for the respirator must be suitable for the maximum expected contaminant concentration (gas/vapor/aerosol/particulates) that may arise when handling the product. If this concentration is exceeded, self-contained breathing apparatus must be used.
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary.
- Skin and body protection** : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Hygiene measures** : Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
Remove respiratory and skin/eye protection only after vapors have been cleared from the area.
Remove contaminated clothing and protective equipment before entering eating areas.
Wash thoroughly after handling.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES



Appearance	:	paste
Color	:	various
Odor	:	mild, musty
Odor Threshold	:	No data available
pH	:	Not applicable
Melting point/range / Freezing point	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	185 °F / 85 °C (Method: closed cup)
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapor pressure	:	0.01 hpa
Relative vapor density	:	No data available
Density	:	ca. 1.12 g/cm ³ (73 °F / 23 °C)
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Autoignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	> 20.5 mm ² /s (104 °F / 40 °C)
Explosive properties	:	No data available
Oxidizing properties	:	No data available
Volatile organic compounds	:	37 g/l



(VOC) content

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Stable under recommended storage conditions.
Conditions to avoid	:	Extremes of temperature and direct sunlight.
Incompatible materials	:	No data available
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Components:**N-(2-aminoethyl)-N'-[3-(trimethoxysilyl)propyl]ethylenediamine:**

Acute oral toxicity	:	LD50 Oral (Rat): 7,758 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): > 1.49 mg/l Exposure time: 4 h Test atmosphere: dust/mist
Acute dermal toxicity	:	LD50 Dermal (Rat): 16,640 mg/kg

octamethylcyclotetrasiloxane:

Acute inhalation toxicity	:	LC50 (Rat): 36 mg/l Exposure time: 4 h Test atmosphere: vapor
---------------------------	---	---

Skin corrosion/irritation

Not classified based on available information.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitization**Skin sensitization**

May cause an allergic skin reaction.

Respiratory sensitization

Not classified based on available information.



Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

IARC	Group 2B: Possibly carcinogenic to humans titanium dioxide	13463-67-7
	Group 2B: Possibly carcinogenic to humans Carbon black	1333-86-4

OSHA Not applicable

NTP Not applicable

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.
Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks : Carbon black (1333-86-4)
Animal Toxicity:
 Rat, oral, duration 2 year
 Effect: no tumors

 Mouse, oral, duration 2 years
 Effect: no tumors
 Mouse, dermal, duration 18 months
 Effect: no skin tumors
 Rat, inhalation, duration 2 years
 Target organ: lungs
 Effect: inflammation, fibrosis, tumors
 Note: Tumors in the rat lung are considered to be related to the "particle overload phenomenon" rather than to a specific chemical effect of carbon black itself in the lung. These effects in rats have been reported in many studies on other poorly soluble inorganic particles and appear to be rat specific. Tumors have not been observed in other species (i.e., mouse and hamster) for carbon black or other poorly soluble particles under similar circumstances and study conditions.
 Mortality studies (human data): A study on carbon black production workers in the UK (Sorahan, 2001) found an increased risk of lung cancer in two of the five plant studied; however, the increase was not related to the dose of carbon



black. Thus, the authors did not consider the increased risk in lung cancer to be due to carbon black exposure. A German study of carbon black workers at one plant (Morfeld, 2006; Buechte, 2006) found a similar increase in lung cancer risk but, like the Sorohan, 2001 (UK study) found no association with carbon black exposure. A large US study of 18 plants showed a reduction in lung cancer risk in carbon black production workers (DEll, 2006). Based upon these studies, the February 2006 Working Group at the International Agency for Research on Cancer (IARC) concluded that the human evidence for carcinogenicity was inadequate (IARC, 2010). Since the IARC evaluation of carbon black, Sorohan and Harrington (2007) have re-analyzed the UK study data using an alternative exposure hypothesis and found a positive association with carbon black exposure in two of the five plants. The same exposure hypothesis was applied by Morfeld and McCunney (2009) to the German cohort; in contrast, they found no association between carbon black exposure and lung cancer risk and, thus, no support for the alternative exposure hypothesis used by Sorohan and Harrington. Overall, as a result of these detailed investigations, no causative link between carbon black exposure and cancer risk in humans has been demonstrated.

IARC CANCER CLASSIFICATION: In 2006 IARC re-affirmed its 1995 finding that there is "inadequate evidence" from human health studies to assess whether carbon black causes cancer in humans. IARC concluded that there is "sufficient evidence" in experimental animal studies for the carcinogenicity of carbon black. IARC's overall evaluation is that carbon black is "possibly carcinogenic to humans" (Group 2B)". This conclusion was based on IARC's guidelines, which generally require such a classification if one species exhibits carcinogenicity in two or more animal studies (IARC, 2010).

Solvent extracts of carbon black were used in one study of rats in which skin tumors were found after dermal application and several studies of mice in which sarcomas were found following subcutaneous injection. IARC concluded that there was "sufficient evidence" that carbon black extracts can cause cancer in animals (Group 2B).

ICGIH CANCER CLASSIFICATION: Confirmed Animal Carcinogen with Unknown Relevance to Humans (Category A3 Carcinogen).

ASSESSMENT: Applying the guidelines of self-classification under the Globally Harmonized System of Classification and Labeling of Chemicals, carbon black is not classified as a carcinogen. Lung tumors are induced in rats as a result of repeated exposure to inert, poorly soluble particles like carbon black and other poorly soluble particles. Rats tumors are a result of a secondary non-genotoxic mechanism that has questionable relevance for classification in humans. In support of this opinion, the CLP Guidance for Specific Target Organ Toxicity - Repeated Exposure (STOT-RE), cites lung overload



under mechanisms not relevant to humans. Human health studies show that exposure to carbon black does not increase the risk to carcinogenicity.

Titanium dioxide (13463-67-7)

In lifetime inhalation studies of rats, airborne respirable-size titanium dioxide particles have shown to cause an increase in lung tumors at concentrations associated with substantial particle lung burdens and consequential pulmonary overload and inflammation. The potential for these adverse health effects appears to be closely related to the particle size and the amount of the exposed surface area that comes into contact with the lung. However, tests with other laboratory animals such as mice and hamsters, indicate that rats are significantly more susceptible to the pulmonary overload and inflammation that causes lung cancer. Epidemiological studies do not suggest an increased risk of cancer in humans from occupational exposure to titanium dioxide. Titanium dioxide has been characterized by IARC as possibly carcinogenic to humans (Group 2B) through inhalation (not ingestion). It has not been characterized as a potential carcinogen by either NTP or OSHA.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

Product:

Additional ecological information : Do not empty into drains; dispose of this material and its container in a safe way.
Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Components:

octamethylcyclotetrasiloxane:

Results of PBT and vPvB assessment : PBT substance
: vPvB substance



SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

- TSCA list** : All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

- SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)
Respiratory or skin sensitization
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)
Serious eye damage or eye irritation

- SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.



Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop 65



WARNING: Cancer and Reproductive Harm -
www.P65Warnings.ca.gov

SECTION 16. OTHER INFORMATION

Full text of other abbreviations

Notes to Reader

The information contained in this Safety Data Sheet applies only to the actual Sika Corporation ("Sika") product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section 1 of this SDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sikausa.com or 201-933-8800.

Revision Date 12/04/2020

000000608042
US / Z8



SAFETY DATA SHEET

THE DOW CHEMICAL COMPANY

Product name: DOWSIL™ 790 Silicone Building Sealant Gray

Issue Date: 02/08/2018

Print Date: 02/09/2018

THE DOW CHEMICAL COMPANY encourages and expects you to read and understand the entire (M)SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

1. IDENTIFICATION

Product name: DOWSIL™ 790 Silicone Building Sealant Gray

Recommended use of the chemical and restrictions on use

Identified uses: Adhesive, binding agents

COMPANY IDENTIFICATION

THE DOW CHEMICAL COMPANY
2030 WILLARD H DOW CENTER
MIDLAND MI 48674-0000
UNITED STATES

Customer Information Number:

800-258-2436
SDSQuestion@dow.com

EMERGENCY TELEPHONE NUMBER

24-Hour Emergency Contact: CHEMTREC +1 800-424-9300

Local Emergency Contact: 800-424-9300

2. HAZARDS IDENTIFICATION

Hazard classification

This material is hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29CFR 1910.1200.

Eye irritation - Category 2A

Reproductive toxicity - Category 2

Label elements

Hazard pictograms



Signal word: **WARNING!**

Hazards

Causes serious eye irritation.
Suspected of damaging fertility or the unborn child.

Precautionary statements**Prevention**

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wash skin thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF exposed or concerned: Get medical advice/ attention.
If eye irritation persists: Get medical advice/ attention.

Storage

Store locked up.

Disposal

Dispose of contents/ container to an approved waste disposal plant.

Other hazards

No data available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature: Silicone elastomer

This product is a mixture.

Component	CASRN	Concentration
Limestone	1317-65-3	>= 50.0 - < 60.0 %
Methylvinyl bis(N-ethylacetamido)silane	87855-59-2	>= 1.0 - < 3.0 %
Dimethyl, methylhydrogen siloxane, dehydrogenated, reaction with hydroxydiethylamine	68952-53-4	>= 1.0 - < 5.0 %
Magnesium carbonate	546-93-0	>= 1.0 - < 5.0 %
N-ethylacetamide	625-50-3	>= 0.1 - < 1.0 %
Octamethyl Cyclotetrasiloxane	556-67-2	>= 0.1 - < 1.0 %

Impurities in methylvinylbis(N-ethylacetamido)silane

Not available

>= 0.1 - < 1.0 %

4. FIRST AID MEASURES

Description of first aid measures

General advice:

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation: Move person to fresh air; if effects occur, consult a physician.

Skin contact: Remove material from skin immediately by washing with soap and plenty of water. Remove contaminated clothing and shoes while washing. Seek medical attention if irritation persists. Wash clothing before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands.

Eye contact: Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist. Suitable emergency eye wash facility should be available in work area.

Ingestion: No emergency medical treatment necessary.

Most important symptoms and effects, both acute and delayed: Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Suitable extinguishing media: Water spray Alcohol-resistant foam Carbon dioxide (CO₂) Dry chemical

Unsuitable extinguishing media: None known.

Special hazards arising from the substance or mixture

Hazardous combustion products: Carbon oxides Silicon oxides Nitrogen oxides (NO_x)

Unusual Fire and Explosion Hazards: Exposure to combustion products may be a hazard to health.

Advice for firefighters

Fire Fighting Procedures: Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Remove undamaged containers from fire area if it is safe to do so. Evacuate area.

Special protective equipment for firefighters: In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures: Use personal protective equipment. Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions: Discharge into the environment must be avoided. Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up: Wipe up or scrape up and contain for salvage or disposal. Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable. For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, Sections 13 and 15 of this SDS provide information regarding certain local or national requirements. See sections: 7, 8, 11, 12 and 13.

7. HANDLING AND STORAGE

Precautions for safe handling: Do not get on skin or clothing. Do not swallow. Do not get in eyes. Take care to prevent spills, waste and minimize release to the environment. Handle in accordance with good industrial hygiene and safety practice. Use only with adequate ventilation. See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Conditions for safe storage: Keep in properly labelled containers. Store locked up. Store in accordance with the particular national regulations.

Do not store with the following product types: Strong oxidizing agents.
Unsuitable materials for containers: None known.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

If exposure limits exist, they are listed below. If no exposure limits are displayed, then no values are applicable.

Component	Regulation	Type of listing	Value/Notation
-----------	------------	-----------------	----------------

Limestone	OSHA Z-1	TWA total dust	15 mg/m ³
	OSHA Z-1	TWA respirable fraction	5 mg/m ³
Magnesium carbonate	OSHA Z-1	TWA total dust	15 mg/m ³
	OSHA Z-1	TWA respirable fraction	5 mg/m ³
Octamethyl Cyclotetrasiloxane	US WEEL	TWA	10 ppm

Although some of the components of this product may have exposure guidelines, no exposure would be expected under normal handling conditions due to the physical state of the material.

Exposure controls

Engineering controls: Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Individual protection measures

Eye/face protection: Use safety glasses (with side shields).

Skin protection

Hand protection: Use gloves chemically resistant to this material. Examples of preferred glove barrier materials include: Butyl rubber. Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl"). Viton. Examples of acceptable glove barrier materials include: Natural rubber ("latex"). **NOTICE:** The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

Other protection: Use protective clothing chemically resistant to this material. Selection of specific items such as face shield, boots, apron, or full body suit will depend on the task.

Respiratory protection: Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if handling at elevated temperatures without sufficient ventilation, use an approved air-purifying respirator.

The following should be effective types of air-purifying respirators: Organic vapor cartridge.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Physical state	paste
Color	grey

Odor	Fishy
Odor Threshold	No data available
pH	Not applicable
Melting point/range	No data available
Freezing point	No data available
Boiling point (760 mmHg)	Not applicable
Flash point	Not applicable
Evaporation Rate (Butyl Acetate = 1)	Not applicable
Flammability (solid, gas)	Not classified as a flammability hazard
Lower explosion limit	No data available
Upper explosion limit	No data available
Vapor Pressure	Not applicable
Relative Vapor Density (air = 1)	No data available
Relative Density (water = 1)	1.48
Water solubility	No data available
Partition coefficient: n-octanol/water	No data available
Auto-ignition temperature	No data available
Decomposition temperature	No data available
Dynamic Viscosity	Not applicable
Kinematic Viscosity	Not applicable
Explosive properties	Not explosive
Oxidizing properties	The substance or mixture is not classified as oxidizing.
Liquid Density	1.48 g/cm ³
Molecular weight	No data available
Particle size	No data available

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Reactivity: Not classified as a reactivity hazard.

Chemical stability: Stable under normal conditions.

Possibility of hazardous reactions: Can react with strong oxidizing agents.

Conditions to avoid: None known.

Incompatible materials: Oxidizing agents

Hazardous decomposition products: Formaldehyde.

11. TOXICOLOGICAL INFORMATION

Toxicological information appears in this section when such data is available.

Acute toxicity

Acute oral toxicity

Very low toxicity if swallowed. Harmful effects not anticipated from swallowing small amounts.

As product: Single dose oral LD50 has not been determined.

Based on information for component(s):
LD50, Rat, > 5,000 mg/kg Estimated.

Acute dermal toxicity

Prolonged skin contact is unlikely to result in absorption of harmful amounts.

As product: The dermal LD50 has not been determined.

Based on information for component(s):
LD50, > 2,000 mg/kg Estimated.

Acute inhalation toxicity

Brief exposure (minutes) is not likely to cause adverse effects. Vapor from heated material may cause respiratory irritation.

As product: The LC50 has not been determined.

Skin corrosion/irritation

Brief contact may cause slight skin irritation with local redness.

Serious eye damage/eye irritation

May cause slight eye irritation.

Sensitization

For skin sensitization:

Contains component(s) which have caused allergic skin sensitization in guinea pigs.

For respiratory sensitization:

No relevant information found.

Specific Target Organ Systemic Toxicity (Single Exposure)

Evaluation of available data suggests that this material is not an STOT-SE toxicant.

Specific Target Organ Systemic Toxicity (Repeated Exposure)

For this family of materials:

Based on available data, repeated exposures are not anticipated to cause significant adverse effects.

Carcinogenicity

For this family of materials: Did not cause cancer in long-term animal studies which used routes of exposure considered relevant to industrial handling. Positive results have been reported in other studies using routes of exposure not relevant to industrial handling. Both the National Toxicology Program (NTP) Third Annual Report on Carcinogens and the International Agency for Research on Cancer (IARC) Monographs cite limited evidence for carcinogenicity to humans of certain nickel compounds, and sufficient evidence for carcinogenicity to animals. However, both state that it is not possible to specify which specific nickel compounds might be carcinogenic to humans. Nickel Antimony Titanium Yellow Rutile is not listed in the groups of compounds thought to be carcinogenic to either humans or animals.

Teratogenicity

Contains component(s) which did not cause birth defects or any other fetal effects in lab animals.

Reproductive toxicity

Contains component(s) which did not interfere with reproduction in animal studies.

Mutagenicity

Contains a component(s) which were negative in in vitro genetic toxicity studies.

Aspiration Hazard

Based on physical properties, not likely to be an aspiration hazard.

COMPONENTS INFLUENCING TOXICOLOGY:**Limestone****Acute inhalation toxicity**

The LC50 has not been determined.

Methylvinyl bis(N-ethylacetamido)silane**Acute inhalation toxicity**

The LC50 has not been determined.

Dimethyl, methylhydrogen siloxane, dehydrogenated, reaction with hydroxydiethylamine**Acute inhalation toxicity**

The LC50 has not been determined.

Magnesium carbonate**Acute inhalation toxicity**

The LC50 has not been determined.

N-ethylacetamide**Acute inhalation toxicity**

Based on data from similar materials LC0, Rat, 8 Hour, vapour, 2.19 mg/l

Octamethyl Cyclotetrasiloxane**Acute inhalation toxicity**

LC50, Rat, male and female, 4 Hour, dust/mist, 36 mg/l OECD Test Guideline 403

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity

Limestone

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).
LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, > 10,000 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, > 1,000 mg/l

Acute toxicity to algae/aquatic plants

EC50, Desmodesmus subspicatus (green algae), 72 Hour, > 200 mg/l

Methylvinyl bis(N-ethylacetamido)silane

Acute toxicity to fish

Material is slightly toxic to aquatic organisms on an acute basis (LC50/EC50 between 10 and 100 mg/L in the most sensitive species tested).
LC50, Danio rerio (zebra fish), 96 Hour, > 100 mg/l
LC50, Oncorhynchus mykiss (rainbow trout), 96 Hour, > 100 mg/l, OECD Test Guideline 203
NOEC, Oncorhynchus mykiss (rainbow trout), 96 Hour, 50 mg/l

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), 48 Hour, 69 mg/l, OECD Test Guideline 202

Acute toxicity to algae/aquatic plants

EC50, Pseudokirchneriella subcapitata (green algae), 72 Hour, > 100 mg/l, OECD Test Guideline 201
NOEC, Pseudokirchneriella subcapitata (green algae), 72 Hour, 100 mg/l

Dimethyl, methylhydrogen siloxane, dehydrogenated, reaction with hydroxydiethylamine

Acute toxicity to fish

No relevant data found.

Magnesium carbonate

Acute toxicity to fish

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

Acute toxicity to algae/aquatic plants

For similar material(s):

EC50, Desmodesmus subspicatus (green algae), static test, 72 Hour, Growth inhibition, > 100 mg/l, OECD Test Guideline 201

For similar material(s):

NOEC, Desmodesmus subspicatus (green algae), static test, 100 mg/l

N-ethylacetamide

Acute toxicity to fish

Based on data from similar materials

LC50, *Leuciscus idus* (Golden orfe), 96 Hour, 3,390 mg/l, DIN 38412

Material is practically non-toxic to aquatic organisms on an acute basis (LC50/EC50/EL50/LL50 >100 mg/L in the most sensitive species tested).

Acute toxicity to aquatic invertebrates

Based on data from similar materials

EC50, *Daphnia magna* (Water flea), 48 Hour, > 580 mg/l, DIN 38412

Acute toxicity to algae/aquatic plants

Based on data from similar materials

EC50, *Desmodesmus subspicatus* (green algae), 96 Hour, > 500 mg/l

Toxicity to bacteria

Based on data from similar materials

EC10, *Pseudomonas putida*, 17 Hour, > 10,000 mg/l, DIN 38 412 Part 8

Octamethyl Cyclotetrasiloxane

Acute toxicity to fish

Not expected to be acutely toxic to aquatic organisms.

No toxicity at the limit of solubility

LC50, *Oncorhynchus mykiss* (rainbow trout), flow-through, 96 Hour, > 0.022 mg/l

No toxicity at the limit of solubility

LC50, *Cyprinodon variegatus* (sheepshead minnow), flow-through, 14 d, > 0.0063 mg/l

Acute toxicity to aquatic invertebrates

No toxicity at the limit of solubility

EC50, *Mysidopsis bahia* (opossum shrimp), flow-through test, 96 Hour, > 0.0091 mg/l

No toxicity at the limit of solubility

EC50, *Daphnia magna* (Water flea), flow-through test, 48 Hour, > 0.015 mg/l

Acute toxicity to algae/aquatic plants

No toxicity at the limit of solubility

ErC50, *Pseudokirchneriella subcapitata* (green algae), 72 Hour, Growth rate, > 0.022 mg/l

Chronic toxicity to fish

No toxicity at the limit of solubility

NOEC, *Oncorhynchus mykiss* (rainbow trout), 93 d, >= 0.0044 mg/l

Chronic toxicity to aquatic invertebrates

No toxicity at the limit of solubility

NOEC, *Daphnia magna* (Water flea), 21 d, >= 0.0079 mg/l

Persistence and degradability

Limestone

Biodegradability: No relevant data found.

Methylvinyl bis(N-ethylacetamido)silane

Biodegradability: Based on stringent OECD test guidelines, this material cannot be considered as readily biodegradable; however, these results do not necessarily mean that the material is not biodegradable under environmental conditions.

Biodegradation: 62.66 %

Method: OECD Test Guideline 301B

Dimethyl, methylhydrogen siloxane, dehydrogenated, reaction with hydroxydiethylamine

Biodegradability: Based on data from similar materials

The product is not biodegradable.

Magnesium carbonate

Biodegradability: No relevant data found.

N-ethylacetamide

Biodegradability: Material is ultimately biodegradable (reaches > 70% mineralization in OECD test(s) for inherent biodegradability).

Based on data from similar materials

Biodegradation: 100 %

Exposure time: 6 d

Octamethyl Cyclotetrasiloxane

Biodegradability: Material is expected to biodegrade very slowly (in the environment). Fails to pass OECD/EEC tests for ready biodegradability.

10-day Window: Not applicable

Biodegradation: 3.7 %

Exposure time: 28 d

Method: OECD Test Guideline 310

Stability in Water (1/2-life)

Hydrolysis, DT50, 69.3 - 144 Hour, pH 7, Half-life Temperature 24.6 °C, OECD Test Guideline 111

Photodegradation

Atmospheric half-life: 16 d

Method: Estimated.

Bioaccumulative potential

Limestone

Bioaccumulation: No relevant data found.

Methylvinyl bis(N-ethylacetamido)silane

Bioaccumulation: No relevant data found.

Dimethyl, methylhydrogen siloxane, dehydrogenated, reaction with hydroxydiethylamine

Bioaccumulation: No relevant data found.

Magnesium carbonate

Bioaccumulation: No relevant data found.

N-ethylacetamide

Bioaccumulation: No relevant data found.

Octamethyl Cyclotetrasiloxane

Bioaccumulation: Bioconcentration potential is high (BCF > 3000 or Log Pow between 5 and 7).

Partition coefficient: n-octanol/water(log Pow): 6.49 Measured

Bioconcentration factor (BCF): 12,400 Pimephales promelas (fathead minnow) Measured

Mobility in soil

Limestone

No relevant data found.

Methylvinyl bis(N-ethylacetamido)silane

No relevant data found.

Dimethyl, methylhydrogen siloxane, dehydrogenated, reaction with hydroxydiethylamine

No relevant data found.

Magnesium carbonate

No relevant data found.

N-ethylacetamide

No relevant data found.

Octamethyl Cyclotetrasiloxane

Expected to be relatively immobile in soil (Koc > 5000).

13. DISPOSAL CONSIDERATIONS

Disposal methods: DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. AS YOUR SUPPLIER, WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN MSDS SECTION: Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Incinerator or other thermal destruction device. For additional information, refer to: Handling & Storage Information, MSDS Section 7 Stability & Reactivity Information, MSDS Section 10 Regulatory Information, MSDS Section 15

Treatment and disposal methods of used packaging: Empty containers should be recycled or otherwise disposed of by an approved waste management facility. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. Do not re-use containers for any purpose.

14. TRANSPORT INFORMATION

DOT

Not regulated for transport

Classification for SEA transport (IMO-IMDG):

**Transport in bulk
according to Annex I or II
of MARPOL 73/78 and the
IBC or IGC Code**

Not regulated for transport
Consult IMO regulations before transporting ocean bulk

Classification for AIR transport (IATA/ICAO):

Not regulated for transport

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

15. REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Serious eye damage or eye irritation
Reproductive toxicity

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning and Community Right-to-Know Act of 1986) Section 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Comprehensive Environmental Response, Compensation, and Liability Act of 1980 (CERCLA) Section 103

This material does not contain any components with a CERCLA RQ.
Calculated RQ exceeds reasonably attainable upper limit.

Components	CASRN	RQ (RCRA Code)
Diethylamine	109-89-7	100 lbs RQ

Pennsylvania Worker and Community Right-To-Know Act:

The following chemicals are listed because of the additional requirements of Pennsylvania law:

Components	CASRN
-------------------	--------------

Limestone	1317-65-3
Polydimethylsiloxane hydroxy-terminated	70131-67-8
Cobalt titanite green spinel	68186-85-6
Aluminium	7429-90-5

California Prop. 65

WARNING: This product can expose you to chemicals including Quartz, Carbon black, Titanium dioxide, Cobalt titanite green spinel, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

United States TSCA Inventory (TSCA)

All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating System**NFPA**

Health	Flammability	Instability
2	1	0

HMIS

Health	Flammability	Physical Hazard
2*	1	0

* = Chronic Effects (See Hazards Identification)

Revision

Identification Number: 4110835 / A001 / Issue Date: 02/08/2018 / Version: 7.0

Most recent revision(s) are noted by the bold, double bars in left-hand margin throughout this document.

Legend

OSHA Z-1	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
TWA	8-hour time weighted average
US WEEL	USA. Workplace Environmental Exposure Levels (WEEL)

Full text of other abbreviations

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International

Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECl - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Information Source and References

This SDS is prepared by Product Regulatory Services and Hazard Communications Groups from information supplied by internal references within our company.

THE DOW CHEMICAL COMPANY urges each customer or recipient of this (M)SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this (M)SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific (M)SDSs, we are not and cannot be responsible for (M)SDSs obtained from any source other than ourselves. If you have obtained an (M)SDS from another source or if you are not sure that the (M)SDS you have is current, please contact us for the most current version.

US

SAFETY DATA SHEET



1. PRODUCT IDENTIFICATION

IDENTIFICATION of the SUBSTANCE or PREPARATION

TRADE NAME (AS LABELED):	Pecora 890 NST Non-Staining Technology™
PRODUCT DESCRIPTION:	Non-Staining, Ultra Low-Modulus Silicone Sealant
CHEMICAL NAME/CLASS:	Polydimethylsiloxane Silicone
SYNONYMS:	890 NST
RELEVANT USE:	Non-Staining Silicone Sealant/Caulking Compound
USES ADVISED AGAINST:	Other Than Relevant Use

COMPANY/UNDERTAKING IDENTIFICATION:

SUPPLIER/MANUFACTURER'S NAME:	Pecora Corporation
ADDRESS:	165 Wambold Road, Harleysville, PA 19438
EMERGENCY PHONE:	800-424-9300 (CHEMTREC, 24-hours)
BUSINESS PHONE:	215-723-6051 (Mon-Fri, 8 AM-5 PM ET)

PREPARATION DATE:	May 2005
REVISION DATE:	March 13, 2017

This product is sold for commercial use. This SDS has been developed to address safety concerns of those individuals working with bulk quantities of this material, as well as those of potential users of this product in industrial/occupational settings. ALL United States Occupational Safety and Health Administration Standard (29 CFR 1910.1200), U.S. State equivalent Standards, Canadian WHMIS 2015 and the Global Harmonization required information is included in appropriate sections based on the Global Harmonization Standard format. This product has been classified in accordance with the hazard criteria of the countries listed above and the SDS contains all the information required by the Canadian WHMIS 2015 [HPR-GHS], the Global Harmonization Standard and OSHA 1910.120.

2. HAZARD IDENTIFICATION

GLOBAL HARMONIZATION LABELING AND CLASSIFICATION: Classified in accordance with Global Harmonization Standard under U.S. OSHA Hazard Communication Standard, Canadian WHMIS HPR-GHS 2015.

Classification: Reproductive Toxicity Cat. 2, Acute Oral Toxicity Cat. 5, Eye Irritation Cat. 2B, Skin Irritation Cat. 3, Skin Sensitization Cat. 1, Aquatic Chronic Toxicity Cat. 4

Signal Word: Warning

Hazard Statement Codes: H361fd, H303, H316, H320, H317, H413

Precautionary Statement Codes: P201, P202, P261, P264, P272, P273, P280, P308 + P313, P305 + P351 + P338, P337 + P313, P302 + P352, P321, P333 + P313, P362 + P364, P405, P501

Hazard Symbols/Pictogram: GHS07, GHS08



EMERGENCY OVERVIEW:

Physical Description: This product is a smooth paste with a slightly medicinal odor and comes in various colors, including Black, Tru-White, Aluminum Stone, Translucent, and Bronze.

Health Hazards: WARNING! Contains trace compound that may cause adverse effects on fertility (based on animal data). May cause eye, skin, and respiratory tract irritation, especially if exposure is prolonged. May be harmful if ingested. May cause skin sensitization in susceptible individuals.

Flammability Hazard: This product is combustible and can ignite if exposed to high temperature or direct flame.

Reactivity Hazard: This product is not reactive.

Environmental Hazard: This product has not been tested for environmental impact. This product contains a compound that can cause chronic aquatic toxicity.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS®)

Health	1*
Flammability	1
Physical Hazard	0

See Section 16 for definitions of ratings

0 = Minimal 3 = Serious
1 = Slight 4 = Severe
2 = Moderate * = Chronic

HMIS® is a registered trademark of the National Paint and Coatings Association.

CANADIAN WHMIS (HPR-GHS) 2015 CLASSIFICATION AND SYMBOLS: See Section 16 for in Classification and Symbols under HPR-GHS 2015.

U.S. OSHA REGULATORY STATUS: This material has a classification under the Global Harmonization Standard, as applied under OSHA regulations, as given earlier in this Section.

3. MATERIAL IDENTIFICATION

Chemical Name	CAS #	W/W%	LABEL ELEMENTS GHS Classification under U.S. OSHA Hazard Communication Standard & Canadian WHMIS (HPR-GHS) 2015 Hazard Statement Codes
Proprietary Polydimethyl Siloxane Mixture Contains the following compound		30.0-60.0	NOTIFIED CLASSIFICATION Classification: Eye Irritation Cat. 2A Hazard Statement Codes: H319
Octamethylcyclotetra-siloxane	556-67-2	>= 0.01 to < 0.5	HARMONISED CLASSIFICATION AND LABELLING (CLP00) Classification: Reproductive Toxicity Cat. 2, Aquatic Chronic Toxicity Cat. 4 Hazard Statement Codes: H361f, H413 ADDITIONAL SELF-CLASSIFICATION Classification: Flammable Liquid Cat. 3, Acute Oral Toxicity Cat. 4, Acute Dermal Toxicity Cat. 4 Hazard Statement Codes: H226, H302 + H312
Calcium Carbonate (Limestone)	1317-65-3	15.0-40.0	NOTIFIED CLASSIFICATION Classification: Skin Irritation Cat. 2 Hazard Statement Codes: H315
Proprietary Crosslinker		3.0-7.0	NOTIFIED CLASSIFICATION Classification: Skin Sensitization Cat. 1B Hazard Statement Codes: H317 ADDITIONAL MFG CLASSIFICATION Classification: STOT RE Cat. 2, Aquatic Chronic Toxicity Cat. 3 Hazard Statement Codes: H373, H412
Proprietary Silicon Dioxide, Fumed		3.0-7.0	SELF CLASSIFICATION Classification: Not Applicable
Mineral Spirits (contains less than 0.1% benzene)		2.0-5.0	HARMONISED CLASSIFICATION - ANNEX VI OF REGULATION (EC) NO 1272/2008 (CLP REGULATION) Classification: Aspiration Hazard Cat. 1 Hazard Statement Codes: H304 ADDITIONAL MFG CLASSIFICATION Classification: Flammable Liquid Cat. 4, STOT (Inhalation-Narcotic Effect) SE Cat. 3, Aquatic Chronic Cat. 1 Hazard Statement Codes: H227, H336, H411
Proprietary Amine Cross-Linker		0.2-0.4	NOTIFIED CLASSIFICATION Classification: Acute Dermal Toxicity Cat. 4, Skin Corrosion Cat. 1B, Skin Sensitization Cat. 1A, Aquatic Acute Toxicity Cat. 2, Aquatic Chronic Cat. 2 Hazard Statement Codes: H312, H314, H317, H401, H411
The following is component information for some of the individual pigmented colors of this product:			
Titanium Dioxide	13463-67-7	0.0-1.1	SELF-CLASSIFICATION Classification: Carcinogenic Cat. 2 Hazard Statement Codes: H351i
Brown Iron Oxide Pigment	Mixture	0.0-0.9	SELF-CLASSIFICATION BASED ON MFG SDS Classification: Skin Irritation Cat. 2, STOT (Inhalation-Respiratory Irritation) SE Cat. 3 Hazard Statement Codes: H315, H335
Carbon Black	1333-86-4	0.0-0.8	NOTIFIED CLASSIFICATION Classification: Carcinogenic Cat. 2 Hazard Statement Codes: H351i
Red Iron Oxide Pigment	Mixture	0.0-0.5	SELF-CLASSIFICATION BASED ON MFG SDS Classification: Skin Irritation Cat. 2, STOT (Inhalation-Respiratory Irritation) SE Cat. 3 Hazard Statement Codes: H315, H335
Other components. Each of the other components is present in less than 1 percent concentration (0.1% concentration for potential carcinogens, reproductive toxins, respiratory tract sensitizers, and mutagens).		Balance	Classification: Not Applicable

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

PROTECTION OF FIRST AID RESPONDERS: Rescuers should not attempt to retrieve victims of exposure to this material without adequate personal protective equipment. Rescuers should be taken for medical attention, if necessary.

DESCRIPTION OF FIRST AID MEASURES: Remove victim(s) to fresh air, as quickly as possible. Only trained personnel should administer supplemental oxygen and/or cardio-pulmonary resuscitation, if necessary. Remove and isolate contaminated clothing and shoes. Seek immediate medical attention. Take copy of label and MSDS to physician or other health professional with victim(s).

Inhalation: If aerosols of this material are inhaled, remove victim to fresh air. If necessary, use artificial respiration to support vital functions.

Skin Exposure: If the material contaminates the skin, immediately begin decontamination with running water. Minimum flushing is for 20 minutes. Do not interrupt flushing. Remove exposed or contaminated clothing, taking care not to contaminate eyes. Victim must seek immediate medical attention.

Eye Exposure: If this product enters the eyes, open victim's eyes while under gently running water. Use sufficient force to open eyelids. Have victim "roll" eyes. Minimum flushing is for 20 minutes. Do not interrupt flushing.

Ingestion: If this material is swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. DO NOT INDUCE VOMITING, unless directly by medical personnel. Have victim rinse mouth with water or give several cupfuls of water, if conscious. Never induce vomiting or give diluents (milk or water) to someone who is unconscious, having convulsions, or unable to swallow. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain an open airway and prevent aspiration.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Dermatitis or other pre-existing skin disorders may be aggravated by exposure to this product.

INDICATION OF IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT IF NEEDED: Treat symptoms and eliminate exposure.

5. FIRE-FIGHTING MEASURES

FLASH POINT: > 140°C (> 300°F)

AUTOIGNITION: Unknown.

FLAMMABLE LIMITS IN AIR: Unknown.

EXTINGUISHING MEDIA:


Suitable Extinguishing Media: Use extinguishing material suitable to the surrounding fire, including foam, halon, carbon dioxide and dry chemical.

Unsuitable Extinguishing Media: None known.

PROTECTION OF FIREFIGHTERS:

Special Hazards Arising From the Substance: This product is combustible and can be ignited when exposed to its flashpoint. Not sensitive to mechanical impact under normal conditions. Not sensitive to static discharge under normal conditions. Closed containers may develop pressure and rupture in event of fire.

Special Protective Actions For Fire-Fighters: Incipient fire responders should wear eye protection. Structural firefighters must wear Self-Contained Breathing Apparatus and full protective equipment. Move containers from fire area if it can be done without risk to personnel. If possible, prevent runoff water from entering storm drains, bodies of water, or other environmentally sensitive areas.



6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS AND EMERGENCY PROCEDURES: An accidental release can result in a fire. Uncontrolled releases should be responded to by trained personnel using pre-planned procedures. Proper protective equipment should be used. Eliminate any possible sources of ignition, and provide maximum explosion-proof ventilation. Use only non-sparking tools and equipment during the response. The atmosphere must at least 19.5 percent Oxygen before non-emergency personnel can be allowed in the area without Self-Contained Breathing Apparatus and fire protection.

PERSONAL PROTECTIVE EQUIPMENT: Responders should wear the level of protection appropriate to the type of chemical released, the amount of the material spilled, and the location where the incident has occurred.

Small Spills: For releases of 1 drum or less, Level D Protective Equipment (gloves, chemical resistant apron, boots, and eye protection) should be worn.

Large Spills: Minimum Personal Protective Equipment should be rubber gloves, rubber boots, face shield, and Tyvek suit. Minimum level of personal protective equipment for releases in which the level of oxygen is less than 19.5% or is unknown must be **Level B: triple-gloves (rubber gloves and nitrile gloves over latex gloves), chemical resistant suit, fire-retardant clothing and boots, hard hat, and Self-Contained Breathing Apparatus.**

METHODS FOR CLEAN-UP AND CONTAINMENT:

All Spills: Access to the spill area should be restricted. Spread should be limited by gently covering the spill with polypads. Scrape up or pick-up spilled material, placing in suitable containers. Absorb any residual on appropriate material, such as sand. All contaminated absorbents and other materials should be placed in an appropriate container and seal. Do not mix with wastes from other materials. Dispose of in accordance with applicable Federal, State, and local procedures (see Section 13, Disposal Considerations). Dispose of recovered material and report spill per regulatory requirements. Remove all residue before decontamination of spill area. Clean spill area with soap and copious amounts of water.

ENVIRONMENTAL PRECAUTIONS: Minimize use of water to prevent environmental contamination. Prevent spill or rinsate from contaminating storm drains, sewers, soil or groundwater. Place all spill residues in a suitable container and seal. Do not discharge effluent containing this product into streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

OTHER INFORMATION: U.S. regulations may require reporting of spills of this material that reach surface waters if a sheen is formed. If necessary, the toll-free phone number for the US Coast Guard National Response Center is 1-800-424-8802.

REFERENCE TO OTHER SECTIONS: See information in Section 8 (Exposure Controls – Personal Protection) and Section 13 (Disposal Considerations) for additional information.

7. HANDLING and STORAGE

PRECAUTIONS FOR SAFE HANDLING: As with all chemicals, avoid getting this product ON YOU or IN YOU. Wash thoroughly after handling this product. Do not eat or drink while handling this material. Avoid contact with eyes, skin, and clothing. Avoid breathing fumes, dusts, vapors or mist. Do not taste or swallow. Use only with adequate ventilation. Keep away from heat and flame. In the event of a spill, follow practices indicated in Section 6: ACCIDENTAL RELEASE MEASURES.

CONDITIONS FOR SAFE STORAGE: This product is stable under ordinary conditions of handling, use and storage. Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible.

CONDITIONS FOR SAFE STORAGE (continued): Store away from incompatible materials (see Section 10: STABILITY AND REACTIVITY). Keep container tightly closed when not in use. Inspect all incoming containers before storage, to ensure containers are properly labeled and not damaged. To prolong shelf life, store at temperatures below 26°C (80°F).

PRODUCT END USE: This product is used as a sealant. Follow all industry standards for use of this product.

8. EXPOSURE CONTROLS - PERSONAL PROTECTION

EXPOSURE LIMITS/CONTROL PARAMETERS:

Ventilation and Engineering Controls: Use with adequate ventilation to ensure exposure levels are maintained below the limits provided below.

Occupational/Workplace Exposure Limits/Guidelines:

Chemical Name	CAS #	Guideline	Value
Calcium Carbonate, Natural	1317-65-3	OSHA PEL TWA NIOSH REL TWA	15 mg/m ³ total dust 5 mg/m ³ respirable fraction 10 mg/m ³ total dust 5 mg/m ³ respirable fraction
Carbon Black	1333-86-4	ACGIH TLV TWA OSHA PEL TWA NIOSH REL TWA DFG MAK TWA	3.5 mg/m ³ (inhalable fraction) 3.5 mg/m ³ 3.5 mg/m ³ (0.1 in the presence of PAHs, as PAHs: 10-hr TWA) As inhalable dust
Proprietary Red and Brown Iron Pigment		ACGIH TLV TWA OSHA PEL TWA NIOSH REL TWA NIOSH IDLH DFG MAK TWA	5 mg/m ³ respirable fraction 10 mg/m ³ fume 5 mg/m ³ dust and fume, as Fe 2500 mg/m ³ , as Fe With the exception of iron oxides which are not biologically available
Proprietary Crosslinker		NE	NE
Octamethylcyclotetrasiloxane	556-67-2	NE	NE
Proprietary Polydimethyl Siloxane Mixture		NE	NE
Proprietary Mineral Spirits		ACGIH TLV TWA OSHA PEL TWA NIOSH REL TWA NIOSH REL STEL	525 mg/m ³ 2900 mg/m ³ 350 mg/m ³ 1800 mg/m ³ (15 min.)
Titanium Dioxide	13463-67-7	ACGIH TLV TWA OSHA PEL TWA NIOSH REL	10 mg/m ³ NIC: 1 mg/m ³ 15 mg/m ³ total dust Lowest feasible concentration (LOQ 0.2 mg/m ³)
Proprietary Amine Cross-Linker Exposure limits given are for diethylenetriamine		ACGIH TLV TWA NIOSH REL TWA DFG MAK	4.2 mg/m ³ (skin) 4 mg/m ³ (skin) Danger of sensitization of the Skin
The following compounds are possible reaction products from contact with water and during curing:			
Methyl Ethyl Ketoxime	96-29-7	DFG MAK TWA AIHA WEEL TWA	Skin, Danger of Sensitization of the Skin 10 ppm (DSEN: May cause dermal sensitization)

NE = Not Established. See Section 16 for Definitions of Terms Used.

Biological Exposure Indices (BEIs): Currently, no BEI's have been established for components of this product.

PERSONAL PROTECTIVE EQUIPMENT (PPE): *The following information on appropriate Personal Protective Equipment is provided to assist employers in complying with OSHA regulations found in 29 CFR Subpart I (beginning at 1910.132, including the Respiratory Protection Standard (29 CFR 1910.134), Eye Protection Standard 29 CFR 1910.13, the Hand Protection Standard 29 CFR 1910.138, and the Foot Protection Standard 29 CFR 1910.136), equivalent standards of Canada (including the Canadian CSA Respiratory Standard Z94.4-93-02, the CSA Eye Protection Standard Z94.3-M1982, Industrial Eye and Face Protectors and the Canadian CSA Foot Protection Standard Z195-M1984, Protective Footwear). Please reference applicable regulations and standards for relevant details.*

Eye/Face Protection: Use approved safety goggles or safety glasses. If necessary, refer to appropriate regulations and standards.

Skin Protection: Wear chemical impervious gloves (e.g., Nitrile or Neoprene). Use triple gloves for spill response. If necessary, refer to appropriate regulations and standards.

Body Protection: Use body protection appropriate for task (e.g., lab coat, coveralls, Tyvek suit). If necessary, refer to the OSHA Technical Manual (Section VII: Personal Protective Equipment) or appropriate Standards of Canada. If a hazard of injury to the feet exists due to falling objects, rolling objects, where objects may pierce the soles of the feet or where employee's feet may be exposed to electrical hazards, use foot protection, as described in appropriate regulations and standards.

Respiratory Protection: If mists or sprays from this product are created during use, use appropriate respiratory protection. If necessary, use only respiratory protection authorized in appropriate regulations. Oxygen levels below 19.5% are considered IDLH by OSHA. In such atmospheres, use of a full-facepiece pressure/demand SCBA or a full facepiece, supplied air respirator with auxiliary self-contained air supply is required under appropriate regulations and standards.

9. PHYSICAL and CHEMICAL PROPERTIES

FORM: Smooth paste.

MOLECULAR WEIGHT: Mixture.

ODOR: Mildly medicinal.

SPECIFIC GRAVITY: 1.1-1.3

RELATIVE VAPOR DENSITY (air = 1): Heavier than air.

SOLUBILITY IN WATER: Insoluble.

MELTING/FREEZING POINT: Not available.

VOC (less water and exempt): < 100 g/L

FLASH POINT: > 140°C (> 300°F)

pH: Not available.

FLAMMABLE LIMITS (in air by volume, %): Lower: Not established; Upper: Not established.

COEFFICIENT OF OIL/WATER DISTRIBUTION (PARTITION COEFFICIENT): Not established.

COLORS: Black, Tru-White, Aluminum Stone, Translucent, and Bronze

MOLECULAR FORMULA: Mixture.

ODOR THRESHOLD: Not available.

VAPOR PRESSURE, mm Hg @ 20°C: Not established.

EVAPORATION RATE (BuAc = 1): < 1

OTHER SOLUBILITIES: Not available.

BOILING POINT: Not established.

WEIGHT % VOC: ~ 10%

AUTOIGNITION TEMPERATURE: Not established.

9. PHYSICAL and CHEMICAL PROPERTIES (Continued)

HOW TO DETECT THIS SUBSTANCE (IDENTIFYING PROPERTIES): The appearance of this product may act as an identifying property in the event of an accidental release.

10. STABILITY and REACTIVITY

CHEMICAL STABILITY: Stable under normal circumstances of use and handling. Methylethyl Ketoxime is generated during curing.

CONDITIONS TO AVOID: Avoid contact with incompatible chemicals and exposure to extreme temperatures.

INCOMPATIBLE MATERIALS: This product is not compatible with strong acids and oxidizers and may have some compatibility with aluminum, ammonium salts and mercury/hydrogen mixtures.

HAZARDOUS DECOMPOSITION PRODUCTS: **Combustion:** Thermal decomposition of this product can generate dusts, irritating fumes, and toxic gases (e.g., carbon, iron, aluminum, titanium, nitrogen and silicone oxides, silicon carbides, formaldehyde, various hydrocarbons). **Hydrolysis:** Methylethyl ketoxime.

POSSIBILITY OF HAZARDOUS REACTIONS/POLYMERIZATION: This product is not expected to undergo hazardous polymerization, decomposition, condensation, or self-reactivity.

11. TOXICOLOGICAL INFORMATION

POTENTIAL HEALTH EFFECTS: The most significant routes of occupational exposure are inhalation and contact with skin and eyes.

The symptoms of exposure to this product are as follows:

Contact with Skin or Eyes: Contact may mildly irritate the skin and cause redness and discomfort. Prolonged or repeated skin contact may cause dermatitis (dry, red skin). Eye contact may cause redness, pain, and tearing.

Skin Absorption: The components of this product are not known to be absorbed through intact skin. Skin contact may cause sensitization and allergic reaction in susceptible individuals. Symptoms may include redness, itching and rash.

Ingestion: If the product is swallowed, it may mildly irritate the mouth, throat, and other tissues of the gastro-intestinal system and may cause nausea, vomiting, and diarrhea.

Inhalation: Exposure to vapors of this product generated during curing, or dusts of this product generated during use after curing may mildly irritate the respiratory tract and cause coughing and sneezing. Vapors or fumes when used in an enclosed space, if heated or during curing may cause irritation of the respiratory system. Symptoms include nose irritation, dry or sore or burning throat, runny nose, shortness of breath, dizziness, incoordination.

Injection: Accidental injection of this product (e.g. puncture with a contaminated object) may cause burning, redness, and swelling in addition to the wound.

Target Organs: **Acute:** Skin, eyes, central nervous system. **Chronic:** Skin, fertility.

Chronic Effects: Prolonged or repeated skin contact may cause dermatitis (dry, red skin), sensitization to the skin or adverse liver or kidney effects.

TOXICITY DATA: There are currently no toxicity data available for this product; the following toxicology information is available for components greater than 1% in concentration. Contact Pecora for additional information.

PROPRIETARY CROSSLINKER:

LD₅₀ (Oral-Rat) > 8000 mg/kg

LD₅₀ (Dermal-Rat) > 4000 mg/kg

LC₅₀ (Inhalation-Rat) > 8000 mg/m³, 4 hours

CALCIUM CARBONATE, NATURAL:

TDLo (Intravenous-Rat) 30 mg/kg: Vascular: BP lowering not characterized in autonomic section; Lungs, Thorax, or Respiration: changes in lung weight; Blood: other changes

TCLo (Inhalation-Rat) 84 mg/m³/4 hours/40 weeks-intermittent: Lungs, Thorax, or Respiration: fibrosis (interstitial); Liver: other changes; Kidney/Ureter/Bladder: other changes

TCLo (Inhalation-Rat) 250 mg/m³/2 hours/24 weeks-intermittent: Lungs, Thorax, or Respiration: fibrosis, focal (pneumoconiosis)

FUMED SILICA:

LD₅₀ (Oral-Rat) 3160 mg/kg

LD₅₀ (Intravenous-Rat) 15 mg/kg: Lungs, Thorax, or Respiration: acute pulmonary edema

TCLo (Inhalation-Rat) 154 mg/m³/6 hours/4 weeks-intermittent: Lungs, Thorax, or Respiration: structural or functional change in trachea or bronchi; Biochemical: Enzyme inhibition, induction, or change in blood or tissue levels: dehydrogenases, Metabolism (Intermediary): other proteins

TCLo (Inhalation-Rat) 5.41 mg/m³/5 days-intermittent: Lungs, Thorax, or Respiration: other changes, changes in lung weight; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TCLo (Inhalation-Rat) 1.39 mg/m³/5 days-intermittent: Nutritional and Gross Metabolic: weight loss or decreased weight gain

TDLo (Intratracheal-Mouse) 96.77 mg/kg: Lungs, Thorax, or Respiration: acute pulmonary edema, other changes; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TDLo (Intratracheal-Mouse) 50 mg/kg: Lungs, Thorax, or Respiration: changes in lung weight

TDLo (Intratracheal-Mouse) 2 mg/kg; 2 mg/kg: Lungs, Thorax, or Respiration: fibrosis, focal (pneumoconiosis), other changes; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TDLo (Intratracheal-Mouse) 2 mg/kg: Lungs, Thorax, or Respiration: other changes; Biochemical: Enzyme inhibition, induction, or change in blood or tissue levels: peptidases

TDLo (Intratracheal-Mouse) 2 mg/kg: Lungs, Thorax, or Respiration: fibrosing alveolitis; Biochemical: Enzyme inhibition, induction, or change in blood or tissue levels: peptidases, Metabolism (Intermediary): effect on inflammation or mediation of inflammation

LDLo (Intratracheal-Rat) 50 mg/kg

LDLo (Intratracheal-Rat) 10 mg/kg

LDLo (Intratracheal-Mouse) 96.77 mg/kg: Lungs, Thorax, or Respiration: acute pulmonary edema, dyspnea, other changes

MINERAL SPIRITS:

Standard Draize Test (Eye-Human) 100 ppm: Mild

Standard Draize Test (Eye-Rabbit) 500 mg/24 hours: Moderate

LC₅₀ (Inhalation-Rat) > 1400 ppm/8 hours

LD (Oral-Rat) > 5 gm/kg: Behavioral: somnolence (general depressed activity)

MINERAL SPIRITS (continued):

LD (Skin-Rabbit) > 3 gm/kg

LC (Inhalation-Rat) > 5500 mg/m³/4 hours: Behavioral: somnolence (general depressed activity)

LC (Inhalation-Dog) > 8 gm/m³/8 hours-continuous: Behavioral: tremor, convulsions or effect on seizure threshold

LCLo (Inhalation-Cat) 1700 ppm/7 hours: Behavioral: tremor, convulsions or effect on seizure threshold

LCLo (Inhalation-Dog) 8000 mg/m³/3 hours.....Behavioral: alteration of classical conditioning

TCLo (Inhalation-Rat) 330 ppm/65 days-intermittent: Kidney/Ureter/Bladder: changes in tubules (including acute renal failure, acute tubular necrosis); Blood: other changes

TCLo (Inhalation-Rat) 480 mg/m³/65 days-intermittent: Blood: normocytic anemia

TCLo (Inhalation-Rat) 1100 mg/m³/65 days-intermittent: Kidney/Ureter/Bladder: renal function tests depressed; Blood: normocytic anemia

TDLo (Oral-Rat) 10 mg/kg: Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TDLo (Skin-Rabbit) 2 gm/kg/4 weeks-intermittent: Skin and Appendages: dermatitis, other (after systemic exposure)

PROPRIETARY POLYDIMETHYL SILOXANE:

LD₅₀ (Oral-Rat) 3160 mg/kg

LD₅₀ (Intravenous-Rat) 15 mg/kg: Lungs, Thorax, or Respiration: acute pulmonary edema

TCLo (Inhalation-Rat) 154 mg/m³/6 hours/4 weeks-intermittent: Lungs, Thorax, or Respiration: structural or functional change in trachea or bronchi; Biochemical: Enzyme inhibition, induction, or change in blood or tissue levels: dehydrogenases, Metabolism (Intermediary): other proteins

TCLo (Inhalation-Rat) 5.41 mg/m³/5 days-intermittent: Lungs, Thorax, or Respiration: other changes, changes in lung weight; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TCLo (Inhalation-Rat) 1.39 mg/m³/5 days-intermittent: Nutritional and Gross Metabolic: weight loss or decreased weight gain

TDLo (Intratracheal-Mouse) 96.77 mg/kg: Lungs, Thorax, or Respiration: acute pulmonary edema, other changes; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TDLo (Intratracheal-Mouse) 50 mg/kg: Lungs, Thorax, or Respiration: changes in lung weight

TDLo (Intratracheal-Mouse) 2 mg/kg; 2 mg/kg: Lungs, Thorax, or Respiration: fibrosis, focal (pneumoconiosis), other changes; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation

TDLo (Intratracheal-Mouse) 2 mg/kg: Lungs, Thorax, or Respiration: other changes; Biochemical: Enzyme inhibition, induction, or change in blood or tissue levels: peptidases

TDLo (Intratracheal-Mouse) 2 mg/kg: Lungs, Thorax, or Respiration: fibrosing alveolitis; Biochemical: Enzyme inhibition, induction, or change in blood or tissue levels: peptidases, Metabolism (Intermediary): effect on inflammation or mediation of inflammation

LDLo (Intratracheal-Rat) 50 mg/kg

LDLo (Intratracheal-Rat) 10 mg/kg

LDLo (Intratracheal-Mouse) 96.77 mg/kg: Lungs, Thorax, or Respiration: acute pulmonary edema, dyspnea, other changes

11. TOXICOLOGICAL INFORMATION (Continued)

TOXICITY DATA (continued):

TITANIUM DIOXIDE:

Standard Draize Test (Skin-Human) 300 µg/3 days-intermittent: Mild
 TC (Inhalation-Rat) 10 mg/m³/18 hours/2 years-intermittent: Tumorigenic; carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration; tumors
 LD (Intratracheal-Rat) > 100 µg/kg; Lungs, Thorax, or Respiration: structural or functional change in trachea or bronchi; Blood: changes in serum composition (e.g. TP, bilirubin, cholesterol); Biochemical: Enzyme inhibition, induction, or change in blood or tissue levels: other Enzymes
 TD (Intramuscular-Rat) 260 mg/kg/84 weeks-intermittent: Tumorigenic: equivocal tumorigenic agent by RTECS criteria; Blood: lymphoma, including Hodgkin's disease; Tumorigenic: tumors at site of application
 TDLo (Oral-Rat) 60 gm/kg: Gastrointestinal: hypermotility, diarrhea, other changes
 TDLo (Intramuscular-Rat) 360 mg/kg/2 years-intermittent: Tumorigenic: neoplastic by RTECS criteria; Blood: lymphoma, including Hodgkin's disease; Tumorigenic: tumors at site of application
 TDLo (Intratracheal-Rat) 1.25 mg/kg: Vascular: regional or general arteriolar constriction; Lungs, Thorax, or Respiration: other changes
 TDLo (Intratracheal-Rat) 1.6 mg/kg; Lungs, Thorax, or Respiration: other changes
 TDLo (Intratracheal-Rat) 5 mg/kg; Lungs, Thorax, or Respiration: other changes; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation
 TDLo (Intratracheal-Mouse) 100 mg/kg: Tumorigenic: increased incidence of tumors in susceptible strains
 TCLo (Inhalation-Rat) 1 mg/kg; Lungs, Thorax, or Respiration: other changes; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation
 TCLo (Inhalation-Rat) 250 mg/m³/6 hours/4 weeks-intermittent: Lungs, Thorax, or Respiration: chronic pulmonary edema, other changes
 TCLo (Inhalation-Rat) 50 mg/m³/6 hours/13 weeks-intermittent: Lungs, Thorax, or Respiration: structural or functional change in trachea or bronchi
 TCLo (Inhalation-Rat) 10 mg/m³/6 hours/13 weeks-intermittent: Lungs, Thorax, or Respiration: fibrosis (interstitial), other changes; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation
 TCLo (Inhalation-Rat) 10 mg/m³/13 weeks-intermittent: Lungs, Thorax, or Respiration: other changes; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation
 TCLo (Inhalation-Rat) 50 mg/m³/13 weeks-intermittent: Lungs, Thorax, or Respiration: sputum; Blood: changes in cell count (unspecified); Biochemical: Enzyme inhibition, induction, or change in blood or tissue levels: dehydrogenases

TITANIUM DIOXIDE (continued):

TCLo (Inhalation-Rat) 250 mg/m³/13 weeks-intermittent: Lungs, Thorax, or Respiration: other changes; Blood: changes in cell count (unspecified); Biochemical: Enzyme inhibition, induction, or change in blood or tissue levels: dehydrogenases
 TCLo (Inhalation-Rat) 274 mg/m³/5 days-intermittent: Lungs, Thorax, or Respiration: changes in lung weight; Biochemical: Enzyme inhibition, induction, or change in blood or tissue levels: multiple enzyme effects, Metabolism (Intermediary): effect on inflammation or mediation of inflammation
 TCLo (Inhalation-Rat) 250 mg/m³/6 hours/2 years-intermittent: Tumorigenic: carcinogenic by RTECS criteria; Lungs, Thorax, or Respiration: tumors
 TCLo (Inhalation-Mouse) 10 mg/m³/6 hours/13 weeks-intermittent: Lungs, Thorax, or Respiration: other changes; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation
 TCLo (Inhalation-Mouse) 10 mg/m³/6 hours/13 weeks-intermittent: Lungs, Thorax, or Respiration: structural or functional change in trachea or bronchi
 TCLo (Inhalation-Mouse) 10 mg/m³/13 weeks-intermittent: Lungs, Thorax, or Respiration: other changes; Biochemical: Metabolism (Intermediary): effect on inflammation or mediation of inflammation
 TCLo (Inhalation-Mouse) 50 mg/m³/13 weeks-intermittent: Lungs, Thorax, or Respiration: sputum; Biochemical: Enzyme inhibition, induction, or change in blood or tissue levels: dehydrogenases
 TCLo (Inhalation-Mouse) 250 mg/m³/13 weeks-intermittent: Lungs, Thorax, or Respiration: sputum; Blood: changes in cell count (unspecified); Biochemical: Enzyme inhibition, induction, or change in blood or tissue levels: dehydrogenases
 TCLo (Inhalation-Hamster) 250 mg/m³/13 weeks-intermittent: Lungs, Thorax, or Respiration: sputum; Blood: changes in cell count (unspecified); Biochemical: Enzyme inhibition, induction, or change in blood or tissue levels: dehydrogenases
 TCLo (Inhalation-Hamster) 250 mg/m³/6 hours/13 weeks-intermittent: Lungs, Thorax, or Respiration: structural or functional change in trachea or bronchi
 DNA Damage (Human Lung) 100 µg/plate
 DNA Damage (Human Lung) 20 µg/disk/4 hours
 Sister Chromatid Exchange (Human Lymphocyte) 2 µmol/L/72 hours
 Micronucleus Test (Human Lymphocyte) 5 µmol/L/72 hours
 Micronucleus Test (Intraperitoneal-Mouse) 3 gm/kg/3 days-continuous
 Micronucleus Test (Hamster Ovary) 5 µmol/L
 DNA Inhibition (Hamster Lung) 500 mg/L
 Sister Chromatid Exchange (Hamster Ovary) 1 µmol/L

CARCINOGENIC POTENTIAL: The following table summarizes the carcinogenicity listing for the components of this product. "NO" indicates that the substance is not considered to be or suspected to be a carcinogen by the listed agency, see section 16 for definitions of other ratings.

CHEMICAL	EPA	IARC	NTP	NIOSH	ACGIH	OSHA	PROP 65
Calcium Carbonate (Natural)	No	No	No	No	No	No	No
Carbon Black	No	2B	No	Ca	No	No	Yes (airborne, unbound particles of respirable size)
Iron Oxide	No	3	No	No	A4	No	No
Mineral Spirits	No	No	No	No	No	No	No
Octamethylcyclotetrasiloxane	No	No	No	No	No	No	No
Proprietary Crosslinker	No	No	No	No	No	No	No
Fumed Silicon Dioxide	No	No	No	No	No	No	No
Titanium Dioxide	2B	No	No	Ca	A4	No	Yes (airborne unbound particles of respirable size)
The following is a compound from reaction with water and generated during curing:							
Methyl Ethyl Ketoxime	No	No	No	No	No	No	No

IARC 1: Carcinogenic to Humans. IARC-2B: Possibly Carcinogenic to Humans. IARC-3: Possibly Carcinogenic to Humans. NTP-K: Known to Be a Human Carcinogen. NIOSH-Ca: Potential Occupational Carcinogen, with No Further Categorization. ACGIH TLV-A2: Suspected Human Carcinogen. ACGIH TLV-A4: Not Classifiable as a Human Carcinogen.

IRRITANCY OF PRODUCT: This product may mildly irritate contaminated tissue, especially if contact is prolonged. Eye irritation may be more pronounced.

SENSITIZATION TO THE PRODUCT: This product may cause skin sensitization and allergic reaction in susceptible individuals due to the Phenyl Oximino Silane component.

TOXICOLOGICAL SYNERGISTIC PRODUCTS: None known.

REPRODUCTIVE TOXICITY INFORMATION: This product has not been tested for reproductive toxicity. Information for some components is given, as follows.

Mutagenicity/Embryotoxicity/ Teratogenicity/Reproductive Toxicity: In a developmental and reproductive toxicity study involving female rats and the trace Octamethylcyclotetrasiloxane component, a significant percentage of female rats exposed experienced reduction of proestrus LH levels, a reduction of ovulation and decreased FSH hormone levels.

BIOLOGICAL EXPOSURE INDICES (BEIs): There are no BEI's established for any component of this product at this time.

12. ECOLOGICAL INFORMATION

ALL WORK PRACTICES MUST BE AIMED AT ELIMINATING ENVIRONMENTAL CONTAMINATION.

MOBILITY: This product has not been tested for mobility in soil.

PERSISTENCE AND BIODEGRADABILITY: This product has not been tested for persistence or biodegradability.

BIO-ACCUMULATION POTENTIAL: This product has not been tested for bio-accumulation potential.

ECOTOXICITY: This product has not been tested for aquatic or animal toxicity. Data are available for the trace Octamethylcyclotetrasiloxane component.

12. ECOLOGICAL INFORMATION (Continued)

ECOTOXICITY (continued): Although no data is available, under the Global Harmonization Standard, the Phenyl Oximino Silane component is classified as having chronic aquatic toxicity.

OCTAMETHYLCYCLOTETRASILOXANE:

LC₅₀ (*Oncorhynchus mykiss* Rainbow trout) 14 days = 10 µg/L

LC₅₀ (*Lepomis macrochirus* Bluegill) 96 hours = > 1000 mg/L

LC₅₀ (*Brachydanio rerio* Zebra danio) 96 hours = >500 mg/L

OTHER ADVERSE EFFECTS: This material is not expected to have any ozone depletion potential.

ENVIRONMENTAL EXPOSURE CONTROLS: Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways.

13. DISPOSAL CONSIDERATIONS

PREPARING WASTES FOR DISPOSAL: As supplied, this product would not be a hazardous waste as defined by U.S. federal regulation (40 CFR 261) if discarded or disposed. State and local regulations may differ from federal regulations. The generator of the waste is responsible for proper waste determination and management.

U.S. EPA WASTE NUMBER: Not applicable.

14. TRANSPORTATION INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION: This product is NOT classified as Dangerous Goods, per U.S. DOT regulations, under 49 CFR 172.101.

TRANSPORT CANADA TRANSPORTATION OF DANGEROUS GOODS REGULATIONS: This product is NOT classified as Dangerous Goods, per regulations of Transport Canada.

INTERNATIONAL AIR TRANSPORT ASSOCIATION SHIPPING INFORMATION (IATA): This product is NOT classified as dangerous goods, per the International Air Transport Association.

INTERNATIONAL MARITIME ORGANIZATION SHIPPING INFORMATION (IMO): This product is not classified as dangerous goods, per the International Maritime Organization.

15. REGULATORY INFORMATION

U.S. REGULATIONS:

U.S. SARA Reporting Requirements: No component of this product is subject to the reporting requirements of Sections 302, 304, and 313 of Title III of the Superfund Amendments and Reauthorization Act.

U.S. SARA Hazard Categories (Section 311/312, 40 CFR 370-21): ACUTE: Yes; CHRONIC: Yes; FIRE: No; REACTIVE: No; SUDDEN RELEASE: No

U.S. TSCA Inventory Status: All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

U.S. CERCLA Reportable Quantity (RQ): Not applicable.

U.S. Clean Air Act (CA 112r) Threshold Quantity (TQ): Not applicable.

Other U.S. Federal Regulations: Not applicable.

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65): This product contains Titanium Dioxide and Carbon Black, suspect carcinogens which are on the list, by the route of inhalation. Due to the form of the product, the Proposition 65 warning is not applicable to these compounds in this product.

CANADIAN REGULATIONS:

Canadian DSL/NDSL Inventory Status: The components of this product are listed on the DSL Inventory.

Canadian Environmental Protection Act (CEPA) Priorities Substances Lists: No component of this product is on the CEPA Priorities Substances Lists.

Canadian WHMIS (HPR-GHS) 2015 Classification and Symbols: See Section 16 in Classification and Symbols under HPR-GHS 2015.

MEXICAN REGULATIONS:

Mexican Workplace Regulations (NOM-018-STPS-2000): This product is not classified as hazardous.

16. OTHER INFORMATION

WARNINGS (per ANSI Z129.1): WARNING! CONTAINS TRACE COMPONENT THAT MAY CAUSE ADVERSE EFFECTS ON FERTILITY, BASED ON ANIMAL DATA. MAY CAUSE EYE, SKIN, AND RESPIRATORY TRACT IRRITATION, ESPECIALLY IF EXPOSURE IS PROLONGED. MAY BE HARMFUL IF ACCIDENTALLY INGESTED. MAY CAUSE SKIN SENSITIZATION AND ALLERGIC REACTION IN SUSCEPTIBLE INDIVIDUALS. COMBUSTIBLE – CAN IGNITE IF EXPOSED TO DIRECT FLAME. CONTAINS COMPOUNDS ACUTELY AND CHRONICALLY TOXIC TO AQUATIC ORGANISMS. Avoid contact with eyes, skin, and clothing. Avoid breathing fumes, dusts, vapors or mist. Do not taste or swallow. Wash thoroughly after handling. Keep container tightly closed. Use only with adequate ventilation. Keep away from heat and flame. Wear gloves, eye protection, respiratory protection, and appropriate body protection. **FIRST-AID:** In case of contact, immediately flush skin and eyes with plenty of water. Remove contaminated clothing and shoes. Get medical attention if irritation develops or persists. If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If swallowed, do not induce vomiting. Get medical attention. **IN CASE OF FIRE:** Use water fog, foam, dry chemical, or CO₂. **IN CASE OF SPILL:** Absorb spilled product with polypads or other suitable absorbing material. Place all spill residue in an appropriate container and seal. Dispose of in accordance with U.S. Federal, State, and local hazardous waste disposal regulations and those of Canada.

16. OTHER INFORMATION (Continued)

GLOBAL HARMONIZATION LABELING AND CLASSIFICATION: Classified in accordance with Global Harmonization Standard under U.S. OSHA Hazard Communication Standard, Canadian WHMIS HPR-GHS 2015.

Classification: Reproductive Toxicity Category 2, Acute Oral Toxicity Category 5, Eye Irritation Category 2B, Skin Irritation Category 3, Skin Sensitization Category 1, Aquatic Chronic Toxicity Category 4

Signal Word: Warning

Hazard Statements: H361f: Suspected of damaging fertility. H303: May be harmful if ingested. H316: Causes mild skin irritation. H320: Causes eye irritation. H317: May cause an allergic skin reaction. H413: May be harmful to aquatic life with long-lasting effects.

Precautionary Statements:

Prevention: P201: Obtain special instructions before use. P202: Do not handle until all safety precautions have been read and understood. P261: Avoid breathing fume. P264: Wash thoroughly after handling. P272: Contaminated work clothing should not be allowed out of the workplace. P273: Avoid release to the environment. P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response: P308 + P313: IF exposed or concerned: Get medical advice/attention. P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. P337 + P313: If eye irritation persists: Get medical advice/attention. P302 + P352: IF ON SKIN: Wash with plenty of soap and water. P333 + P313: If skin irritation or rash occurs: Get medical advice/attention. P362 + P364: Take off contaminated clothing and wash it before reuse. P321: Specific treatment (remove from exposure and treat symptoms).

Storage: P405: Store locked up.

Disposal: P501: Dispose of contents/containers in accordance with all local, regional, national and international regulations.

Hazard Symbols/Pictogram: GHS07, GHS08

DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

The information presented in this Material Safety Data Sheet is presented in good faith based on data believed to be accurate as of the date this Material Safety Data Sheet was prepared. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OR COMPLETENESS OF THE INFORMATION PROVIDED ABOVE, THE RESULTS TO BE OBTAINED FROM THE USE OF THIS INFORMATION OR THE PRODUCT, THE SAFETY OF THIS PRODUCT, OR THE HAZARDS RELATED TO ITS USE. In no case shall the descriptions, information, data or designs provided be considered a part of our terms and conditions of sale.

All materials may present hazards and should be used with caution. Because many factors may affect processing or application/use, we recommend that you make tests to determine the suitability of a product for your particular purpose prior to use. No responsibility is assumed for any damage or injury resulting from abnormal use or from any failure to adhere to recommended practices or applicable federal, state, or local laws or regulations. The information provided above, and the product, are furnished on the condition that the person receiving them shall make their own determination as to the suitability of the product for their particular purpose and on the condition that they assume the risk of their use. In addition, no authorization is given nor implied to practice any patented invention without a license.

REFERENCES AND DATA SOURCES: Contact the supplier for information.

METHODS OF EVALUATING INFORMATION FOR THE PURPOSE OF CLASSIFICATION: Bridging principles were used to classify this product.

REVISION DETAILS: July 2012: Up-date and revise entire MSDS to include current GHS requirements. December 2015: Correction of classification. March 2017: Up-date due to change in formulation and up-date to most current format and regulations.

DATE OF PRINTING

March 21, 2017

DEFINITIONS OF TERMS

A large number of abbreviations and acronyms appear on a MSDS. Some of these, which are commonly used, include the following:

KEY ACRONYMS:

CHEMTREC: Chemical Transportation Emergency Center, a 24-hour emergency information and/or emergency assistance to emergency responders.

CEILING LEVEL: The concentration that shall not be exceeded during any part of the working exposure.

DFG MAKs: Federal Republic of Germany Maximum Concentration Values in the workplace. Exposure limits are given as TWA (Time-Weighted Average) or PEAK (short-term exposure) values.

DFG MAK Germ Cell Mutagen Categories: **1:** Germ cell mutagens that have been shown to increase the mutant frequency in the progeny of exposed humans. **2:** Germ cell mutagens that have been shown to increase the mutant frequency in the progeny of exposed mammals. **3A:** Substances that have been shown to induce genetic damage in germ cells of human of animals, or which produce mutagenic effects in somatic cells of mammals *in vivo* and have been shown to reach the germ cells in an active form. **3B:** Substances that are suspected of being germ cell mutagens because of their genotoxic effects in mammalian somatic cell *in vivo*; in exceptional cases, substances for which there are no *in vivo* data, but that are clearly mutagenic *in vitro* and structurally related to known *in vivo* mutagens. **4:** Not applicable (Category 4 carcinogenic substances are those with non-genotoxic mechanisms of action. By definition, germ cell mutagens are genotoxic. Therefore, a Category 4 for germ cell mutagens cannot apply. At some time in the future, it is conceivable that a Category 4 could be established for genotoxic substances with primary targets other than DNA [e.g. purely aneugenic substances] if research results make this seem sensible.) **5:** Germ cell mutagens, the potency of which is considered to be so low that, provided the MAK value is observed, their contribution to genetic risk for humans is expected not to be significant.

DFG MAK Pregnancy Risk Group Classification: **Group A:** A risk of damage to the developing embryo or fetus has been unequivocally demonstrated. Exposure of pregnant women can lead to damage of the developing organism, even when MAK and BAT (Biological Tolerance Value for Working Materials) values are observed. **Group B:** Currently available information indicates a risk of damage to the developing embryo or fetus must be considered to be probable. Damage to the developing organism cannot be excluded when pregnant women are exposed, even when MAK and BAT values are observed. **Group C:** There is no reason to fear a risk of damage to the developing embryo or fetus when MAK and BAT values are observed. **Group D:** Classification in one of the groups A-C is not yet possible because, although the data available may indicate a trend, they are not sufficient for final evaluation.

IDLH: Immediately Dangerous to Life and Health. This level represents a concentration from which one can escape within 30-minutes without suffering escape-preventing or permanent injury.

LOQ: Limit of Quantitation.

NE: Not Established. When no exposure guidelines are established, an entry of NE is made for reference.

NIC: Notice of Intended Change.

NIOSH CEILING: The exposure that shall not be exceeded during any part of the workday. If instantaneous monitoring is not feasible, the ceiling shall be assumed as a 15-minute TWA exposure (unless otherwise specified) that shall not be exceeded at any time during a workday.

NIOSH RELs: NIOSH's Recommended Exposure Limits.

KEY ACRONYMS (continued):

PEL: OSHA's Permissible Exposure Limits. This exposure value means exactly the same as a TLV, except that it is enforceable by OSHA. The OSHA Permissible Exposure Limits are based in the 1989 PELs and the June, 1993 Air Contaminants Rule (Federal Register: 58: 35338-35351 and 58: 40191). Both the current PELs and the vacated PELs are indicated. The phrase, "Vacated 1989 PEL" is placed next to the PEL that was vacated by Court Order.

SKIN: Used when there is a danger of cutaneous absorption.

STEL: Short Term Exposure Limit, usually a 15-minute time-weighted average (TWA) exposure that shall not be exceeded at any time during a workday, even if the 8-hr TWA is within the TLV-TWA, PEL-TWA or REL-TWA.

TLV: Threshold Limit Value. An airborne concentration of a substance that represents conditions under which it is generally believed that nearly all workers may be repeatedly exposed without adverse effect. The duration must be considered, including the 8-hour.

TWA: Time Weighted Average exposure concentration for a conventional 8-hr (TLV, PEL) or up to a 10-hr (REL) workday and a 40-hr workweek.

WEEL: Workplace Environmental Exposure Limits from the AIHA.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD RATINGS:

This rating system was developed by the National Paint and Coating Association and has been adopted by industry to identify the degree of chemical hazards.

HEALTH HAZARD: 0 Minimal Hazard: No significant health risk, irritation of skin or eyes not anticipated. *Skin Irritation:* Essentially non-irritating. Mechanical irritation may occur. *PII or Draize = 0. Eye Irritation:* Essentially non-irritating, minimal effects clearing in < 24 hours. Mechanical irritation may occur. *Draize = 0. Oral Toxicity LD₅₀ Rat > 5000 mg/kg. Dermal Toxicity LD₅₀ Rat or Rabbit > 2000 mg/kg. Inhalation Toxicity 4-hrs LC₅₀ Rat > 20 mg/L. 1 Slight Hazard:* Minor reversible injury may occur; may irritate the stomach if swallowed; may defat the skin and exacerbate existing dermatitis. *Skin Irritation:* Slightly or mildly irritating. *PII or Draize > 0 < 5. Eye Irritation:* Slightly to mildly irritating, but reversible within 7 days. *Draize > 0 ≤ 25. Oral Toxicity LD₅₀ Rat > 500-5000 mg/kg. Dermal Toxicity LD₅₀ Rat or Rabbit > 1000-2000 mg/kg. Inhalation Toxicity LC₅₀ 4-hrs Rat > 2-20 mg/L. 2 Moderate Hazard:* Temporary or transitory injury may occur; prolonged exposure may affect the CNS. *Skin Irritation:* Moderately irritating; primary irritant; sensitizer. *PII or Draize ≥ 5, with no destruction of dermal tissue. Eye Irritation:* Moderately to severely irritating; reversible corneal opacity; corneal involvement or irritation clearing in 8-21 days. *Draize = 26-100, with reversible effects. Oral Toxicity LD₅₀ Rat > 50-500 mg/kg. Dermal Toxicity LD₅₀ Rat or Rabbit > 200-1000 mg/kg. Inhalation Toxicity LC₅₀ 4-hrs Rat > 0.5-2 mg/L. 3 Serious Hazard:* Major injury likely unless prompt action is taken and medical treatment is given; high level of toxicity; corrosive. *Skin Irritation:* Severely irritating and/or corrosive; may cause destruction of dermal tissue, skin burns, and dermal necrosis. *PII or Draize > 5-8, with destruction of tissue. Eye Irritation:* Corrosive, irreversible destruction of ocular tissue; corneal involvement or irritation persisting for more than 21 days. *Draize > 80 with effects irreversible in 21 days. Oral Toxicity LD₅₀ Rat > 1-50 mg/kg. Dermal Toxicity LD₅₀ Rat or Rabbit > 20-200 mg/kg. Inhalation Toxicity LC₅₀ 4-hrs Rat > 0.05-0.5 mg/L.*

DEFINITIONS OF TERMS (Continued)

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD RATINGS (continued):

HEALTH HAZARD (continued): 4 Severe Hazard: Life-threatening; major or permanent damage may result from single or repeated exposure; extremely toxic; irreversible injury may result from brief contact. *Skin Irritation:* Not appropriate. Do not rate as a 4, based on skin irritation alone. *Eye Irritation:* Not appropriate. Do not rate as a 4, based on eye irritation alone. *Oral Toxicity LD₅₀ Rat:* ≤ 1 mg/kg. *Dermal Toxicity LD₅₀ Rat or Rabbit:* ≤ 20 mg/kg. *Inhalation Toxicity LC₅₀ 4-hrs Rat:* ≤ 0.05 mg/L.

FLAMMABILITY HAZARD: 0 Minimal Hazard: Materials that will not burn in air when exposure to a temperature of 815.5°C (1500°F) for a period of 5 minutes. **1 Slight Hazard:** Materials that must be pre-heated before ignition can occur. Material requires considerable pre-heating, under all ambient temperature conditions before ignition and combustion can occur. This usually includes the following: Materials that will burn in air when exposed to a temperature of 815.5°C (1500°F) for a period of 5 minutes or less; Liquids, solids and semisolids having a flash point at or above 93.3°C (200°F) (i.e. OSHA Class IIIB); and Most ordinary combustible materials (e.g. wood, paper, etc.). **2 Moderate Hazard:** Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. Materials in this degree would not, under normal conditions, form hazardous atmospheres in air, but under high ambient temperatures or moderate heating may release vapor in sufficient quantities to produce hazardous atmospheres with air. This usually includes the following: Liquids having a flash-point at or above 37.8°C (100°F); Solid materials in the form of course dusts that may burn rapidly but that generally do not form explosive atmospheres; Solid materials in a fibrous or shredded form that may burn rapidly and create flash fire hazards (e.g. cotton, sisal, hemp); and Solids and semisolids (e.g. viscous and slow flowing as asphalt) that readily give off flammable vapors. **3 Serious Hazard:** Liquids and solids that can be ignited under almost all ambient temperature conditions. Materials in this degree produce hazardous atmospheres with air under almost all ambient temperatures, or, unaffected by ambient temperature, are readily ignited under almost all conditions. This usually includes the following: Liquids having a flash point below 22.8°C (73°F) and having a boiling point at or above 38°C (100°F) point at or above 22.8°C (73°F) and below 37.8°C (100°F) (i.e. OSHA Class IB and IC); Materials that on account of their physical form or environmental conditions can form explosive mixtures with air and are readily dispersed in air (e.g., dusts of combustible solids, mists or droplets of flammable liquids); and Materials that burn extremely rapidly, usually by reason of self-contained oxygen (e.g. dry nitrocellulose and many organic peroxides). **4 Severe Hazard:** Materials that will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air, and that will burn readily. This usually includes the following: Flammable gases; Flammable cryogenic materials; Any liquid or gaseous material that is liquid while under pressure and has a flash point below 22.8°C (73°F) and a boiling point below 37.8°C (100°F) (i.e. OSHA Class IA); and Materials that ignite spontaneously when exposed to air at a temperature of 54.4°C (130°F) or below (pyrophoric).

PHYSICAL HAZARD: 0 Water Reactivity: Materials that do not react with water. *Organic Peroxides:* Materials that are normally stable, even under fire conditions and will not react with water. *Explosives:* Substances that are Non-Explosive. *Compressed Gases:* No Rating. *Pyrophorics:* No Rating. *Oxidizers:* No 0 rating. *Unstable Reactives:* Substances that will not polymerize, decompose, condense, or self-react. **1 Water Reactivity:** Materials that change or decompose upon exposure to moisture. *Organic Peroxides:* Materials that are normally stable, but can become unstable at high temperatures and pressures. These materials may react with water, but will not release energy violently. *Explosives:* Division 1.5 & 1.6 explosives. Substances that are very insensitive explosives or that do not have a mass explosion hazard. *Compressed Gases:* Pressure below OSHA definition. *Pyrophorics:* No Rating. *Oxidizers:* Packaging Group III oxidizers; Solids: any material that in either concentration tested, exhibits a mean burning time less than or equal to the mean burning time of a 3:7 potassium bromate/cellulose mixture and the criteria for Packing Group I and II are not met. Liquids: any material that exhibits a mean pressure rise time less than or equal to the pressure rise time of a 1:1 nitric acid (65%)/cellulose mixture and the criteria for Packing Group I and II are not met. *Unstable Reactives:* Substances that may decompose, condense, or self-react, but only under conditions of high temperature and/or pressure and have little or no potential to cause significant heat generation or explosion hazard. Substances that readily undergo hazardous polymerization in the absence of inhibitors. **2 Water Reactivity:** Materials that may react violently with water. *Organic Peroxides:* Materials that, in themselves, are normally unstable and will readily undergo violent chemical change, but will not detonate. These materials may also react violently with water. *Explosives:* Division 1.4 explosives. Explosive substances where the explosive effects are largely confined to the package and no projection of fragments of appreciable size or range are expected. An external fire must not cause virtually instantaneous explosion of almost the entire contents of the package. *Compressed Gases:* Pressurized and meet OSHA definition but < 514.7 psi absolute at 21.1°C (70°F) [500 psig]. *Pyrophorics:* No Rating. *Oxidizers:* Packaging Group II oxidizers. Solids: any material that, either in concentration tested, exhibits a mean burning time of less than or equal to the mean burning time of a 2:3 potassium bromate/cellulose mixture and the criteria for Packing Group I are not met. Liquids: any material that exhibits a mean pressure rise time less than or equal to the pressure rise of a 1:1 aqueous sodium chlorate solution (40%)/cellulose mixture and the criteria for Packing Group I are not met. *Reactives:* Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure, but have a low potential (or low risk) for significant heat generation or explosion. Substances that readily form peroxides upon exposure to air or oxygen at room temperature. **3 Water Reactivity:** Materials that may form explosive reactions with water. *Organic Peroxides:* Materials that are capable of detonation or explosive reaction, but require a strong initiating source or must be heated under confinement before initiation; or materials that react explosively with water. *Explosives:* Division 1.3 explosives. Explosive substances that have a fire hazard and either a minor blast hazard or a minor projection hazard or both, but do not have a mass explosion hazard. *Compressed Gases:* Pressure ≥ 514.7 psi absolute at 21.1°C (70°F) [500 psig]. *Pyrophorics:* No Rating. *Oxidizers:* Packaging Group I oxidizers. Solids: any material that, in either concentration tested, exhibits a mean burning time less than the mean burning time of a 3:2 potassium bromate/cellulose mixture. Liquids: any material that spontaneously ignites when mixed with cellulose in a 1:1 ratio, or which exhibits a mean pressure rise time less than the pressure rise time of a 1:1 perchloric acid (50%)/cellulose mixture. *Unstable Reactives:* Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure and have a moderate potential (or moderate risk) to cause significant heat generation or explosion. **4 Water Reactivity:** Materials that react explosively with water without requiring heat or confinement. *Organic Peroxides:* Materials that are readily capable of detonation or explosive decomposition at normal temperature and pressures. *Explosives:* Division 1.1 & 1.2 explosives. Explosive substances that have a mass explosion hazard or have a projection hazard. A mass explosion is one that affects almost the entire load instantaneously. *Compressed Gases:* No Rating. *Pyrophorics:* Add to the definition of Flammability 4. *Oxidizers:* No 4 rating. *Unstable Reactives:* Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure and have a high potential (or high risk) to cause significant heat generation or explosion. *Pyrophorics:* Add to the definition of Flammability 4.

HAZARDOUS MATERIALS IDENTIFICATION SYSTEM HAZARD RATINGS (continued):

PHYSICAL HAZARD (continued): 4 (continued): Oxidizers: No 4 rating. *Unstable Reactives:* Substances that may polymerize, decompose, condense, or self-react at ambient temperature and/or pressure and have a high potential (or high risk) to cause significant heat generation or explosion.

NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS

HEALTH HAZARD: 0 Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials. Gases and vapors with an LC₅₀ for acute inhalation toxicity greater than 10,000 ppm. Dusts and mists with an LC₅₀ for acute inhalation toxicity greater than 200 mg/L. Materials with an LD₅₀ for acute dermal toxicity greater than 2000 mg/kg. Materials with an LD₅₀ for acute oral toxicity greater than 2000 mg/kg. Materials essentially non-irritating to the respiratory tract, eyes, and skin. **1** Materials that, under emergency conditions, can cause significant irritation. Gases and vapors with an LC₅₀ for acute inhalation toxicity greater than 5,000 ppm but less than or equal to 10,000 ppm. Dusts and mists with an LC₅₀ for acute inhalation toxicity greater than 10 mg/L but less than or equal to 200 mg/L. Materials with an LD₅₀ for acute dermal toxicity greater than 1000 mg/kg but less than or equal to 2000 mg/kg. Materials that slightly to moderately irritate the respiratory tract, eyes and skin. Materials with an LD₅₀ for acute oral toxicity greater than 500 mg/kg but less than or equal to 2000 mg/kg. **2** Materials that, under emergency conditions, can cause temporary incapacitation or residual injury. Gases with an LC₅₀ for acute inhalation toxicity greater than 3,000 ppm but less than or equal to 5,000 ppm. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater than one-fifth its LC₅₀ for acute inhalation toxicity, if its LC₅₀ is less than or equal to 5000 ppm and that does not meet the criteria for either degree of hazard 3 or degree of hazard 4. Dusts and mists with an LC₅₀ for acute inhalation toxicity greater than 2 mg/L but less than or equal to 10 mg/L. Materials with an LD₅₀ for acute dermal toxicity greater than 200 mg/kg but less than or equal to 1000 mg/kg. Compressed liquefied gases with boiling points between -30°C (-22°F) and -55°C (-66.5°F) that cause severe tissue damage, depending on duration of exposure. Materials that are respiratory irritants. Materials that cause severe, but reversible irritation to the eyes or skin. **3** Materials that, under emergency conditions, can cause serious or permanent injury. Gases with an LC₅₀ for acute inhalation toxicity greater than 1,000 ppm but less than or equal to 3,000 ppm. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater its LC₅₀ for acute inhalation toxicity, if its LC₅₀ is less than or equal to 3000 ppm and that does not meet the criteria for degree of hazard 4. Dusts and mists with an LC₅₀ for acute inhalation toxicity greater than 0.5 mg/L but less than or equal to 2 mg/L. Materials with an LD₅₀ for acute dermal toxicity greater than 40 mg/kg but less than or equal to 200 mg/kg. Materials that are corrosive to the respiratory tract. Materials that are corrosive to the eyes or cause irreversible corneal opacity. Materials corrosive to the skin. Cryogenic gases that cause frostbite and irreversible tissue damage. Compressed liquefied gases with boiling points below -55°C (-66.5°F) that cause frostbite and irreversible tissue damage. Materials with an LD₅₀ for acute oral toxicity greater than 5 mg/kg but less than or equal to 50 mg/kg. **4** Materials that, under emergency conditions, can be lethal. Gases with an LC₅₀ for acute inhalation toxicity less than or equal to 1,000 ppm. Any liquid whose saturated vapor concentration at 20°C (68°F) is equal to or greater than ten times its LC₅₀ for acute inhalation toxicity, if its LC₅₀ is less than or equal to 1000 ppm. Dusts and mists whose LC₅₀ for acute inhalation toxicity is less than or equal to 0.5 mg/L. Materials whose LD₅₀ for acute dermal toxicity is less than or equal to 40 mg/kg. Materials whose LD₅₀ for acute oral toxicity is less than or equal to 5 mg/kg.

FLAMMABILITY HAZARD: 0 Materials that will not burn under typical fire conditions, including intrinsically noncombustible materials such as concrete, stone, and sand. Materials that will not burn in air when exposed to a temperature of 816°C (1500°F) for a period of 5 minutes in according with Annex D of NFPA 704. **1** Materials that must be preheated before ignition can occur. Materials in this degree require considerable preheating, under all ambient temperature conditions, before ignition and combustion can occur: Materials that will burn in air when exposed to a temperature of 816°C (1500°F) for a period of 5 minutes in according with Annex D of NFPA 704. Liquids, solids, and semisolids having a flash point at or above 93.4°C (200°F) (i.e. Class IIIB liquids). Liquids with a flash point greater than 35°C (95°F) that do not sustain combustion when tested using the *Method of Testing for Sustained Combustibility*, per 49 CFR 173, Appendix H or the *UN Recommendations on the Transport of Dangerous Goods, Model Regulations* (current edition) and the related *Manual of Tests and Criteria* (current edition). Liquids with a flash point greater than 35°C (95°F) in a water-miscible solution or dispersion with a water non-combustible liquid/solid content of more than 85% by weight. Liquids that have no fire point when tested by ASTM D 92, *Standard Test Method for Flash and Fire Points by Cleveland Open Cup*, up to the boiling point of the liquid or up to a temperature at which the sample being tested shows an obvious physical change. Combustible pellets with a representative diameter of greater than 2 mm (10 mesh). Most ordinary combustible materials. Solids containing greater than 0.5% by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent. **2** Materials that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur. Materials in this degree would not under normal conditions form hazardous atmospheres with air, but under high ambient temperatures or under moderate heating could release vapor in sufficient quantities to produce hazardous atmospheres with air. Liquids having a flash point at or above 37.8°C (100°F) and below 93.4°C (200°F) (i.e. Class II and Class IIIA liquids.) Solid materials in the form of powders or coarse dusts of representative diameter between 420 microns (40 mesh) and 2 mm (10 mesh) that burn rapidly but that generally do not form explosive mixtures with air. Solid materials in fibrous or shredded form that burn rapidly and create flash fire hazards, such as cotton, sisal, and hemp. Solids and semisolids that readily give off flammable vapors. Solids containing greater than 0.5% by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent. **3** Liquids and solids that can be ignited under almost all ambient temperature conditions. Materials in this degree produce hazardous atmospheres with air under almost all ambient temperatures or, though unaffected by ambient temperatures, are readily ignited under almost all conditions. Liquids having a flash point below 22.8°C (73°F) and having a boiling point at or above 37.8°C (100°F) and those liquids having a flash point at or above 22.8°C (73°F) and below 37.8°C (100°F) (i.e. Class IB and IC liquids). Materials that on account of their physical form or environmental conditions can form explosive mixtures with air and are readily dispersed in air. Flammable or combustible dusts with representative diameter less than 420 microns (40 mesh). Materials that burn with extreme rapidity, usually by reason of self-contained oxygen (e.g. dry nitrocellulose and many organic peroxides). Solids containing greater than 0.5% by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent. **4** Materials that will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature or that are readily dispersed in air and will burn readily. Flammable gases. Flammable cryogenic materials. Any liquid or gaseous materials that is liquid while under pressure and has a flash point below 22.8°C (73°F) and a boiling point below 37.8°C (100°F) (i.e. Class IA liquids). Materials that ignite when exposed to air, Solids containing greater than 0.5% by weight of a flammable or combustible solvent are rated by the closed cup flash point of the solvent.

DEFINITIONS OF TERMS (Continued)

NATIONAL FIRE PROTECTION ASSOCIATION HAZARD RATINGS (continued):

INSTABILITY HAZARD: 0 Materials that in themselves are normally stable, even under fire conditions. Materials that have an instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) below 0.01 W/mL. Materials that do not exhibit an exotherm at temperatures less than or equal to 500°C (932°F) when tested by differential scanning calorimetry. **1** Materials that in themselves are normally stable, but that can become unstable at elevated temperatures and pressures. Materials that have an instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 0.01 W/mL and below 10 W/mL. **2** Materials that readily undergo violent chemical change at elevated temperatures and pressures. Materials that have an instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 10 W/mL and below 100W/mL. **3** Materials that in themselves are capable of detonation or explosive decomposition or explosive reaction, but that require a strong initiating source or that must be heated under confinement before initiation. Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) at or above 100 W/mL and below 1000 W/mL. Materials that are sensitive to thermal or mechanical shock at elevated temperatures and pressures. **4** Materials that in themselves are readily capable of detonation or explosive decomposition or explosive reaction at normal temperatures and pressures. Materials that are sensitive to localized thermal or mechanical shock at normal temperatures and pressures. Materials that have an estimated instantaneous power density (product of heat of reaction and reaction rate) at 250°C (482°F) of 1000 W/mL or greater.

FLAMMABILITY LIMITS IN AIR:

Much of the information related to fire and explosion is derived from the National Fire Protection Association (NFPA). **Flash Point:** Minimum temperature at which a liquid gives off sufficient vapor to form an ignitable mixture with air near the surface of the liquid or within the test vessel used. **Autoignition Temperature:** Minimum temperature of a solid, liquid, or gas required to initiate or cause self-sustained combustion in air with no other source of ignition. **LEL:** Lowest concentration of a flammable vapor or gas/air mixture that will ignite and burn with a flame. **UEL:** Highest concentration of a flammable vapor or gas/air mixture that will ignite and burn with a flame.

TOXICOLOGICAL INFORMATION:

Human and Animal Toxicology: Possible health hazards as derived from human data, animal studies, or from the results of studies with similar compounds are presented. **LD₅₀:** Lethal Dose (solids & liquids) that kills 50% of the exposed animals. **LC₅₀:** Lethal Concentration (gases) that kills 50% of the exposed animals. **ppm:** Concentration expressed in parts of material per million parts of air or water. **mg/m³:** Concentration expressed in weight of substance per volume of air. **mg/kg:** Quantity of material, by weight, administered to a test subject, based on their body weight in kg. **TDL₀:** Lowest dose to cause a symptom. **TCL₀:** Lowest concentration to cause a symptom. **TD₀, LD₀, and LD₅₀, or TC, TC₀, LCL₀, and LC₀:** Lowest dose (or concentration) to cause lethal or toxic effects. **Cancer Information:** **IARC:** International Agency for Research on Cancer. **NTP:** National Toxicology Program. **RTECS:** Registry of Toxic Effects of Chemical Substances. IARC and NTP rate chemicals on a scale of decreasing potential to cause human cancer with rankings from 1 to 4. Subrankings (2A, 2B, etc.) are also used. **Other Information:** **BEI:** ACGIH Biological Exposure Indices, represent the levels of determinants which are most likely to be observed in specimens collected from a healthy worker who has been exposed to chemicals to the same extent as a worker with inhalation exposure to the TLV.

REPRODUCTIVE INFORMATION: A **mutagen** is a chemical that causes permanent changes to genetic material (DNA) such that the changes will propagate through generational lines. An **embryotoxin** is a chemical that causes damage to a developing embryo (i.e. within the first eight weeks of pregnancy in humans), but the damage does not propagate across generational lines. A **teratogen** is a chemical that causes damage to a developing fetus, but the damage does not propagate across generational lines. A **reproductive toxin** is any substance that interferes in any way with the reproductive process.

ECOLOGICAL INFORMATION:

EC: Effect concentration in water. **BCF:** Bioconcentration Factor, which is used to determine if a substance will concentrate in life forms that consume contaminated plant or animal matter. **TLM:** Median threshold limit. **log K_{OW}** or **log K_{OC}:** Coefficient of Oil/Water Distribution is used to assess a substance's behavior in the environment.

REGULATORY INFORMATION: This section explains the impact of various laws and regulations on the material.

U.S.:

EPA: U.S. Environmental Protection Agency. **ACGIH:** American Conference of Governmental Industrial Hygienists, a professional association that establishes exposure limits. **OSHA:** U.S. Occupational Safety and Health Administration. **NIOSH:** National Institute of Occupational Safety and Health, which is the research arm of OSHA. **DOT:** U.S. Department of Transportation. **TC:** Transport Canada. **SARA:** Superfund Amendments and Reauthorization Act. **TSCA:** U.S. Toxic Substance Control Act. **CERCLA:** Comprehensive Environmental Response, Compensation, and Liability Act. Marine Pollutant status according to the DOT; CERCLA or Superfund; and various state regulations. This section also includes information on the precautionary warnings that appear on the material's package label.

CANADA:

WHMIS: Canadian Workplace Hazardous Materials Information System. **TC:** Transport Canada. **DSL/NDL:** Canadian Domestic/Non-Domestic Substances List.