

Revision Date: 08/18/2023

This is a kit that contains the following components: DURAL 452 GEL PART A DURAL 452 GEL 1:1 PART B



Revision Date: 08/18/2023

SAFETY DATA SHEET

1. Identification

Product identifier: DURAL 452 GEL PART A

Product Code: 002DG 02

Recommended use and restriction on use

Recommended use: Sealant Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

EUCLID CHEMICAL COMPANY 19218 REDWOOD ROAD CLEVELAND OH 44110

US

Contact person:EH&S DepartmentTelephone:216-531-9222

Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Skin Corrosion/Irritation Category 2
Serious Eye Damage/Eye Irritation Category 2A
Skin sensitizer Category 1
Carcinogenicity Category 1A

Unknown toxicity - Health

Acute toxicity, oral 9.27 %
Acute toxicity, dermal 9.52 %
Acute toxicity, inhalation, vapor 97.45 %
Acute toxicity, inhalation, dust 97.05 %

or mist

Environmental Hazards

Acute hazards to the aquatic Category 2

environment

Chronic hazards to the aquatic Category 2

environment

Unknown toxicity - Environment

Acute hazards to the aquatic 14.86 %

environment



Revision Date: 08/18/2023

Chronic hazards to the aquatic 13.01 % environment

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause cancer.

Toxic to aquatic life with long lasting effects.

Precautionary Statements

Prevention: Wash thoroughly after handling. Wear protective gloves/ protective clothing/

eye protection/ face protection. Avoid breathing

dust/fume/gas/mist/vapors/spray. Contaminated work clothing should not be allowed out of the workplace. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use

personal protective equipment as required. Avoid release to the

environment.

Response: IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of

soap and water. If skin irritation or rash occurs: Get medical

advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before

reuse. Collect spillage.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None.

3. Composition/information on ingredients

Mixtures



Revision Date: 08/18/2023

Chemical Identity	CAS number	Content in percent (%)*
Bisphenol A Polyglycidyl Ether Resin	25068-38-6	50 - <100%
Neopentyl glycol diglycidyl ether	17557-23-2	1 - <5%
Titanium dioxide	13463-67-7	1 - <5%
Epichlorohydrin polymer	25085-99-8	1 - <2.5%
Polyethylene	9002-88-4	0.1 - <1%
o-Cresyl glycidyl ether	2210-79-9	0.1 - <1%
Aluminum hydroxide	21645-51-2	0.1 - <1%
Amorphous silica	7631-86-9	0.1 - <1%
Carbon Black	1333-86-4	0.1 - <1%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Description of necessary first-aid measures

Inhalation: Move to fresh air.

Skin Contact: Get medical attention. Destroy or thoroughly clean contaminated

shoes. Immediately remove contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic

skin reaction develops, get medical attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy

to do, remove contact lenses. Get medical attention.

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Personal Protection for First-

aid Responders:

Self-contained breathing apparatus and full protective clothing must

be worn in case of fire.

Most important symptoms/effects, acute and delayed

Symptoms: Prolonged or repeated contact with skin may cause redness, itching,

irritation and eczema/chapping.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.



Revision Date: 08/18/2023

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for fire-fighters

Special fire-fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and

emergency procedures:

See Section 8 of the SDS for Personal Protective Equipment. Do not touch

damaged containers or spilled material unless wearing appropriate

protective clothing. Keep unauthorized personnel away.

Accidental release measures: In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.

Methods and material for containment and cleaning

containn

Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for

disposal according to local regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Handling

Technical measures (e.g. Local and general ventilation):

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical

ventilation or local exhaust ventilation may be required.

Safe handling advice: Provide adequate ventilation. Wear appropriate personal protective

equipment. Observe good industrial hygiene practices. Wash hands thoroughly after handling. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with eyes. Avoid

contact with skin. Avoid contact with eyes, skin, and clothing.

Contact avoidance measures: No data available.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. Avoid contact with eyes. Wash contaminated clothing before reuse. Avoid contact with skin. Contaminated

work clothing should not be allowed out of the workplace.

Storage

Safe storage conditions: Store locked up.



Revision Date: 08/18/2023

Safe packaging materials: No data available.

8. Exposure controls/personal protection

Control Parameters

Chemical Identity	Туре	Exposure Limit Values	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)	
Titanium dioxide - Total dust.	PEL	15 mg/m3		
Titanium dioxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)	
Titanium dioxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)	
Titanium dioxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)	
Titanium dioxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)	
Titanium dioxide - Respirable finescale particles	TWA	2.5 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2022)	
Titanium dioxide - Respirable nanoscale particles	TWA	0.2 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2022)	
Polyethylene - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2015)	
Polyethylene - Respirable particles.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2015)	
Polyethylene - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)	
Polyethylene - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)	
	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)	
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)	
Polyethylene - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)	
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)	
Aluminum hydroxide - Respirable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)	
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)	
Aluminum hydroxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)	
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)	
Aluminum hydroxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), a amended (03 2016)	
Aluminum hydroxide - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)	





Revision Date: 08/18/2023

Aluminum hydroxide -	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as
Respirable particles.		_	amended (01 2021)
Amorphous silica - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Amorphous silica - Respirable particles.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Amorphous silica -	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as
Respirable fraction. Amorphous silica - Total dust.	TWA	15 mg/m3	amended (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000), as
uust.	TWA	50 millions of particles per cubic foot of air	amended (09 2016) US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Amorphous silica - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Amorphous silica	TWA	0.8 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
	TWA	20 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Carbon Black	PEL	3.5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (12 2010)
Carbon Black - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Carbon Black - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)





Revision Date: 08/18/2023

Chemical name	cal name Type Exposure Limit Values		Source		
Wollastonite - fibers, total dust	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)		
Wollastonite - Fiber.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)		
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)		
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)		
Titanium dioxide	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)		
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)		
Polyethylene - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (05 2013)		
Polyethylene - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (05 2013)		
Polyethylene - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)		
Polyethylene - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)		
Polyethylene - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)		
Polyethylene - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (06 2020)		
Polyethylene - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (06 2020)		
Aluminum hydroxide - Respirable fraction.	TWA	1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)		
Aluminum hydroxide - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)		
Aluminum hydroxide - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)		
Aluminum hydroxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)		
Aluminum hydroxide - Respirable particles.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)		
Aluminum hydroxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (06 2020)		





Revision Date: 08/18/2023

Aluminum hydroxide - Inhalable particles.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Aluminum hydroxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (06 2020)
Aluminum hydroxide - Respirable dust.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (04 2022)
Aluminum hydroxide - Respirable.	TWA	1.0 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (06 2022)
Amorphous silica - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (06 2020)
Amorphous silica - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Amorphous silica - Respirable particles.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Amorphous silica - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Amorphous silica - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Amorphous silica - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (06 2020)
Amorphous silica - Inhalable particles.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Carbon Black - Inhalable	TWA	3 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (09 2011)
Carbon Black - Inhalable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Carbon Black - Inhalable dust.	TWA	3 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
	TWA	0.05 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (04 2022)
Stoddard solvent (Mineral Spirits)	STEL	580 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
	TWA	290 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)



Revision Date: 08/18/2023

Stoddard solvent (Mineral Spirits)	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm	525 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
1-Methoxy-2-propanol acetate	TWA	50 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
	STEL	75 ppm		Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
1-Methoxy-2-propanol acetate	TWA	50 ppm	270 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (12 2007)
1,2,4-Trimethylbenzene	TWA	25 ppm	123 mg/m3	Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended (07 2009)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical

ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Additional Information: Use suitable protective gloves if risk of skin contact.

Skin and Body Protection: Wear suitable protective clothing. Wear chemical-resistant gloves,

footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific

information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product. Avoid contact with eyes. Wash contaminated clothing before reuse. Avoid contact with skin. Contaminated

work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical state: liquid
Form: liquid
Color: Gray
Odor: Mild

Odor threshold:

pH:

No data available.

No data available.



Revision Date: 08/18/2023

Melting point/freezing point:No data available.
Initial boiling point and boiling range:
No data available.

Flash Point: > 93 °C > 200 °F(Setaflash Closed Cup)

Evaporation rate: Slower than Ether

Flammability (solid, gas): No Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper:

Explosive limit - lower:

No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density: 1.13

Solubility(ies)

Solubility in water:
Solubility (other):
No data available.
Partition coefficient (n-octanol/water):
No data available.
No data available.
No data available.
Viscosity:
No data available.
No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

Products:

No data available.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: No data available.

Hazardous Decomposition

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation: In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

Skin Contact: May be harmful in contact with skin. Causes skin irritation. May cause an

allergic skin reaction.

Eye contact: Causes serious eye irritation.

Ingestion: May be harmful if swallowed.



Revision Date: 08/18/2023

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Bisphenol A Polyglycidyl

Ether Resin

LD 50 (Rat): > 2,000 mg/kg

Polyethylene LD 50 (Rat): 5,001 mg/kg

o-Cresyl glycidyl ether LD 50 (Rat): > 5,000 mg/kg

Aluminum hydroxide LD 50 (Rat): > 2,000 mg/kg

Amorphous silica LD 50 (Rat): > 6,350 mg/kg

Carbon Black LD 50 (Rat): > 10,000 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Polyethylene LD 50 (Rabbit): 5,001 mg/kg

o-Cresyl glycidyl ether LD 50 (Rat): > 2,000 mg/kg

Amorphous silica LD 50 (Rat): > 2,000 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.



Revision Date: 08/18/2023

Specified substance(s):

Bisphenol A Polyglycidyl

Ether Resin

LC 50: > 20 mg/l LC 50: > 5 mg/l

Polyethylene LC 50 (Rabbit): 20.1 mg/l

o-Cresyl glycidyl ether LC 50 (Rat): 6,090 mg/m3

Aluminum hydroxide LC 50 (Rat): 7.6 mg/l

Amorphous silica LC 50 (Rat): > 2.08 mg/l

Repeated dose toxicity

Product:

No data available.

Skin Corrosion/Irritation

Product:

No data available.

Specified substance(s):

Bisphenol A

Polyglycidyl Ether

Resin

in vivo (Rabbit): Moderately irritating , 24 h

o-Cresyl glycidyl ether in vivo (Rabbit): Not irritant, 7 d

Aluminum hydroxide in vivo (Rabbit): Not classified as an Irritant, 24 - 72 h

Amorphous silica in vivo (Rabbit): Not irritant, 48 h

Carbon Black in vivo (Rabbit): Not irritant , 120 h

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Aluminum hydroxide Rabbit, 24 - 72 h: Not irritant

Amorphous silica Rabbit, 24 - 72 h: Not irritant

Carbon Black Rabbit, 24 - 72 h: Not irritant

Respiratory or Skin Sensitization

Product: No data available.



Revision Date: 08/18/2023

Carcinogenicity

Product: Suspected of causing cancer.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Carbon Black Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Carbon Black Known To Be Human Carcinogen.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

Product: No data available.

Specific Target Organ Toxicity - Repeated Exposure

Product: No data available.

Aspiration Hazard

Product: No data available.

Other effects: Constituents of this product may include crystalline silica which, if in inhalable form, may cause silicosis, a form of progressive pulmonary

fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimis exposure to these impurities in inhalable form may be carcinogenic

or cause other serious lung problems.



Revision Date: 08/18/2023

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Bisphenol A Polyglycidyl

Ether Resin

LC 50 (Oncorhynchus mykiss, 96 h): 1.5 mg/l Experimental result, Key study

LC 50 (Oncorhynchus mykiss, 96 h): 2.8 - 5.1 mg/l Experimental result, Key o-Cresyl glycidyl ether

study

Aluminum hydroxide LC 50 (Oncorhynchus mykiss, 96 h): 7.4 mg/l Experimental result, Weight of

Evidence study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Bisphenol A Polyglycidyl

Ether Resin

EC 50 (Daphnia magna, 48 h): 1.1 mg/l experimental result Experimental

result, Key study

EC 50 (Daphnia magna, 48 h): 3.3 mg/l experimental result Experimental o-Cresyl glycidyl ether

result, Key study

EC 50 (Ceriodaphnia dubia, 48 h): 1.5 mg/l experimental result Experimental Aluminum hydroxide

result, Weight of Evidence study

LC 50 (Daphnia sp., 48 h): 164 mg/l QSAR QSAR, Key study Carbon Black

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Aluminum hydroxide NOAEL (Pimephales promelas): 0.16 mg/l read-across based on grouping of

substances (category approach) Read-across based on grouping of

substances (category approach), Weight of Evidence study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Aluminum hydroxide

Bisphenol A Polyglycidyl

NOAEL (Daphnia magna): 0.3 mg/l experimental result Experimental result, Ether Resin

Key study

NOAEL (Daphnia magna): 0.076 mg/l experimental result Experimental

result, Weight of Evidence study

Carbon Black EC 50 (Daphnia sp.): 4.9 mg/l QSAR QSAR, Key study



Revision Date: 08/18/2023

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

Bisphenol A Polyglycidyl

Ether Resin

82 % Detected in water. Experimental result, Key study

o-Cresyl glycidyl ether 11 - 17 % (28 d) Detected in water. Experimental result, Key study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Bisphenol A Polyglycidyl

Ether Resin

Bioconcentration Factor (BCF): 31 Aquatic sediment QSAR, Key study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Bisphenol A Polyglycidyl

Ether Resin

Log Kow: 2.64 - 3.78 25 °C Yes Experimental result, Key study

Mobility in soil: No data available.

Other adverse effects: Toxic to aquatic life with long lasting effects.

13. Disposal considerations

Disposal methods: Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Epoxy Resin), 9, PG III



Revision Date: 08/18/2023

CFR / DOT:

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Epoxy Resin), 9, PG III

IMDG:

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Epoxy Resin), 9, PG III, MARINE POLLUTANT

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended

Chemical IdentityOSHA hazard(s)Crystalline Silicakidney effects(Quartz)/ Silica Sandlung effects

immune system effects

Cancer

CERCLA Hazardous Substance List (40 CFR 302.4):

None present or none present in regulated quantities.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard Skin Corrosion or Irritation Serious eye damage or eye irritation Respiratory or Skin Sensitization Carcinogenicity

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

US. EPCRA (SARA Title III Section 313 Toxic Chemical Release Inventory (TRI) Reporting

<u>Chemical Identity</u> % by weight



Revision Date: 08/18/2023

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING

Cancer - www.P65Warnings.ca.gov

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC: When appropriately mixed with the other part, product has a VOC less water and exempt solvent of: 91 g/l

Regulatory VOC (less water and

< 5 g/l

exempt solvent)

VOC Method 310 : 0.04 %



Revision Date: 08/18/2023

Inventory Status:

Canada DSL Inventory List: All components in this product are

listed on or exempt from the

Inventory.

EC Inventory: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan (ENCS) List: One or more components in this

product are not listed on or exempt

from the Inventory.

Canada NDSL Inventory: One or more components in this

product are not listed on or exempt

from the Inventory.

US TSCA Inventory: All components in this product are

listed on or exempt from the

Inventory.

Japan ISHL Listing: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this

product are not listed on or exempt

from the Inventory.

Australia AICS: One or more components in this

product are not listed on or exempt

from the Inventory.

Ontario Inventory:

One or more components in this

product are not listed on or exempt

from the Inventory.

China Inv. Existing Chemical

Substances:

One or more components in this product are not listed on or exempt

from the Inventory.

Korea Existing Chemicals Inv. (KECI): One or more components in this

product are not listed on or exempt

from the Inventory.

Mexico INSQ:

One or more components in this

product are not listed on or exempt

from the Inventory.

New Zealand Inventory of Chemicals: One or more components in this



Revision Date: 08/18/2023

product are not listed on or exempt

from the Inventory.

Philippines PICCS: One or more components in this

product are not listed on or exempt

from the Inventory.

Taiwan Chemical Substance Inventory: One or more components in this

product are not listed on or exempt

from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date: 08/18/2023

Version #: 7.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.



Revision Date: 08/18/2023

SAFETY DATA SHEET

1. Identification

Product identifier: DURAL 452 GEL 1:1 PART B

Product Code: 002DG 02

Recommended use and restriction on use

Recommended use: Curative Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

EUCLID CHEMICAL COMPANY 19218 REDWOOD ROAD CLEVELAND OH 44110

US

Contact person: EH&S Department **Telephone:** 216-531-9222

Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Acute toxicity (Oral)

Acute toxicity (Inhalation - vapor)

Acute toxicity (Inhalation - dust and

Category 4

Category 4

nist)

Skin Corrosion/Irritation

Serious Eye Damage/Eye Irritation

Skin sensitizer

Category 1

Category 1

Category 1

Category 2

Unknown toxicity - Health

Acute toxicity, oral 10.28 %
Acute toxicity, dermal 33.72 %
Acute toxicity, inhalation, vapor 90.02 %
Acute toxicity, inhalation, dust 87.56 %

or mist

Environmental Hazards

Acute hazards to the aquatic Category 1

environment

Chronic hazards to the aquatic Category 2

environment



Revision Date: 08/18/2023

Unknown toxicity - Environment

Acute hazards to the aquatic 34.75 %

environment

Chronic hazards to the aquatic 34.75 %

environment

Label Elements

Hazard Symbol:



Signal Word: Danger

Hazard Statement: Harmful if swallowed or if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

Very toxic to aquatic life.

Toxic to aquatic life with long lasting effects.

Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Do not breathe

dust/fume/gas/mist/vapors/spray. Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/ protective clothing/ eye protection/

face protection. Use personal protective equipment as required.

Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call a POISON

CENTER or doctor/ physician if you feel unwell. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instructions on this label). IF INHALED: Remove person to fresh air and

keep comfortable for breathing. Immediately call a POISON

CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Collect

spillage.

Storage: Store locked up.

Disposal: Dispose of contents/ container to an approved facility in accordance with

local, regional, national and international regulations.



Revision Date: 08/18/2023

Hazard(s) not otherwise classified (HNOC):

None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
1,2-Cyclohexanediamine	694-83-7	10 - <25%
4-Nonylphenol	84852-15-3	10 - <25%
Benzyl alcohol	100-51-6	5 - <10%
4-tert-Butylphenol	98-54-4	2.5 - <5%
Wollastonite	13983-17-0	1 - <5%
m-Xylenediamine	1477-55-0	1 - <3%
1,3-Cyclohexanedimethanamine	2579-20-6	1 - <3%
Polyethylene	9002-88-4	0.1 - <1%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Description of necessary first-aid measures

Inhalation: Call a physician or poison control center immediately. If breathing

stops, provide artificial respiration. Move to fresh air. If breathing is

difficult, give oxygen.

Skin Contact: Call a physician or poison control center immediately. Destroy or

thoroughly clean contaminated shoes. Immediately remove

contaminated clothing and shoes and wash skin with soap and plenty of water. If skin irritation or an allergic skin reaction develops, get

medical attention.

Eye contact: Immediately flush with plenty of water for at least 15 minutes. If easy

to do, remove contact lenses. Call a physician or poison control

center immediately.

Ingestion: Rinse mouth. Call a physician or poison control center immediately.

Never give liquid to an unconscious person. Do not induce vomiting

without advice from poison control center.

Personal Protection for First-

aid Responders:

Self-contained breathing apparatus and full protective clothing must

be worn in case of fire.

Most important symptoms/effects, acute and delayed

Symptoms: Prolonged or repeated contact with skin may cause redness, itching,

irritation and eczema/chapping. Extreme irritation of eyes and mucous

membranes, including burning and tearing.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed



Revision Date: 08/18/2023

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for fire-fighters

Special fire-fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

worn in case of fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: See Section 8 of the SDS for Personal Protective Equipment. Do not touch

damaged containers or spilled material unless wearing appropriate

protective clothing. Keep unauthorized personnel away.

Accidental release measures:

In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.

Methods and material for containment and cleaning

up:

Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for

disposal according to local regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Handling

Technical measures (e.g. Local and general ventilation):

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical

ventilation or local exhaust ventilation may be required.



Revision Date: 08/18/2023

Safe handling advice: Provide adequate ventilation. Wear appropriate personal protective

equipment. Observe good industrial hygiene practices. Do not taste or swallow. Wash hands thoroughly after handling. Do not get in eyes. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Do not get in eyes, on skin, on clothing. Avoid contact with eyes,

skin, and clothing.

Contact avoidance measures: No data available.

Hygiene measures: Observe good industrial hygiene practices. Do not eat, drink or smoke

when using the product. Wash hands after handling. Do not get in eyes. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Do not get this material in contact with skin. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with

skin.

Storage

Safe storage conditions: Store locked up.

Safe packaging materials: No data available.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Limit Values	Source
Wollastonite - Inhalable fraction.	TWA	1 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2019)
m-Xylenediamine	Ceiling	0.018 ppm	US. ACGIH Threshold Limit Values, as amended (01 2022)
Polyethylene - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2015)
Polyethylene - Respirable particles.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (03 2015)
Polyethylene - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Polyethylene - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Polyethylene - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)

EUCLID CHEMICAL

Version: 7.0

Revision Date: 08/18/2023

Chemical name	Туре	Exposure Limit V	alues	Source
Wollastonite - fibers, total dust	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Wollastonite - Fiber.	TWA		5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
m-Xylenediamine	CEILING	C).1 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
m-Xylenediamine	CEV	C).1 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
m-Xylenediamine	CEILING	C).1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Polyethylene - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (05 2013)
Polyethylene - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (05 2013)
Polyethylene - Inhalable fraction.	TWA		10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Polyethylene - Respirable fraction.	TWA		3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Polyethylene - Total dust.	TWA		10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Polyethylene - Respirable fraction.	TWA		3 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (06 2020)
Polyethylene - Total dust.	TWA		10 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (06 2020)
Stoddard solvent (Mineral Spirits)	STEL	5.	80 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
	TWA	2	90 mg/m3	Canada. British Columbia OELs: Table of Exposure Limits for Chemical Biological Substances (Workers Compensation Board); as amended (07 2007)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Stoddard solvent (Mineral Spirits)	TWA	100 ppm 5.	25 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment



Revision Date: 08/18/2023

Eye/face protection: Wear a full-face respirator, if needed. Wear safety glasses with side shields

(or goggles) and a face shield.

Skin Protection

Hand Protection: Additional Information: Use suitable protective gloves if risk of skin contact.

Skin and Body Protection: Wear suitable protective clothing. Wear chemical-resistant gloves,

footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific

information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Do not eat, drink or smoke

when using the product. Wash hands after handling. Do not get in eyes. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Do not get this material in contact with skin. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Avoid contact with

skin.

9. Physical and chemical properties

Appearance

Physical state: liquid
Form: liquid
Color: Black

Odor: Mild pungent
Odor threshold: No data available.
pH: No data available.
Melting point/freezing point: No data available.
Initial boiling point and boiling range: No data available.

Flash Point: > 93 °C > 200 °F(Setaflash Closed Cup)

Evaporation rate: Slower than Ether

Flammability (solid, gas): No
Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper:

Explosive limit - lower:

Vapor pressure:

No data available.

No data available.

No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density: 1.007

Solubility(ies)



Revision Date: 08/18/2023

Solubility in water: Practically Insoluble
Solubility (other): No data available.
Partition coefficient (n-octanol/water): No data available.
Auto-ignition temperature: No data available.
Decomposition temperature: No data available.
Viscosity: No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: Avoid contact with acids.

Hazardous Decomposition

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

Inhalation: In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

Skin Contact: May be harmful in contact with skin. Causes severe skin burns. May cause

an allergic skin reaction.

Eye contact: Causes serious eye damage.

Ingestion: Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: ATEmix: 1,539.68 mg/kg

Dermal



Revision Date: 08/18/2023

Product: ATEmix: 3,329.33 mg/kg

Inhalation

Product: ATEmix: 11.07 mg/l

ATEmix: 3.1 mg/l

Repeated dose toxicity

Product: No data available.

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

4-Nonylphenol in vivo (Rabbit): Irritating , 1 - 8 d

Benzyl alcohol in vivo (Rabbit): Slightly irritating

4-tert-Butylphenol in vivo (Rabbit): Not Classified, 7 - 10 d

m-Xylenediamine in vivo (Mouse): Corrosive, 4 h

1,3- in vivo (Rabbit): Corrosive, 1 h

Cyclohexanedimethana

mine

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

1,2- Rabbit, 24 - 72 h: Category 1

Cyclohexanediamine

4-Nonylphenol Rabbit, 24 - 72 h: Corrosive

4-tert-Butylphenol Rabbit, 24 - 72 h: Category 1

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified



Revision Date: 08/18/2023

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

Product: No data available.

In vivo

Product: No data available.

Reproductive toxicity

Product: Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure
Product:

No data available.

Specific Target Organ Toxicity - Repeated Exposure
Product:
No data available.

Aspiration Hazard

Product: No data available.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

1,2-Cyclohexanediamine LC 50 (Pimephales promelas, 96 h): 1,825 mg/l Read-across based on

grouping of substances (category approach), Key study

4-Nonylphenol EC 50 (Pimephales promelas, 96 h): 96 μg/l Experimental result, Key study

Benzyl alcohol LC 50 (Pimephales promelas, 96 h): 460 mg/l Experimental result, Key study

4-tert-Butylphenol LC 50 (Fathead minnow (Pimephales promelas), 96 h): 4.71 - 5.62 mg/l

Mortality

m-Xylenediamine LC 50 (Oryzias latipes, 96 h): 87.6 mg/l Experimental result, Key study



Revision Date: 08/18/2023

1,3-LC 50 (Leuciscus idus, 96 h): 130 mg/l Experimental result, Key study

Cyclohexanedimethanam

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

1,2-Cyclohexanediamine EC 50 (Daphnia magna, 48 h): 19.8 mg/l read-across based on grouping of

substances (category approach) Read-across based on grouping of

substances (category approach), Key study

4-Nonviphenol EC 50 (Daphnia magna, 48 h): 84.4 µg/l experimental result Experimental

result, Key study

Benzyl alcohol EC 50 (Daphnia magna, 48 h): 230 mg/l experimental result Experimental

result, Key study

EC 50 (Daphnia magna, 48 h): 4.8 mg/l experimental result Experimental 4-tert-Butylphenol

result, Key study

EC 50 (Daphnia magna, 48 h): 15.2 mg/l experimental result Experimental m-Xylenediamine

result. Key study

EC 50 (Daphnia magna, 48 h): 33.1 mg/l experimental result Experimental 1.3-

Cyclohexanedimethanam

ine

result, Key study

Chronic hazards to the aquatic environment:

Fish

No data available. **Product:**

Specified substance(s):

4-Nonylphenol NOAEL (Oncorhynchus mykiss): 0.006 mg/l experimental result

Experimental result, Key study

NOAEL (Pimephales promelas): 10 µg/l experimental result Experimental 4-tert-Butylphenol

result, Key study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

1,2-Cyclohexanediamine NOAEL (Daphnia magna): 4.16 mg/l read-across based on grouping of

substances (category approach) Read-across based on grouping of

substances (category approach), Key study

NOAEL (Daphnia magna): 0.024 mg/l experimental result Experimental 4-Nonylphenol

result, Key study

Benzyl alcohol NOAEL (Daphnia magna): 51 mg/l experimental result Experimental result.

Key study

4-tert-Butylphenol NOAEL (Daphnia magna): 0.73 mg/l experimental result Experimental result,

Key study



Revision Date: 08/18/2023

m-Xylenediamine NOAEL (Daphnia magna): 4.7 mg/l experimental result Experimental result,

Key study

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

1,2-Cyclohexanediamine 100 % Detected in water. Experimental result, Key study

4-Nonylphenol 48.2 % (35 d) Detected in water. Experimental result, Key study

Benzyl alcohol 97 % (21 d) Detected in water. Experimental result, Key study

4-tert-Butylphenol 60 % (28 d) Detected in water. Experimental result, Key study

m-Xylenediamine 49 % (28 d) Detected in water. Experimental result, Key study

1,3- 29 % (28 d) Detected in water. Experimental result, Key study

Cyclohexanedimethanami

ne

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

4-Nonylphenol Pimephales promelas, Bioconcentration Factor (BCF): 740 Aquatic sediment

Experimental result, Key study

4-tert-Butylphenol Cyprinus carpio, Bioconcentration Factor (BCF): 44 - 48 Aquatic sediment

Experimental result, Key study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Benzyl alcohol Log Kow: 1.10

Mobility in soil: No data available.

Other adverse effects: Very toxic to aquatic life with long lasting effects. Toxic to aquatic life with

long lasting effects.



Revision Date: 08/18/2023

13. Disposal considerations

Disposal methods: Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Nonylphenol), 9, PG III

CFR / DOT:

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Nonylphenol), 9, PG III

IMDG:

UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Nonylphenol), 9, PG III, MARINE POLLUTANT

Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Chemical Identity Reportable quantity

4-Nonylphenol De minimis concentration: TSCA 5(a)(2)% One-Time Export Notification

only.

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended

Chemical IdentityOSHA hazard(s)Crystalline Silicakidney effects(Quartz)/ Silica Sandlung effects

immune system effects

Cancer

CERCLA Hazardous Substance List (40 CFR 302.4):

None present or none present in regulated quantities.



Revision Date: 08/18/2023

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate (Acute) Health Hazards
Delayed (Chronic) Health Hazard
Acute toxicity (any route or exposure)
Skin Corrosion or Irritation
Serious eye damage or eye irritation
Respiratory or Skin Sensitization
Reproductive toxicity

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

Not Regulated.

US. EPCRA (SARA Title III Section 313 Toxic Chemical Release Inventory (TRI) Reporting

<u>Chemical Identity</u> <u>% by weight</u> 4-Nonylphenol 1.0%

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

None present or none present in regulated quantities.

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



WARNING

Cancer - www.P65Warnings.ca.gov

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable

VOC: When appropriately mixed with the other part, product has a VOC less water and exempt solvent of: 91 g/l



Revision Date: 08/18/2023

Regulatory VOC (less water and : 171 g/l exempt solvent)

VOC Method 310 : 16.97 %

35/37



Revision Date: 08/18/2023

Inventory Status:

Canada DSL Inventory List: One or more components in this

product are not listed on or exempt

from the Inventory.

EC Inventory: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan (ENCS) List: One or more components in this

product are not listed on or exempt

from the Inventory.

China Inv. Existing Chemical

Substances:

One or more components in this product are not listed on or exempt

from the Inventory.

Korea Existing Chemicals Inv. (KECI): One or more components in this

product are not listed on or exempt

from the Inventory.

Canada NDSL Inventory: One or more components in this

product are not listed on or exempt

from the Inventory.

Philippines PICCS: One or more components in this

product are not listed on or exempt

from the Inventory.

US TSCA Inventory: All components in this product are

listed on or exempt from the

Inventory.

New Zealand Inventory of Chemicals: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan ISHL Listing: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this

product are not listed on or exempt

from the Inventory.

Ontario Inventory: One or more components in this

product are not listed on or exempt

from the Inventory.

Mexico INSQ: One or more components in this



Revision Date: 08/18/2023

product are not listed on or exempt

from the Inventory.

Taiwan Chemical Substance Inventory: One or more components in this

product are not listed on or exempt

from the Inventory.

Australia Industrial Chem. Act (AIIC): One or more components in this

product are not listed on or exempt

from the Inventory.

Switzerland New Subs Notified/Registered:

One or more components in this product are not listed on or exempt

from the Inventory.

Thailand DIW Existing Chemical Inv.

List:

One or more components in this product are not listed on or exempt

from the Inventory.

Vietnam National Chemical Inventory: One or more components in this

product are not listed on or exempt

from the Inventory.

16.Other information, including date of preparation or last revision

Revision Date: 08/18/2023

Version #: 7.0

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.