

MISCELLANEOUS

Master Format #: 03 01 30.51

EUCO CLEAN & STRIP

CONCRETE FLOOR STRIPPER



EUCLID CHEMICAL

PACKAGING

- 5 gal (18.9 L) pail
Code: 045C 05
- 55 gal (208 L) drum
Code: 045C 55
- 1 gal (3.8 L) jugs, 4 per case
Code: 045C 27

CLEAN UP

Clean tools and equipment with soap and water.

SHELF LIFE

2 years in original, unopened package

DESCRIPTION

EUCO CLEAN & STRIP is a heavy duty concrete floor cleaner and stripper that is effective at removing curing compounds, oils, grease, most concrete sealers, and other contaminants from concrete floors. EUCO CLEAN & STRIP is formulated with a citrus-based solvent that will not etch concrete like acid based removers. EUCO CLEAN & STRIP is a safer alternative to petroleum and chlorinated solvent based removal products.

PRODUCT CHARACTERISTICS

FEATURES/BENEFITS

- High strength, concentrated formula
- Easy to apply - rinses clean with water

PRIMARY APPLICATIONS

- Facilitates removal of concrete curing compounds and cure & seals
- Breaks down grease, oil, dirt stains and rubber tire marks

APPEARANCE

Clear, light yellow liquid

PHYSICAL PROPERTIES

Weight per Gallon: 7.0 lbs/gal (0.84 kg/L)
Flash Point: 117 °F (47 °C)
Odor: Citrus

COVERAGE

Euco Clean & Strip can be diluted with water or used full strength, depending on the extent of the cleaning or stripping to be done. Experimenting with different dilution ratios will be necessary to determine which strength is most suitable. Always test a small area before use.

Stripping curing compounds or cure and seals, degreasing, heavy duty cleaning:

Suggested dilution ratio range: 5:1 (water to Clean & Strip) to full strength
Coverage: 100 to 200 ft²/gal (2.5 to 4.9 sq m²/L)

Light cleaning:

Suggested dilution ratio range: 5:1 to 10:1 (water to Clean & Strip)
Coverage: 400 to 500 ft²/gal (9.8 to 12.3 m²/L)

DIRECTIONS FOR USE

Apply the Euco Clean & Strip solution to the floor while scrubbing with a stiff broom or mechanical floor scrubber. Then, allow the Euco Clean & Strip solution to dwell on the surface for sufficient time to soften the soil, curing compounds, or cure & seal. This typically takes 20 to 40 minutes. Longer dwell times may be necessary for removal of curing compounds or cure and seals. Do not allow Euco Clean & Strip solution to dry during the dwell period - add more Euco Clean & Strip if necessary to keep the concrete wet. After the dwell period, rinse the entire floor thoroughly with water before the product dries. Additional scrubbing and pressure washing may be necessary to remove curing compounds, cure and seals, and stubborn stains. Re-application may be necessary for extremely dirty, stained floors, or hard-to-remove curing compounds or cure and seals.

PRECAUTIONS/LIMITATIONS

- Use in well ventilated areas.
- Wear protective clothing (gloves, eye protection, etc.)
- Keep away from heat and flame.
- Do not use near food.
- Do not use on resilient tile, asphalt, or painted surfaces.
- Euco Clean & Strip may soften rubber tires and cause them to become tacky. Use caution when operating wheeled equipment in these conditions.
- In all cases, consult the Safety Data Sheet before use.

Rev. 05.24

WARRANTY: The Euclid Chemical Company ("Euclid") solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Euclid, no other representations or statements made by Euclid or its representatives, in writing or orally, shall alter this warranty. EUCLID MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Euclid product fails to conform with this warranty, Euclid will replace the product at no cost to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Euclid does not authorize anyone on its behalf to make any written or oral statements which in any way alter Euclid's installation information or instructions in its product literature or on its packaging labels. Any installation of Euclid products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Euclid's products for the Buyer's intended purposes.