



Finish Line Extreme Joint Compound

Finish Line Extreme Joint Compound is a ready to use, non-asbestos, vinyl-formulation for embedding drywall tape reinforcement, metal corner beads and drywall trims over wallboard. Extreme Joint Compound may also be used for filling, applying simple textures, and smoothing and finishing coats.

Superior Characteristics

- **Resists Shrinkage and Cracking:**

Ideal because it resists shrinkage, cracks and has excellent adhesion.

- **Consistent from Batch to Batch:**

Finish Line is extremely consistent. We achieve this through thorough testing to make Finish Line products the best for our consumers.

- **Safety:**

The National Institute for Occupational Safety and Health recommends for consumer safety that eye protection be worn. They also suggest a respirator especially in a dry sanding or extremely dusty environment. Finish Line recommends wet sanding or sponging finished joints to avoid extreme amounts of dust.

- **Warranty:**

Maximum liability shall be limited to replacement of Finish Line's product.

Specifications:

Finish Line Joint Compounds are professional quality factory pre mixed vinyl based compounds. They are designed for embedding drywall tape, finishing wallboard joints, fasteners, corner bead and drywall trims. They also can be used for skim-coating, simple hand textures and patching cracks in plaster walls.

Superior Standards:

- Meets ASTM C475-89 (standard specification for joint compound and joint tape for finishing gypsum wallboard) and OSHA safety requirements

Advantages:

- Factory pre mixed
- Contractor and job site formulated
- Easy to Sand
- Approximately 20% lighter than standard joint compound
- Easy to sand
- Low shrinkage and crack resistant
- Superior Application Characteristics
- Excellent Adhesion

Job Requirements and Storage:

- Maintain 50° F minimum working temperature until dry and stable, avoid excessive heat, direct sunlight or freezing conditions

Coverage:

- 4.5 gallons covers at least 600 sq ft depending on job conditions and methods of applications

Available Packaging:

- 4.5 gal. pail
- 3.5 gal. box

Application:

- Surface should be dry and clean prior to application, final wallboard finish should meet requirements of the five levels of gypsum board finish approved by the gypsum association

Precautions:

- Wet sanding is recommended to avoid creating dust
- Use eye protection and a respirator (OSHA approved) when dry sanding
- Do not ingest
- May contain mica, talc, limestone, perlite, plaster, clay and latex
- Keep out of reach of children

Submit Approval:

Contractor: _____

Approved By: _____

Job Name: _____

Location of Job: _____

Date: _____

Signatures: _____

Finish Line Extreme Joint Compound Product Data:

- Coverage: 120 to 155 lb for every 1200 sq. foot of gypsum board (Depending on conditions of application)
- Storage: Protect from freezing or overheating and Finish Line products will have a shelf life of 1 year, under proper storage conditions.
- Finish Line Extreme Joint Compound is available by the 4.5 gallon pail or 3.5 gallon box.



FINISH LINE
PRODUCTS, INC

Finish Line Products
747 Tucker Road
Winder, GA 30680

Office (770)-307-1503
Fax (770)-307-1504