


1. Identification

| | |
|---|--|
| Product identifier | AcryliTop PC-100 - Gray |
| Other means of identification | |
| Product code | W56RACTOPG |
| Recommended use | Architectural coating and waterproofing |
| Recommended restrictions | None known. |
| Manufacturer/Importer/Supplier/Distributor information | |
| Distributed by | Holcim Solutions and Products US, LLC |
| Address | 26 Century Boulevard, Suite 205 Nashville, TN 37214 Elevate™ is a Holcim Solutions and Products US, LLC brand. |
| Website | holcimelevate.com |
| Telephone Number | 1-800-428-4442 |
| Emergency Telephone Number | For Chemical Emergency, Spill, Leak, Fire, Exposure, or Incident: CHEMTREC within USA and Canada: 1-800-424-9300 CHEMTREC outside USA and Canada: +1 703-527-3887 (collect calls accepted) |

2. Hazard(s) identification

| | | |
|--|---|-------------|
| Physical hazards | Not classified. | |
| Health hazards | Sensitization, skin | Category 1A |
| Environmental hazards | Hazardous to the aquatic environment, acute hazard | Category 2 |
| | Hazardous to the aquatic environment, long-term hazard | Category 2 |
| OSHA defined hazards | Not classified. | |
| Label elements |  | |
| Signal word | Warning | |
| Hazard statement | May cause an allergic skin reaction. Harmful to aquatic life with long lasting effects. | |
| Precautionary statement | | |
| Prevention | Avoid breathing mist/vapors. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves. | |
| Response | If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. | |
| Storage | Store away from incompatible materials. | |
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. | |
| Hazard(s) not otherwise classified (HNOC) | None known. | |
| Supplemental information | None. | |

3. Composition/information on ingredients

Mixtures

| Chemical name | CAS number | % |
|------------------------------|------------|-----------|
| Titanium Dioxide | 13463-67-7 | 3 - 7 |
| Propane -1,2 -diol | 57-55-6 | 1 - 5 |
| Quartz (SiO ₂) | 14808-60-7 | 0.1 - < 1 |
| Diuron | 330-54-1 | 0.1 |
| 2-octyl-2H-isothiazol-3-one | 26530-20-1 | 0.07 |
| 2-Methyl-2H-isothiazol-3-one | 2682-20-4 | 0.006 |

Composition comments All concentrations are in percent by weight unless otherwise indicated. Components not listed are either non-hazardous or are below reportable limits. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical During fire, gases hazardous to health may be formed such as: Carbon oxides (CO_x).

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up This product is miscible in water. Prevent product from entering drains.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

| Components | Type | Value |
|---|------|------------------------|
| Quartz (SiO ₂) (CAS 14808-60-7) | TWA | 0.05 mg/m ³ |

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|------------------------------------|------|----------------------|----------------------|
| Ammonium hydroxide (CAS 1336-21-6) | PEL | 35 mg/m ³ | |
| | | 50 ppm | |
| Limestone (CAS 1317-65-3) | PEL | 5 mg/m ³ | Respirable fraction. |
| | | 15 mg/m ³ | Total dust. |
| Titanium Dioxide (CAS 13463-67-7) | PEL | 15 mg/m ³ | Total dust. |

US. OSHA Table Z-3 (29 CFR 1910.1000)

| Components | Type | Value | Form |
|---|------|-----------------------|----------------------|
| Limestone (CAS 1317-65-3) | TWA | 5 mg/m ³ | Respirable fraction. |
| | | 15 mg/m ³ | Total dust. |
| | | 50 mppcf | Total dust. |
| | | 15 mppcf | Respirable fraction. |
| Quartz (SiO ₂) (CAS 14808-60-7) | TWA | 0.1 mg/m ³ | Respirable. |
| | | 2.4 mppcf | Respirable. |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|---|------|-------------------------|--------------------------------|
| Ammonium hydroxide (CAS 1336-21-6) | STEL | 35 ppm | |
| | TWA | 25 ppm | |
| Diuron (CAS 330-54-1) | TWA | 10 mg/m ³ | |
| Quartz (SiO ₂) (CAS 14808-60-7) | TWA | 0.025 mg/m ³ | Respirable fraction. |
| Titanium Dioxide (CAS 13463-67-7) | TWA | 2.5 mg/m ³ | Respirable finescale particles |
| | | 0.2 mg/m ³ | Respirable nanoscale particles |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|------------------------------------|------|----------------------|-------------|
| Ammonium hydroxide (CAS 1336-21-6) | STEL | 27 mg/m ³ | |
| | | 35 ppm | |
| | | 18 mg/m ³ | |
| Diuron (CAS 330-54-1) | TWA | 25 ppm | |
| | | 10 mg/m ³ | |
| Limestone (CAS 1317-65-3) | TWA | 5 mg/m ³ | Respirable. |
| | | 10 mg/m ³ | Total |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|---|------|------------------------|------------------|
| Quartz (SiO ₂) (CAS 14808-60-7) | TWA | 0.05 mg/m ³ | Respirable dust. |

US. Workplace Environmental Exposure Level (WEEL) Guides

| Components | Type | Value | Form |
|----------------------------------|------|----------------------|----------|
| Propane -1,2 -diol (CAS 57-55-6) | TWA | 10 mg/m ³ | Aerosol. |

| | |
|--|---|
| Biological limit values | No biological exposure limits noted for the ingredient(s). |
| Appropriate engineering controls | Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. |
| Individual protection measures, such as personal protective equipment | |
| Eye/face protection | Wear safety glasses with side shields (or goggles). Face shield is recommended. |
| Skin protection | |
| Hand protection | Wear appropriate chemical resistant gloves. Examples of preferred glove barrier materials include: Nitrile. Suitable gloves can be recommended by the glove supplier. |
| Skin protection | |
| Other | Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. |
| Respiratory protection | If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. |
| Thermal hazards | Wear appropriate thermal protective clothing, when necessary. |
| General hygiene considerations | Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace. |

9. Physical and chemical properties**Appearance**

Physical state Liquid.

Form Viscous liquid.

Color Light gray.

Odor Mild ammonia.

Odor threshold Not available.

pH 8.8 (68 °F (20 °C))

Melting point/freezing point Not determined.

Initial boiling point and boiling range Not determined.

Flash point > 199.4 °F (> 93 °C) Closed Cup

Evaporation rate Not determined.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not determined.

Explosive limit - upper (%) Not determined.

Vapor pressure Not determined.

Vapor density Not determined.

Relative density 1.4 (77 °F (25 °C))

Solubility(ies)

Solubility (water) Soluble.

Partition coefficient (n-octanol/water) Not applicable, product is a mixture.

| | |
|----------------------------------|-------------------------|
| Auto-ignition temperature | Not determined. |
| Decomposition temperature | Not determined. |
| Viscosity | 115 ku (77 °F (25 °C)) |
| Other information | Solids content: 65% |
| Density | Not determined. |
| Explosive properties | Not explosive. |
| Kinematic viscosity | Not determined. |
| Oxidizing properties | Not oxidizing. |
| VOC | 44.5 g/l 0.37 lb/gal |

10. Stability and reactivity

| | |
|---|---|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |
| Conditions to avoid | Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| Incompatible materials | Strong oxidizing agents. Fluorine. |
| Hazardous decomposition products | No hazardous decomposition products are known. |

11. Toxicological information

Information on likely routes of exposure

| | |
|---|--|
| Inhalation | No adverse effects due to inhalation are expected. Inhalation of titanium dioxide dust may cause cancer, however due to the physical form of the product, inhalation of dust is not likely. Crystalline silica poses a health hazard when it is inhaled as a dust. Normal use of product does not generate silica or other dust. |
| Skin contact | May cause an allergic skin reaction. |
| Eye contact | Direct contact with eyes may cause temporary irritation. |
| Ingestion | Expected to be a low ingestion hazard. |
| Symptoms related to the physical, chemical and toxicological characteristics | May cause an allergic skin reaction. Dermatitis. Rash. |

Information on toxicological effects

| | |
|-----------------------|-----------------------------------|
| Acute toxicity | Not expected to be acutely toxic. |
|-----------------------|-----------------------------------|

| Components | Species | Test Results |
|---|---------|--------------|
| 2-octyl-2H-isothiazol-3-one (CAS 26530-20-1) | | |
| <u>Acute</u> | | |
| Dermal | | |
| ATE | | 311 mg/kg |
| Inhalation | | |
| <i>Mist</i> | | |
| ATE | | 0.27 mg/l |
| Oral | | |
| ATE | | 125 mg/kg |
| 3-Iodo-2-propynyl butylcarbamate (CAS 55406-53-6) | | |
| <u>Acute</u> | | |
| Dermal | | |
| LD50 | Rabbit | > 2000 mg/kg |
| Oral | | |
| LD50 | Rat | 1.1 g/kg |

| Components | Species | Test Results |
|---|--|--------------------------|
| Ammonium hydroxide (CAS 1336-21-6) | | |
| Acute | | |
| Oral | | |
| LD50 | Rat | 350 mg/kg |
| Propane -1,2 -diol (CAS 57-55-6) | | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | 20800 mg/kg |
| Oral | | |
| LD50 | Rat | 22000 mg/kg |
| Quartz (SiO ₂) (CAS 14808-60-7) | | |
| Chronic | | |
| Inhalation | | |
| LOEC | Human | 0.0563 mg/m ³ |
| Titanium Dioxide (CAS 13463-67-7) | | |
| Acute | | |
| Oral | | |
| LD50 | Rat | > 5000 mg/kg |
| Skin corrosion/irritation | Prolonged skin contact may cause temporary irritation. | |
| Serious eye damage/eye irritation | Direct contact with eyes may cause temporary irritation. | |
| Respiratory or skin sensitization | | |
| Respiratory sensitization | Not a respiratory sensitizer. | |
| Skin sensitization | May cause an allergic skin reaction. | |
| Germ cell mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. | |
| Carcinogenicity | Due to the form of the product, exposure to the potentially carcinogenic components is not expected. Titanium dioxide is considered carcinogenic only when in an inhalable powdered form. Crystalline silica poses a health hazard when it is inhaled as a dust. Normal use of product does not generate silica or other dust. | |
| IARC Monographs. Overall Evaluation of Carcinogenicity | | |
| Quartz (SiO ₂) (CAS 14808-60-7) | 1 Carcinogenic to humans. | |
| Titanium Dioxide (CAS 13463-67-7) | 2B Possibly carcinogenic to humans. | |
| NTP Report on Carcinogens | | |
| Quartz (SiO ₂) (CAS 14808-60-7) | Known To Be Human Carcinogen. | |
| OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) | | |
| Quartz (SiO ₂) (CAS 14808-60-7) | Cancer | |
| Reproductive toxicity | This product is not expected to cause reproductive or developmental effects. | |
| Specific target organ toxicity - single exposure | Not classified. | |
| Specific target organ toxicity - repeated exposure | Not classified. | |
| Aspiration hazard | Not an aspiration hazard. | |

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

| Components | Species | Test Results |
|--|---------|----------------------|
| 2-octyl-2H-isothiazol-3-one (CAS 26530-20-1) | | |
| Aquatic | | |
| <i>Acute</i> | | |
| Algae | EC50 | Algae |
| Crustacea | EC50 | Crustacea |
| | | 0.15 mg/l, 72 Hours |
| | | 0.181 mg/l, 48 Hours |

| Components | | Species | Test Results |
|----------------|------|-----------|----------------------|
| Fish | LC50 | Fish | 0.122 mg/l, 96 Hours |
| <i>Chronic</i> | | | |
| Algae | NOEC | Algae | 0.068 mg/l, 72 Hours |
| Crustacea | NOEC | Crustacea | 0.035 mg/l, 21 days |
| Fish | NOEC | Fish | 0.022 mg/l, 21 days |

3-Iodo-2-propynyl butylcarbamate (CAS 55406-53-6)

Aquatic

Fish LC50 Oncorhynchus mykiss 67 µg/l, 96 hours

Titanium Dioxide (CAS 13463-67-7)

Aquatic

Acute

Crustacea EC50 Daphnia magna > 100 mg/l, 48 Hours

Fish LL50 Oryzias latipes > 100 mg/l, 96 Hours

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available for this product.

Partition coefficient n-octanol / water (log Kow)

Ammonium hydroxide (CAS 1336-21-6) -2.66

Diuron (CAS 330-54-1) 2.68

Propane -1,2 -diol (CAS 57-55-6) -0.92

Mobility in soil No data available.

Other adverse effects No data available.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number UN3082

UN proper shipping name Environmentally hazardous substance, liquid, n.o.s. (Diuron RQ = 100000 LBS, 2-octyl-2H-isothiazol-3-one)

Transport hazard class(es)

Class 9

Subsidiary risk -

Label(s) 9

Packing group III

Environmental hazards

Marine pollutant Yes.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions 8, 146, 173, 335, IB3, T4, TP1, TP29

Packaging exceptions 155

Packaging non bulk 203

Packaging bulk 241

Non-bulk shipments may not be subject to DOT provisions as per 49CFR 171.4(c). Refer to regulation for specific requirements for this exception.

IATA

UN number UN3082
UN proper shipping name Environmentally hazardous substance, liquid, n.o.s. (Diuron, 2-octyl-2H-isothiazol-3-one)
Transport hazard class(es)
Class 9
Subsidiary risk -
Packing group III
Environmental hazards Yes.
ERG Code 9L
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Non-bulk shipments may not be subject to IATA provisions as per special provision A147. Refer to IATA regulations for specific requirements for this exception.

IMDG

UN number UN3082
UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Diuron, 2-octyl-2H-isothiazol-3-one)
Transport hazard class(es)
Class 9
Subsidiary risk -
Packing group III
Environmental hazards
Marine pollutant Yes.
EmS F-A, S-F
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Non-bulk shipments may not be subject to IMDG provisions as per special provision 375. Refer to IMDG regulations for specific requirements for this exception.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

2-Methyl-2H-isothiazol-3-one (CAS 2682-20-4) 1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

Ammonium hydroxide (CAS 1336-21-6) Listed.
Diuron (CAS 330-54-1) Listed.

SARA 304 Emergency release notification

Ammonia; Ammonia (anhydrous) (CAS 1336-21-6) 100 LBS

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (SiO₂) (CAS 14808-60-7) Cancer
lung effects
immune system effects
kidney effects

Toxic Substances Control Act (TSCA) All components of the mixture on the TSCA 8(b) inventory are designated "active".

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

| Chemical name | CAS number | Reportable quantity (pounds) | Threshold planning quantity (pounds) | Threshold planning quantity, lower value (pounds) | Threshold planning quantity, upper value (pounds) |
|---------------|------------|------------------------------|--------------------------------------|---|---|
|---------------|------------|------------------------------|--------------------------------------|---|---|

Ammonium hydroxide 1336-21-6 100 500

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Respiratory or skin sensitization

SARA 313 (TRI reporting)
Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Ammonium hydroxide (CAS 1336-21-6)

Safe Drinking Water Act (SDWA) Contains component(s) regulated under the Safe Drinking Water Act.

US state regulations

US. Massachusetts RTK - Substance List

Ammonium hydroxide (CAS 1336-21-6)
Diuron (CAS 330-54-1)
Limestone (CAS 1317-65-3)
Quartz (SiO₂) (CAS 14808-60-7)
Titanium Dioxide (CAS 13463-67-7)

US. New Jersey Worker and Community Right-to-Know Act

3-Iodo-2-propynyl butylcarbamate (CAS 55406-53-6)
Ammonium hydroxide (CAS 1336-21-6)
Diuron (CAS 330-54-1)
Limestone (CAS 1317-65-3)
Propane -1,2 -diol (CAS 57-55-6)
Quartz (SiO₂) (CAS 14808-60-7)
Titanium Dioxide (CAS 13463-67-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Ammonium hydroxide (CAS 1336-21-6)
Diuron (CAS 330-54-1)
Limestone (CAS 1317-65-3)
Propane -1,2 -diol (CAS 57-55-6)
Quartz (SiO₂) (CAS 14808-60-7)
Titanium Dioxide (CAS 13463-67-7)

US. Rhode Island RTK

Ammonium hydroxide (CAS 1336-21-6)
Diuron (CAS 330-54-1)
Limestone (CAS 1317-65-3)
Propane -1,2 -diol (CAS 57-55-6)
Quartz (SiO₂) (CAS 14808-60-7)
Titanium Dioxide (CAS 13463-67-7)

California Proposition 65



WARNING: This product can expose you to chemicals including 1,4-Dioxane, Diuron, Ethylene oxide, Methyloxirane, which are known to the State of California to cause cancer, and Ethylene oxide, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

| | |
|------------------------------|-------------------------|
| 1,4-Dioxane (CAS 123-91-1) | Listed: January 1, 1988 |
| Diuron (CAS 330-54-1) | Listed: May 31, 2002 |
| Ethylene oxide (CAS 75-21-8) | Listed: July 1, 1987 |
| Methyloxirane (CAS 75-56-9) | Listed: October 1, 1988 |

California Proposition 65 - CRT: Listed date/Developmental toxin

Ethylene oxide (CAS 75-21-8) Listed: August 7, 2009

California Proposition 65 - CRT: Listed date/Female reproductive toxin

Ethylene oxide (CAS 75-21-8) Listed: February 27, 1987

California Proposition 65 - CRT: Listed date/Male reproductive toxin

Ethylene oxide (CAS 75-21-8) Listed: August 7, 2009

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Ammonium hydroxide (CAS 1336-21-6)

Quartz (SiO₂) (CAS 14808-60-7)

Titanium Dioxide (CAS 13463-67-7)

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| Australia | Australian Inventory of Industrial Chemicals (AICIS) | No |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | Yes |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| Taiwan | Taiwan Chemical Substance Inventory (TCSI) | No |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision**Issue date** 14-December-2022**Revision date** -**Version #** 01**HMIS® ratings**
Health: 2
Flammability: 0
Physical hazard: 0**Disclaimer**
Holcim Solutions and Products US, LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.