

# Technical Information Sheet



## Ceramic Coated Roofing Granules

Item Description	Item Number
White	W70RACGGWH
Black	W70RACGGBK

### Description

Ceramic coated roofing granules are made available in 50 lb (22.7 kg) metal pails.

### Method of Application

Holcim recommends that granules be applied to areas of asphalt “bleed-out” while the asphalt is still in a molten state. Areas of “bleed-out” at inside and outside corners require application of granules.

### Precautions

- Refer to Safety Data Sheets (SDS) for additional safety information.
- Minimize the amount of dust generated when applying or handling this product. Use in well ventilated area.

### LEED® Information

Post-Consumer Recycled Content: 0%  
 Post Industrial Recycled Content: 0%  
 Manufacturing Location: Beech Grove, IN

**NOTE:** LEED® is a registered trademark of the U.S. Green Building Council

Packaging	
Properties	Value
Pail	5 Gallon (18.9 L)
Weight	50 lb (22.7 kg)
Pallet Size	48" x 39" (1.2 m x 1.0 m)
Pails per Pallet	36
Pallet Weight	2000 lb (907 kg)
Pallets per Truckload	24

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.