

Technical Information Sheet

Image Coming Soon

Coiled Metal Batten Strip

Item Description	Item Number
3" (76.2 mm) o.c. Pre-Punched Strips	W56RAC3052

Description

Coiled Metal Batten Strip is specifically designed to be used for anchoring Elevate membranes and flashing details as specified in Elevate Specifications and Details. Coiled Metal Batten Strip is packaged in a weather-resistant cardboard dispensing package which contains 220' (67 m) of batten strip. Using Coiled Metal Batten Strips in lieu of conventional pre-cut strips reduces labor and storage space. Coiled Metal Batten Strip has 3" (76.2 mm) o.c. pre-punched holes for greater flexibility in attaching to steel decks.

Method of Application

Attach batten strips to the roof substrate or penetration using the appropriate Elevate fastener. Do not overdrive or underdrive fasteners. Start at one end of the batten strip and fasten towards the other to reduce bowing between fasteners.

Storage

Store in original unopened containers protected from the weather.

Packaging

220' (67 m) per coil, 52 coils per pallet

Precautions

When cutting battens, round ends and remove burrs and sharp edges with a file.

LEED® Information

Post-Consumer Recycled Content: 8%

Post Industrial Recycled Content: 17%

Manufacturing Location: Cleveland, OH

NOTE: LEED® is a registered trademark of the U.S. Green Building Council



Typical Properties

Properties	Value
Material	Galvalume® AZ 55
Corrosion Resistance	Meets FM No. 4470 criteria
Length	220' (67 m) per coil
Width	1" (25.4 mm)
Thickness	0.04"/0.05" (1.13 mm/1.29 mm)
Holes	0.34" (8.7 mm) diameter, at 3" (76.2 mm) o.c. (Accommodates Elevate All-Purpose, Heavy-Duty, Heavy-Duty Plus and Concrete Drive Fasteners)
Weight	32 lb (14.5 kg) per coil
<i>Galvalume® is a registered trademark of BIEC International, Inc.</i>	

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.