

Technical Information Sheet



EcoWhite™ 6" QuickSeam™ Flashing P

Item Description	Item Number
6" x 100' (152 mm x 30.5 m) color: white	W56RACEF60

Description

Elevate™ EcoWhite 6" (152 mm) QuickSeam Flashing P is a semi-cured EPDM flashing laminated to cured QuickSeam tape. EcoWhite QuickSeam Flashing P is used to flash gravel stops and other details as specified in the Specifications and Details.

Method of Application

1. Use Single-Ply QuickPrime™ Primer or Single-Ply QuickPrime LVOC Primer with a QuickScrubber™ or QuickScrubber Plus pad and handle to clean and prime membrane and metal mating surfaces.
2. Refer to application instructions for specifics: Technical Database, www.holcimelevate.com

Storage

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 100 °F (37.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.
- Shelf life of 6 months can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

Shelf Life

Shelf life of 6 months can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C). Shelf life will be shortened if exposed to elevated temperatures.

Precautions

- Refer to Safety Data Sheets (SDS) for additional safety information.
- EcoWhite EPDM QuickSeam Flashing is semi-cured. DO NOT STRETCH.

LEED® Information

Post-Consumer Recycled Content: 0%
 Post Industrial Recycled Content: 0%
 Manufacturing Location: Prescott, AR

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

Typical Properties			
QuickSeam Tape		EPDM Flashing	
	Value		Value
Base	Rubber Polymer	Base	EPDM
Color	White	Color	White
Solvents	None	Solvents	None
Solids	100%	Solids	100%
Cured State	Cured	Cured State	Uncured
Thickness	0.025" (0.635 mm) ± 0.007" (0.18 mm)	Thickness	0.060" (1.6 mm) ± 0.005" (0.13 mm)
Width	6 1/4" (159 mm) +0, -1/16"	Width	6" (152 mm) +0, -1/8"

Packaging			
Item	Size	Carton	Pallet
Roll	6" (152 mm) x 100' (30.5 m)	2 Roll per Carton	36 Cartons per Pallet
NOTE: QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.			

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.