

**1. Identification****Product identifier** Elevate EcoWhite Lap Sealant**Other means of identification****Product code** W56358703A**Recommended use** Construction. Sealant.**Recommended restrictions** None known.**Manufacturer/Importer/Supplier/Distributor information****Distributed by** Holcim Solutions and Products US, LLC**Address** 26 Century Boulevard, Suite 205  
Nashville, TN 37214

Elevate™ is a Holcim Solutions and Products US, LLC brand.

**Website** holcimelevate.com**Telephone Number** 1-800-428-4442**Emergency Telephone Number**

For Chemical Emergency, Spill, Leak, Fire, Exposure, or Incident:

CHEMTREC within USA and Canada: 1-800-424-9300

CHEMTREC outside USA and Canada: +1 703-527-3887 (collect calls accepted)

**2. Hazard(s) identification****Physical hazards** Flammable solids Category 1**Health hazards** Skin corrosion/irritation Category 2**Environmental hazards** Hazardous to the aquatic environment, acute hazard Category 3

Hazardous to the aquatic environment, long-term hazard Category 3

**OSHA defined hazards** Not classified.**Label elements****Signal word** Danger**Hazard statement** Flammable solid. Causes skin irritation. Harmful to aquatic life with long lasting effects.**Precautionary statement****Prevention**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Wash thoroughly after handling. Avoid release to the environment. Wear protective gloves/eye protection/face protection.

**Response**

If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use carbon dioxide, dry powder, water fog to extinguish.

**Storage**

Store away from incompatible materials.

**Disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations.

**Hazard(s) not otherwise classified (HNOC)**

None known.

**Supplemental information**

None.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	CAS number	%
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	7 - 13
Solvent naphtha (petroleum), medium aliph.	64742-88-7	1 - 5
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	< 2.5
Titanium Dioxide	13463-67-7	< 2.5
Quartz (SiO <sub>2</sub> )	14808-60-7	< 0.5

#### Composition comments

All concentrations are in percent by weight unless otherwise indicated. Components not listed are either non-hazardous or are below reportable limits. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

### 4. First-aid measures

#### Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

#### Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

#### Eye contact

Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.

#### Ingestion

Rinse mouth. Get medical attention if symptoms occur.

#### Most important symptoms/effects, acute and delayed

Skin irritation. May cause redness and pain.

#### Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

#### General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

### 5. Fire-fighting measures

#### Suitable extinguishing media

Water fog. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>).

#### Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

#### Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed such as: Carbon oxides (CO<sub>x</sub>).

#### Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

#### Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers.

#### Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

#### General fire hazards

Flammable solid.

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up**

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Prevent product from entering drains. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Absorb in vermiculite, dry sand or earth and place into containers. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

**Environmental precautions**

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

**7. Handling and storage****Precautions for safe handling**

Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. When using do not smoke. Explosion-proof general and local exhaust ventilation.

**Conditions for safe storage, including any incompatibilities**

Keep away from heat, spark, open flames and other sources of ignition. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

**8. Exposure controls/personal protection****Occupational exposure limits****US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)**

Components	Type	Value
Quartz (SiO <sub>2</sub> ) (CAS 14808-60-7)	TWA	0.05 mg/m <sup>3</sup>

**US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	PEL	5 mg/m <sup>3</sup>	Mist.
		2000 mg/m <sup>3</sup>	
		500 ppm	
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)	PEL	400 mg/m <sup>3</sup>	
		100 ppm	
Solvent naphtha (petroleum), medium aliph. (CAS 64742-88-7)	PEL	400 mg/m <sup>3</sup>	
		100 ppm	
Titanium Dioxide (CAS 13463-67-7)	PEL	15 mg/m <sup>3</sup>	Total dust.

**US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)**

Components	Type	Value	Form
Quartz (SiO <sub>2</sub> ) (CAS 14808-60-7)	TWA	0.1 mg/m <sup>3</sup>	Respirable.
		2.4 mppcf	Respirable.
Titanium Dioxide (CAS 13463-67-7)	TWA	5 mg/m <sup>3</sup>	Respirable fraction.
		15 mg/m <sup>3</sup>	Total dust.
		50 mppcf	Total dust.

**US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)**

Components	Type	Value	Form
		15 mppcf	Respirable fraction.

**US. ACGIH Threshold Limit Values (TLV)**

Components	Type	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	TWA	5 mg/m3	Inhalable fraction.
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Titanium Dioxide (CAS 13463-67-7)	TWA	2.5 mg/m3	Respirable finescale particles
		0.2 mg/m3	Respirable nanoscale particles

**NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended**

Components	Type	Value
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	IDLH	2500 mg/m3
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)	IDLH	1 %
		1000 ppm
Quartz (SiO2) (CAS 14808-60-7)	IDLH	50 mg/m3
Solvent naphtha (petroleum), medium aliph. (CAS 64742-88-7)	IDLH	1 %
		1000 ppm

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)	TWA	400 mg/m3	
		100 ppm	
Quartz (SiO2) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

**Biological limit values**

No biological exposure limits noted for the ingredient(s).

**Appropriate engineering controls**

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.

**Individual protection measures, such as personal protective equipment**

**Eye/face protection**

Wear safety glasses with side shields (or goggles).

**Skin protection**

**Hand protection**

Wear appropriate chemical resistant gloves. Examples of preferred glove barrier materials include: Nitrile. Nitrile butyl rubber (NBR). Chloroprene rubber. Suitable gloves can be recommended by the glove supplier.

**Skin protection**

**Other**

Wear appropriate chemical resistant clothing.

<b>Respiratory protection</b>	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Appropriate respirator selection should be made by a qualified professional.
<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>General hygiene considerations</b>	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

### Appearance

<b>Physical state</b>	Solid.
<b>Form</b>	Paste.
<b>Color</b>	White.
<b>Odor</b>	Petroleum-like.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not determined.
<b>Melting point/freezing point</b>	Not determined.
<b>Initial boiling point and boiling range</b>	267.8 °F (131 °C)
<b>Flash point</b>	< 77 °F (< 25 °C)
<b>Evaporation rate</b>	9.2 (68 °F (20 °C))
<b>Flammability (solid, gas)</b>	Flammable solid.

### Upper/lower flammability or explosive limits

<b>Explosive limit - lower (%)</b>	Not applicable, material is a solid.
<b>Explosive limit - upper (%)</b>	Not applicable, material is a solid.

<b>Vapor pressure</b>	Not determined.
<b>Vapor density</b>	3.8
<b>Relative density</b>	1.35 (68 °F (20 °C))

### Solubility(ies)

<b>Solubility (water)</b>	Soluble
<b>Partition coefficient (n-octanol/water)</b>	Not applicable, product is a mixture.

<b>Auto-ignition temperature</b>	509 °F (265 °C)
<b>Decomposition temperature</b>	Not applicable as the product is not unstable.

<b>Viscosity</b>	Not available.
------------------	----------------

<b>Other information</b>	Solids: 83.6% Organic solvents: 16.4%
--------------------------	--

<b>Density</b>	11.8499 lb/gal 1.42 g/cm <sup>3</sup>
----------------	--

<b>Explosive properties</b>	Not explosive.
-----------------------------	----------------

<b>Kinematic viscosity</b>	> 20.5 cSt
----------------------------	------------

<b>Oxidizing properties</b>	Not oxidizing.
-----------------------------	----------------

<b>VOC</b>	< 250 g/l
------------	-----------

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
-------------------	---

<b>Chemical stability</b>	Material is stable under normal conditions.
---------------------------	---

<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
---	---

<b>Conditions to avoid</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with incompatible materials.
----------------------------	---

<b>Incompatible materials</b>	Acids. Strong oxidizing agents. Fluorine.
-------------------------------	---

**Hazardous decomposition products** No hazardous decomposition products are known.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	No adverse effects due to inhalation are expected. Crystalline silica poses a health hazard when it is inhaled as a dust. Normal use of product does not generate silica or other dust.
<b>Skin contact</b>	Causes skin irritation.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Ingestion</b>	Expected to be a low ingestion hazard.

**Symptoms related to the physical, chemical and toxicological characteristics** Skin irritation. May cause redness and pain.

### Information on toxicological effects

**Acute toxicity** Not expected to be acutely toxic.

<b>Components</b>	<b>Species</b>	<b>Test Results</b>
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
<i>Aerosol</i>		
LC50	Rat	> 5.53 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rat	> 2920 mg/kg
<b>Inhalation</b>		
LC50	Rat	> 23300 mg/m <sup>3</sup>
<b>Oral</b>		
LD50	Rat	> 5840 mg/kg
Quartz (SiO <sub>2</sub> ) (CAS 14808-60-7)		
<b>Chronic</b>		
<b>Inhalation</b>		
LOEC	Human	0.0563 mg/m <sup>3</sup>
Solvent naphtha (petroleum), medium aliph. (CAS 64742-88-7)		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	> 2000 mg/kg
<b>Inhalation</b>		
<i>Vapor</i>		
LC50	Rat	> 5.28 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg
Titanium Dioxide (CAS 13463-67-7)		
<b>Acute</b>		
<b>Inhalation</b>		
LC50	Rat	> 6.82 mg/l, 4 Hours
<b>Oral</b>		
LD50	Rat	> 5000 mg/kg

<b>Skin corrosion/irritation</b>	Causes skin irritation.
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation.
<b>Respiratory or skin sensitization</b>	
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	Crystalline silica poses a health hazard when it is inhaled as a dust. Normal use of product does not generate silica or other dust. Inhalation of titanium dioxide dust may cause cancer, however due to the physical form of the product, inhalation of dust is not likely.

#### **IARC Monographs. Overall Evaluation of Carcinogenicity**

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	3 Not classifiable as to carcinogenicity to humans.
Quartz (SiO <sub>2</sub> ) (CAS 14808-60-7)	1 Carcinogenic to humans.
Titanium Dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.

#### **NTP Report on Carcinogens**

Quartz (SiO <sub>2</sub> ) (CAS 14808-60-7)	Known To Be Human Carcinogen.
---	-------------------------------

#### **OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)**

Quartz (SiO <sub>2</sub> ) (CAS 14808-60-7)	Cancer
---	--------

<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.
<b>Specific target organ toxicity - single exposure</b>	Not classified.
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	Not an aspiration hazard.

## **12. Ecological information**

<b>Ecotoxicity</b>	Harmful to aquatic life with long lasting effects.
<b>Persistence and degradability</b>	No data is available on the degradability of this product.
<b>Bioaccumulative potential</b>	No data available.
<b>Mobility in soil</b>	The product is soluble in water.
<b>Other adverse effects</b>	The product contains volatile organic compounds which have a photochemical ozone creation potential.

## **13. Disposal considerations**

<b>Disposal instructions</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Local disposal regulations</b>	Dispose in accordance with all applicable regulations.
<b>Hazardous waste code</b>	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Waste from residues / unused products</b>	Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## **14. Transport information**

<b>DOT</b>	
<b>UN number</b>	UN1325
<b>UN proper shipping name</b>	Flammable solids, organic, n.o.s. (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics RQ = 885 LBS; Solvent Naphtha (petroleum), Medium Aliph. RQ = 2273 LBS)
<b>Transport hazard class(es)</b>	
<b>Class</b>	4.1
<b>Subsidiary risk</b>	-

<b>Label(s)</b>	4.1
<b>Packing group</b>	II
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.
<b>Special provisions</b>	A1, IB8, IP2, IP4, T3, TP33
<b>Packaging exceptions</b>	151
<b>Packaging non bulk</b>	212
<b>Packaging bulk</b>	240

#### IATA

<b>UN number</b>	UN1325
<b>UN proper shipping name</b>	Flammable solid, organic, n.o.s. (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics; Solvent Naphtha (petroleum), Medium Aliph.)
<b>Transport hazard class(es)</b>	
<b>Class</b>	4.1
<b>Subsidiary risk</b>	-
<b>Packing group</b>	II
<b>Environmental hazards</b>	No.
<b>ERG Code</b>	3L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

#### IMDG

<b>UN number</b>	UN1325
<b>UN proper shipping name</b>	FLAMMABLE SOLID, ORGANIC, N.O.S. (Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics; Solvent Naphtha (petroleum), Medium Aliph.)
<b>Transport hazard class(es)</b>	
<b>Class</b>	4.1
<b>Subsidiary risk</b>	-
<b>Packing group</b>	II
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No.
<b>EmS</b>	F-A, S-G
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

## 15. Regulatory information

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0) Listed.

Solvent naphtha (petroleum), medium aliph. (CAS 64742-88-7) Listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (SiO <sub>2</sub> ) (CAS 14808-60-7)	Cancer lung effects immune system effects kidney effects
---	---

**Toxic Substances Control Act (TSCA)** All components of the mixture on the TSCA 8(b) inventory are designated "active".

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

##### SARA 302 Extremely hazardous substance

Not listed.



**SARA 311/312 Hazardous chemical** Yes  
**Classified hazard categories** Flammable (gases, aerosols, liquids, or solids)  
Skin corrosion or irritation

**SARA 313 (TRI reporting)**  
Not regulated.

#### Other federal regulations

##### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

##### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

#### US state regulations

##### US. Massachusetts RTK - Substance List

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)

Quartz (SiO<sub>2</sub>) (CAS 14808-60-7)

Titanium Dioxide (CAS 13463-67-7)

##### US. New Jersey Worker and Community Right-to-Know Act

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)

Quartz (SiO<sub>2</sub>) (CAS 14808-60-7)

Solvent naphtha (petroleum), medium aliph. (CAS 64742-88-7)

Titanium Dioxide (CAS 13463-67-7)

##### US. Pennsylvania Worker and Community Right-to-Know Law

Quartz (SiO<sub>2</sub>) (CAS 14808-60-7)

Titanium Dioxide (CAS 13463-67-7)

##### US. Rhode Island RTK

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)

Quartz (SiO<sub>2</sub>) (CAS 14808-60-7)

Titanium Dioxide (CAS 13463-67-7)

##### California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

##### US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (CAS 64742-49-0)

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

**Issue date** 28-February-2023

**Revision date** 02-August-2023

**Version #** 02

**HMIS® ratings** Health: 2  
Flammability: 1  
Physical hazard: 0  
Personal protection: D

**Disclaimer** Holcim Solutions and Products US, LLC cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.