

# Technical Information Sheet



## EcoWhite™ QuickSeam™ Corner Flashing

Item Description	Item Number
Corner Flashing 8.5" (216 mm) Diameter	W56RACEWCF

### Description

Elevate™ EcoWhite EPDM QuickSeam Corner Flashing consists of Elevate flashing factory laminated to QuickSeam Tape. It is 8.5" (216 mm) in diameter and is designed to flash inside and outside corners in conjunction with EcoWhite EPDM Roof Systems.

### Method of Application

1. Use Single-Ply QuickPrime™ Primer or Single-Ply QuickPrime LVOC Primer with a QuickScrubber™ or QuickScrubber Plus pad and handle to clean and prime mating surfaces.
2. Refer to Elevate Installation Instruction Sheet for EcoWhite EPDM QuickSeam Corner Flashing (included in each carton) and Holcim Specifications and Details.
3. When cloudy conditions below 60 °F (15.6 °C) occur, use heat guns (without ignition sources) to heat EcoWhite EPDM QuickSeam Corner Flashing. This will ensure good formability of the EcoWhite EPDM QuickSeam Corner Flashing to the primed substrate.
4. On sunny days less than 70 °F (21.1 °C), place EcoWhite EPDM QuickSeam Corner Flashing on roof (prior to application) with flashing side up to allow EcoWhite EPDM QuickSeam Corner Flashing to warm to ensure good formability.
5. On sunny days greater than 70 °F (21.1 °C), place EcoWhite EPDM QuickSeam Corner Flashing on roof (prior to application) with release paper side up to prevent EcoWhite EPDM QuickSeam Corner Flashing from gaining too much heat and to ensure good formability.
6. Refer to application instructions for specifics: Technical Database, [www.holcimelevate.com](http://www.holcimelevate.com)

### Storage

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 100 °F (37.7 °C).
- When exposed to lower temperatures, restore to room temperature prior to use.
- Shelf life of 6 months can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

## Shelf Life

Shelf life of 6 months can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C). Shelf life will be shortened if exposed to elevated temperatures.

## Precautions

- Refer to Safety Data Sheets (SDS) for additional safety information.
- EcoWhite EPDM QuickSeam Flashing is semi-cured. DO NOT STRETCH.

## LEED® Information

Post-Consumer Recycled Content: 0%  
 Post Industrial Recycled Content: 0%  
 Manufacturing Location: Michigan Center, MI

NOTE: LEED® is a registered trademark of the U.S. Green Building Council

Typical Properties			
QuickSeam Tape	Value	EPDM Flashing	Value
Base	Rubber Polymer	Base	EPDM
Color	White	Color	White
Solvents	None	Solvents	None
Solids	100%	Solids	100%
Cured State	Cured	Cured State	Semi-cured
Thickness	0.025" (0.64 mm) ± 0.005" (0.127 mm)	Thickness	0.060" (1.6 mm) ± 0.005" (0.13 mm)
Width	8.5" (216 mm) +0, -1/16"	Width	8.5" (216 mm) +0, -1/8"

Packaging			
Item	Size	Carton	Pallet
Corner Flashing	6" (152 mm) x 100' (30.5 m)	20 units per Carton	100 Cartons per Pallet

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.