

# Technical Information Sheet

Image Coming Soon

## EcoWhite™ QuickSeam™ Curb Flashing

Item Description	Item Number
50' (15.2 m) Roll	W56RAC160F

### Description

EcoWhite QuickSeam Curb Flashing consists of 18" (457 mm) wide 60-gauge non-reinforced EcoWhite membrane with 3" (76 mm) wide tape factory laminated along one edge. The 3" (76 mm) tape portion is used to splice the EcoWhite QuickSeam Curb Flashing to the roof membrane. The balance of the EcoWhite QuickSeam Curb Flashing is applied to the vertical surface with Elevate Single-Ply LVOC Bonding Adhesive, EPDM Bonding Adhesive BA-2004 (T), or Water-Based Bonding Adhesive S to adhere the membrane in place and terminated using an approved termination detail.

### Method of Application

1. Use Elevate Single-Ply QuickPrime™ Primer or QuickPrime Plus LVOC Primer applied with QuickScrubber™ or QuickScrubber Plus pad and handle to clean and prime membrane area to receive tape.
2. Refer to Elevate Specifications and Details. Application temperature range is between -10 °F (-23 °C) and 120 °F (49 °C).
3. Refer to application instructions for specifics: Technical Database, [www.HolcimElevate.com](http://www.HolcimElevate.com)

### Storage

- Store in original unopened containers indoors at temperatures between 60 °F (16 °C) and 80 °F (27 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (27 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.

### Shelf Life

Shelf life of 24 months can be expected when stored in original container at temperatures between 60 °F (16 °C) and 80 °F (27 °C). Shelf life will be shortened if exposed to elevated temperatures.

### Precautions

Refer to Safety Data Sheets (SDS) for additional safety information.

## Packaging

1 - 50' (15.2 m) roll per carton, 24 cartons per pallet

**NOTE:** QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

## LEED® Information

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Prescott, AR or Michigan Center, MI

**NOTE:** LEED® is a registered trademark of the U.S. Green Building Council

Typical Properties	
Properties – QuickSeam Tape	Value
Base	Rubber Polymers
Color	White
Solvents	None
Solids	100%
Cured State	Cured
Thickness	0.030" (.64 mm) ± 0.005" (0.13 mm)
Width	3" (77 mm)
Properties – EcoWhite Membrane	Value
Base	EPDM, Non-Reinforced
Color	White Layer Over Black
Solvents	None
Cured State	Cured
Thickness	0.060" (1.5 mm) ± 0.005" (0.13 mm)
Width	18" (457 mm)

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.