

TECHNICAL INFORMATION SHEET

EcoWhite™ QuickSeam™ Pipe Flashing

Item Description

White Molded Pipe Flashing

Item Number

W56358106A

Product Information

Description:

Firestone EcoWhite EPDM QuickSeam Pipe Flashings are specifically designed to be used in roofing applications for flashing of round penetrations. EcoWhite EPDM QuickSeam Pipe Flashings will fit various penetrations from 1" (25 mm) to 6" (152 mm) and must be cut to correct pipe diameter before installation. EcoWhite EPDM QuickSeam Pipe Flashings may be used to flash penetrations on EcoWhite EPDM and TPO installations (refer to UltraBlend specifications for more information on using QuickSeam products on TPO systems).

Method of Application:

1. Clean and prime the membrane to receive the tape flange using Single-Ply QuickPrime™ Primer or Single-Ply LVOC Primer with a QuickScrubber™ or QuickScrubber Plus pad and handle to remove all dusting agent, dirt and other contaminants that will affect the finished bond.
2. Allow the primer to dry completely according to the touch-push test.
3. Cut along the top edge of the ring on the EcoWhite QuickSeam Pipe Flashing corresponding to the size of the pipe.
4. Remove the release paper.
5. Install the pipe flashing and roll the flange with a silicone hand roller.
6. Install the clamping ring and EcoWhite EPDM Lap Sealant or Firestone AP Sealant per Firestone Specifications.

Storage:

- Store in original unopened containers indoors at temperatures between 60 °F (16 °C) and 80 °F (27 °C).
- Do not store on roof in direct sunlight or at temperatures above 80 °F (27 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.

Shelf Life:

- Shelf life of 24 months can be expected when stored in original container at temperatures between 60 °F (16 °C) and 80 °F (27 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

Precautions:

- Do not install on uneven substrates.
- Refer to Safety Data Sheet (SDS).

Packaging:

Each carton contains 10 pipe flashings, 10 stainless steel clamps

LEED® Information:

Post-Consumer Recycled Content:

0%

Post Industrial Recycled Content:

21%

Manufacturing Location:

Bensenville, IL / Michigan Center, MI

*NOTE: LEED® is a registered trademark of the U.S. Green Building Council.

TECHNICAL INFORMATION SHEET

EcoWhite™ QuickSeam™ Pipe Flashing

Fits Pipe Outside Diameters

1"	25 mm
1.5"	38 mm
2"	51 mm
3"	76 mm
4"	102 mm
5"	127 mm
6"	152 mm
NOTE: Make cut along top edge of rib.	

Typical Properties

Property	Value
Molded Pipe Flashing:	
Base	Molded EPDM
Color	White
Sizes	Universal – Fits 1" O.D. to 6" O.D. (25 mm to 152 mm)
Clamp	Stainless Steel – worm gear type (clamps are included)
Pipe Flange	13" (330 mm) O.D.
Thickness	0.055"-0.075" (1.4 mm – 1.9 mm)
QuickSeam Tape:	
Base	Rubber Polymer
Color	White
Solvents	None
Percent Solids	100%
Cured State	Cured
Thickness	0.030" (0.762 mm) + 0.005" (0.13 mm)

Please contact Firestone Technical Services at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications or other technical documents, subject to normal roof manufacturing tolerances. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.