



- Elevate™ RubberGard EPDM Membrane
- Mechanically Attached with Appropriate Fastening System
- Cover Board (Optional) – Mechanically Attached
- Insulation – Mechanically Attached
- Steel Deck

Consult Elevate Technical Specifications, Guides and Details at www.HolcimElevate.com

Slope Requirement:

Positive drainage required for warranty.

Construction Type:

- New Construction Complete Tear-off
- Recover (Any wet or damaged materials removed prior to installation) (New Elevate insulation required for 25 year)

Building Height Limitation:

Elevate RubberGard EPDM Mechanically Attached Systems are limited to buildings 120' (36.6 m) or less.

Air Barrier:

An air barrier is recommended for projects with large wall openings greater than 10% of the total wall area.

Vapor Barrier:

- V-Force™ and Thermal Barrier V-Force w/o Thermal Barrier* 4-6 mil poly

*Thermal barrier required when using V-Force over a Steel Deck on FM Insured or FM Specified projects.

Base Tie-Ins:

Must be attached to substrates which provide a minimum of 200 lbf (1 kN) in any direction.

Increased Wind Speed and Codes:

Any wind speed coverage exceeding 55 mph (88 km/h) or projects with code requirements must be reviewed by a Elevate Regional Technical Coordinator.

Deck Requirement:

- Minimum 22 Gauge Steel

Insulation Fasteners and Plates:

- Heavy Duty Fasteners and Insulation Plates HailGard™ Fastener (with HailGard Composite Board or OSB only)
- All Purpose Fasteners and Insulation Plates Elevate #12 Fasteners and Insulation Plates
- Pre-Assembled #12 Fastener and Plate IsoFast #12 Belted Fasteners and Insulation Plates
- AP AccuTrac Kit

Membrane Attachment (Row Spacing):

- Appropriate Membrane Maximum 10' Row Spacing, Fasteners Spaced Maximum 12" o.c. (20-year max)
- Appropriate Reinforced Membrane Maximum 10' Row Spacing, Fasteners Spaced Maximum 12" o.c. Field, 6" o.c. Perimeter and Corner (25-year max)

Membrane Fasteners and Plates:

- Elevate Heavy Duty Fastener and V-Plate
- Elevate Heavy Duty Fastener and Metal Batten Strip
- Elevate Heavy Duty Fastener, 2" Metal Plate and RMA Strip

Membrane Requirement:

- RubberGard EPDM, 45 mil (Batten Attachment Only) (15 year max) RubberGard MAX EPDM, 45 mil (15 year max)
- RubberGard EPDM, 60 mil (Batten Attachment Only) (20 year max) RubberGard MAX EPDM, 60 mil
- RubberGard Platinum EPDM, 90 mil (Batten Attachment Only) (20 year max) RubberGard MAX EPDM, 75 mil

Seaming Requirement:

- Minimum 3" QuickSeam™ Splice Tape in side and end laps
- Minimum 6" QuickSeam™ Splice Tape in side and end laps
(NOTE: Required when Elevate V Plates are used with MAX Membrane)
- QuickSeam Joint Covers are required at all T-Joints and at angle changes 1:12 or greater

| Elevate Factory Formed Edge Metal System: | | |
|--|---|--|
| <input type="checkbox"/> Coping System (QS-EDGE METAL-901) | <input type="checkbox"/> Fascia System (QS-EDGE METAL-902) | |
| <input type="checkbox"/> Water Control (QS-EDGE METAL-903) | <input type="checkbox"/> Wood Nailer Alternative (QS-EDGE METAL-904) | |
| Elevate ES-1 Cleat Program Metal Offering (5 – 20 Year Warranty): | | |
| <input type="checkbox"/> Drip Edge | <input type="checkbox"/> Gravel Stop | <input type="checkbox"/> Flat Coping |
| <input type="checkbox"/> Snap-On Coping | <input type="checkbox"/> Snap-On Fascia | <input type="checkbox"/> Tapered Coping |
| Non-Factory Formed Edge Conditions: | | |
| <input type="checkbox"/> Elevate Drain Bar | <input type="checkbox"/> Elevate Termination Bar | <input type="checkbox"/> Elevate Approved Detail |
| Substrate Attachment Rates for Standard 55 mph Wind Speed (Top Layer, 4' x 8' Board) | | |
| Thickness | Substrate Material | Minimum Fasteners |
| <input type="checkbox"/> 1.0" –1.4" | <input type="checkbox"/> ISOGARD GL / ISO 95+ GL or <input type="checkbox"/> ISOGARD CG / Resista | 5 |
| <input type="checkbox"/> 1.5" –1.9" | | 5 |
| <input type="checkbox"/> 2.0" –4.0" | | 5 |
| <input type="checkbox"/> 1.5" –1.9" | <input type="checkbox"/> ISOGARD HG / HailGard Composite / <input type="checkbox"/> OSB / <input type="checkbox"/> Plywood (Plate and Fastener) | 5 |
| <input type="checkbox"/> 2.0" –4.0" | | 5 |
| <input type="checkbox"/> ISOGARD HG / HailGard Composite / OSB / Plywood (HailGard Fastener) | | 5 |
| <input type="checkbox"/> ISOGARD HD Composite | | 5 |
| <input type="checkbox"/> ISOGARD HD Cover Board | | 5 |
| <input type="checkbox"/> 1/4" | <input type="checkbox"/> SECUROCK® Brand Gypsum-Fiber Roof Board | 5 |
| <input type="checkbox"/> 1/2" | | 5 |
| <input type="checkbox"/> 5/8" | | 5 |
| <input type="checkbox"/> 1/4" | DensDeck® or DensDeck® Prime Roof Board | 5 |
| <input type="checkbox"/> 1/2" | | 5 |
| <input type="checkbox"/> 5/8" | | 5 |
| <input type="checkbox"/> 5/8" | DensDeck Prime StormX™ Roof Board | 5 |
| <input type="checkbox"/> 1/4" | DEXcell® Glass Mat Roof Board | 5 |
| <input type="checkbox"/> 1/2" | | 5 |
| <input type="checkbox"/> 5/8" | | 5 |
| <input type="checkbox"/> 1/4" | DEXcell FA™ Glass Mat Roof Board | 5 |
| <input type="checkbox"/> 1/2" | | 5 |
| <input type="checkbox"/> 5/8" | | 5 |
| <input type="checkbox"/> 7/16" | DEXcell Cement Roof Board | 5 |
| <input type="checkbox"/> 5/8" | | 5 |
| <input type="checkbox"/> 5/8" | DEXcell FA VSH™ Glass Mat Roof Board | 5 |
| <input type="checkbox"/> 1/2" | Structodek® High Density Wood Fiber Board (max. 20-year warranty) | 5 |
| <input type="checkbox"/> 1/2" | Alleguard Fanfold Rigid Board Insulation (max. 20-year warranty, Re-Cover only) | 5 per 32 sq. ft. |
| NOTE: | | |
| <ol style="list-style-type: none"> 1. Only Elevate brand products are covered in a Red Shield Warranty. 2. Refer to the Elevate Technical Database at www.HolcimElevate.com for additional information regarding appropriate roof systems and roof system warranty requirements. Review appropriate details and installation requirements based on warranty term requested. 3. It is the installing contractor's responsibility to follow all applicable building codes. 4. Contact Holcim Technical Services for full warranty requirements. 5. DensDeck is a registered trademark of Georgia-Pacific Gypsum LLC, SECUROCK is a registered trademark of USG Corporation, Structodek is a registered trademark of Blue Ridge Fiberboard, Inc., and DEXcell is a registered trademark of National Gypsum Company. | | |

Please contact Elevate Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.