

# Technical Information Sheet



## QuickSeam™ Conduit Flashing

Item Description	Item Number
Various sizes from ½" to 2 ½"	W563581070

### Description

Elevate QuickSeam Conduit Flashing is specifically designed to be used in roofing applications for flashing of rigid round penetrations and conduit. Conduit Flashing will fit various size penetrations from ½" to 2 ½" (12.7 mm to 63.5 mm) and can be cut to desired diameter before installation.

QuickSeam Conduit Flashing may be used to flash small diameter penetrations and conduit for RubberGard™ EPDM as well as APP and SBS modified bitumen systems. On modified bitumen systems, a target patch of smooth APP must first be installed per Elevate's details.

### Method of Application

1. Penetration must be clean of prior flashing and foreign materials.
2. Cut along the top edge of the ring on the QuickSeam Conduit Flashing corresponding to the size of pipe or conduit.
3. Clean the RubberGard membrane using QuickPrime™ Plus and a QuickScrubber™ or QuickScrubber Plus pad and handle to remove all dusting agent, dirt and other contaminants that will affect the finished bond.
4. Allow to dry according to the touch-push test.
5. Remove the release paper.
6. Install the pipe flashing and roll the flange with a silicone hand roller.
7. Install the clamping ring and Lap Sealant per Elevate Specifications and Details.
8. **Modified Bitumen Membrane Preparation:** Install per specific requirements as outlined on the QuickSeam Pipe Flashing Technical Information Sheet located in the Elevate Asphalt Technical Manual.

### Shelf Life

24 Months

## Precautions

- Refer to Safety Data Sheets (SDS) for additional safety information.
- Do not install on uneven substrates.

## LEED® Information

Post-Consumer Recycled Content: 0%

Post Industrial Recycled Content: 0%

Manufacturing Location: Bensenville, IL

**NOTE: LEED® is a registered trademark of the U.S. Green Building Council**

Typical Properties	
Properties	Value
<b>Molded Pipe Flashing</b>	
Base	Molded EPDM
Color	Black
Clamp	Stainless Steel – worm gear type (clamps are included)
Pipe Flange	9" (229 mm) outside diameter
Thickness	0.055" – 0.075" (1.4 mm -1.9 mm)
<b>QuickSeam Tape</b>	
Base	Rubber Polymer
Color	Black
Solvents	None
Percent Solids	100%
Cured State	Cured
Thickness	0.030" (0.762 mm) + 0.005" (0.13 mm)

Fit Guide		
½" (12.7 mm)	1¼" (32.0 mm)	2" (51.0 mm)
¾" (19.0 mm)	1½" (37.0 mm)	2¼" (57.15 mm)
1" (25.4 mm)	1¾" (45.0 mm)	2½" (64.0 mm)

Please contact Holcim Technical Services at 800-428-4511 for further information.

This sheet is meant to highlight Elevate products and specifications and is subject to change without notice. Holcim takes responsibility for furnishing quality materials that meet published Elevate product specifications or other technical documents, subject to normal manufacturing tolerances. Neither Holcim nor its representatives practice architecture. Holcim offers no opinion on and expressly refuses any responsibility for the soundness of any structure. Holcim accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Holcim representative is authorized to vary this disclaimer.